

StatsBomb API Lineups Specification v5.0.0

[StatsBomb API - last updated 9 March 2026]

This document describes the API used to request team lineups for a match to which the user has licensed access. Credentials need to be supplied as described in the general API notes.

Summary of Changes for API v5.0.0

- Added HOPS player ratings
- Documentation corrections:
 - Add table to represent lineup[].country in more detail
 - Add missing lineup[].stats object
 - Add missing counterpart_id and counterpart_name to lineup[].positions[]

Accessing the API

The new API version has changed URLs from "/v4/lineups" to "/v5/lineups" due to some data structure differences between API versions. Therefore, we have updated the URL call to access the API. If you wish to upgrade to the most recent version of StatsBomb data, please make a call to the newest version of the API at the url below.

The updated API can be accessed by making a request to <https://data.statsbomb.com/api/v5/lineups/?>. The question mark should be replaced by the desired match ID.

Previous versions of the API can be accessed by changing v5 in the URL to v4, v3, v2 or v1. The question mark should be replaced by the desired match ID. Please see our data website for the documentation of previous API versions.

An R package has been written for users to conveniently access the API and clean the data. The R package is available at <https://github.com/statsbomb/StatsBombR>.

Response

The response will be in JSON format. The response is an array containing lineup information for both teams:

Column	Type	Description
team_id	Integer	The unique identifier for each team.
team_name	Integer	The name of the team.
lineup	Array	An array of players on the team sheet for this team.
formations	Array	An array of formation objects.
events	Array	An array of simplified event objects.

Lineup Objects

The lineup variable is an array containing the following variables:

Column	Type	Description
player_id	Integer	The unique identifier for this player.
player_name	Integer	The name of the player.
player_nickname	String	The nickname of the player on the team.
player_gender	String	The gender of the player on the team.
player_weight	Number	The weight of the player on the team (in kg).
player_height	Number	The height of the player on the team (in cm).

birth_date	Date	The player's date of birth.
jersey_number	Integer	The number on the player's shirt for this match.
country	Object	The player's nationality, a country object with ID and name attributes. See country objects table for details.
positions	Array	The positions occupied by the player in the course of the match. See Position Objects table for details.
stats	Object	An overview of a player's goals, assists etc. See the Stats Objects table for details.
skills	Object	A map of skill name to the scores the player has for that skill. See the Skills Objects for details.

Event Objects

The event attribute contains an array of the following objects:

Column	Type	Description	Values
player_id	Integer	The unique identifier for this player.	24664
player_name	Integer	The name of the player.	"Pawel Kieszek"
period	Integer	The numeric match period during which the card was issued.	1 (1st half) 2 (2nd half) 3 (3rd period) 4 (4th period) 5 (Penalty Shootout)
timestamp	String	The timestamp at which the event occurred in HH:MM:SS.SSS format. Times reset at period starts, so even if the last event of the first half is "00:47:12.234", the first event of the second half will be "00:45:00.000".	e.g. "00:47:12.234"
type	String	The type of event (limited to fouls resulting in cards, period	"Foul Committed" "Bad Behaviour"

		start/ends, goals, penalties, penalty saves).	"Half Start" "Half End" "Shot" "Penalty" "Goal Keeper"
outcome	String	The outcome of the event	"Yellow Card" "Second Yellow" "Red Card" "Goal" "Off T" "Penalty Saved" "Saved To Post"

Formation Objects

Each formation object is an array containing the following variables:

Column	Type	Description	Values
period	Integer	The numeric match period during which the card was issued.	1 (1st half) 2 (2nd half) 3 (3rd period) 4 (4th period) 5 (Penalty Shootout)
timestamp	String	The timestamp at which the formation change occurred in HH:MM:SS.SSS format. Times reset at period starts, so even if the last event of the first half is "00:47:12.234", the first event of the second half will be "00:45:00.000".	e.g. "00:47:12.234"
reason	String	The reason for the formation change.	"Starting XI" "Tactical Shift"
formation	Integer	A number matching the formation.	e.g. 433

Position Objects

Each position object is an array containing the following variables:

Column	Type	Description	Values
position_id	Integer	The number of the player's position.	1 ... 25
position	String	The name of the position. Note: Secondary Striker has been deprecated as a position for future matches.	
			Position Number
			Position Name
			1
			Goalkeeper
			2
			Right Back
			3
			Right Center Back
			4
			Center Back
			5
			Left Center Back
			6
			Left Back
			7
			Right Wing Back
			8
			Left Wing Back
			9
			Right Defensive Midfield
			10
			Center Defensive Midfield
			11
			Left Defensive Midfield
			12
			Right Midfield
			13
			Right Center Midfield
			14
			Center Midfield
			15
			Left Center Midfield
			16
			Left Midfield
			17
			Right Wing
			18
			Right Attacking Midfield
			19
			Center Attacking Midfield
			20
			Left Attacking Midfield
			21
			Left Wing
			22
			Right Center Forward
			23
			Striker
			24
			Left Center Forward
			25
			Secondary Striker
from	String	The timestamp at which the event occurred in HH:MM:SS.SSS format. Times reset at period starts, so even if the last event of the first half is "00:47:12.234", the first event of the second half will be "00:45:00.000".	e.g. "00:47:12.234"

to	String	The timestamp at which the event occurred in HH:MM:SS.SSS format. Times reset at period starts, so even if the last event of the first half is "00:47:12.234", the first event of the second half will be "00:45:00.000".	e.g. "00:47:12.234"
from_period	integer	The match period during which the player's occupancy of this position began .	1 (1st half) 2 (2nd half) 3 (3rd period) 4 (4th period) 5 (Penalty Shootout)
to_period	integer	The match period during which the player's occupancy of this position ended.	1 (1st half) 2 (2nd half) 3 (3rd period) 4 (4th period) 5 (Penalty Shootout)
start_reason	String	The reason for the start of the player's occupancy of this position.	"Player On" "Player On (Off Camera)" "Starting XI" "Tactical Shift" "Substitution - On" "Substitution - On (Injury)" "Substitution - On (Off Camera)" "Substitution - On (Tactical)" "Tactical Shift"
end_reason	String	The reason for the end of the player's occupancy of this position.	"Final Whistle" "Player Off" "Player Off (Off Camera)" "Player Off (Permanent)" "Starting XI" "Substitution Off" "Substitution - Off (Injury)" "Substitution - Off (Off Camera)" "Substitution - Off (Tactical)" "Tactical Shift" "Red Card" "Second Yellow Card"
counterpart_id	Integer	The id of the other player in the event of a substitution on or off.	

counterpart_name	String	The name of the other player in the event of a substitution on or off.	
------------------	--------	--	--

Country Objects

Each country object contains the following variables:

Column	Type	Description	Values
id	Integer	The ID of the country	e.g. 220
name	String	The name of the country	e.g. "Sweden"

Stats Objects

Each stats object contains the following variables:

Column	Type	Description	Values
goals	Integer	The number of goals a player scored	
assists	Integer	The number of assists a player made	
own_goals	Integer	The number of own goals a player scored	
penalties_missed	Integer	The number of penalties a player missed	
penalties_saved	Integer	The number of penalties a player saved	
penalties_scored	Integer	The number of penalties a player scored	

Skills Objects

Each skills object contains the following variables:

Column	Type	Description	Values
"HOPS"	Object	The HOPS skill values	See the HOPS Objects table for details.

HOPS Objects

Each HOPS object contains the following variables:

Column	Type	Description	Values
rating	Number	The normalised value (0 - 1) of the model score for the player	e.g. 0.745
raw_rating	Number	The raw model score for the player	e.g. 436.52

[End of Document]