

Exposure Checker

Security Scan Report — Gull

10 Jun 2026 10:58 UTC

Score: 90 / 100



Findings

HIGH

No active firewall detected

FIREWALL STATUS

No firewall appears to be running — all open ports are directly reachable.

Fix: [Install and enable ufw: sudo apt install ufw && sudo ufw enable](#)

INFO

SUID: /usr/bin/chage

SUID / SGID BINARIES

SGID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.

Fix: [Remove the setuid/setgid bit if unneeded: chmod u-s '/usr/bin/chage'](#)

SUID: /usr/bin/chfn

SUID / SGID BINARIES

SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.

Fix: [Remove the setuid/setgid bit if unneeded: chmod u-s '/usr/bin/chfn'](#)

SUID: /usr/bin/chsh

SUID / SGID BINARIES

SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.

Fix: [Remove the setuid/setgid bit if unneeded: chmod u-s '/usr/bin/chsh'](#)

SGID: /usr/bin/crontab

SUID / SGID BINARIES

SGID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.

Fix: [Remove the setuid/setgid bit if unneeded: chmod u-s '/usr/bin/crontab'](#)

SGID: /usr/bin/expiry

SUID / SGID BINARIES

SGID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.

Fix: [Remove the setuid/setgid bit if unneeded: chmod u-s '/usr/bin/expiry'](#)

SUID: /usr/bin/fusermount3

SUID / SGID BINARIES

SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.

Fix: [Remove the setuid/setgid bit if unneeded: chmod u-s '/usr/bin/fusermount3'](#)

SUID: /usr/bin/gpasswd

SUID / SGID BINARIES

SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.

Fix: [Remove the setuid/setgid bit if unneeded: chmod u-s '/usr/bin/gpasswd'](#)

SUID: /usr/bin/mount

SUID / SGID BINARIES

SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.

Fix: [Remove the setuid/setgid bit if unneeded: chmod u-s '/usr/bin/mount'](#)

SUID: /usr/bin/ntfs-3g	SUID / SGID BINARIES
SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.	
Fix: Remove the setuid/setgid bit if unneeded: <code>chmod u-s '/usr/bin/ntfs-3g'</code>	
SUID: /usr/bin/passwd	SUID / SGID BINARIES
SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.	
Fix: Remove the setuid/setgid bit if unneeded: <code>chmod u-s '/usr/bin/passwd'</code>	
SUID: /usr/bin/pkexec	SUID / SGID BINARIES
SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.	
Fix: Remove the setuid/setgid bit if unneeded: <code>chmod u-s '/usr/bin/pkexec'</code>	
SGID: /usr/bin/ssh-agent	SUID / SGID BINARIES
SGID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.	
Fix: Remove the setuid/setgid bit if unneeded: <code>chmod u-s '/usr/bin/ssh-agent'</code>	
SUID: /usr/bin/su	SUID / SGID BINARIES
SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.	
Fix: Remove the setuid/setgid bit if unneeded: <code>chmod u-s '/usr/bin/su'</code>	
SUID: /usr/bin/sudo.ws	SUID / SGID BINARIES
SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.	
Fix: Remove the setuid/setgid bit if unneeded: <code>chmod u-s '/usr/bin/sudo.ws'</code>	
SUID: /usr/bin/umount	SUID / SGID BINARIES
SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.	
Fix: Remove the setuid/setgid bit if unneeded: <code>chmod u-s '/usr/bin/umount'</code>	
SUID: /usr/lib/cargo/bin/su	SUID / SGID BINARIES
SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.	
Fix: Remove the setuid/setgid bit if unneeded: <code>chmod u-s '/usr/lib/cargo/bin/su'</code>	
SUID: /usr/lib/cargo/bin/sudo	SUID / SGID BINARIES
SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.	
Fix: Remove the setuid/setgid bit if unneeded: <code>chmod u-s '/usr/lib/cargo/bin/sudo'</code>	
SUID: /usr/lib/dbus-1.0/dbus-daemon-launch-helper	SUID / SGID BINARIES
SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.	
Fix: Remove the setuid/setgid bit if unneeded: <code>chmod u-s '/usr/lib/dbus-1.0/dbus-daemon-launch-helper'</code>	
SUID: /usr/lib/openssh/ssh-keysign	SUID / SGID BINARIES
SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.	
Fix: Remove the setuid/setgid bit if unneeded: <code>chmod u-s '/usr/lib/openssh/ssh-keysign'</code>	
SUID: /usr/lib/slack/chrome-sandbox	SUID / SGID BINARIES
SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.	
Fix: Remove the setuid/setgid bit if unneeded: <code>chmod u-s '/usr/lib/slack/chrome-sandbox'</code>	
SGID: /usr/sbin/pam_extrausers_chkpwd	SUID / SGID BINARIES
SGID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.	
Fix: Remove the setuid/setgid bit if unneeded: <code>chmod u-s '/usr/sbin/pam_extrausers_chkpwd'</code>	
SUID: /usr/sbin/pppd	SUID / SGID BINARIES

SUID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.

Fix: [Remove the setuid/setgid bit if unneeded: chmod u-s '/usr/sbin/pppd'](#)

SGID: /usr/sbin/unix_chkpwd

SUID / SGID BINARIES

SGID binary runs as its owner (typically root) regardless of who invokes it — verify this is intentional.

Fix: [Remove the setuid/setgid bit if unneeded: chmod u-s '/usr/sbin/unix_chkpwd'](#)