JA SOLAR

Harvest the Sunshine

640W

JAM66D45 LB n-type Double Glass Bifacial Modules

Premium Cells

n-Bycium+ 16BB

MBB Half-Cell Technology

26% Up To

Cell Conversion Efficiency

Premium Modules

- Higher power generation better LCOE
- n-type with very Lower LID
- Better Temperature Coefficient
- Better low irradiance response



1% 1st-year Degradation 0.4% Annual Degradation Over 30 years

- 12-year product warranty
- 30-year linear power output warranty



Comprehensive Certificates

- IEC 61215, IEC 61730, UL 61215, UL 61730
- ISO 9001: 2015 Quality management systems
- ISO 14001: 2015 Environmental management systems
- ISO 45001: 2018 Occupational health and safety management systems
- IEC 62941: 2019 Terrestrial photovoltaic (PV) modules - Quality system for PV module manufacturing

DEEP BLUE 4.0 Pro

JAM66D45 LB n-type Double Glass Bifacial Modules

DEEP BLUE 4.0 Pro



MECHANICAL PARAMETERS

Cell	Mono
Weight	41.0kg
Dimensions	2382±2mm×1134±2mm×35±1mm
Cable Cross Section Size	4mm²(IEC), 12 AWG(UL)
No. of cells	132(6×22)
Junction Box	IP68, 3diodes
Connector	QC 4.10-351/ MC4-EVO2
Cable Length (Including Connector)	Portrait: 300mm(+) /400mm(-) Landscape: 1500mm(+)/1500mm(-)
Front Glass/Back Glass	3.2mm/2.0mm
Packaging Configuration	31pcs/Pallet, 465pcs/40HQ Container

Remark: customized frame color and cable length available upon request

ELECTRICAL PARAMETERS AT STC

TYPE	JAM66D45 -615/LB	JAM66D45 -620/LB	JAM66D45 -625/LB	JAM66D45 -630/LB	JAM66D45 -635/LB	JAM66D45 -640/LB
Rated Maximum Power(Pmax) [W]	615	620	625	630	635	640
Open Circuit Voltage (Voc) [V]	48.30	48.50	48.70	48.90	49.10	49.39
Maximum Power Voltage(Vmp) [V]	39.96	40.21	40.45	40.70	40.94	41.20
Short Circuit Current(Isc) [A]	16.10	16.13	16.15	16.18	16.21	16.24
Maximum Power Current(Imp) [A]	15.39	15.42	15.45	15.48	15.51	15.54
Module Efficiency [%]	22.8	23.0	23.1	23.3	23.5	23.7
Power Tolerance	0~+3%					
Temperature Coefficient of Isc/α_Isc)	+0.045%/°C					
Temperature Coefficient of Voc (β_Voc)	-0.250%/°C					
Temperature Coefficient of Pmax(γ_Pmp)	-0.290%/°C					
STC	Irradiance 1000W/m², cell temperature 25°C, AM1.5G					

Remark: Electrical data in this catalog do not refer to a single module and they are not part of the offer.
They only serve for comparison among different module types.

CHARACTERISTICS





ELECTRICAL CHARACTERISTICS WITH 10% SOLAR IRRADIATION RATIO

TYPE	JAM66D45 -615/LB	JAM66D45 -620/LB	JAM66D45 -625/LB	JAM66D45 -630/LB	JAM66D45 -635/LB	JAM66D45 -640/LB
Rated Max Power(Pmax) [W]	664	670	675	680	688	691
Open Circuit Voltage(Voc) [V]	48.30	48.50	48.70	48.90	49.10	49.39
Max Power Voltage(Vmp) IV]	39.96	40.21	40.45	40.70	40.94	41.20
Short Circuit Current(Isc) [Al	17.39	17.42	17.44	17.47	17.51	17.54
Max Power Current(Imp) [A]	16.62	16.65	16.69	16.72	16.75	16.78
Irradiation Ratio (rear/front)	10%					

* For Nextracker installations, maximum static load please take compatibility approve letter between JA Solar and Nextracker for reference.
-

OPERATING CONDITIONS

Maximum System Voltage	1500V DC
Operating Temperature	-40°C~+85°C
Maximum Series Fuse Rating	35A
Maximum Static Load, Front*	5400Pa(112 lb/ft²)
Maximum Static Load, Back*	2400Pa(50 lb/ft²)
NOCT	45±2°C
Bifaciality-	80%±5%
Safety Class	Class II
Fire Performance	UL Type 29/Class C

JA SOLAR

Headquarters No. 8 Building, Nuode Center, No.1 Courtyard, East Auto Museum Road, Fengtai District, Beijing
Tel: +86 10 6361 1888 Fax: +86 10 6361 1999
E-mail: sales@jasolar.com marketing@jasolar.com www.jasolar.com

Specifications subject to technical changes and tests.
JA Solar reserves the right of final interpretation.

Version No. : Global-EN-20241121A