

PENETRATION TESTING REPORT

FOOTPRINTING & NETWORK SCANNING PHASES

W2-PM1 & W2-PM5 | CYBERSECURITY | NETWORKWALKS

Pentester Name (Cybersecurity Professional)	Ikpomwosa Osariemen
Contact Email	[Add your email address]
Program/Batch	B083-Networkwalks
Date	18 September 2026
Modules completed	W2-PM1 (Multiple Kali Tools) W2-PM5 (Zenmap Scanning)
Client/Target	1. Networkwalks (secured written permission already, per course terms) 2. My own local LAN network
Permission secured from client?	Yes
Phases covered	Phase 1: Reconnaissance & Footprinting Phase 2: Scanning & Network Discovery Phase 3-5: In Progress

1. Liability Disclaimer

I have performed these activities only on the systems & devices where I had secured written permission or the devices/systems that I own myself. All these materials are for education and research purpose only. Do not use anything from here to break the law. The instructor, the authors and Networkwalks are not responsible for what you do with this knowledge. Every action you take is your own responsibility. Misuse can lead to criminal charges, heavy fines, loss of your job and a permanent record. In most countries unauthorised access is a crime even when nothing is damaged.

2. Introduction

This report covers footprinting the networkwalks.com domain using multiple Kali Linux tools (W2-PM1) and scanning my own local network with Zenmap (W2-PM5). One module covers the footprinting phase and the other covers the scanning phase, so together they show how an attacker moves from gathering public information to mapping live hosts on a network. It is the Week 2 part of my ongoing internship program at Networkwalks.

All commands were run in Kali Linux (footprinting) and on a Windows PC with Zenmap installed (scanning). Every step below includes the exact command used, the result I observed, a screenshot as evidence, and a short note on why the finding matters from an attacker's point of view.

3. Tools Used

The table below lists each tool used in this report and its purpose.

Tool	Purpose
Kali Linux & Windows	Operating systems used for reconnaissance activities
WHOIS	Find domain registration details (owner, dates, name servers).
whatweb	Fingerprint web technologies (server, CMS, plugins, IP).
nslookup	Resolve the domain name to its IP address using DNS.
curl -I	Read the HTTP response headers of the website.
wafw00f	Detect whether a Web Application Firewall protects the site.
dnsrecon	Enumerate all DNS records (NS, MX, SPF, TXT, SRV).
Zenmap (Nmap GUI)	Scan the local subnet to find live hosts, IPs and MAC addresses.
Windows CMD	Local IP and MAC address identification

4. Activities Performed

4.1 Footprinting & Reconnaissance

I performed reconnaissance against the networkwalks.com domain using six Kali Linux tools: WHOIS, WhatWeb, Nslookup, Curl, Wafw00f and DNSRecon. Each tool was used to collect a different type of information about the target.

First, I used WHOIS to obtain publicly available domain registration information. The registrant details are protected by GoDaddy's privacy service (Domains By Proxy, LLC, 100 S. Mill Ave, Suite 1600, Tempe, Arizona), and the domain shows clientTransferProhibited, clientUpdateProhibited, clientRenewProhibited and clientDeleteProhibited status locks.

I then used WhatWeb to identify technologies used by the website. The results identified WordPress 7.1 and WordPress Download Manager 3.3.58, running on an Apache server with Bootstrap 7.1 and jQuery 3.7.1, and exposed an email address (info@networkwalks.com) and the server IP (192.232.216.135).

Using Nslookup, I resolved the domain name to its IP address. The result identified 192.232.216.135.

I used Curl with the -I option to inspect the HTTP response headers. The response returned HTTP/2 200 from an Apache server, showed the site is cached through WordPress, and exposed the WordPress REST API endpoint (/wp-json/) along with a session cookie (__wpdm_client).

Next, I used Wafw00f to determine whether a Web Application Firewall was protecting the website. The result identified ModSecurity (SpiderLabs).

Finally, I used DNSRecon to enumerate DNS records. The results identified the name servers (ns6135.hostgator.com, running Bind 9.16.23-RH), the mail server (mail.networkwalks.com), an SPF TXT record authorizing websitewelcome.com and IP 50.87.144.87 to send mail, a Google site-verification TXT record, and SRV autodiscover records pointing to cpanelmaildiscovery.cpanel.net for email client auto-configuration. No DNSSEC record was found.

4.2 Network Scanning with Zenmap

For the second activity, I used Zenmap to perform network discovery on my own local network. The practical required me to identify my local IP address and subnet, discover live hosts, identify their IP and MAC addresses, and generate a network topology.

I first used the Windows ipconfig command to identify my local IP address (192.168.0.199) and LAN subnet (255.255.255.0, i.e. 192.168.0.0/24). I then entered this subnet into Zenmap and selected Ping Scan (nmap -sn 192.168.0.0/24) to identify active hosts.

The scan identified 3 live hosts (including my own PC) out of 256 addresses scanned:

- 192.168.0.1 - MAC 7C:99:2E:12:96:52 (Shanghai Notion Information Technology) - this is my router/gateway
- 192.168.0.199 - my own PC (MAC not returned by the ping scan since it is the local host)
- 192.168.0.200 - MAC D4:0A:DC:93:71:43 (Qingdao Intelligent&Precise Electronics)

After completing the scan, I opened the Topology tab in Zenmap, reviewed the legend, and saved the network topology in PDF format to my desktop as required by the practical task.

5. Risk Analysis / Impact

Based on the information collected during the footprinting and network scanning activities, I identified the following potential risks.

#	Risk / Finding	Evidence / Observation	Potential Impact	Risk Level
1	Web technology & version exposed	WhatWeb identified WordPress 7.1 and WP Download Manager 3.3.58	Attackers may match exposed versions against known vulnerabilities requiring further review	● Medium
2	Domain registrant details locked but hosting exposed	WHOIS shows privacy-protected registrant but confirms GoDaddy/HostGator hosting via status codes	Provides infrastructure/provider info useful for social engineering or targeting	● Low
3	Server IP address identifiable	Nslookup resolved the domain to 192.232.216.135	Reveals network location of the web service	● Low
4	HTTP technical information exposed	Curl returned response headers and exposed /wp-json/ REST API endpoint	May assist technology fingerprinting and further enumeration	● Low
5	WAF technology identifiable	Wafw00f identified ModSecurity (SpiderLabs)	Reveals information about the web application's security architecture	● Low
6	DNS & mail infrastructure exposed	DNSRecon identified name servers, SPF record, and cPanel autodiscover SRV records	DNS information can help build a broader infrastructure profile	● Medium
7	Multiple live hosts visible on local network	Zenmap identified 3 live hosts on my home network, including an unidentified device at 192.168.0.200	Unknown or unauthorized devices may potentially be present on a network	● Medium

Risk level key: ● **Critical** ● **Medium** ● **Low**

The risks above are observations from the footprinting and scanning exercises, not confirmed vulnerabilities.

The practical exercises primarily involved information gathering and host discovery. No exploitation or vulnerability validation was performed as part of these two modules.

Therefore, the presence of information such as a software version, IP address or DNS record does not by itself mean that the system is vulnerable. Further authorized security testing would be required to confirm any actual vulnerability.

6. Recommendations

Based on the observations from these activities, I recommend the following security improvements:

- 1. Review publicly exposed technology information:** Organizations should regularly review what information about their web technologies, CMS and plugins is publicly visible.
- 2. Keep software updated:** CMS platforms, plugins and other web technologies should be regularly updated and reviewed against current security advisories.
- 3. Review HTTP headers:** HTTP response headers should be reviewed to determine whether unnecessary technical information is being exposed.

- 4. Review DNS records regularly:** DNS records should be checked periodically to ensure that only required information and services are publicly exposed.
- 5. Properly configure and monitor the WAF:** Keep the WAF (ModSecurity) enabled and tuned, since it already blocks naive attacks.
- 6. Perform regular internal network discovery:** Organizations (and home users) should periodically scan their own networks to identify active devices.
- 7. Investigate unknown devices:** Any unexpected device discovered during network scanning, such as the unidentified device at 192.168.0.200, should be investigated and verified.
- 8. Maintain network documentation:** Network topology and device information should be documented and updated regularly.
- 9. Perform security testing with authorization:** Reconnaissance and scanning should only be performed against systems and networks where appropriate authorization has been provided.

7. Conclusion

During Week 2 of my Cybersecurity & Ethical Hacking internship, I completed practical activities covering footprinting, reconnaissance and network scanning.

In the footprinting activity, I used six Kali Linux tools to collect information about the target domain. I learned how WHOIS can provide domain information, WhatWeb can identify web technologies, Nslookup can resolve domain names, Curl can inspect HTTP headers, Wafw00f can identify a WAF, and DNSRecon can provide additional DNS information.


In the network scanning activity, I used Zenmap to identify my local network configuration and discover active hosts. I also collected IP and MAC address information and created a network topology.

The exercises showed me that information gathering is an important part of cybersecurity. Even before attempting to exploit a system, a security professional can learn a significant amount about an environment by carefully analyzing publicly available information and network responses.


I also learned that technical findings should be documented clearly. A good cybersecurity report should explain what was performed, what was discovered, what the observation means, what risk it may create, and what can be done to reduce that risk.

Finally, I learned that reconnaissance and scanning must always be performed within an authorized scope. These activities were completed as part of the assigned educational cybersecurity lab.


8. Evidences Collected




Evidence 1: whois networkwalks.com — registrant/domain status (Kali Linux)




Evidence 2: whois networkwalks.com — VeriSign registry notice




Evidence 3: whatweb networkwalks.com — WordPress 7.1, WP Download Manager 3.3.58




Evidence 4: nslookup networkwalks.com — resolves to 192.232.216.135




Evidence 5: curl -I https://networkwalks.com — HTTP response headers




Evidence 6: wafw00f networkwalks.com — ModSecurity (SpiderLabs) WAF detected



Evidence 7: dnsrecon -d networkwalks.com — DNS records enumerated



Evidence 8: Zenmap ping scan (nmap -sn 192.168.0.0/24) — 3 live hosts identified



Evidence 9: Zenmap network topology with legend — 192.168.0.1 (router), .199 (my PC), .200

-End-

 **Author**
Ikpomwosa Osariemen
Cybersecurity Professional

 **Project Information**
Program Name: Cybersecurity program at Networkwalks | Week: 02