unistra.jpg

Indoor Air Quality (IAQ) modelling, application to COVID-19 transmission

Mariam Grigoryan

From June 7th 2021 to July 30th 2021

Supervised by :
Mr Christophe Prud'homme / Mrs Zohra Djatouti

Introduction

- The air quality within and around buildings.
- Responsible for 1.5 million to 2 million deaths in 2000.



Indoor air quality facts [1]

- COVID-19 consequences.

1. https ://www.pinterest.fr/pin/534661787013453107/

Internship host

- Cemosis : Strasbourg Center for Modelling and Simulation .
- Cemosis[2] created in January 2013 by Christophe Prud'homme.
- Cemosis and Synapse-Concept project 4fastsim-ibat[3].
- Reduce and control energy consumption in buildings.
- Air quality of indoor spaces and its consequences[4].

---

2. `https://www.cemosis.fr/`
3. `https://www.cemosis.fr/projects/4fastsim-ibat/`
4. `http://agrohome.com.br/wp-content/uploads/2020/12/DINAMARCA-Produtividade.pdf`

Objectives

- Proceed the model of the airborne transmission of COVID-19.
- Modelling indoor air quality (IAQ) applied to COVID-19's transmission .
- Couple the IAQ model with the zero-equation turbulence model.

I.Indoor Air Quality (IAQ)

Indoor air quality [5]

5. https://catalysts.basf.com/products-and-industries/indoor-air-quality

Different pollutants

- Principal pollutants of indoor air :
  - Chemical pollutants : volatile organic compounds (VOCs), nitrogen oxides (NOx), carbon monoxide (CO)...
  - Biological contaminants : moulds, pets , pollens ...
  - Particles and fibers : asbestos, artificial mineral fibers...
- Main sources of residential buildings :
  - Mold,
  - Tabacco smoke,
  - Household Products,
  - Carpet,
  - Pet Dander...

Effects of nefarious IAQ

- Major effects on comfort and health,
- Simple discomforts :
  - drowsiness
  - eye and skin irritation
  - lost productivity at work.
- Severe pathologies :
  - respiratory allergies,
  - asthma,
  - cancer,
  - poisoning...
- Sick Building Syndrome (SBS).
- Causes and solutions.

Recommendations to enhance IAQ

- Indoor Air Quality top 5 most urgent environmental risks to public health.
- Major recommendations :
  - eliminate individual sources of pollution or to reduce their emissions.
  - increase the amount of outdoor air coming indoors.
  - air cleaners collecting pollutants from indoor air.

Modeling IAQ

- Three principal categories of models.
- Statistical :
  - estimate the distribution of indoor pollutant exposures,
  - using Monte Carlo techniques to combine the databases.
- Mass balance :
  - estimate the impacts of sources, sinks and IAQ control options on pollutant concentrations.
- Computational fluid dynamics (CFD) :
  - room air movement and contaminant transport application.
  - incompressible,inviscid,irrotational fluid.

ARD Equation

- The advection–reaction–diffusion equation :

$$\frac{\partial C}{\partial t} = \nabla.(K\nabla C) - \nabla.(\vec{v}\, C) + S.$$

- C = concentration of airborne infectious particles ($particles/m^2$
  t = time(s)
  ∇ = two-dimensional gradient operator
  K = isotropic eddy diffusion coefficient (turbulent diffusion)
  $\vec{v}$ = advection velocity of the air($m.s^{-1}$)
  S = sum of sources and sinks of viral particles.

II. COVID-19 transmission

- The COVID-19 virus since december 2019.
- Pandemic declared on 11th March 2020.
- Overs 200 million confirmed cases and 4.36 milion deaths.
- 81% moderate symptoms, 14% severe and 5% critical symptoms.
- 4.45 billion vaccine doses administered.

Transmission's modes



Figure – Transmission and the infection of COVID-19.

. [6]

6. https ://world-heart-federation.org/resource/covid-19-transmission/

Focus on models

- Data-driven models.
- Exemple of Italy.
- Importance of strong social-distancing strategies.

Our model

- Based on ADR equation.
- An infectious person talking or breathing with or without a mask S_{inf}.
- The room contains an air-conditioning unit.
- The airborne particles transported by advection caused by the airflow.
- The infectious particles are removed due to three factors :
  - the ventilation system (S_{vent}), - biological deactivation of the virus (S_{deact}),
  - gravitational settling of the virus (S_{set}).
- $$\frac{\partial C}{\partial t} + \nabla.(\vec{v}C) - \nabla.(K\nabla C) = S_{inf} - S_{vent} - S_{deact} - S_{set}$$
- The eddy diffusion coefficient $K(m^2/s)$:

$$K = c_v Q(2c_\epsilon VN^2)^{1/3}$$

Modelling environment and tools

- Using Feel++ finite library.
- Coefficient Form PDEs described by [7]

$$d\frac{\partial u}{\partial t} + \nabla \cdot (-c\nabla u - \alpha u + \gamma) + \beta \cdot \nabla u + au = f \quad in \quad \Omega$$

- d : damping or mass coefficient
- c : diffusion coefficient
- α : conservative flux convection coefficient
- γ : conservative flux source term
- β : convection coefficient
- a : absorption or reaction coefficient
- f : source term

7. `https://docs.feelpp.org/toolboxes/0.109/cfpdes/introduction.html`

Application

- Assumptions :
  - the advection–diffusion–reaction equation governs the concentration of the virus.
  - particles released with zero initial velocity.
  - only one infectious person in the room.



Figure – Schematic of the modelled room. One infectious person is located at the centre of the room.

Application(folow-up)

- Unwraping the loop surface of the airflow to the two-dimensional domain $(\xi, y) \in [0, 2l] \times [0, w]$.



- Boundary conditions :
  - $C(0, y, t) = C(2l, y, t)$ at the wall $\xi = 0$.

  - $\frac{\partial C}{\partial \xi}(0, y, t) = \frac{\partial C}{\partial \xi}(2l, y, t)$ at $\xi = 2l$.

  - $\frac{\partial C}{\partial y}(\xi, 0, t) = \frac{\partial C}{\partial y}(\xi, w, t) = 0$ at $y = 0, w$.

References

- Coronavirus disease(COVID-19) updatehttps://www.who.int/bangladesh/emergencies/coronavirus-disease-(covid-19)-update
-
- Z. Lau, K. Kaouri, I. Griffiths. Modelling Airborne Transmission of COVID-19 in Indoor Spaces Using an Advection–Diffusion–Reaction Equation. School of Mathematics, Cardiff University and Mathematical Institute, University of Oxford.
- B. Zhao and X. Li. A simplified system for indoor airflow simulation. Building and Environment © April 2003
- Zohra Djatouti, Christophe Prud'homme, Vincent Chabannes, Romain Hild, 4FastSim-IBat
- https://twitter.com/T_Fiolet/status/13789583682179075?s=09