

# **Software Requirements Engineering (SE2001)**



**Dr. Syed Muazzam Ali Shah**

*HEC Approved Ph.D. Supervisor*

*(Assistant Professor)*

Department of Software Engineering

NUCES-FAST Karachi

*Contact#:* (021) 111-128-128 Ext. 130

*Website:* [sites.google.com/view/muazzam-kazmi/home](https://sites.google.com/view/muazzam-kazmi/home)

*Official page:* <https://khi.nu.edu.pk/personnel/dr-syed-muazzam-ali-shah-2/>

*Google Scholar:* <https://scholar.google.com.tw/citations?hl=en&user=OvcfR-IAAAAJ>

# Non Functional Requirements as Goals

2

- ❖ Non-functional requirements are sometimes written as general goals,
  - which are difficult to verify
- ❖ They should be expressed quantitatively using metrics (measures) that can be objectively tested

# Non Functional Requirements as Goals

3

## ❖ Goal (unverifiable)

- The system should be easy to use by experienced controllers and should be organized in such a way that user errors are minimized

## ❖ Non-functional requirement (verifiable)

- Experienced controllers shall be able to use all the system functions after a total of two hours' training. After this training, the average number of errors made by experienced users shall not exceed two per day

# Metrics for Non Functional Requirements (NFRs) <sup>4</sup>

- ❖ Speed/Performance
- ❖ Size
- ❖ Ease of Use
- ❖ Reliability
- ❖ Robustness
- ❖ Portability

# Metrics for NFRs

5

Property	Measure
Speed/Performance	<ol style="list-style-type: none"><li>1. Processed transactions/second</li><li>2. Response time</li><li>3. Screen refresh time</li></ol>

Requirements related to “Speed” can use different measures to quantify the goal

# Metrics for NFRs

6

Property	Measure
Size	<ol style="list-style-type: none"><li>1. K bytes</li><li>2. Number of function points</li></ol>

Requirements related to “Size” can use different measures to quantify the goal

# Metrics for NFRs

7

Property	Measure
Size	<ol style="list-style-type: none"><li>1. K bytes</li><li>2. Number of function points</li></ol>

Requirements related to “Size” can use different measures to quantify the goal

# Metrics for NFRs

8

Property	Measure
Reliability	<ol style="list-style-type: none"><li>1. Mean time to failure</li><li>2. Probability of unavailability</li><li>3. Rate of failure occurrence</li><li>4. Availability</li></ol>

Requirements related to “Reliability” can use different measures to quantify the goal



# Metrics for NFRs

9

Property	Measure
Robustness	<ol style="list-style-type: none"><li>1. Time to restart after failure</li><li>2. Percentage of events causing failure</li><li>3. Probability of data corruption on failure</li></ol>

Requirements related to “Robustness” can use different measures to quantify the goal

# Discussion on Metrics for NFRs

10

- ❖ With the help of these measures the NFRs can be verified quantitatively.
- ❖ It should also be noted that the cost of quantitatively verifying each NFR may be very high.

# Domain Requirements

11

- ❖ Requirements that come from the application domain and reflect fundamental characteristics of that application domain.
- ❖ These can be both the functional or non-functional requirements

# Domain Requirements

12

- ❖ These requirements, sometimes, are not explicitly mentioned.
- ❖ Domain experts find it difficult to convey domain requirements.
- ❖ Their absence can cause significant dissatisfaction.

# Domain Requirements

13

- ❖ Domain requirements can impose strict constraints on solutions. This is particularly true for scientific and engineering domains.
- ❖ Domain-specific terminology can also cause confusion.

# Domain Requirements: Example

14

- In a commission-based sales businesses, there is no concept of negative commission.  
However, if care is not taken novice developers can be lured into developing systems, which calculate negative commission

# Domain Requirements Examples

15

- Banking domain has its own specific constraints, for example, most banks do not allow over-draw on most accounts, however, most banks allow some accounts to be over-drawn.

# Inverse Requirements

16

- ❖ They explain what the system shall **not** do.
- ❖ Many people find it convenient to describe their needs in this manner.
- ❖ These requirements indicate the indecisive nature of customers about certain aspects of a new software product.



# Inverse Requirements: Example

17

- ❖ The system shall not use red color in the user interface, whenever it is asking for inputs from the end-user.

# Design and implementation constraints

- ❖ They are development guidelines within which the designer must work.
- ❖ These requirements can seriously limit design and implementation options.
- ❖ Can also have impact on human resources.

# Design and implementation constraints

- ❖ They are development guidelines within which the designer must work.
- ❖ These requirements can seriously limit design and implementation options.
- ❖ Can also have impact on human resources.

# Design and implementation constraints : Example

- ❖ The system shall be developed using the Microsoft .Net platform
- ❖ The system shall be developed using open source tools and shall run on Linux operating system.



# **THANK YOU**

Dr. Syed Muazzam Ali Shah  
[muazzam.ali@nu.edu.pk](mailto:muazzam.ali@nu.edu.pk)