

JAVA NESTED CLASSES(INNER CLASSES)

Several thin, white, parallel diagonal lines are positioned in the bottom right corner of the slide, extending from the bottom edge towards the top right.

- ▶ nested class is a class that is declared inside the class or interface.
- ▶ We use inner classes to logically group classes and interfaces in one place to be more readable and maintainable.
- ▶ **It can access all the members of the outer class, including private data members and methods.**

INTRO.

```
class Java_Outer_class{  
    //code  
    class Java_Inner_class{  
        //code  
    }  
}
```

SYNTAX OF INNER CLASS

1. Nested classes represent a particular type of relationship that is **it can access all the members (data members and methods) of the outer class**, including private.
2. Nested classes are used **to develop more readable and maintainable code** because it logically group classes and interfaces in one place only.
3. **Code Optimization:** It requires less code to write.

ADVANTAGE OF JAVA INNER CLASSES

- ▶ users need to program a class in such a way so that no other class can access it

NEED

- ▶ An inner class is a part of a nested class.
- ▶ Non-static nested classes are known as inner classes.

DIFFERENCE BETWEEN NESTED CLASS AND INNER CLASS IN JAVA

Several white lines of varying lengths and orientations are positioned in the bottom right corner of the slide, creating a modern, abstract design element.

- ▶ **Non-static nested class (inner class)**

- ▶ Member inner class
- ▶ Anonymous inner class
- ▶ Local inner class

- ▶ **Static nested class**

TYPES OF NESTED CLASSES

Type		Description
Member Inner Class		A class created within class and outside method.
Anonymous Class	Inner	A class created for implementing an interface or extending class. The java compiler decides its name.
Local Inner Class		A class was created within the method.
Static Nested Class		A static class was created within the class.
Nested Interface		An interface created within class or interface.

- ▶ A non-static class that is created inside a class.
- ▶ But outside a method.
- ▶ It is also known as a **regular inner class**.
- ▶ It can be declared with access modifiers like `public`, `default`, `private`, and `protected`.

MEMBER INNER CLASS

```
class Outer{  
    //code  
    class Inner{  
        //code  
    }  
}
```

SYNTAX

Several white lines of varying lengths and slopes are positioned in the bottom right corner of the slide, creating a modern, abstract graphic element.

```
class Outer{  
    private int data=30;  
    class Inner{  
        void msg(){    System.out.println("data is "+data); }  
    }  
    public static void main(String args[]){  
        Outer obj=new Outer();  
        Outer.Inner in=obj.new Inner();  
        in.msg();  
    } }  

```

EXAMPLE

- ▶ An object or instance of a member's inner class always exists within an object of its outer class.
- ▶ The new operator is used to create the object of member inner class with slightly different syntax.
- ▶ **SYNTAX:** OuterClassRef.**new** InnerClassConstructor();
- ▶ **Example:** obj.**new** Inner();

INTERNAL CODE

- ▶ The java compiler creates two class files in the case of the inner class.
- ▶ The Java compiler creates a class file named **Outer\$Inner** in this case.
- ▶ We must have to create the instance of the outer class.
- ▶ The inner class has the reference of Outer class that is why it can access all the data members of Outer class including private

INTERNAL CODE

```
import java.io.PrintStream;
class Outer$Inner
{
    final Outer this$0;
    Outer$Inner()
    { super();
      this$0 = Outer.this;
    }
    void msg()
    {
        System.out.println((new StringBuilder()).append("data is ")
                           .append(Outer.access$000(Outer.this)).toString());
    }
}
```

- ▶ Java anonymous inner class is an inner class without a name.
- ▶ And for which only a single object is created.
- ▶ An anonymous inner class can be useful when making an instance of an object with certain "extras" such as overloading methods of a class or interface, without having to actually subclass a class.
- ▶ A class that has no name is known as an anonymous inner class in Java.


ANONYMOUS INNER CLASS

► It should be used if you have to override a method of class or interface. Java Anonymous inner class can be created in two ways:

1. Class (may be abstract or concrete).
2. Interface.


```
abstract class Person{  
    abstract void eat();  
}  
class Test {  
    public static void main(String args[]){  
        Person p=new Person(){  
            void eat(){System.out.println("nice fruits");}  
        };  
        p.eat();  
    }  
}
```

EXAMPLE

- ▶ A class is created, but its name is decided by the compiler, which extends the Person class and provides the implementation of the eat() method.
 - ▶ An object of the Anonymous class is created that is referred to by 'p,' a reference variable of Person type.
- 
- A series of white diagonal lines of varying lengths and thicknesses are positioned in the bottom right corner of the slide, creating a modern, abstract graphic element.

```
import java.io.PrintStream;
static class Test$1 extends Person
{
    TestAnonymousInner$1(){}
    void eat()
    {
        System.out.println("nice fruits");
    }
}
```

INTERNAL CODE

```
interface Eatable{  
    void eat();  
}  
class Test1{  
    public static void main(String args[]){  
        Eatable e=new Eatable(){  
            public void eat(){System.out.println("nice fruits");}  
        };  
        e.eat();  
    }  
}
```

USING AN INTERFACE

- ▶ A class i.e., created inside a method, is called local inner class in java.
- ▶ Created inside a block.
- ▶ Sometimes this block can be a for loop, or an if clause.
- ▶ Local Inner classes are not a member of any enclosing classes.
- ▶ Local inner classes cannot have any access modifiers associated with them.
- ▶ They can be marked as final or abstract.
- ▶ These classes have access to the fields of the class enclosing it.

LOCAL INNER CLASS

```
public class local_o {  
    private int data=30;  
    void display(){  
        class Local{  
            void msg(){System.out.println(data);}  
        }  
        Local l=new Local();  
        l.msg();  
    }  
    public static void main(String args[]){  
        local_o obj=new local_o();  
        obj.display();  
    }  
}
```

EXAMPLE

```
import java.io.PrintStream;
class local_o$Local
{
    final local_o this$0;
    local_o$Local()
    {
        super();
        this$0 = Simple.this;
    }
    void msg()
    {
        System.out.println(localInner1.access$000(local_o.this));
    }
}
```

INTERNAL CODE

- 1) Local inner class cannot be invoked from outside the method.

RULES FOR JAVA LOCAL INNER CLASS

Several white lines of varying lengths and slopes are positioned in the bottom right corner of the slide, creating a modern, abstract design element.


```
class localInner2{  
    private int data=30;//instance variable  
    void display(){  
        int value=50  
        class Local{  
            void msg(){System.out.println(value);  
        }  
    }  
    Local l=new Local();  
    l.msg();  
}  
public static void main(String args[]){  
    localInner2 obj=new localInner2();  
    obj.display();  
}  
}
```

EXAMPLE

- ▶ A static class is a class that is created inside a class, is called a static nested class in Java.
- ▶ It cannot access non-static data members and methods.
- ▶ It can be accessed by outer class name.
- ▶ It can access static data members of the outer class, including private.
- ▶ The static nested class cannot access non-static (instance) data members

STATIC NESTED CLASS

```
class Outer{  
    static int data=30;  
    static class Inner{  
        void msg(){System.out.println("data is "+data);}  
    }  
    public static void main(String args[]){  
        Outer.Inner obj=new Outer.Inner();  
        obj.msg();  
    }  
}
```

EXAMPLE

```
public class Outer2{  
    static int data=30;  
    static class Inner{  
        static void msg(){System.out.println("data is "+data);}  
    }  
    public static void main(String args[]){  
        Outer2.Inner.msg();  
        //no need to create the instance of static nested class  
    }  
}
```

EXAMPLE

```
import java.io.PrintStream;
static class TestOuter1$Inner
{
    TestOuter1$Inner(){}
    void msg(){
        System.out.println((new StringBuilder()).append("data is ")
            .append(TestOuter1.data).toString());
    }
}
```

INTERNAL CODE