ProQuality
Conference

Commit Notations

for Quality and Testability

Ilyas Landikov

TDD Software Engineer

- 13+ years in IT
- Embedded, telecom, web projects

Agenda

1. Context
2. Why?
3. Commit notations
4. Branches and PR’s
5. Benefits
6. Use in CI/CD
7. Q&A

Context

obsidian-tasks

1. Thanks to Clare Macrae
2. Task management plugin
   - For Electron-based browser (Obsidian)
   - Open source
   - Query engine + edit modal
   - TypeScript + Svelte
   - 2.3M downloads
3. TDD + Pair programming with Clare Macrae
   - No QA team/role

Why?

- Colleagues have questions seeing my commits
- Just sharing
- Being clever and smart, saving time

Conventional Commits

- Message: `<type>: <description>`
- `<type>: fix, feat, chore, docs, refactor, test,` etc.
- `refactor: rename variables`
- https://www.conventionalcommits.org/

Arlo’s Commit Notation

- Message: `<risk> <type + visibility> <message>`
- `<type>: r, b/B, f/F, d/D,` etc.
- `<risk>: . ^ ! @`
- `^ r rename variables`
- https://github.com/RefactoringCombos/ArlosCommitNotation

Conventional Commits... with a Twist =)

<type>: <risk> <description>

```
- <risk>
    - . automated action
        - refactor: . rename variable
    - - unit tested
        - feat: - allow quantity to be zero
    - ! manual tested or integration tested
        - feat: ! get location after loading
    - @ cannot be tested
    - ** breaks unit tests
    - /none/
```

Show Me the... Numbers

obsidian-tasks

2022/12 - 2025/05:

- 1539 commits
- 1530 conventional commits
- 1295 conventional commits with risks:
  - automated: 42%
  - unit tested: 46%
  - manual tested: 11%
  - breaking unit tests: <1%
  - cannot be tested: <1%

Branches and PRs

```
refactor: - remove comments                    origin & feat-include-...
feat: - better explanation and error messages from include instructions
test: - check error message for includes
test: - text explanation of nested includes
test: - test nested include instructions
feat: - teach query to parse multi-line include instructions
feat: - give a meaningful error for non-existent includes
test: - test layout instruction
test: - test query source
feat: - accept any single-line include instruction
feat: - accept `include not_done` instruction
test: - add failing test for include instruction
docs: document includes
```

```
refactor: . rename variable
refactor: - remove unused part of an object
refactor: . convert parameters to object
refactor: - remove unused parameter and code
refactor: ! use local anonymous client
refactor: . move function to dedicated file
refactor: ! reuse queryAsAnonymousUser()
refactor: ! add resolver parameter
refactor: ! add type assertion and generic parameter
refactor: ! get property with a string value
refactor: . add query parameter
refactor: - add TInput generic parameter
refactor: ! extract queryAsAnonymousUser()
refactor: . rename variable
refactor: - remove unused interface
```

Use in CI/CD

Quality gate!

- Only `risk=.` commits
  - Release
- At least `risk=-` commit
  - Manual exploratory testing
  - Release
- At least 1 `risk=!` commit
  - Manual testing
  - Integration testing
  - Release

Pros & Cons

Reduced times of manual tests

Branch risk/safety

Branch separation

Discipline

Q&A

Feel free to contact me:
linkedin: ilandikov

Rate the event

How to find us

PRO
QUALITY