



Borcelli Engineering

5555 Peachtree Rd NE Ste 145-2085

Atlanta GA 30050

555-555-5555

SUBMITTAL & SPEC SHEET PACKET

October 25, 2025

borcellieng.com

Generated using Submittal & Spec Sheet Builder for WordPress

Table of Contents

Overview

..... 3

Model Specifications

24x24 Fine Fissured, White — Acoustic Ceilings 5

24x48 Smooth Tegular, White — Acoustic Ceilings 6

24x24 Micro-Perforated, Silver — Acoustic Ceilings 7

15/16" Exposed Tee, White — Suspension Systems 8

12x24 Porcelain, Grey — Ceramic & Porcelain Tile 9

24x24 Porcelain, White — Ceramic & Porcelain Tile 10

3x12 Ceramic Subway, White — Ceramic & Porcelain Tile 11

Generated using [Submittal & Spec Sheet Builder](#) for WordPress

Summary

This packet contains 7 model(s) across 3 products.

Acoustic Ceilings (3 models)

QTY	TYPE	MODEL	KEY SPECIFICATIONS	NOTES
10	Mineral Fiber Tiles	24x24 Fine Fissured, White	Size: 24x24 in; Thickness: 5/8 in; Nrc: 0.70	
5	Mineral Fiber Tiles	24x48 Smooth Tegular, White	Size: 24x48 in; Thickness: 3/4 in; Nrc: 0.80	
1500	Metal Panels	24x24 Micro-Perforated, Silver	Size: 24x24 in; Material: Aluminum; Perforation: Micro	

Suspension Systems (1 model)

QTY	TYPE	MODEL	KEY SPECIFICATIONS	NOTES
1	Grid — Exposed Tee	15/16" Exposed Tee, White	Face_width: 15/16 in; Material: Steel; Finish: Baked Enamel	

Ceramic & Porcelain Tile (3 models)

QTY	TYPE	MODEL	KEY SPECIFICATIONS	NOTES
1	Floor Tile	12x24 Porcelain, Grey	Size: 12x24 in; Thickness: 10 mm; Pei: IV	
1	Floor Tile	24x24 Porcelain, White	Size: 24x24 in; Thickness: 10 mm; Pei: IV	
1	Wall Tile	3x12 Ceramic Subway, White	Size: 3x12 in; Thickness: 8 mm; Finish: Gloss	

24x24 Fine Fissured, White

Quantity: 10

Technical Specifications

Size	24x24 in
Thickness	5/8 in
Nrc	0.70
Cac	35
Fire rating	Class A
Edge	Square Lay-In
Notes	Low VOC

24x48 Smooth Tegular, White

Quantity: 5

Technical Specifications

Size	24x48 in
Thickness	3/4 in
Nrc	0.80
Cac	37
Fire rating	Class A
Edge	Tegular

24x24 Micro-Perforated, Silver

Quantity: 1500

Technical Specifications

Size	24x24 in
Material	Aluminum
Perforation	Micro
Nrc	0.85 (with pad)
Finish	Powder Coat
Fire rating	Class A

15/16" Exposed Tee, White

Technical Specifications

Face width	15/16 in
Material	Steel
Finish	Baked Enamel
Seismic	I-III
Standard	ASTM C635/C636

12x24 Porcelain, Grey

Technical Specifications

Size	12x24 in
Thickness	10 mm
Pei	IV
Cof	≥0.60 (wet)
Water absorption	<0.5%
Standard	ANSI A137.1
Notes	Rectified

24x24 Porcelain, White

Technical Specifications

Size	24x24 in
Thickness	10 mm
Pei	IV
Cof	≥0.60 (wet)
Water absorption	<0.5%
Standard	ANSI A137.1

3x12 Ceramic Subway, White

Technical Specifications

Size	3x12 in
Thickness	8 mm
Finish	Gloss
Water absorption	10–20%
Standard	ANSI A137.1