

# Your Way of qPCR

## qTOWER<sup>3</sup> Product Family



# qTOWER<sup>3</sup> Product Family

Redefining excellence:

The qTOWER<sup>3</sup> product family sets new standards of flexibility and precision – for all real-time PCR applications.

The quantitative polymerase chain reaction (qPCR) is an established method for the highly sensitive detection and quantification of DNA or RNA. The measuring principle is based on fluorescent signals, which, cycle by cycle, capture the presence of the existing target sequence in real time. The key features of this detection method are outstanding high-performance optics as well as excellent temperature uniformity over 96 or up to 384 samples.

The qTOWER<sup>3</sup> product family guarantees well-founded real-time PCR results as it benefits from peerless temperature control precision in the sample block regardless of the number of samples used. The patented high-performance optics guarantee the outstanding homogeneous excitation and illumination of all individual samples. The qTOWER<sup>3</sup> product family achieves unique flexibility with its proven filter module equipment, which can be freely configured and expanded at any time, and enables up to six-fold multiplexing.



qTOWER<sup>3</sup> 84

## qTOWER<sup>3</sup> Product Family

Your Way of qPCR



qTOWER³

qTOWER³ touch

## qTOWER<sup>3</sup>

See, marvel, experience:

The performance of the new real-time PCR thermal cycler qTOWER<sup>3</sup> impresses across the board.

The patented fiber-optic shuttle system with its unique light source, composed of four high-performance LEDs, guarantees the ideal excitation of known fluorescent dyes up to the deep red range. In the process, the detection module can accept up to six different color filter modules. The retrofitting option ensures that users can also integrate future innovative developments from Analytik Jena.

The proven silver block technology of the qPCR cycler offers outstanding control precision of  $\pm 0.1^\circ\text{C}$  over the entire 96 well block in 0.2 ml format. Thanks to the gradient function, the device can be optimally adapted to new assays. The qTOWER<sup>3</sup> is available either as a stand-alone device with integrated touchscreen operation (10") or as a computer-aided system. The software contains a broad spectrum of optimized analysis algorithms, including absolute and relative quantification, ddCt method, PCR efficiency, allelic discrimination, end-point detection, and melting curve and protein analysis.



## qTOWER<sup>3</sup>

Get in *touch* with High-Class qPCR

### qPCRsoft Package



### Maximum Flexibility



### Ideal Real-Time PCR Signals



### Optimal Thermal Conductivity



### qPCRsoft Package for Convenient Control and Operation

- **Convenient:** Stand-alone operation via integrated tablet control (10") and/or comprehensive PC control
- **Transparent:** No costs for software licenses or updates
- **Universal:** Covers the entire spectrum from a simple representation of Ct values to the ddCt method and multiplate analysis
- **Multilingual:** Available in multiple languages, including German

### Expandable Filter Module System for Maximum Flexibility

- **Practical:** The twelve color, FRET, and protein modules can be retrofitted or exchanged within five minutes
- **Future-proof:** Thanks to new filter modules, adaptable to new applications at any time
- **Durable:** 10-year long-term guarantee for high-performance optical components

### Patented Fiber-optic System for Ideal Real-Time PCR

- **Efficient:** Minimal scan times of 6 seconds for up to six-fold multiplexing
- **Innovative:** New light source with four long-stability LEDs (RGWB) with no preheating time and a long service life
- **Brilliant:** Ideal illumination and excitation of all 96 samples with no edge effects

### High-Quality Silver Sample Block for Optimal Thermal Conductivity

- **Fast:** Heating rates of 8 °C/s, cooling rates of 6 °C/s
- **Unrivalled:** Ideal temperature homogeneity and unmatched control precision ( $\pm 0.1$  °C)
- **Precise:** Programming of integer temperatures from column to column of the 96 well sample block using the Linear Gradient Tool (max. range 40 °C).



# Patented Fiber-Optic Shuttle System

For the ideal reproducibility and maximum data security of all real-time PCR results, the integrated high-performance optics guarantee the homogeneous excitation of each individual sample and the reliable recording of the emitted fluorescent signals.

In the application area of quantitative real-time PCR, a wide range of fluorescent dyes with different characteristics are used. In order to optimally excite each of these dyes across a large spectrum, the qTOWER<sup>3</sup> has a light source with four different-colored, long-life LEDs (RGBW). This ensures that each dye used in a real-time PCR experiment achieves the best possible quantum yield.

Special, highly sophisticated multiplex applications with up to six fluorescent-labeled probes from blue to the near-infrared range can be handled without difficulty. Fiber-optic system (FOS): The optical unit from a shuttle system with eight high-performance fibers ensures an extremely fast read-out from the 96 well plate in just 6 seconds – regardless of the number of dyes to be measured.

All components of the high-performance fiber optics have a 10-year long-term guarantee.

- Patented high-performance optics with eight optical fibers and four different-colored LEDs
- Optimal homogeneous excitation and detection in each of the 96 wells
- Special plus: Read-out of a 96 well microplate in just 6 seconds – regardless of the number of dyes
- No edge effects – no need for a passive reference

## Maximum Flexibility

The color filter equipment of the qTOWER<sup>3</sup> family can be freely configured and, depending on the application, can also be adapted to intercalating or protein-binding dyes and hydrolysis and hybridization probes (FRET probes).

The retrofitting option makes the device system particularly future-proof: Additional color, FRET, or protein modules can be integrated at any time to further expand the range of applications.

All the various filter modules contain an optimized combination of excitation and emission filters which, in combination with the light source, enables the ideal detection of a large number of commercially available fluorescent dyes.

- Freely configurable selection of color filters
- Can accept up to six different color, FRET, or protein modules
- Use of intercalating dyes, hydrolysis or hybridization probes, and protein-binding dyes

## Innovative Silver Block Technology

Aside from the optical components for the detection of real-time signals, amplification plays a key role in real-time PCR. More than 25 years of experience in the field of thermal cyclers offer the promise of first-class quality with the qTOWER<sup>3</sup>.

The sample block forms the basis for the reliable performance of quantitative real-time PCR in the qTOWER<sup>3</sup> and the qTOWER<sup>3</sup> *touch*. To ensure the best-possible results and an outstanding transfer of energy to the sample, the thermal block is made of gold-coated silver. As a result, the qTOWER<sup>3</sup> is distinguished by excellent temperature control precision of  $\pm 0.1$  °C (over 96 wells) and first-class heating rates of up to 8 °C/s. This combination makes the entire system absolutely ideal for any real-time PCR application.

- Quantitative real-time PCR in the proven 0.2 ml format with 96 wells
- Innovative silver block with outstanding ramping rates of up to 8 °C
- Excellent temperature control of  $\pm 0.1$  °C across the entire sample block
- Gradient function over 12 columns with a 40 °C spread using linear programming (Linear Gradient Tool)

To ensure the highest specificity for different assays, the device is equipped with a gradient function with a spread of up to 40 °C. Instead of simply setting lower and upper limits, the Linear Gradient Tool (LGT) allows different integer temperature levels to be entered in relation to the calculated annealing temperature of the primers – further evidence of the simple, intuitive operation of the qTOWER<sup>3</sup>.

To avoid condensation and the resulting loss of samples, the device system is fitted with a motorized heated lid. This can be variably set to up to 110 °C and guarantees optimal contact pressure on the sample vessels throughout the real-time PCR run, regardless of the consumable used.

The open platform makes it possible to use low profile (0.1 ml) and standard profile (0.2 ml) plastic. Non-, semi- and full-skirted qPCR plates can likewise be used.







# Intuitive Operation and Automatic Analysis

The qTOWER<sup>3</sup> can be intuitively and easily controlled both through a desktop PC or laptop and by means of an integrated tablet. A comprehensive package of individual analysis methods and helpful additional functions complete the entire system.

The qPCRsoft control and analysis software proves itself to be flexible and user-friendly. The logical, clear arrangement of all the tools, the intuitive handling, and last but not least the parameter-oriented memory and programming concept make the software easier to use. During a live run, the data from previous experiments can be simultaneously analyzed without difficulty.

To ensure that operation is as simple as possible, many of the steps occur automatically – such as threshold calculation for determining Ct values or possible standard curves and PCR efficiencies. Further analyses can likewise be conducted automatically, such as absolute or relative quantifications, or the ddCt method (with or without reference to PCR efficiency). qPCRsoft also includes analysis methods for probe-based, allelic discrimination, e.g. for the identification of point mutations and the use of a positive/negative analysis via the end-point detection of samples.

- qPCRsoft: User-friendly and clearly structured
- Integrated analysis algorithms: Absolute and relative quantification, ddCt method, genotyping, end-point detection, and melting curve, protein, and multiplate analysis.
- User administration with three authorization levels
- MIQE-compliant documentation
- License-free, free updates



qPCRsoft





qPCRsoft *touch*.

### Get in *touch* with qTOWER<sup>3</sup>

The strong performance of the qTOWER<sup>3</sup> can optionally be supplemented by a highly innovative operation concept. The qTOWER<sup>3</sup> *touch* is a modern stand-alone system that does not require any external control. The integrated 10" tablet leaves nothing to be desired when it comes to planning and conducting experiments.

The touchscreen operation impresses with its simple, intuitive menu navigation which enables cycle programming, online monitoring, and the final determination of Ct values. The data files are compatible with the comprehensive PC software at all times and allow subsequent analyses to be conducted without difficulty.


Regardless of whether it is the qTOWER<sup>3</sup> or the qTOWER<sup>3</sup> *touch* – the real-time PCR thermal cyclers from Analytik Jena are ideal and reliable tools for everyday laboratory work.

## Impressive Performance – qTOWER<sup>3</sup>


The combination of unique optics and a high-quality silver block with incomparably precise temperature control ensures ideal amplification results. This makes the qTOWER<sup>3</sup> an unbeatable partner for quantitative real-time PCR applications.

**Fig. 1:**

Amplification of 10 orders of magnitude with automatic determination of the standard curve including important parameters like  $R^2$  and PCR efficiency.



Logarithmic view




Standard curve


The example of human genomic DNA amplification shows an optimal linearity over 10 orders of magnitude from  $10^9$  to  $10^0$  copies. Accordant PCR efficiency of 100 % with  $R^2 > 0.999$  was automatically determined by qPCRsoft.

**Fig. 2:**

Amplification of an *E.coli* specific target sequence in 96 wells. The main ct value of 12.99 with a standard deviation of 0.07 was determined automatically.



Linear view




Logarithmic view


The single excitation and detection of each well avoids the often observed edge effects and allows excellent, homogeneous amplification plots over the entire 96 well block with a standard deviation below 0.07.

**Fig. 3:**

Examination of 9 patients with the FTD ACE diagnostic kit. The calculation of the viral load is performed automatically by generating a standard curve.



Linear view



Melting curve analysis

The flexible filter configuration of qTOWER<sup>3</sup> ensures verifications of a broad spectra of application fields, e.g. the Fast-Track ACE Kit for detection of adenovirus, cytomegalovirus, Epstein-Barr virus and internal control.



## qTOWER<sup>3</sup> 84

### Enhance Your Throughput – A New Standard for Speed and Precision in High-throughput qPCR

With steadily growing sample volumes and new options for molecular biology experiments, the requirements for quantitative real-time PCR are changing. The transition to the multiwell format with 384 samples opens up new application areas in gene expression, mutation analysis, and diagnostics.

The qTOWER<sup>3</sup> 84 includes all of the strengths of the qTOWER<sup>3</sup> product family and transfers its precise performance to the 384 well high-throughput format. The proven high-performance optics have been expanded to 16 fibers and enable an ultra-fast read-out time of just 6 seconds for a complete 384 well plate – regardless of the number of filters used. Here, too, the system benefits from the complete flexibility of freely configurable filter equipment, allowing it to be adapted to any application. The innovative light source with four different-colored LEDs also enables read-outs of very small sample volumes, which play an increasingly important role in the high-throughput format along with existing factors like speed and experimental precision.

The high-quality aluminum block guarantees precise, accurate conductivity combined with unmatched temperature uniformity across the entire sample set. A peerless feature of the qTOWER<sup>3</sup> 84 G is the gradient over a total of 24 columns, which can be programmed using the proven Linear Gradient Tool. The license-free, comprehensive qPCRsoft package completes the system, and a detailed analysis can be easily obtained even in the 384 well format thanks to analysis algorithms which are already integrated.



## qTOWER<sup>3</sup> 84

The next Level of qPCR



#### qPCRsoft Package for Convenient Control and Operation

- **Convenient:** Comprehensive PC control
- **Transparent:** No costs for software licenses or updates
- **Universal:** Covers the entire spectrum from a simple representation of Ct values to the ddCt method and multiplate analysis
- **Multilingual:** Available in multiple languages, including German



#### Patented Fiber-optic System for Ideal Real-Time PCR

- **Efficient:** Minimal scan times of 6 seconds for up to six-fold multiplexing
- **Innovative:** New light source with four long-stability LEDs (RGWB) with no preheating time and a long service life
- **Brilliant:** Ideal illumination and excitation of all 384 samples with no edge effects



#### Expandable Filter Module System for Maximum Flexibility

- **Practical:** The twelve color, FRET, and protein modules can be retrofitted or exchanged within five minutes
- **Future-proof:** Thanks to new filter modules, adaptable to new applications at any time
- **Durable:** 10-year long-term guarantee for high-performance optical components



#### High-Quality Aluminium Sample Block for Optimal Thermal Conductivity

- **Fast:** Minimal scan times of six seconds for up to six-fold multiplexing
- **Unrivalled:** Ideal temperature homogeneity and unmatched control precision ( $\pm 0.1^\circ\text{C}$ )
- **Precise:** Programming of integer temperatures for 24 columns of the 384-well sample block using the Linear Gradient Tool (max. range  $24^\circ\text{C}$ ).



# High-Performance System for High Throughput

The qTOWER<sup>3</sup> 84 achieves the next level of a powerful DNA detection system by increasing qPCR throughput while simultaneously miniaturizing individual reactions.

The centerpiece of the device is extremely precise and reliable temperature control, together with optical signal recognition for all 384 samples that are used for qualitative and quantitative DNA characterization.

The proven fiber-optic shuttle system in the qTOWER<sup>3</sup> has been perfectly adapted to the 384 well format and expanded to 16 scanning fibers. In combination with an outstanding, long-life source of light from four different LEDs, an extremely fast read-out of the fluorescences in just six seconds is guaranteed for a complete 384 well plate with up to six-fold multiplexing.

The 384 well aluminum block with its excellent temperature uniformity is the foundation of the qTOWER<sup>3</sup> 84 and is indispensable for the extremely precise and reliable amplification of PCR products. These reaction parameters guarantee the high specificity and yield of the reaction and are directly related to the speed and precision of the result. The excellent control precision of the sample block ensures homogeneous heat distribution across all the wells of a plate, which ultimately means the highest possible reproducibility from well to well and from cycle to cycle.

- Patented high-performance optics with 16 optical fibers and four different-colored LEDs
- Optimal homogeneous excitation and detection in each of the 384 wells
- Special plus: Read-out of a 384 well microplate in just 6 seconds – regardless of the number of dyes
- No edge effects – no need for a passive reference

- Quantitative real-time PCR in the high-throughput format with 384 wells
- Proven aluminum block with outstanding ramping rates of up to 4 °C
- Excellent temperature uniformity of  $\pm 0.15$  °C across the entire sample block
- Gradient function over 24 columns with a 24 °C spread using linear programming (Linear Gradient Tool)






## Complete System – Everything from a Single Source – Sample Processing at the Highest Level

Precise results for quantitative real-time PCR in high-throughput format with 384 samples require an accurate sample setup, which involves substantial time and effort.

### Meet Your Throughput Needs

To standardize and improve the precision and reproducibility of real-time PCR reactions, the use of a pipetting robot is recommended. With its large number of liquid-handling systems, Analytik Jena offers the perfect solution for daily pipetting routines.


For example, GeneTheatre greatly simplifies all pending pipetting tasks in the laboratory and allows for full automation. The standardization of processes significantly reduces errors with reactions involving 10 or 5 microliter batch volumes – regardless of the experience and skill of the user. In combination with its qTOWER<sup>3</sup> 84, as well as its diverse reagent portfolio as a further option, Analytik Jena offers a customized complete system here that can be tailored to individual application, throughput, and capacity requirements.



## Impressive Performance - qTOWER<sup>3</sup> 84


The reliable device technology ensures a convincing demonstration of real-time PCR results in 384 well format. In addition to the lightning read-out speed the qTOWER<sup>3</sup> 84 represents the right choice for high-throughput real-time PCR application.

**Fig. 1:**  
Amplification of an *E. coli* specific target gene sequence in 384 wells. The main Ct value of 13.37 with a standard deviation of 0.18 was determined automatically



The single excitation and detection of each well avoids the often observed edge effects and allows excellent, homogeneous amplification plots over the entire 384 well block.

**Fig. 2:**  
Amplification of 5  $\mu$ l 10  $\mu$ l, 15  $\mu$ l and 20  $\mu$ l qPCR reactions volume. By using qPCRsoft a main Ct value of  $26.22 \pm 0.07$  and a main melting point of  $79.88 \pm 0.08$  °C was determined.



Also regarding to the used PCR reaction volume the qTOWER<sup>3</sup> shows an enormous capacity. In a range of 5  $\mu$ l to 20  $\mu$ l a standard deviation of only 0.07 for Ct values and 0.08 °C for melting temperature can be achieved.

# Technical Data

	qTOWER <sup>3</sup> and qTOWER <sup>3</sup> touch	qTOWER <sup>3</sup> 84
Thermal block	Silver sample block with gold coating	Aluminum, special alloy
Block capacity	96 wells in 0.2 ml format	384 wells
Sample volume	5 - 80 µl	2 - 30 µl (5 - 20 µl recommended)
Heating	8 °C/s	4 °C/s
Cooling	6 °C/s	2 °C/s
Temperature setting range	4 - 99 °C	
Temperature control precision	± 0.1 °C	
Temperature uniformity	55 °C ± 0.15 °C after 15 sec	
Max. / min. gradient	qTOWER <sup>3</sup> G and qTOWER <sup>3</sup> G touch: 40 °C/0.1 °C	qTOWER <sup>3</sup> 84 G: 24 °C/0.1 °C
Heated lid		
Lid temperature	30 °C to 110 °C	
Contact pressure	30 kg, automated	
qPCR application		
Sensitivity	1 copy of the target sequence	
Dynamic range	10 log levels	
Optics		
Measuring principle	Fiber-optic shuttle system with 8-fold scanner and filter modules	Fiber-optic shuttle system with 16-fold scanner and filter modules
Light source	4 long-life, high-performance LEDs (RGBW)	
Detector	Highly sensitive PMT (photo multiplier tube)	
Color modules	12 color, FRET, and protein modules 6 positions in the device	
Read-out time	6 seconds for 96 wells regardless of the number of filters	6 seconds for 384 wells regardless of the number of filters
Operation		
Software	Choice between PC or stand-alone version qTOWER <sup>3</sup> touch: 10" tablet, color	PC software
Dimensions		
Weight	30 kg	
Size (width x height x depth)	275 mm x 585 mm x 275 mm	
Additional technical data		
Interfaces	PC connection: USB Tablet: USB for data transfer, barcode reader	PC connection: USB
Noise emission	45 db	
Warranty	2 years warranty on device system 10 years long-term warranty on high performance optics	

# Order Information

## Parameters color module

Description/Order number	Excitation	Emission	Example fluorescent dyes*
Color module 1, Order number: 844-00520-0	470 nm	520 nm	FAM <sup>TM</sup> , Sybr <sup>®</sup> Green, Alexa488 <sup>®</sup>
Color module 2, Order number: 844-00521-0	515 nm	545 nm	JOE <sup>TM</sup> , HEX <sup>TM</sup> , VIC <sup>®</sup> , YakimaYellow <sup>®</sup>
Color module 3, Order number: 844-00522-0	535 nm	580 nm	TAMRA <sup>TM</sup> , DFO <sup>TM</sup> , Alexa546 <sup>®</sup> , NED <sup>TM</sup>
Color module 4, Order number: 844-00523-0	565 nm	605 nm	ROX <sup>TM</sup> , TexasRed <sup>®</sup> , Cy3.5 <sup>®</sup>
Color module 5, Order number: 844-00524-0	630 nm	670 nm	Cy5 <sup>®</sup> , Alexa633 <sup>®</sup> , Quasar670 <sup>TM</sup>
Color module 6, Order number: 844-00525-0	660 nm	705 nm	Cy5.5 <sup>®</sup> , LightCycler Red <sup>®</sup>
FRET module 1, Order number: 844-00526-0	470 nm	580 nm	FAM <sup>TM</sup> (donor) / TAMRA <sup>TM</sup> (acceptor)
FRET module 2, Order number: 844-00527-0	470 nm	670 nm	FAM <sup>TM</sup> (donor) / Cy5 <sup>®</sup> (acceptor)
FRET module 3, Order number: 844-00528-0	470 nm	705 nm	FAM <sup>TM</sup> (donor) / Cy5.5 <sup>®</sup> (acceptor)
FRET module 4, Order number: 844-00529-0	515 nm	670 nm	JOE <sup>TM</sup> (donor) / Cy5 <sup>®</sup> (acceptor)
FRET module 5, Order number: 844-00531-0	470 nm	605 nm	FAM <sup>TM</sup> (donor) / ROX <sup>TM</sup> (acceptor)
Color modul Protein 1, Order number: 844-00530-0	490 nm	580 nm	SYPRO <sup>®</sup> Orange

\* The Color or FRET modules can be ordered separately. The qTOWER<sup>3</sup>/84 can be equipped with up to 6 modules.

Yakima Yellow is registered trademark of Epoch Biosciences, Inc. Cy is a trademark of GE Healthcare. FAM, HEX, JOE, VIC, TAMRA, NED and ROX are trademarks of Applied Biosystems Corporation or its subsidiaries in the US and/or certain other countries. SYBR, Alexa Fluor, SYPRO and Texas Red are registered trademarks of Molecular Probes, Inc. TaqMan and LightCycler are registered trademarks of Roche Group, Inc. Quasar Dyes are trademarks of Biosearch Technologies Inc. DFO<sup>TM</sup> is a trademark of Eurogentec S.A. Windows and Excel are trademarks of Microsoft Corporation.

## Corresponding Products

Order number	Description
<b>qPCR reagents</b>	
845-AS-1310100	innuMIX qPCR SyGreen Sensitive - 100 reactions
845-AS-1310200	innuMIX qPCR SyGreen Sensitive - 200 reactions
845-AS-1310500	innuMIX qPCR SyGreen Sensitive - 500 reactions
845-AS-1320100	innuMIX qPCR DSGreen Standard - 100 reactions
845-AS-1320200	innuMIX qPCR DSGreen Standard - 200 reactions
845-AS-1320500	innuMIX qPCR DSGreen Standard - 500 reactions
<b>Plastics and Accessories</b>	
844-70036-0	96 Well PCR Plate (0.2 ml; HP), non-skirted, white - 100 pieces
844-70037-0	96 Well PCR Plate (0.2 ml; HP), half-skirted, white - 100 pieces
844-70038-0	96 Well PCR Plate (0.2 ml; LP), full-skirted, white - 100 pieces
844-70045-0	Optical sealing foil (77 x 140 mm), transparent, peeling - 100 pieces
844-70086-0	Optical sealing foil (77 x 140 mm), adhesive, transparent, peeling able - 100 pieces
844-70087-0	8 Well Strip (0.2 ml; HP), white without lid - 120 pieces
847-0501001102	RoboStrip <sup>®</sup> 8 well strip low profile (0.1 ml) polypropylene white incl. sealing foil - 125 Strips

# qTOWER<sup>3</sup> Product Family

## To Fit Your Laboratory Needs

qTOWER <sup>3</sup> Product Family	qTOWER <sup>3</sup>	qTOWER <sup>3</sup> G	qTOWER <sup>3</sup> touch	qTOWER <sup>3</sup> G touch	qTOWER <sup>3</sup> 84	qTOWER <sup>3</sup> 84 G
						
Order number	<b>844-00553-2</b> Base unit incl. Color module 1	<b>844-00554-2</b> Base unit incl. Color module 1	<b>844-00555-2</b> Base unit incl. Color module 1	<b>844-00556-2</b> Base unit incl. Color module 1	<b>844-00508-2</b> Base unit	<b>844-00509-2</b> Base unit
Sample block	Silver sample block with gold coating	Silver sample block with gold coating	Silver sample block with gold coating	Silver sample block with gold coating	Aluminum block special alloy	Aluminum block special alloy
Block capacity	96 wells in 0.2 ml format	96 wells in 0.2 ml format	96 wells in 0.2 ml format	96 well à 0.2 ml	384 wells	384 wells
Reaction volume	5 - 80 µl	5 - 80 µl	5 - 80 µl	5 - 80 µl	2 - 30 µl (5 - 20 µl recommended)	2-30 µl (5 - 20 µl recommended)
Heating	Max. 8 °C/s	Max. 8 °C/s	Max. 8 °C/s	Max. 8 °C/s	Max. 4 °C/s	Max. 4 °C/s
Cooling	Max. 6 °C/s	Max. 6 °C/s	Max. 6 °C/s	Max. 6 °C/s	Max. 2 °C/s	Max. 2 °C/s
Temperature uniformity	55 °C ± 0.15 °C after 15 s	55 °C ± 0.15 °C after 15 s	55 °C ± 0.15 °C after 15 s	55 °C ± 0.15 °C after 15 s	55 °C ± 0.15 °C after 15 s	55 °C ± 0.15 °C after 15 s
Gradient	-	0.1 °C - 40 °C over 12 columns Linear Gradient Tool	-	0.1 °C - 40 °C over 12 columns Linear Gradient Tool	-	0.1 °C - 24 °C over 24 columns Linear Gradient Tool
Control	qPCRsoft package for PC	qPCRsoft package for PC	Stand-alone version with 10" touchscreen display incl. qPCRsoft package for PC	Stand-alone version with 10" touchscreen display incl. qPCRsoft package for PC	qPCRsoft package for PC	qPCRsoft package for PC
Filter configuration	Flexible filter configuration: 6 positions in the device	Flexible filter configuration: 6 positions in the device	Flexible filter configuration: 6 positions in the device	Flexible filter configuration: 6 positions in the device	Flexible filter configuration: 6 positions in the device	Flexible filter configuration: 6 positions in the device

### Headquarters

Analytik Jena AG  
Konrad-Zuse-Str. 1  
07745 Jena · Germany

Phone +49 3641 77 70  
Fax +49 3641 77 9279  
info@analytik-jena.com  
www.analytik-jena.com

Pictures: Analytik Jena AG  
Subject to changes in design and scope of delivery as well as further technical development.

en - 01/2018 - 844-MA146-2-B  
Forster & Bornes GmbH & Co. KG  
© Analytik Jena AG