

WEIGHTLAB INSTRUMENTS

HIGH SPEED MICRO CENTRIFUGE

1. Intuitive simple interface for fast and convenient setting
2. Lid lock safety - automatically unlocks after operation is complete
3. One-touch RPM / RCF conversion
4. Digital display with speed and time display
5. Suitable for use in hoods or cold rooms
6. Optional Mini Hematocrit Rotor and PCR strip rotor
7. Maximum volume of 12 x 1.5 / 2 ml
8. Unbalance detector with automatic cut-off for safe operation
9. Brushless DC motor for maintenance-free performance



Specifications	WN-CM15N
Rotor Capacity	12 x 1.5ml / 2.0 ml microtubes
Optional Rotor Options	2 PCR Strips
Maximum RPM / RCF	500 - 15000 / 15596 g
Operating Time	1 - 99 minutes & continuous mode
Display	Digital screen
Unbalance detector	When a sample is placed in the device in a way that disrupts the balance, it detects the error and automatically shuts down the process.
Noise Level	< 60 db
Rotor	Kapaklı rotor
Motor Type	(BLDC) DC motor
Acceleration Time	65 ± 2 seconds
Deceleration Time	55 ± 2 seconds
Dimensions (L x W x H)	190 x 120 x 270 mm
Adaptors (standard package contents)	0.1 / 0.2 ml /0.5 ml micro tube adaptor