

CO331: Network and Web Security

Tutorial 6: Code review for PHP and SQLI*

February 13, 2018

For each fragment of PHP code that follows:

- Find an SQL injection vulnerability.
- Write an exploit that delivers the requested payload.
- Fix the vulnerabilities in the PHP code that makes the SQL injection possible.

The database server runs MySQL and contains a `users` table that was created with the following SQL command:

```
CREATE TABLE users (  
  userid INT(4) NOT NULL AUTO_INCREMENT PRIMARY KEY,  
  username VARCHAR(30) NOT NULL UNIQUE,  
  password VARCHAR(30) NOT NULL,  
  forename VARCHAR(20) NOT NULL,  
  surname VARCHAR(20) NOT NULL  
);
```

1. The payload for your SQL injection attack should log in the attacker with the username `admin`. Assume that the `login()` function is defined elsewhere, and logs in the user with the username provided.

```
1 <?php  
2 $u = mysql_real_escape_string($_GET['username']);  
3 $p = $_GET['password'];  
4 $q = "SELECT * FROM users WHERE (username = '$u') AND (password = '$p')";  
5 $result = mysql_query($q) or die(mysql_error());  
6 $matching_users = mysql_numrows($result);  
7 if ($matching_users === 1) {  
8     $username = mysql_result($result, 0, "username");  
9     login($username);  
10 } else {  
11     die("Account not found");  
12 }  
13 ?>
```

*Thanks to Chris Novakovic c.novakovic@imperial.ac.uk for preparing this material.

2. The payload for your SQL injection attack should show the usernames and passwords of all registered users.

```
1 <?php
2 $uid = $_GET['userid'];
3 $q = "SELECT forename, surname FROM users WHERE userid = '$uid'";
4 $result = mysql_query($q) or die("Database error");
5 $users = mysql_numrows($result);
6 $i = 0;
7 while ($i < $users) {
8     $forename = mysql_result($result, $i, "forename");
9     $surname = mysql_result($result, $i, "surname");
10    echo "User's full name: $forename $surname";
11    $i++;
12 }
13 if ($users === 0) echo "No user with given user ID";
14 ?>
```

3. The payload for your SQL injection attack should log in the attacker with the user ID 1. Assume that the login() function is defined elsewhere, and logs in the user with the username provided.

```
1 <?php
2 $uid = mysql_real_escape_string($_GET['userid']);
3 $p = mysql_real_escape_string($_GET['password']);
4 $q = "SELECT * FROM users WHERE userid = $uid AND password = '$p'";
5 $result = mysql_query($q) or die("Account not found");
6 $matching_users = mysql_numrows($result);
7 if ($matching_users === 1) {
8     $username = mysql_result($result, 0, "username");
9     login($username);
10 } else {
11     die("Account not found");
12 }
13 ?>
```

The following resources may be helpful:

- PHP APIs for MySQL:
 - mysql (old, deprecated): <https://secure.php.net/manual/en/book.mysql.php>
 - mysqli (newer): <https://secure.php.net/manual/en/book.mysqli.php>
- MySQL SELECT syntax: <https://dev.mysql.com/doc/refman/5.7/en/select.html>
- PHP Data Objects (database abstraction layer): <https://secure.php.net/manual/en/book.pdo.php>

Sample Answers

1. Vulnerabilities:

- Line 4: unsanitised attacker-controlled parameter `password` concatenated with SQL query
- Line 5: output of `mysql_error()` shown in response body

Possible exploit: `vulnerable.php?username=admin&password=x' OR 1=1)--`

Possible fixes:

- Line 4: sanitise `$p` (e.g. with `mysql_real_escape_string()`) before concatenating
- Line 5: use parameterised queries instead of `mysql_query()`
- Line 5: don't include `mysql_error()` in `die()`

2. Vulnerabilities:

- Line 3: unsanitised attacker-controlled parameter `userid` concatenated with SQL query
- Line 4: malformed SQL query gives noticeably different output to that given when no matching users are found

Possible exploit: `vulnerable.php?userid=' UNION SELECT username, password FROM users --`

Possible fixes:

- Line 3: sanitise the value of `$uid` (e.g. with `mysql_real_escape_string()`) before concatenating it with the rest of the query
- Line 4: use parameterised queries instead of `mysql_query()`
- Line 4: also display the “No user with given user ID” error message if a malformed query is executed, to leak less information

3. Vulnerability:

- Line 2: attacker-controlled parameter `userid` passed into SQL query but its value is not expected to be a string, so `mysql_real_escape_string()` performs insufficient input validation

Possible exploit: `vulnerable.php?userid=1 -- &password=x`

Possible fixes:

- Line 2: instead of using `mysql_real_escape_string()`, check that `$uid` only contains digits (e.g. with a regular expression)
- Line 5: use parameterised queries instead of `mysql_query()`