

CO331 – Network and Web Security

10. HTTP

Dr Sergio Maffeis

Department of Computing


Course web page: <http://www.doc.ic.ac.uk/~maffeis/331>

URLs

`https://host1.example.com:5588/private/login.php`

- Uniform Resource Locators
- **Scheme** specifies what protocol to use
 - Many options: 238 and counting...
 - Main ones: http, https, ftp, javascript, mailto, chrome, data ...
 - “Full” list at <http://www.iana.org/assignments/uri-schemes/>
- **Host** is the target IP address
 - Or hostname, that needs to be resolved via DNS
- **Port** identifies the port on the target
 - If unspecified, it defaults to the standard port for the scheme
 - 80 for HTTP, 443 for HTTPS, 21 for FTP
- **Path** denotes the requested resource
 - An image, a HTML file, the output of running a PHP script, ...
- **Origin = (scheme, port, host):** crucial concept for web security!!!


URLs



- **Credentials** are used in a protocol-dependent way
 - If absent, defaults to anonymous access
- **Query string** contains parameters that are passed to the resource handler
- **Fragment** remains on the client
 - Tells browser to scroll to a specific point in an HTML document
- In practice, it's up to the client and server how to interpret the fields of a URL
 - Query strings can be anything, so careful about misinterpreting `http://a.com?{b:"a5 = z; "}`
 - We shall see examples when we talk about the browser
- Security considerations
 - URLs contain key information for web applications
 - We care about the confidentiality of credentials
 - We care about integrity of the path (REST requests have side effects on server)
 - We care about integrity and confidentiality query string (may be sensitive data)
 - Parsing URLs incorrectly may lead to security issues
 - Quiz: what is the **origin** of these requests?
 - `http://a.com#b:c@d.com`
 - `http://a.com:b:c@d.com`

HTTP/1.1

- Client-server protocol
 - Client initiates a TCP connection
 - Client sends a request conforming to HTTP protocol format
 - Server replies with a protocol-specific response
 - Typically containing data or an error message
 - Server closes the TCP connection
- *Keepalive*: for efficiency, the TCP connection is now kept open for a few seconds, in case there is a follow-up request
- Yet, the protocol is stateless
 - Each request is handled independently of the previous request
 - It's up to client and server to maintain state
 - Cookies help: much about them later...
- Main *methods*: GET, POST
 - Less common: HEAD, PUT, DELETE, CONNECT, TRACE, OPTIONS
 - Possible to add custom methods



GET

- Fetch a resource from the server
 - Can pass parameters in the query string
 - Empty body
 - Originally meant to be side-effect free and idempotent
 - In practice, it's up to the server to decide

```
GET /resource/?key=value HTTP/1.1
```

Request

```
Host: cate.doc.ic.ac.uk
```

Trying to access a bogus resource

```
Connection: keep-alive
```

```
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*
```

```
Upgrade-Insecure-Requests: 1
```

```
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10_9_5) AppleWebKit/537.1
```

```
Accept-Encoding: gzip, deflate, sdch
```

```
Accept-Language: en-US,en;q=0.8
```

Response

If I was logged in on CATE, response body would contain an HTML page

```
HTTP/1.1 401 Unauthorized
Date: Wed, 03 Feb 2016 08:48:51 GMT
Server: Apache/2.4.7 (Ubuntu)
Strict-Transport-Security: max-age=31!
WWW-Authenticate: Negotiate
WWW-Authenticate: Basic realm="CATE"
Content-Length: 381
Keep-Alive: timeout=15, max=100
Connection: Keep-Alive
Content-Type: text/html; charset=iso-8859-1
```

POST

- Submit data to the server
 - Contains a body with the payload
 - Can still pass parameters in the query string
 - Standard web forms use the body instead
 - Meant to change state on the server
 - Clients should ask confirmation before resubmitting

```
POST /login.php HTTP/1.0
Host: www.someplace.example
Pragma: no-cache
```

```
Cache-Control: no-cache
User-Agent: Mozilla/5.0 (X11; U; Linux i686; en-US; rv:1.5a)
Referer: http://www.someplace.example/login.php
Content-type: application/x-www-form-urlencoded
Content-length: 49
```


```
username=jdoe&password=BritneySpears
```

Request headers

- Main request headers
 - Host
 - Specifies target host on the server
 - Supports virtual-hosting
 - User-Agent
 - Describes browser compatibility
 - More in lecture on privacy and tracking
 - Referer
 - Where present, is the URL of where the request originated from
 - We'll see that it's important for security...
 - Cookie
 - Contains the cookies (key-value pairs) stored on behalf of the server
 - Authorization
 - Provide credentials for HTTP Basic or Digest authentication schemes
 - Accept-Encoding
 - Specifies acceptable compression methods for the HTTP response
- Like for URLs, original meaning of header may not be reflected in current use
 - Client and server can add, override, misuse headers
 - We'll see an example related to user tracking

HTTP response codes

- 200 OK Success
 - The request has succeeded
 - 2xx codes are for successful requests
- 302 Found
 - The requested resource resides temporarily under a different URI
 - 3xx codes indicates that a redirection is necessary
 - In principle only GET or HEAD requested should be redirected automatically by the client
 - In practice also POST requests are redirected, but changed into GET (removing body)
- 404 Not Found
 - The server has not found anything matching the Request-URI
 - 4xx codes denote an error in the client request
- 500 Internal Server Error
 - The server encountered an unexpected condition which prevented it from fulfilling the request
 - 5xx codes denote a server error



Response headers

- Main response headers
 - Content-Type
 - Specifies MIME type and character set for response
 - Location
 - Combined with 3xx response code, redirects client to different server
 - Set-Cookie
 - Requests client to store or delete some cookie on behalf of the server
 - WWW-Authenticate
 - HTTP Basic or Digest authentication schemes must be used to access resource
 - Content-Encoding
 - Specifies compression method used
 - Cache-Control
 - Specifies desired caching behaviour for client and intermediary caches
- Many more headers are currently in use
 - We'll see the security-relevant ones: CSP, CORS, HSTS, HPKP, ...

HTTP security issues

- HTTP is over TCP/IP
 - No confidentiality or integrity of headers or messages against eavesdroppers or MITM
- Caching
 - If an HTTP proxy cache is poisoned, downstream clients will receive rogue HTTP responses
- Referrer header
 - User visits site A and then site B
 - Privacy issue: B learns that user visited A
 - Security issue: if query string for A contained sensitive parameters, B can see them
 - Put sensitive data in the POST body, rather than in the GET query string
- Response splitting
 - Attacker could confuse client to accept bogus responses over keepalive connection

HTTP/1.1 200 OK[CR][LF]

Set-Cookie: term=[CR]Content-Length: 0[CR][CR]HTTP/1.1 200 OK[CR]Gotcha: Yup[CR][LF]

Content-Length: 17[CR][LF]

[CR][LF]

Action completed.

HTTP/1.1 200 OK
Set-Cookie: term=
Content-Length: 0

HTTP/1.1 200 OK
Gotcha: Yup
Content-Length: 17

Action completed.

HTTP versions

- HTTP/0.9: HyperText Transfer Protocol
 - Co-designed with HTML
 - By Berner Lee et al. at CERN (1989)
- HTTP/1.1 currently supported by most of the web
 - Originally specified in RFC 2616 (1999)
 - Superseded by RFCs 7230-7235 (2014)
 - Mostly backward compatible with HTTP/1.0
 - Compatibility with HTTP/0.9 introduces some issues
 - See *Tangled Web*
- HTTP/2, based on Google's SPDY
 - Approved as Proposed Standard by IESG in February 2015
 - By now most browsers support it, about 23% of websites can use it
 - Retains compatibility with HTTP 1.1
 - Adds features (mostly, it's faster)
 - Servers can push data
 - Requests are multiplexed over TCP connections, saving time to start new ones
 - Headers can be compressed
 - Some implementations use HTTP/2 only over TLS: security by default


HTTPS

- HTTPS consists in running HTTP over an encrypted TLS connection
 - TLS provides confidentiality and integrity to the HTTP connection
 - Prevents DNS spoofing
 - Attacker should not be able to create fake certificate for spoofed domain
- HTTPS (RFC 2818) is supported by vast majority of HTTP clients
 - Yet not all traffic goes over HTTPS
 - Some cost of using public-key crypto
 - Increased latency: first request to a website is slowed down
 - ISPs cannot cache HTTPS traffic
 - Owning and maintaining certificates can be expensive
 - <https://letsencrypt.org> initiative provides free certs to improve uptake of HTTPS
- HTTPS runs in the browser, and a human controls the browser
 - Problems with accepting invalid certificates
 - When we talk about browser security, we will see UI attack example
- Spoofed certificates, compromised CAs invalidate TLS guarantees
 - Countermeasure: HTTP Public Key Pinning (HPKP)
 - Domain includes a response header


```
Public-Key-Pins: max-age=5184000; pin-sha256="r/mIkG3eEpVdm+u/ko/cwxzOMo1bk4TyHlByibiA5E="; ...
```
 - Browser caches hash of public key for that domain
 - Time validity: too short defeats the purpose, too long prevents revocation

SSL stripping and HSTS

- Unsafe to upgrade a connection from HTTP to HTTPS
 - **SSL stripping attack:**



- Countermeasure: Strict Transport Security (HSTS)
 - HTTP response header: `Strict-Transport-Security`
 - Tells browser to load pages from that domain only over HTTPS
 - Saved for future requests depending on `max-age = seconds` parameter
- Bootstrapping problem: HSTS header must be sent over HTTPS
 - How to prevent SSL stripping on the first connection from HTTP?
 - Browsers have lists of websites that must be connected over HTTPS directly (this doesn't scale)
 - DANE: associate HSTS to DNSSEC