Mechanistic Interpretability

Iliad Intensive

Julian Schulz

September 22, 2026

Overview

What is Mechanistic Interpretability?

Early MechInterp on CNNs

Features in Language Models

Superposition

Sparse Autoencoders

Circuits in Transformers

Fuzzy Interpretability

Discussion

What is Mechanistic Interpretability? ←
Early MechInterp on CNNs
Features in Language Models
Superposition
Sparse Autoencoders
Circuits in Transformers
Fuzzy Interpretability
Discussion

What is Mechanistic Interpretability?

Two Ways to Relate to Models

Machine Learning

- Output-oriented
- Find hyperparameters to improve models

Mech. Interpretability

- Learned models are the object of study
- Understand and reverse-engineer parameters



MICROGRAPHIA:

OR SOME

Physiological Descriptions

OF

MINUTE BODIES

MADE BY

MAGNIFYING GLASSES.

WITH

OBSERVATIONS and INQUIRIES thereupon.

By R. HOOKE, Fellow of the ROYAL SOCIETY.

Nam posse oculo quantum contendere Lincus,
Nonnumen idcirco contemnas Lippus inungis. Horat. Ep. lib. 1.

LONDON, Printed by *Jo. Martyn*, and *Ja. Allestry*, Printers to the ROYAL SOCIETY, and are to be sold at their Shop at the *Bell* in S. *Paul's* Church-yard. M DC LX V.



From [Olah et al. 2020]

Schwann's Claims (1839)

1. The cell is the unit of structure, physiology, and organization in living things.
2. The cell retains a dual existence as a distinct entity and a building block in the construction of organisms.
3. Cells form by free-cell formation, similar to the formation of crystals.



Mikroskopische

Untersuchungen

über

die Uebereinstimmung in der Struktur und dem Wachsthum

der

Thiere und Pflanzen

von

Dr. *Th. Schwann.*

Mit vier Kupfertafeln.

Berlin 1839.
Verlag der Sander'schen Buchhandlung.
(G. E. Reimer.)

Image: Deutsches Textarchiv

Three Speculative Claims

1. **Features** are the fundamental unit of neural networks. They correspond to directions. These features can be rigorously studied and understood.
2. Features are connected by weights, forming **circuits**. These circuits can also be rigorously studied and understood.
3. **Universality**: Analogous features and circuits form across models and tasks.

"Zoom In: An Introduction to Circuits" [Olah et al., 2020]

How would MechInterp help AI safety?

Theories of Impact

- Auditing for misalignment/deception
- Enumerative safety
- Eliciting latent knowledge

"A Longlist of Theories of Impact for Interpretability" [Nanda, 2022]

What is Mechanistic Interpretability?
Early MechInterp on CNNs ←
Features in Language Models
Superposition
Sparse Autoencoders
Circuits in Transformers
Fuzzy Interpretability
Discussion

Early MechInterp on CNNs

Why CNNs?


Conv_1
Convolution
(5 x 5) kernel
valid padding
Max-Pooling
(2 x 2)
Conv_2
Convolution
(5 x 5) kernel
valid padding
Max-Pooling
(2 x 2)
fc_3
Fully-Connected
Neural Network
ReLU activation
fc_4
Fully-Connected
Neural Network
(with dropout)
Flattened
INPUT
(28 x 28 x 1)
n1 channels
(24 x 24 x n1)
n1 channels
(12 x 12 x n1)
n2 channels
(8 x 8 x n2)
n2 channels
(4 x 4 x n2)
n3 units
0
1
2
9
OUTPUT

What would convince you a CNN channel has the function of "detecting a curve?"

Argument 1: Feature Visualization

Optimizing the input to maximally activate curve detectors reliably produces curves. This establishes a causal link.

"Zoom In: An Introduction to Circuits" [Olah et al., 2020]

Argument 2: Dataset Examples

ImageNet images that strongly activate these neurons reliably contain curves in the expected orientation.

"Zoom In: An Introduction to Circuits" [Olah et al., 2020]

Argument 3: Synthetic Examples

Curve detectors respond as expected to synthetic curves with varying orientations and curvatures. They do not fire for straight lines or sharp corners.

"Zoom In: An Introduction to Circuits" [Olah et al., 2020]

Argument 4: Joint Tuning



Rotating a stimulus smoothly transfers activation between orientation-selective detectors. Together, they tile the full 360 degrees.

"Zoom In: An Introduction to Circuits" [Olah et al., 2020]

Argument 5: Feature Implementation



A curve detection algorithm can be read off the weights. No evidence of a secondary cause of firing.

"Zoom In: An Introduction to Circuits" [Olah et al., 2020]

Argument 6: Feature Use



Downstream clients are features that naturally involve curves: circles, spirals, 3d curvature.

"Zoom In: An Introduction to Circuits" [Olah et al., 2020]

Argument 7: Handwritten Circuits

We can do a cleanroom reimplementation, hand-setting all weights to reimplement curve detection. These handwritten weights significantly mimic the original.

"Zoom In: An Introduction to Circuits" [Olah et al., 2020]

A Complex Feature: Cars in Superposition



"Zoom In: An Introduction to Circuits" [Olah et al., 2020]

Universality in Image Models



"Zoom In: An Introduction to Circuits" [Olah et al., 2020]

Polysemanticity



"Zoom In: An Introduction to Circuits" [Olah et al., 2020]

If Universality Is True

- What features are universal? Why?
- Discussed in the Natural Abstractions discourse

"Alignment By Default — LessWrong" [Wentworth, 2020]

"Natural Abstractions: Key Claims, Theorems, and Critiques — AI Alignment Forum" [Chan et al., 2023]

Feature Visualization Exercise

What is Mechanistic Interpretability?
Early MechInterp on CNNs
Features in Language Models ←
Superposition
Sparse Autoencoders
Circuits in Transformers
Fuzzy Interpretability
Discussion

Features in Language Models

Features Represent Human-Understandable Concepts





"Linguistic Regularities in Continuous Space Word Representations" [Mikolov et al., 2013]

How do we identify features in Transformers?

Getting a Feature Direction

Contrastive pairs:

$$r = \text{Emb}(\text{“Spanish”}) - \text{Emb}(\text{“French”})$$

Linear probe: x_i: sample activation, $y_i \in \{+1, -1\}$: label

$$r = \arg\max_{\|r\|=1} \sum_i y_i \cdot r^\top x_i$$

CAA: $x_i^{(+)}, x_i^{(-)}$: positive/negative example of a property

$$r = \frac{1}{N} \sum_{i=1}^{N} \left(x_i^{(+)} - x_i^{(-)} \right)$$

What To Do with a Feature Direction

Activation addition (steering):

$$x' \leftarrow x + \alpha \cdot r$$

Direction ablation (make the model blind to the concept):

$$x' \leftarrow x - \hat{r}\hat{r}^\top x$$

Probing (read out a concept):

$$s = r^\top x$$

r: feature direction x: activation α: steering strength

Linear Probes Can Classify Text Properties



Figure 4. The subspace representation gamma W acts as a linear probe for W . The histograms show gamma T W lambda (x fr j) vs. gamma T W lambda (x es j) (left) and gamma T Z lambda (x fr j) vs. gamma T Z lambda (x es j) (right) for W = French =¿ Spanish and Z = male =¿ female , where x fr j and x es j are random contexts from French and Spanish Wikipedia, respectively. We also see that gamma Z does not act as a linear probe for W , as expected.

"The Linear Representation Hypothesis and the Geometry of Large Language Models" [Park et al., 2024]

Linear Probes Can Measure World Models



Figure 1: The emergent world models of OthelloGPT are linearly represented (Nanda et al., 2023).

"Emergent Linear Representations in World Models of Self-Supervised Sequence Models" [Nanda, Lee, et al., 2023]

Linear Probes Can Measure World Models

	x^0	x^1	x^2	x^3	x^4	x^5	x^6	x^7
Randomized	37	35.1	33.9	35.5	34.8	34.7	34.4	34.5
Probabilistic				61.8				
Linear {BLACK, WHITE, EMPTY}	62.2	74.8	74.9	75.0	75.0	74.9	74.8	74.4
Non-Linear {BLACK, WHITE, EMPTY}	63.4	88.6	93.3	96.3	97.5	98.3	98.7	98.3
Linear {MINE, YOURS, EMPTY}	**90.9**	**94.8**	**97.2**	**98.3**	**99**	**99.4**	**99.6**	**99.5**

Table 1: Probing accuracy for board states. OthelloGPT linearly encodes the board state relative to the current player at each timestep (MINE vs. YOURS, as opposed to colours BLACK or WHITE.

"Emergent Linear Representations in World Models of Self-Supervised Sequence Models" [Nanda, Lee, et al., 2023]

Intervening on the World Model



Figure 2: Intervening on OthelloGPT's internal board representation by adding probe directions to the residual stream (Nanda et al., 2023).

"Emergent Linear Representations in World Models of Self-Supervised Sequence Models" [Nanda, Lee, et al., 2023]

Intervening on the World Model

Flipping colours	Avg. # Errors
Null Intervention Baseline	2.723
Non-Linear Intervention	0.12
Linear Probe Addition	**0.10**
Erasing	**Avg. # Errors**
Null Intervention	2.73
Non-Linear Intervention	0.11
Linear Probe Addition	**0.02**

Table 2: Error rates from interventions.

"Emergent Linear Representations in World Models of Self-Supervised Sequence Models" [Nanda, Lee, et al., 2023]

Probing LLMs



Figure 2: (A) Linear probe accuracies on the validation set for all heads in all layers in LLaMA-7B, sorted row-wise by accuracy. Darker blue represents higher accuracy. 50

Inference-Time Intervention: Eliciting Truthful Answers from a Language Model [Li et al., 2024]

Adding in Truthfulness



Figure 3: A sketch of the computation on the last token of a transformer with inference-time intervention (ITI) highlighted.

Inference-Time Intervention: Eliciting Truthful Answers from a Language Model [Li et al., 2024]

Adding in Truthfulness

	True*Info (%)	True (%)	MC acc. (%)	CE	KL
Baseline	30.5	31.6	25.7	2.16	0.0
Supervised Finetuning	36.1	47.1	24.2	2.10	0.01
Few-shot Prompting	49.5	49.5	**32.5**	-	-
Baseline + ITI	43.5	49.1	25.9	2.48	0.40
Few-shot Prompting + ITI	**51.4**	**53.5**	**32.5**	-	-

In Table 1, we compare ITI with the alternative baselines (subsection 4.2) 23 . Due to the limit of context length for few-shot prompting, we adapt SFT and ITI to use 5

Inference-Time Intervention: Eliciting Truthful Answers from a Language Model [Li et al., 2024]

Steering via Contrastive Features



(a) Diagram of steering vector generation for CAA.

Steering Llama 2 via Contrastive Activation Addition [Panickssery et al., 2024]

Steering via Contrastive Features



Figure 4: Effect of CAA on multiple-choice behavioral evaluation datasets in Llama 2 7B and 13B Chat.

Steering Llama 2 via Contrastive Activation Addition [Panickssery et al., 2024]

Refusal Is Mediated by a Single Direction



Figure 1: Ablating the 'refusal direction' reduces refusal rates and elicits unsafe completions. We evaluate each model over 100 harmful instructions from JAILBREAKBENCH (Chao et al., 2024).

Refusal in Language Models Is Mediated by a Single Direction [Arditi et al., 2024]

Refusal Is Mediated by a Single Direction



Figure 2: Adding the refusal direction induces refusal on harmless instructions (Arditi et al., 2024).

Refusal in Language Models Is Mediated by a Single Direction [Arditi et al., 2024]

Logit Lens



Interpreting GPT: The Logit Lens [nostalgebraist, 2020]

Logit Lens Exercise

Normal Exercise

Hard Exercise

What is Mechanistic Interpretability?
Early MechInterp on CNNs
Features in Language Models
Superposition ←
Sparse Autoencoders
Circuits in Transformers
Fuzzy Interpretability
Discussion

Superposition

Superposition





Toy Models of Superposition [Elhage, Hume, et al., 2022]

Superposition



Toy Models of Superposition [Elhage, Hume, et al., 2022]

Johnson–Lindenstrauss Lemma

In N dimensions, we can pack

$$m \geq e^{c \cdot \varepsilon^2 \cdot N}$$

vectors with pairwise dot product at most ε.

Features scale **exponentially** with dimensions, given overlap ε.

"Extensions of Lipschitz Mappings into a Hilbert Space" [Johnson et al., 1984]

Demonstrating Superposition



Our first experiments will test the extent to which the idealized activations of an imagined larger model can be **stored** and **recovered** from a lower-dimensional space.

Toy Models of Superposition [Elhage, Hume, et al., 2022]

Demonstrating Superposition

$$h = Wx \qquad \hat{x} = \mathrm{ReLU}(W^\top h + b)$$

$$L = \mathbb{E}_x \left[\| I\,(x - \hat{x}) \|^2 \right]$$

$I = \mathrm{diag}(I_i)$: per-feature importance Sparsity S: probability that $x_i = 0$

Toy Models of Superposition [Elhage, Hume, et al., 2022]

Demonstrating Superposition



Toy Models of Superposition [Elhage, Hume, et al., 2022]

Dimensions per Feature

$$D = \frac{m}{\|W\|_F^2}$$

On average, how many hidden dimensions does the network use per feature?

m: number of hidden dimensions $\|W\|_F$: Frobenius norm of W

Toy Models of Superposition [Elhage, Hume, et al., 2022]

Dimensions per Feature



Toy Models of Superposition [Elhage, Hume, et al., 2022]

Feature Dimensionality

$$D_i = \frac{1}{\sum_j \frac{(W_i \cdot W_j)^2}{\|W_i\|^2 \|W_j\|^2}}$$

How many dimensions does the network allocate to encoding feature i?

Toy Models of Superposition [Elhage, Hume, et al., 2022]

Feature Geometry



Toy Models of Superposition [Elhage, Hume, et al., 2022]

Feature Geometry



Figure 1: Circular representations of days of the week, months of the year, and years of the 20th century in layer 7 of GPT-2-small colored by the token they fire on. These representations were discovered via clustering SAE dictionary elements, described in Section 4. Points are colored according to the token which created the representation. See Fig. 14 for other axes and Fig. 15 for similar plots for Mistral 7B.

"NOT ALL LANGUAGE MODEL FEATURES ARE ONE-DIMENSIONALLY LINEAR" [Engels et al., 2025]

Can we disentangle features in superposition?

Dictionary Learning

Setup: Unknown dictionary $A = [A_1, \ldots, A_m] \in \mathbb{R}^{n \times m}$ with $m > n$.

We observe samples $y = Ax$, where $x \in \mathbb{R}^m$ is k-sparse. We know neither x nor A.

Claim: A is recoverable up to permutation and sign, in polynomial time, if:

- **Sparsity:** $k \leq c \cdot \min\left(m^{2/5}, \frac{\sqrt{n}}{\mu \log n}\right)$
- **Incoherence:** $|\langle A_i, A_j \rangle| \leq \frac{\mu}{\sqrt{n}}$ for all $i \neq j$
- **Sufficient data:** $p = \Omega\left(\frac{m^2}{k^2} \log m\right)$ samples with varying support
- **Well-behaved coefficients:** independent, symmetric, bounded away from zero

New Algorithms for Learning Incoherent and Overcomplete Dictionaries [Arora et al., 2013]

Compressed Sensing

Setup: Known dictionary $A \in \mathbb{R}^{n \times m}$. We observe $y = Ax$, where x is k-sparse. We want to recover x.

Problem: $m > n$, so there are infinitely many solutions to $Ax = y$.

Claim: If A satisfies the Restricted Isometry Property (RIP), then

$$\min_z \|z\|_1 \quad \text{s.t.} \quad Az = y$$

recovers x exactly.

ℓ_1 minimization finds the sparse solution; ℓ_2 minimization does not.

Robust Uncertainty Principles: Exact Signal Reconstruction from Highly Incomplete Frequency Information [Candes et al., 2004]

"Compressed Sensing" [Donoho, 2006]

How to disentangle features in superposition?

What is Mechanistic Interpretability?
Early MechInterp on CNNs
Features in Language Models
Superposition
Sparse Autoencoders ←
Circuits in Transformers
Fuzzy Interpretability
Discussion

Sparse Autoencoders

Sparse Autoencoders



Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

Sparse Autoencoders

$$f = \text{ReLU}(W_{\text{enc}}(x - b_{\text{dec}}) + b_{\text{enc}})$$

$$\hat{x} = W_{\text{dec}} f + b_{\text{dec}}$$

$$\mathcal{L} = \underbrace{\|x - \hat{x}\|_2^2}_{\text{reconstruction}} + \lambda \underbrace{\|f\|_1}_{\text{sparsity}}$$

Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

Identifying SAE Features



Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

Identifying SAE Features



Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

https://www.neuronpedia.org/gemma-3-27b/31-gemmascope-2-res-16k

Trouble with SAEs: Feature Absorption



(a) When features fire independently, the SAE learns exactly one latent per feature, and the decoder perfectly recovers each feature direction.

A Is for Absorption: Studying Feature Splitting and Absorption in Sparse Autoencoders [Chanin et al., 2024]

Trouble with SAEs: Feature Absorption



A Is for Absorption: Studying Feature Splitting and Absorption in Sparse Autoencoders [Chanin et al., 2024]

Trouble with SAEs: Feature Shrinkage



"Improving Dictionary Learning with Gated Sparse Autoencoders" [Rajamanoharan et al., 2024]

The Cambrian Explosion of SAEs

Gated SAEs



"Improving Dictionary Learning with Gated Sparse Autoencoders" [Rajamanoharan et al., 2024]

JumpReLU SAEs

$$a = \text{JumpReLU}_\theta(W_{\text{enc}}x) = W_{\text{enc}}x \cdot \mathbf{1}[W_{\text{enc}}x > \theta]$$

$$\mathcal{L} = \underbrace{\|x - \hat{x}\|_2^2}_{\text{reconstruction}} + \lambda \sum_i \underbrace{\tanh(c \cdot \|W_{\text{dec},i}\| \cdot a_i)}_{\approx \mathbf{1}[a_i > 0] \text{ for large } c}$$

Hard threshold θ: features are either fully on or off. Sparsity penalty approximates L0 — no shrinkage on active features.

"Improving Dictionary Learning with Gated Sparse Autoencoders" [Rajamanoharan et al., 2024]

Top-K SAEs

$$f_{\text{TopK}}(x) = \text{TopK}(W_{\text{enc}}(x - b_{\text{dec}}))$$

Set all but the top K feature activations to zero. No L1 penalty needed.

BatchTopK Sparse Autoencoders [Bussmann, Leask, et al., 2024]

Matryoshka SAEs



Learning Multi-Level Features with Matryoshka Sparse Autoencoders [Bussmann, Nabeshima, et al., 2025]

Staircase SAEs



Figure 1: The staircase SAE architecture for a transformer with $L = 3$ layers. Each layer i uses a slice of the shared encoder $\mathbf{W}_{enc}$ and decoder $\mathbf{W}_{dec}$ weights. SAE chunks of identical colour indicate weights shared within the slices $\mathbf{W}^i_{enc}$ and $\mathbf{W}^i_{dec}$.

SCALAR: Benchmarking SAE Interaction Sparsity in Toy LLMs [Fillingham et al., 2025]

Comparing SAEs



Figure 2: Scores for the Loss Recovered, Automated Interpretability, Absorption, SCR, and Sparse Probing metrics on the 65k width Gemma-2-2B suite of SAEs.

SAEs Scale



Scaling Monosemanticity: Extracting Interpretable Features from Claude 3 Sonnet [Templeton et al., 2024]

Bigger Models, More Specific Features

Feature #34M/31164353 **Golden Gate Bridge** feature example

The feature activates strongly on English descriptions and associated concepts

in the Presidio at the end (that's the↵ huge park right next to the Golden Gate bridge), perfect. But not all people

repainted, roughly,every dozen years." "while across the country in san fran cisco, the golden gate bridge was

it is a suspension bridge and has similar coloring, it is often↵> compared to the Golden Gate Bridge in San Francisco, US

They also activate in multiple other languages on the same concepts

ゴールデン・ゲート・ブリッジ、金門橋は、ア メリカ西海岸のサンフランシスコ湾と太平洋が 接続するゴールデンゲート海

골든게이트 교 또는 금문교 는 미국 캘리포니아주 골든게이트 해협에 위치한 현수교이다. 골든게이 트 교는 캘리포니아주 샌프란시

мост золотые ворота — висячий мост через пролив золотые ворота. он со единяет город сан-франц

And on relevant images as well

Scaling Monosemanticity: Extracting Interpretable Features from Claude 3 Sonnet [Templeton et al., 2024]

Golden Gate Claude

Reading Claude's Mind



Scaling Monosemanticity: Extracting Interpretable Features from Claude 3 Sonnet [Templeton et al., 2024]

Safety-Relevant Feature Steering

In the Claude Opus 4.5 system card:

1. Find **evaluation awareness** features via:
   - Contrastive vectors (eval vs. non-eval prompts)
   - SAE features (discriminating eval transcripts)
2. **Inhibit** these features (negative steering at 25% of activation norm)

Results:

- Reduced verbalized evaluation awareness
- Modestly increased misaligned behavior
- Random feature steering also had a (weaker) effect

Claude Opus 4.5 System Card [Anthropic, 2025]

Transcoders and Crosscoders



Sparse Crosscoders for Cross-Layer Features and Model Diffing [Lindsey, Templeton, et al., 2024]

Transcoders and Crosscoders



Sparse Crosscoders for Cross-Layer Features and Model Diffing [Lindsey, Templeton, et al., 2024]

Model Diffing



Sparse Crosscoders for Cross-Layer Features and Model Diffing [Lindsey, Templeton, et al., 2024]

Model Diffing



Sparse Crosscoders for Cross-Layer Features and Model Diffing [Lindsey, Templeton, et al., 2024]

SAE Exercise

What is Mechanistic Interpretability?
Early MechInterp on CNNs
Features in Language Models
Superposition
Sparse Autoencoders
Circuits in Transformers ←
Fuzzy Interpretability
Discussion

Circuits in Transformers

Complete Reverse Engineering



Figure 1: The algorithm implemented by the one-layer transformer for modular addition. Given two numbers a and b, the model projects each point onto a corresponding rotation using its embedding matrix. Using its attention and MLP layers, it then composes the rotations to get a representation of $a + b \mod P$. Finally, it "reads off" the logits for each $c \in \{0, 1, ..., P-1\}$, by rotating by $-c$ to get $\cos(w(a+b-c))$, which is maximized when $a + b \equiv c \mod P$ (since w is a multiple of $\frac{2\pi}{P}$).

Progress Measures for Grokking via Mechanistic Interpretability [Nanda, Chan, et al., 2023]

Complete Reverse Engineering



Figure 3: *(Left)* The norms of the Fourier components in the embedding matrix W_E. As discussed in Section 4.1, the sparsity of W_E in the Fourier basis is evidence that the network is operating in this basis. Of the six non-zero frequencies, five "key frequencies" appear in later parts of the network, corresponding to $k \in \{14, 35, 41, 42, 52\}$. *(Right)* Norm of Fourier components of the neuron-logit map W_L. A Fourier transform is taken over the logit axis, and then the norm is taken over the neuron axis. As discussed in Section 4.2, W_L is well-approximated by the 5 key frequencies w_k.

Progress Measures for Grokking via Mechanistic Interpretability [Nanda, Chan, et al., 2023]

Plotting Attention Patterns



A Mathematical Framework for Transformer Circuits [Elhage, Nanda, et al., 2021]

Logit Attribution



Raw attention pattern and logit effect for the induction head `1:8` on some segments of the first paragraph of *Harry Potter and the Philosopher's Stone*. The "logit effect" value shown is the effect of the result vector for the present token on the logit for the next token, $(W_U W_O^h r^h_{\text{pres_tok}})_{\text{next_tok}}$, which is equivalent to running the full OV circuit and inspecting the logit this head contributes to the next token.

A Mathematical Framework for Transformer Circuits [Elhage, Nanda, et al., 2021]

K-Composition



"Induction Heads - Illustrated — LessWrong" [McDougall, 2023]

Q-Composition



"Induction Heads - Illustrated — LessWrong" [McDougall, 2023]

Path Patching



Figure 1: Left: We isolated a *circuit* (in orange) responsible for the flow of information connecting the indirect object "Mary" to the next token prediction. The nodes are attention layers and the edges represent the interactions between these layers. Right: We discovered and validated this circuit using causal interventions, including both path patching and knockouts of attention heads.

Interpretability in the Wild: A Circuit for Indirect Object Identification in GPT-2 Small [Wang et al., 2022]

The IOI Circuit



Figure 2: We discover a circuit in GPT-2 small that implements IOI. The input tokens on the left are passed into the residual stream. Attention heads move information between residual streams: the query and output arrows show which residual streams they write to, and the key/value arrows show which residual streams they read from.

Interpretability in the Wild: A Circuit for Indirect Object Identification in GPT-2 Small [Wang et al., 2022]

Automated Circuit Discovery

Task	Example Prompt	Output	Metric
1: IOI (Appendix F.2)	"When John and Mary went to the store, Mary gave a bottle of milk to"	"_John"	Logit difference

2: Docstring (Appendix H.1)	`def f(self, files, obj, state, size, shape, option):`
	`  """document string example`
	
	`  :param state: performance analysis`
	`  :param size: pattern design`
	`  :param`
		"_shape"	Logit difference

3: Greater-Than (Appendix G)	"The war lasted from 1517 to 15"	"18" or "19" or ... or "99"	Probability difference
4: tracr-xproportion (Appendix I.1)	`["a", "x", "b", "x"]`	`[0, 0.5, 0.33, 0.5]`	Mean Squared Error
5: tracr-reverse (Appendix I.2)	`[0, 3, 2, 1]`	`[1, 2, 3, 0]`	Mean Squared Error
6: Induction (Section 4.2)	"Vernon *Durs*ley and Petunia *Durs*"	"ley"	Negative log-probability

Table 1: Five behaviors for which we have an end-to-end circuit from previous mechanistic interpretability work, plus Induction. We automatically rediscover the circuits for behaviors 1-5 in Section 4. Tokens beginning with space have a "_" prepended for clarity.

Towards Automated Circuit Discovery for Mechanistic Interpretability [Conmy et al., 2023]

Automated Circuit Discovery



(a) Choose computational graph, task, and threshold τ.



(b) At each head, prune unimportant connections.



(c) Recurse until the full circuit is recovered.

Figure 2: **How ACDC works** (Steps 2a-2c). Step 2a: a practitioner specifies a computational graph of the model, the task they want to investigate, and a threshold under which to remove connections. Step 2b: ACDC iterates over nodes in the computational graph, replacing activations of connections between a node and its children, and measuring the effect on the output metric. Connections are removed if their measured effect on the metric under corruption is below the threshold τ. Step 2c: recursively apply Step 2b to the remaining nodes. The ACDC procedure returns a subgraph of the original computational graph.

Towards Automated Circuit Discovery for Mechanistic Interpretability [Conmy et al., 2023]

Automated Circuit Discovery

Algorithm 1: The ACDC algorithm.

Data: Computational graph G, dataset $(x_i)_{i=1}^n$, corrupted datapoints $(x_i')_{i=1}^n$ and threshold $\tau > 0$.

Result: Subgraph $H \subseteq G$.

$H \leftarrow G$ `// Initialize H to the full computational graph`

$H \leftarrow H.reverse_topological_sort()$ `// Sort H so output first`

for $v \in H$ **do**

  for w *parent of* v **do**

    $H_{\text{new}} \leftarrow H \setminus \{w \to v\}$ `// Temporarily remove candidate edge`

    if $D_{KL}(G||H_{\text{new}}) - D_{KL}(G||H) < \tau$ **then**

      $H \leftarrow H_{\text{new}}$ `// Edge is unimportant, remove permanently`

    end

  end

end

return H

Towards Automated Circuit Discovery for Mechanistic Interpretability [Conmy et al., 2023]

Recovered IOI Circuit



Figure 1: **Automatically discovering circuits with ACDC.** *Left:* a computational graph for GPT-2 Small, with a recovered circuit for the IOI task highlighted in red. Only edges between adjacent layers are shown. *Right:* the recovered circuit with labelled nodes. All heads recovered were identified as part of the IOI circuit by Wang et al. (2023). Edge thickness is proportional to importance.

Circuit Tracing: Cross-Layer Transcoders



Figure 1: The cross-layer transcoder (CLT) forms the core architecture of our replacement model.

Circuit Tracing: Revealing Computational Graphs in Language Models [Ameisen et al., 2025]

Replacement Models

Original Transformer Model

The underlying model that we study is a transformer-based large language model.

Replacement Model

We replace the neurons of the original model with *features*. There are typically more features than neurons. Features are sparsely active and often represent interpretable concepts.





Feature



To understand what a feature represents, we use a *feature visualization*, which shows dataset examples for which the feature is most strongly active. In this example, the feature fires strongly when the model is about to say a state capital.

Figure 2: The replacement model is obtained by replacing the original model's neurons with the cross-layer transcoder's sparsely-active features.

Circuit Tracing: Revealing Computational Graphs in Language Models [Ameisen et al., 2025]

Attribution Graphs

Local Replacement Model

The local replacement model is specific to a prompt of interest. We add an error adjustment term, and freeze attention patterns to be what they were in the original model on the given prompt. It produces the exact same output as the original model, but replaces as much computation as possible with features.



Reconstruction Error

Error nodes represent the difference between the original MLP output and the replacement model's reconstruction

Attention-mediated weights

Attention patterns are frozen to their value in the original model, allowing us to define weights between features in different token positions

Attribution Graph

We trace from input to output through active features, pruning paths that don't influence the output.



Figure 4: The local replacement model is obtained by adding error terms and fixed attention patterns to the replacement model to exactly reproduce the original model's behavior on a specific prompt.

Circuit Tracing: Revealing Computational Graphs in Language Models [Ameisen et al., 2025]

Example: Acronym Circuit



Figure 8: A simplified diagram of the attribution graph for 18L completing a fictional acronym.

Circuit Tracing: Revealing Computational Graphs in Language Models [Ameisen et al., 2025]

Feature Suppression



Figure 9: A schematic of multiplicative patching.

Circuit Tracing: Revealing Computational Graphs in Language Models [Ameisen et al., 2025]

Feature Suppression Example



Figure 10: Suppressing the word "Group" in the fictional organization's name causes 18L to output other acronyms with "DA" in them.

Circuit Tracing: Revealing Computational Graphs in Language Models [Ameisen et al., 2025]

Explore attribution graphs yourself

https://www.neuronpedia.org/gemma-2-2b/graph

Circuit Tracing on Claude: Math



Figure 29: A simplified attribution graph of Haiku computing the answer to an arithmetic expression with two steps. A lookup table feature active on addition prompts is used as an intermediate result for the larger expression.

On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]

Misaligned Model Pipeline



Figure 54: Summary of how Marks *et al.* produce their model. Figure reproduced from Marks *et al.*

On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]

Misaligned Circuit



Figure 55: A simplified attribution graph of a case where the model organism exhibits its self-referential poem behavior. Note the role of the reward bias feature.

View detailed graph

On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]

Misaligned Intervention



Figure 56: Intervention exploring the self-referential poem behavior.

On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]

General Patterns in Circuits

- High-abstraction features in middle layers, simple token features in early/late layers
- Attention moves most information in early layers
- "Default" circuits that get overwritten (e.g. "unknown person" $\rightarrow$ specific person)
- Multiple pathways/shortcuts to the answer
- Computation on special token positions (e.g. full stops, `<assistant:>`)
- Confidence-reducing features (cf. negative name movers in IOI)
- Many "boring" features active but not part of the core computation

On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]

Normal Exercise

Hard Exercise

What is Mechanistic Interpretability?
Early MechInterp on CNNs
Features in Language Models
Superposition
Sparse Autoencoders
Circuits in Transformers
Fuzzy Interpretability ←
Discussion

Fuzzy Interpretability

Activation Oracles



Activation Oracles: Training and Evaluating LLMs as General-Purpose Activation Explainers [Karvonen, Chua, et al., 2026]

Activation Oracles: Benchmarks



Activation Oracles: Training and Evaluating LLMs as General-Purpose Activation Explainers [Karvonen, Chua, et al., 2026]

Natural Language Autoencoders



Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

NLAs Reveal Unverbalized Reasoning



Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

NLAs Hallucinate



Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

NLAs Detect Unverbalized Evaluation Awareness



Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

NLAs Win the Auditing Game



Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

Application: Opus 4.8 System Card

In 5% of sampled RL episodes, Claude Opus 4.8 is internally aware of a grader, but never verbalizes it.

Claude Opus 4.8 System Card [Anthropic, 2026]

Exercise: Play with an NLA

neuronpedia.org/llama3.3-70b-it/nla

What is Mechanistic Interpretability?
Early MechInterp on CNNs
Features in Language Models
Superposition
Sparse Autoencoders
Circuits in Transformers
Fuzzy Interpretability
Discussion ←

Discussion

Open Problems in MechInterp

Decomposition: problems with Sparse Dictionary Learning

- High reconstruction errors
- Expensive for large models
- Sparsity is a flawed proxy for interpretability
- Dataset dependent
- No clarity on the concept of a “feature”

Open Problems in Mechanistic Interpretability [Sharkey et al., 2025]

Open Problems in MechInterp

Description: interpreting component roles

- Highly activating examples are correlational
- Attribution methods are first-order approximations
- Causal interventions are expensive at scale

Open Problems in Mechanistic Interpretability [Sharkey et al., 2025]

Open Problems in MechInterp

Validation: testing our explanations

- Different methods yield different explanations
- Performance is seldom demonstrated on real-world tasks
- Conclusions are often not validated

Open Problems in Mechanistic Interpretability [Sharkey et al., 2025]

Open Problems in MechInterp

Automation: scaling up interpretability

- Scaling up current methods does not yield more interesting results
- "Streetlight interpretability"

Open Problems in Mechanistic Interpretability [Sharkey et al., 2025]

Open Problems in MechInterp

Applications: using interpretability in practice

- Can't reliably distinguish recognizing vs. applying a concept
- Mechanistic verification of behavior not possible
- Mechanistic understanding might further capabilities by pruning models

Open Problems in Mechanistic Interpretability [Sharkey et al., 2025]

Critiques of Mechanistic Interpretability

Pick one paper to read and discuss:

1. *A Pragmatic Vision for Interpretability* (Nanda et al., 2025) ∼15 min
2. *Against Almost Every Theory of Impact of Interpretability* (Ségerie, 2023) ∼20 min
3. *The Misguided Quest for Mechanistic AI Interpretability* (Hendrycks, 2025) ∼20 min
4. *Activation Space Interpretability May Be Doomed* (Chughtai, 2025) ∼15 min

References i

- Ameisen, Emmanuel, Jack Lindsey, Adam Pearce, Wes Gurnee, Nicholas L. Turner, Brian Chen, Craig Citro, David Abrahams, Shan Carter, Basil Hosmer, Jonathan Marcus, Michael Sklar, Adly Templeton, Trenton Bricken, Callum McDougall, Hoagy Cunningham, Thomas Henighan, Adam Jermyn, Andy Jones, Andrew Persic, Zhenyi Qi, T. Ben Thompson, Sam Zimmerman, Kelley Rivoire, Thomas Conerly, Chris Olah, and Joshua Batson [Mar. 2025]. ***Circuit Tracing: Revealing Computational Graphs in Language Models.*** URL: https://transformer-circuits.pub/2025/attribution-graphs/methods.html.
- Anthropic [2025]. ***Claude Opus 4.5 System Card.*** Tech. rep. Anthropic. URL: https://www.anthropic.com/claude-opus-4-5-system-card.
- — [2026]. ***Claude Opus 4.8 System Card.*** Tech. rep. Anthropic.
- Arditi, Andy, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda [Oct. 2024]. ***Refusal in Language Models Is Mediated by a Single Direction.*** URL: http://arxiv.org/abs/2406.11717 [visited on 03/31/2026].

References ii

- Arora, Sanjeev, Rong Ge, and Ankur Moitra [Aug. 2013]. ***New Algorithms for Learning Incoherent and Overcomplete Dictionaries.*** URL: https://arxiv.org/abs/1308.6273.
- Bricken, Trenton, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermyn, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, Robert Lasenby, Yifan Wu, Shauna Kravec, Nicholas Schiefer, Tim Maxwell, Nicholas Joseph, Alex Tamkin, Karina Nguyen, Brayden McLean, Josiah E Burke, Tristan Hume, Shan Carter, Tom Henighan, and Chris Olah [Oct. 2023]. ***Towards Monosemanticity: Decomposing Language Models With Dictionary Learning.*** Tech. rep. Anthropic. URL: https://transformer-circuits.pub/2023/monosemantic-features.
- Bussmann, Bart, Patrick Leask, and Neel Nanda [Dec. 2024]. ***BatchTopK Sparse Autoencoders.*** URL: http://arxiv.org/abs/2412.06410 [visited on 04/02/2026].

References iii

- Bussmann, Bart, Noa Nabeshima, Adam Karvonen, and Neel Nanda [Mar. 2025]. ***Learning Multi-Level Features with Matryoshka Sparse Autoencoders.*** URL: http://arxiv.org/abs/2503.17547 [visited on 04/02/2026].
- Candes, Emmanuel, Justin Romberg, and Terence Tao [Sept. 2004]. ***Robust Uncertainty Principles: Exact Signal Reconstruction from Highly Incomplete Frequency Information.*** URL: http://arxiv.org/abs/math/0409186 [visited on 03/30/2026].
- Chan, Lawrence, Leon Lang, and Erik Jenner [Mar. 2023]. **"Natural Abstractions: Key Claims, Theorems, and Critiques — AI Alignment Forum".** In: URL: https://www.alignmentforum.org/posts/gvzW46Z3BsaZsLc25/natural-abstractions-key-claims-theorems-and-critiques-1 [visited on 03/31/2026].
- Chanin, David, James Wilken-Smith, Tomáš Dulka, Hardik Bhatnagar, Satvik Golechha, and Joseph Bloom [Sept. 2024]. ***A Is for Absorption: Studying Feature Splitting and Absorption in Sparse Autoencoders.*** URL: https://arxiv.org/abs/2409.14507.

- Conmy, Arthur, Augustine N. Mavor-Parker, Aengus Lynch, Stefan Heimersheim, and Adrià Garriga-Alonso [Oct. 2023]. ***Towards Automated Circuit Discovery for Mechanistic Interpretability.*** URL: http://arxiv.org/abs/2304.14997 [visited on 04/02/2026].
- Donoho, D.L. [Apr. 2006]. **"Compressed Sensing".** In: *IEEE Transactions on Information Theory* 52.4. URL: http://ieeexplore.ieee.org/document/1614066/ [visited on 03/30/2026].
- Elhage, Nelson, Tristan Hume, Catherine Olsson, Nicholas Schiefer, Tom Henighan, Shauna Kravec, Zac Hatfield-Dodds, Robert Lasenby, Dawn Drain, Carol Chen, Roger Grosse, Sam McCandlish, Jared Kaplan, Dario Amodei, Martin Wattenberg, and Christopher Olah [Sept. 2022]. ***Toy Models of Superposition.*** URL: http://arxiv.org/abs/2209.10652 [visited on 07/17/2025].

References v

- Elhage, Nelson, Neel Nanda, Catherine Olsson, Tom Henighan, Nicholas Joseph, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, Nova DasSarma, Dawn Drain, Deep Ganguli, Zac Hatfield-Dodds, Danny Hernandez, Andy Jones, Jackson Kernion, Liane Lovitt, Kamal Ndousse, Dario Amodei, Tom Brown, Jack Clark, Jared Kaplan, Sam McCandlish, and Chris Olah [Dec. 2021]. ***A Mathematical Framework for Transformer Circuits.*** URL: https://transformer-circuits.pub/2021/framework/index.html.
- Engels, Joshua, Eric J Michaud, Isaac Liao, Wes Gurnee, and Max Tegmark [2025]. **"NOT ALL LANGUAGE MODEL FEATURES ARE ONE-DIMENSIONALLY LINEAR".** In.
- Fillingham, Sean P., Andrew Gordon, Peter Lai, Xavier Poncini, David Quarel, and Stefan Heimersheim [Nov. 2025]. ***SCALAR: Benchmarking SAE Interaction Sparsity in Toy LLMs.*** URL: http://arxiv.org/abs/2511.07572 [visited on 04/02/2026].

- Fraser-Taliente, Kit, Subhash Kantamneni, Euan Ong, Dan Mossing, Christina Lu, Paul C. Bogdan, Emmanuel Ameisen, James Chen, Dzmitry Kishylau, Adam Pearce, Julius Tarng, Alex Wu, Jeff Wu, Yang Zhang, Daniel M. Ziegler, Evan Hubinger, Joshua Batson, Jack Lindsey, Samuel Zimmerman, and Samuel Marks [May 2026]. ***Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations.*** URL: https://transformer-circuits.pub/2026/nla/ [visited on 06/05/2026].
- Johnson, William B. and Joram Lindenstrauss [1984]. **"Extensions of Lipschitz Mappings into a Hilbert Space".** In.
- Karvonen, Adam, James Chua, Clément Dumas, Kit Fraser-Taliente, Subhash Kantamneni, Julian Minder, Euan Ong, Arnab Sen Sharma, Daniel Wen, Owain Evans, and Samuel Marks [Jan. 2026]. ***Activation Oracles: Training and Evaluating LLMs as General-Purpose Activation Explainers.*** URL: http://arxiv.org/abs/2512.15674 [visited on 03/30/2026].

- Karvonen, Adam, Can Rager, Johnny Lin, Curt Tigges, Joseph Bloom, David Chanin, Yeu-Tong Lau, Eoin Farrell, Callum McDougall, Kola Ayonrinde, Demian Till, Matthew Wearden, Arthur Conmy, Samuel Marks, and Neel Nanda [June 2025]. ***SAEBench: A Comprehensive Benchmark for Sparse Autoencoders in Language Model Interpretability.*** URL: http://arxiv.org/abs/2503.09532 [visited on 03/30/2026].
- Li, Kenneth, Oam Patel, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg [June 2024]. ***Inference-Time Intervention: Eliciting Truthful Answers from a Language Model.*** URL: http://arxiv.org/abs/2306.03341 [visited on 03/31/2026].

- Lindsey, Jack, Wes Gurnee, Emmanuel Ameisen, Brian Chen, Adam Pearce, Nicholas L. Turner, Craig Citro, David Abrahams, Shan Carter, Basil Hosmer, Jonathan Marcus, Michael Sklar, Adly Templeton, Trenton Bricken, Callum McDougall, Hoagy Cunningham, Thomas Henighan, Adam Jermyn, Andy Jones, Andrew Persic, Zhenyi Qi, T. Ben Thompson, Sam Zimmerman, Kelley Rivoire, Thomas Conerly, Chris Olah, and Joshua Batson [Mar. 2025]. ***On the Biology of a Large Language Model.*** URL: https://transformer-circuits.pub/2025/attribution-graphs/biology.html.
- Lindsey, Jack, Adly Templeton, Jonathan Marcus, Thomas Conerly, Joshua Batson, and Christopher Olah [Oct. 2024]. ***Sparse Crosscoders for Cross-Layer Features and Model Diffing.*** URL: https://transformer-circuits.pub/2024/crosscoders/index.html.
- McDougall, Callum [Jan. 2023]. **"Induction Heads - Illustrated — LessWrong".** In: URL: https://www.lesswrong.com/posts/TvrfY4c9eaGLeyDkE/induction-heads-illustrated [visited on 04/02/2026].

- Mikolov, Tomas, Wen-tau Yih, and Geoffrey Zweig [June 2013]. **"Linguistic Regularities in Continuous Space Word Representations".** In: *Proceedings of the 2013 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*. Atlanta, Georgia: Association for Computational Linguistics. URL: https://aclanthology.org/N13-1090/ [visited on 03/30/2026].
- Nanda, Neel [Mar. 2022]. **"A Longlist of Theories of Impact for Interpretability".** In: URL: https://www.lesswrong.com/posts/uK6sQCNMw8WKzJeCQ/a-longlist-of-theories-of-impact-for-interpretability [visited on 03/31/2026].
- Nanda, Neel, Lawrence Chan, Tom Lieberum, Jess Smith, and Jacob Steinhardt [Jan. 2023]. ***Progress Measures for Grokking via Mechanistic Interpretability*.** URL: https://arxiv.org/abs/2301.05217.

References x

- Nanda, Neel, Andrew Lee, and Martin Wattenberg [2023]. **"Emergent Linear Representations in World Models of Self-Supervised Sequence Models".** In: *Proceedings of the 6th BlackboxNLP Workshop: Analyzing and Interpreting Neural Networks for NLP*. Singapore: Association for Computational Linguistics. URL: https://aclanthology.org/2023.blackboxnlp-1.2 [visited on 03/30/2026].
- nostalgebraist [Aug. 2020]. ***Interpreting GPT: The Logit Lens.*** URL: https://www.lesswrong.com/posts/AcKRB8wDpdaN6v6ru/interpreting-gpt-the-logit-lens.
- Olah, Chris, Nick Cammarata, Ludwig Schubert, Gabriel Goh, Michael Petrov, and Shan Carter [Mar. 2020]. **"Zoom In: An Introduction to Circuits".** In: *Distill* 5.3. URL: https://distill.pub/2020/circuits/zoom-in [visited on 03/30/2026].
- Panickssery, Nina, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Matt Turner [July 2024]. ***Steering Llama 2 via Contrastive Activation Addition.*** URL: http://arxiv.org/abs/2312.06681 [visited on 08/12/2025].

- Park, Kiho, Yo Joong Choe, and Victor Veitch [July 2024]. **"The Linear Representation Hypothesis and the Geometry of Large Language Models".** In.
- Rajamanoharan, Senthooran, Arthur Conmy, Lewis Smith, Tom Lieberum, Vikrant Varma, János Kramár, Rohin Shah, and Neel Nanda [Apr. 2024]. **"Improving Dictionary Learning with Gated Sparse Autoencoders".** In.
- Sharkey, Lee, Bilal Chughtai, Joshua Batson, Jack Lindsey, Jeff Wu, Lucius Bushnaq, Nicholas Goldowsky-Dill, Stefan Heimersheim, Alejandro Ortega, Joseph Bloom, Stella Biderman, Adria Garriga-Alonso, Arthur Conmy, Neel Nanda, Jessica Rumbelow, Martin Wattenberg, Nandi Schoots, Joseph Miller, Eric J. Michaud, Stephen Casper, Max Tegmark, William Saunders, David Bau, Eric Todd, Atticus Geiger, Mor Geva, Jesse Hoogland, Daniel Murfet, and Tom McGrath [Jan. 2025]. ***Open Problems in Mechanistic Interpretability.*** URL: `http://arxiv.org/abs/2501.16496` [visited on 03/30/2026].

- Templeton, Adly, Tom Conerly, Jonathan Marcus, Jack Clark, Yan Shlegeris, Trenton Bricken, Aidan O'Gara, Emmanuel Ameisen, Adam Jermyn, Baobao Zhang, Chris Olah, and Sam McCandlish [May 2024]. ***Scaling Monosemanticity: Extracting Interpretable Features from Claude 3 Sonnet.*** URL: https://transformer-circuits.pub/2024/scaling-monosemanticity/ [visited on 03/26/2026].
- Wang, Kevin, Alexandre Variengien, Arthur Conmy, Buck Shlegeris, and Jacob Steinhardt [Nov. 2022]. ***Interpretability in the Wild: A Circuit for Indirect Object Identification in GPT-2 Small.*** URL: https://arxiv.org/abs/2211.00593.
- Wentworth, John [Aug. 2020]. **"Alignment By Default — LessWrong".** In: URL: https://www.lesswrong.com/posts/Nwgdq6kHke5LY692J/alignment-by-default [visited on 03/31/2026].