# Learning Dynamics

Guillaume Corlouer

Stormglass

# Big questions

- How do models generalize?
- How does internal structure (e.g. goals) form during training?
- How can we intervene on the data, training objective, architecture, and optimizer to shape which internal structures are learned throughout training?

# How: making mathematical models of learning


- Tractable toy models: deep linear networks, shallow nonlinear networks, tensor networks, polynomial neural networks
- Take limits in depth, width, data, and training time
- Exploit symmetries: quotient them out and find conserved quantities
- Identify useful observables: learning coefficient, correlation functions, sufficient statistics...
- Validate with tight feedback loops: experiments, symbolic derivations, and mathematical proofs

# Safety motivations

- A central question in AI safety is how can we shape the training process to select an aligned instead of a harmful model (scheming, spiteful...)
- Develop stronger interpretability methods by decomposing models throughout training
- Our approach is to develop better models of training to find control levers in the training process that make us confident training will select a safe model

# Emergent misalignment

Jan Betley et al., "Emergent Misalignment: Narrow finetuning can produce broadly misaligned LLMs" (Figure 1)



# Setup

# Deep neural network


Let $\theta \in \Omega$ be the parameters, let $x \in \mathbb{R}^{d_0}$, and let $W_\ell \in \mathbb{R}^{d_\ell \times d_{\ell-1}}$ with biases $b_\ell$ and activation $\sigma$. With $h_0 = x$,

$$h_\ell(\theta, x) = \sigma(W_\ell h_{\ell-1}(\theta, x) + b_\ell),$$
$$\ell = 1, \ldots, L-1.$$

A deep neural network is a function $f_\theta$ such that

$$f_\theta(x) = W_L h_{L-1}(\theta, x)$$

Other architectural components include residual streams, tokenization, embeddings, attention for sequence modeling, and layer normalization.



# Deep linear network

The function is linear in the data and multi-linear (nonlinear) in the parameters:

$$f\colon \mathbb{R}^{d_0} \times \prod_{\ell=1}^{L} \mathbb{R}^{d_\ell \times d_{\ell-1}} \longrightarrow \mathbb{R}^{d_L},$$
$$(x, W_1, \ldots, W_L) \longmapsto W_L \cdots W_1 x = Wx.$$

$d_0$ is the input dimension; $d_\ell$, $1 \leq \ell \leq L$, is the width of layer $\ell$. Define the product map:

$$\mu(\theta) := W_L \cdots W_1 = W,$$

where $W$ is the student matrix.

# Data, loss function, gradient flow

## Quadratic population loss and gradient flow

Let $M$ be the teacher matrix, with $y = Mx$ and $x \sim \mathcal{N}(0, I_{d_0})$. The input-output covariance is $\Sigma_{YX} = \mathbb{E}[yx^\top] = M$.

$$\mathcal{L}(\theta) := \frac{1}{2}\|M - W_L \cdots W_1\|_F^2 = \frac{1}{2}\|M - W\|_F^2$$

Initialize $\theta_0 \sim \mathcal{N}(0, d_L^{-\gamma} I)$, where $\gamma$ controls the initialization scale. The gradient flow is

$$\dot{W}_\ell = -\nabla_{W_\ell} \mathcal{L}(\theta).$$


Frobenius norm: $\|A\|_F := \sqrt{\mathrm{Tr}(A^\top A)}$.
Global minimizers achieve zero loss: $\exists \theta^\star \in \Omega,\ \mu(\theta^\star) = W^\star = M$.
The structure of the data is encoded by $\Sigma_{YX}$.

# Geometry


# Global minima and saddle point

Loss: $\ell_1(x, y) = \frac{1}{2}(xy - 1)^2$
Global minima: $\{(x, y) : xy = 1\}$, $\ell_1 = 0$
Saddle point: $(0, 0)$, $\ell_1(0, 0) = \frac{1}{2}$
Strict saddle: along $x = y = t$ the loss decreases near 0, while along $x = -y = t$ the loss increases near 0

3D loss surface




Contour plot




Global minima form the hyperbola $xy = 1$, while $(0, 0)$ is a strict saddle point.

# Deep learning without poor local minima

Assume that $\Sigma_X$ and $\Sigma_{YX}$ are full rank, and that $\Sigma_{YX}$ has $d_L$ distinct singular values.

**No non-global local minima**

The loss function of a DLN of depth $L$ is non-convex and non-concave, and every critical point that is not a global minimum is a saddle point.

The training dynamics cannot get stuck in spurious local minima.
Reference: *Kawaguchi, Kenji. "Deep learning without poor local minima." Advances in neural information processing systems 29 (2016)*

# Parametrization of critical points

Teacher SVD: $M = \sum_{i=1}^{r_m} s_i u_i v_i^\top$.

**Saddle points**

Let $\theta \in \Omega$ be a critical point of rank $r$. Then there exists a subset $S$ of left singular vectors of $M$ and a projector $P_S$ onto their span such that

$$P_S := \sum_{i \in S} u_i u_i^\top, \qquad \mu(\theta) = P_S M = \sum_{i \in S} s_i u_i v_i^\top.$$

The saddle points are given by a subset of singular values and (left) singular vectors of the teacher $M$.

Reference: *Achour, El Mehdi, François Malgouyres, and Sébastien Gerchinovitz. "The loss landscape of deep linear neural networks: a second-order analysis." Journal of Machine Learning Research 25.242 (2024): 1-76.*

# Symmetries

Let $G_{\mathbf{d}} := \prod_{\ell=0}^{L} \mathrm{GL}_{d_\ell}$ act on $\Omega$ via

$$(W_1, \ldots, W_L) \mapsto (g_1 W_1 g_0^{-1},\ g_2 W_2 g_1^{-1},\ \ldots,\ g_L W_L g_{L-1}^{-1}).$$

## Equivariance of the multiplication map

Since $W_L g_{L-1}^{-1} g_{L-1} W_{L-1} \cdots g_1^{-1} g_1 W_1 = W_L \cdots W_1$, the multiplication map $\mu$ is $G_{\mathbf{d}}$-equivariant and invariant under the hidden gauge group $G_h$:

$$\mu(g \cdot \theta) = g_L \mu(\theta) g_0^{-1}, \qquad \mu(g_h \cdot \theta) = \mu(\theta).$$

A DLN is degenerate: infinitely many parameter values can map to the same student matrix.

It is natural to study solutions up to $G_{\mathbf{d}}$ symmetries. By equivariance of $\mu$, $G_{\mathbf{d}}$ acts on the determinantal variety

$$\Sigma_{\mathbf{d}}^{r} := \{\theta \in \Omega \mid \mathrm{rank}(\mu(\theta)) = r\}.$$

# Stratification of the fiber of the product map

## Orbits are parameterized by rank patterns

The $G_{\mathbf{d}}$-orbits in $\Sigma^r_{\mathbf{d}}$ are indexed by rank patterns

$$\rho_{ij} := \operatorname{rank}(W_j \cdots W_i), \qquad 1 \le i \le j \le L.$$

The corresponding orbit decomposition is

$$\Sigma^r_{\mathbf{d}} = \bigsqcup_{\rho} \mathcal{O}_\rho.$$

Two DLNs are in the same $G_{\mathbf{d}}$-orbit if and only if they have the same rank pattern. Since $\Sigma^r_{\mathbf{d}} = G_{\mathrm{out}} \cdot \mu^{-1}(W)$, this gives a combinatorial description of the fiber of the product map $\mu^{-1}(W)$.

Rank patterns are natural observables arising from geometric invariants of DLNs.

# Link with SLT

## Codimension of the global minima

For a teacher matrix $M$ of rank $r_m$, we have:

$$\begin{aligned}\operatorname{codim}\big(\mu^{-1}(M)\big) &= \operatorname{codim}\big(\Sigma_{\mathbf{d}}^{r_m}\big) + r_m(d_0 + d_L - r_m) \\ &= 2\ \mathrm{RLCT}_0(\mathcal{L}).\end{aligned}$$

In general, we only have:

$$\mathrm{RLCT}_0(\mathcal{L}) \leq \frac{1}{2} \operatorname{codim}_{\mathrm{Rep}_{\mathbf{d}}}\big(\mathcal{L}^{-1}(0)\big).$$

Ref: *Lehalleur, Simon Pepin, and Richárd Rimányi. "Geometry of fibers of the multiplication map of deep linear neural networks." arXiv preprint arXiv:2411.19920 (2024).*

# Discussion

**Takeaways**

Under full-rank and nondegenerate-data assumptions:

- Critical points of DLNs are either saddles or global minima
- Gauge symmetries mean there is a whole algebraic variety of degenerate minima
- Geometric invariants give observables and a combinatorial description of the parameter-function map and the global minima

# References


- Kenji Kawaguchi. Deep learning without poor local minima. *Advances in Neural Information Processing Systems*, 29, 2016.
- El Mehdi Achour, François Malgouyres, and Sébastien Gerchinovitz. The loss landscape of deep linear neural networks: a second-order analysis. *Journal of Machine Learning Research*, 25(242):1–76, 2024.
- Anna Choromanska, Mikael Henaff, Michael Mathieu, Gérard Ben Arous, and Yann LeCun. The loss surfaces of multilayer networks. In *Artificial Intelligence and Statistics*, pages 192–204. PMLR, 2015.
- Lehalleur, Simon Pepin and Rimányi, Richárd. Geometry of fibers of the multiplication map of deep linear neural networks, arXiv preprint arXiv:2411.19920, 2024.
- Chen, Po and Jiang, Rujun and Wang, Peng. A Complete Loss Landscape Analysis of Regularized Deep Matrix Factorization, arXiv preprint arXiv:2506.20344, 2025.

# Dynamics

# Gradient flow and NTK dynamics

In the small-learning-rate limit, gradient descent becomes gradient flow:

$$\theta_{t+1} = \theta_t - \eta \nabla_\theta \mathcal{L}(\theta_t) \qquad \rightsquigarrow \qquad \dot{\theta}(t) = -\nabla_\theta \mathcal{L}(\theta(t))$$

Neural Tangent Kernel (NTK):

$$K_\theta(x, x') = \nabla_\theta f_\theta(x) \cdot \nabla_\theta f_\theta(x')^\top = \sum_{i=1}^{p} \partial_{\theta_i} f_\theta(x)\, \partial_{\theta_i} f_\theta(x')^\top.$$

For a quadratic loss on a dataset $(x_i, y_i)$, the dynamics in function space are

$$\frac{d}{dt} f_{\theta_t}(x) = -\sum_{i=1}^{N} K_{\theta_t}(x, x_i)\big(f_{\theta_t}(x_i) - y_i\big).$$

# Conserved quantities in DLNs

Conserved quantities under gradient flow:


$$\beta_\ell := W_{\ell+1}^\top W_{\ell+1} - W_\ell W_\ell^\top, \qquad \ell = 1, \dots, L-1.$$

Along the flow, $\beta_\ell$ is constant. When $\beta_\ell = 0$, we have **balanced weights**.

For a one-dimensional, two-layer DLN, we get a hyperbolic equation:

$$w_2^2 - w_1^2 = \beta.$$

# Foliation of parameter space by balance leaves




**Definition of the balance leaves**

$$\mathcal{M}_\beta := \Big\{\theta \in \Omega : W_{\ell+1}^\top W_{\ell+1} - W_\ell W_\ell^\top = \beta_\ell, \ \forall\, \ell = 1, \dots, L-1\Big\}$$

$$\mathcal{M}_0 := \Big\{\theta \in \Omega : W_{\ell+1}^\top W_{\ell+1} - W_\ell W_\ell^\top = 0, \ \forall\, \ell = 1, \dots, L-1\Big\}$$

- Gradient flow remains on a fixed balance leaf.

# The manifold of gradient flow

Gradient flow is constrained to the following hyperbolic manifold:

$$\mathcal{M}_\beta := \{\theta \in \Omega \mid W_{\ell+1}^\top W_{\ell+1} - W_\ell W_\ell^\top = \beta_\ell,\ \ell = 1, \dots, L-1\}.$$

## Gradient flow on the balanced variety

On the balanced variety $\mathcal{M}_0$, the self-consistent gradient flow equation in function space is

$$\dot{W} = \sum_{k=1}^{L} (WW^\top)^{\frac{L-k}{L}} R(W) (W^\top W)^{\frac{k-1}{L}}, \qquad R(W) := \Sigma_{YX} - W.$$

For depth $L = 2$:


$$\mathcal{M}_0 = \{(W_1, W_2) \mid W_2^\top W_2 = W_1 W_1^\top\}.$$

$$\dot{W} = (WW^\top)^{\frac{1}{2}} R(W) + R(W)(W^\top W)^{\frac{1}{2}}.$$

# Learning rate: Edge of stability

Descent lemma: for an $L_{\text{smooth}}$-smooth convex loss, the loss decreases if $0 < \eta < 2/L_{\text{smooth}}$.

The loss is nonconvex, but the Hessian oscillates near and slightly above $\frac{2}{\eta}$; this regularizes away sharp minima.




Ref: Gradient Descent on Neural Networks Typically Occurs at the Edge of Stability, Cohen et al.

# Takeaways

**Key points**

- NTK preconditions gradient flow in function space
- Symmetries can induce conserved quantities that constrain the gradient flow
- Gradient flow in function space for balanced quantities leads to self-consistent equations
- The effect of the learning rate can be understood via the edge of stability

# References


- Menon, Govind. The geometry of the deep linear network. Symposium on Probability and Stochastic Processes. Cham: Springer Nature Switzerland, 2023.
- Sibylle Marcotte, Rémi Gribonval, and Gabriel Peyré. Abide by the law and follow the flow: Conservation laws for gradient flows. *Advances in neural information processing systems*, 36:63210–63221, 2023.
- Sanjeev Arora, Nadav Cohen, Noah Golowich, and Wei Hu. *A convergence analysis of gradient descent for deep linear neural networks*. arXiv preprint arXiv:1810.02281, 2018
- Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: Convergence and generalization in neural networks. *Advances in Neural Information Processing Systems*, 31, 2018.
- Jeremy M. Cohen, Alex Damian, Ameet Talwalkar, J. Zico Kolter, and Jason D. Lee. Understanding optimization in deep learning with central flows. arXiv preprint arXiv:2410.24206, 2024.

# Initialization, Width, and Depth


# Training losses

Initialize weights: $\theta \sim \mathcal{N}(0, d_L^{-\gamma} I)$


$\gamma < 1$: large initialization, linear regime (NTK)

$\gamma > 1$: small initialization, saddle-to-saddle


$\gamma = 1$: intermediate regime



# Singular values of the student matrix



# Singular values of individual weight matrices



# Lazy regime (NTK or linear regime)

For a DLN of depth $L$ with initialization $\theta(0) \sim \mathcal{N}(0, \sigma^2 I)$ and $\sigma^2 = d_L^{-\gamma}$, with $\gamma < 1$:

$$\dot{W} \approx K_0(M - W).$$

This leads to the following solution:


$$W(t) = M - \exp(-K_0 t)\big(M - W(0)\big).$$

The timescale of learning is fixed by the NTK at initialization:

$$t \approx -K_0^{-1} \log\left(\frac{s - w_f}{s - w_0}\right)$$

This behaves like a shallow linear network: student interpolates between $M$ and a random matrix $W_0$.

# Alignment happens at the same time as learning singular values



# Rich regime

For balanced, and aligned weights, and $\gamma > 1$ (small init.), the singular values of the student satisfy

$$\dot{w}_\alpha = 2\left(s_\alpha - w_\alpha\right) w_\alpha.$$


Solving this ODE for $w(t) := w_\alpha$ gives:

$$w(t) = \frac{s}{1 + \left(\frac{s}{w_0} - 1\right) e^{-2st}}.$$


The timescale of learning is

$$t = \frac{1}{2s} \ln\left(\frac{w_f\left(s - w_0\right)}{w_0\left(s - w_f\right)}\right), \qquad s \neq 0.$$

# Alignment happens before learning singular values



# Rich vs Lazy


rich vs lazy — feature learning diagnostics
NTK movement (frozen kernel ⇔ lazy)
rich
lazy
$\|K_t - K_0\|_F / \|K_0\|_F$
training time $t = \eta \times$ step
kernel-task alignment (silent alignment observable)
rich
lazy
$\frac{\mathrm{vec}(yy^\top)^\top K_t \mathrm{vec}(M)}{\|K_t\|_F \|yy^\top\|_F}$
training time $t = \eta \times$ step
do the weight matrices themselves align?
rich: $W_1$ right vecs vs $V$
rich: $W_1$ left vecs vs $U$
lazy: $W_1$ right vecs vs $V$
lazy: $W_1$ left vecs vs $U$
random overlap
mean alignment over modes
training time $t = \eta \times$ step
alignment vs training progress
rich
lazy
mean singular-vector alignment
remaining loss fraction $\mathcal{L}/\mathcal{L}_0$ (training →)

# Takeaways

## Key points


- Depth and specific initialization induce different learning regimes
- Large initialization and large width give the NTK regime: no feature learning, and the NTK is frozen: linear regression.
- In the saddle to saddle regime, learning happens in two phases: task alignment and amplification.
- In the saddle to saddle regime, the timescale of learning is set by the target singular values
- Gradient flow has a simplicity bias toward learning low hanging fruit directions

# References


- Saxe, Andrew M., James L. McClelland, and Surya Ganguli. A mathematical theory of semantic development in deep neural networks. *Proceedings of the National Academy of Sciences* 116.23 (2019): 11537-11546.
- Jacot, Arthur, et al. Saddle-to-saddle dynamics in deep linear networks: Small initialization training, symmetry, and sparsity. *arXiv preprint* arXiv:2106.15933 (2021).
- Dominé, Clémentine CJ, et al. From lazy to rich: Exact learning dynamics in deep linear networks. *arXiv preprint* arXiv:2409.14623 (2024).
- Zhang, Yedi, Andrew Saxe, and Peter E. Latham. Saddle-to-Saddle Dynamics Explains A Simplicity Bias Across Neural Network Architectures. *arXiv preprint* arXiv:2512.20607 (2025).
- Zhenfeng Tu, Santiago Tomas Aranguri Diaz, and Arthur Jacot. Mixed dynamics in linear networks: Unifying the lazy and active regimes. *Advances in Neural Information Processing Systems*, 37:106059–106104, 2024.

# Towards nonlinearity


# Neural race reduction in gated DLNs




*The Neural Race Reduction: Dynamics of Abstraction in Gated Networks, Andrew M. Saxe et al.*


# MLP and linear transformers

*Saddle-to-Saddle Dynamics Explains A Simplicity Bias Across Neural Network Architectures, Saxe et al.*



# Alternating Gradient Flows


*Alternating Gradient Flows: A Theory of Feature Learning in Two-layer Neural Networks*



**Algorithm 1: AGF**

**Initialize:** $\mathcal{D} \leftarrow [H]$, $\mathcal{A} \leftarrow \emptyset$, $\mathcal{S} \leftarrow 0 \in \mathbb{R}^H$
**while** $\nabla \mathcal{L}(\Theta_{\mathcal{D}}) \neq 0$ **do**
  **while** $\forall i \in \mathcal{D} \quad \mathcal{S}_i \leq c_i$ **do**
    **for** $i \in \mathcal{D}$ **do**
      $\frac{d\bar{\theta}_i}{dt} = \eta_\alpha \|\theta_i\|^{\kappa-2} \mathbf{P}^{\perp}_{\bar{\theta}_i} \nabla \mathcal{U}(\bar{\theta}_i, r)$
      $\frac{d\mathcal{S}_i}{dt} = \eta_\alpha \kappa \mathcal{U}(\bar{\theta}_i, r)$
    Activate neuron: $\mathcal{D}, \mathcal{A} \leftarrow \mathcal{D} \setminus \{i_*\}, \mathcal{A} \cup \{i_*\}$
  **while** $\nabla \mathcal{L}(\Theta_{\mathcal{A}}) \neq 0$ **do**
    **for** $j \in \mathcal{A}$ **do**
      $\frac{d\theta_j}{dt} = -\nabla_{\theta_j} \mathcal{L}(\Theta_{\mathcal{A}})$
    Remove collapsed neurons: $\mathcal{D}, \mathcal{A} \leftarrow \mathcal{D} \cup \mathcal{C}, \mathcal{A} \setminus \mathcal{C}$

**Conceptual Illustration: AGF**



**Key points**

- Nonlinearity modeled with gated DLNs: neural race reduction
- MLPs and linear transformers also have saddle-to-saddle dynamics
- Alternating gradient flow on quadratic networks: towards a more general theory of the saddle-to-saddle regime

# Stochasticity

# Langevin dynamics

- SGD: Sample a batch from a dataset and compute the batch gradient
- Continuous model with Brownian motion $B_t$

$$d\theta_t = -\nabla \mathcal{L}(\theta_t)\, dt + \sqrt{\eta}\, \Sigma^{1/2}(\theta_t)\, dB_t.$$

- The gradient-noise covariance $\Sigma(\theta_t)$ depends on geometry: it is anisotropic and state-dependent

# Fokker-Planck: Boltzmann equilibria

The Fokker-Planck equation (for density $p(\theta, t)$) is a local conservation law:

$$\begin{aligned} \partial_t p(\theta, t) &= -\nabla \cdot j(\theta, t), \\ j(\theta, t) &= -p(\theta, t)\nabla \mathcal{L}(\theta) - \frac{\eta}{2}\nabla_\theta^\top (\Sigma(\theta) p(\theta, t)) \,. \end{aligned}$$

Important special case:

- Stationary distribution: $\partial_t p^*(\theta) = 0$
- Thermal equilibrium: $j = 0$
- White noise: $\Sigma = \sigma^2 I$

$$p^*(\theta) \propto \exp\left(-\frac{2}{\eta\sigma^2}\mathcal{L}_N(\theta)\right) \qquad \text{(Boltzmann)}.$$

# Noise anisotropy


- In general, noise is anisotropic: it introduces a different implicit bias
- In function space, Langevin dynamics introduce an additional drift

$$\frac{\eta}{2}\,\mathrm{Tr}\big(\Sigma(\theta)H(\theta)\big)$$

- Heuristic: bias toward flatter minima
- More:
  - See Govind Menon On the implicit regularization of Langevin dynamics with projected noise
  - Our paper deriving Langevin dynamics for DLNs during the saddle-to-saddle regime

# Golden Path hypothesis

- Lots of debate about the implicit bias of SGD noise
- Transient regime (drift-dominated) versus low-loss regime (diffusion-dominated):




*Beyond Implicit Bias: The Insignificance of SGD Noise in Online Learning*

# Takeaways

**Key points**

- SGD can be modeled by an SDE with state-dependent noise
- If the noise is white and the system is at thermal equilibrium, the stationary distribution of the SDE is Boltzmann
- The implicit bias of stochasticity is not fully understood (flatness?), but it is more of a second-order effect

# Promising directions

- Polynomial neural networks (quadratic activations)
- Related: tensor networks and tree tensor networks

**Big questions**

- Toy models of deep nonlinear learning
- Theory that captures natural data
- Making explicit the implicit biases of realistic architectures
- Mixing rich and lazy regimes
- A statistical field theory of deep neural networks

Reference: *There Will Be a Scientific Theory of Deep Learning, Jamie Simon et al.*