CPU Emulator Tutorial

This program is part of the software suite
that accompanies

The Elements of Computing Systems

by Noam Nisan and Shimon Schocken

MIT Press

www.nand2tetris.org

This software was developed by students at the
Efi Arazi School of Computer Science at IDC

Chief Software Architect: Yaron Ukrainitz

Background

The Elements of Computing Systems evolves around the construction of a complete computer system, done in the framework of a 1- or 2-semester course.

In the first part of the book/course, we build the hardware platform of a simple yet powerful computer, called Hack. In the second part, we build the computer's software hierarchy, consisting of an assembler, a virtual machine, a simple Java-like language called Jack, a compiler for it, and a mini operating system, written in Jack.

The book/course is completely self-contained, requiring only programming as a pre-requisite.

The book's web site includes some 200 test programs, test scripts, and all the software tools necessary for doing all the projects.



The book's software suite



(All the supplied tools are dual-platform: **`Xxx.bat`** starts **`Xxx`** in Windows, and **`Xxx.sh`** starts it in Unix)

Simulators

(**`HardwareSimulator`**, **`CPUEmulator`**, **`VMEmulator`**):

- Used to build hardware platforms and execute programs;
- Supplied by us.

Translators (**`Assembler`**, **`JackCompiler`**):

- Used to translate from high-level to low-level;
- Developed by the students, using the book's specs; Executable solutions supplied by us.

Other

- **`Bin`**: simulators and translators software;
- **`builtIn`**: executable versions of all the logic gates and chips mentioned in the book;
- **`os`**: executable version of the Jack OS;
- **`TextComparer`**: a text comparison utility.

Tutorial Objective

The Hack computer

This CPU emulator simulates the operations of the Hack computer, built in chapters 1-5 of the book.

Hack -- a 16-bit computer equipped with a screen and a keyboard -- resembles hand-held computers like game machines, PDA's, and cellular telephones.

Before such devices are actually built in hardware, they are planned and simulated in software.

The CPU emulator is one of the software tools used for this purpose.

CPU Emulator Tutorial

I. Basic Platform

II. I/O devices

III. Interactive simulation

IV. Script-based simulation

V. Debugging

Relevant reading (from "*The Elements of Computing Systems*"):

- Chapter 4: *Machine Language*
- Chapter 5: *Computer Architecture*
- Appendix B: *Test Scripting Language*


Part I:
Basic Platform

The Hack Computer Platform (simulated)



The Hack Computer Platform



Instruction memory



Data memory (RAM)



Registers


CPU Emulator (1.4b3) - G:\examples\Rect.asm
File View Run Help
Animate:
Slow
Fast
Program
ROM
Asm
RAM
PC
A
Registers (all 16-bit):
D: Data register
A: Address register
M: Stands for the memory register whose address is the current value of the Address register
M (=RAM[A])
D
A
ALU
D Input :
M/A Input :
ALU output :
17184
25
17184

Arithmetic/Logic Unit



Arithmetic logic unit (ALU)

- The ALU can compute various arithmetic and logical functions (let's call them f) on subsets of the three registers {M,A,D}
- All ALU instructions are of the form {M,A,D} = f ({M,A,D})
  (e.g. M=M-1, MD=D+A , A=0, etc.)
- The ALU operation (LHS destination, function, RHS operands) is specified by the current instruction.


Part II:
I/O Devices

I/O devices: screen and keyboard



Screen action demo



Keyboard action demo



Keyboard action demo



Perspective: That's how computer programs read from the keyboard: they peek some keyboard-oriented memory device, one character at a time.

This is rather tedious in machine language programming, but quite easy in high-level languages that handle the keyboard indirectly, using OS routines like **`readLine`** or **`readInt`**, as we will see in Chapters 9 and 12.

Since all high level programs and OS routines are eventually translated into machine language, they all end up doing something like this example.


Part III:
Interactive
Simulation

Loading a program



Loading a program



Running a program



Running a program



Hack programming at a glance (optional)



Animation options




Part IV:
Script-Based
Simulation

Interactive VS Script-Based Simulation

A program can be executed and debugged:

- **Interactively**, by ad-hoc playing with the emulator's GUI (as we have done so far in this tutorial)
- **Batch-ly**, by running a pre-planned set of tests, specified in a *script*.

Script-based simulation enables planning and using tests that are:

- Pro-active
- Documented
- Replicable
- Complete (as much as possible)

Test scripts:

- Are written in a *Test Description Language* (described in Appendix B)
- Can cause the emulator to do anything that can be done interactively, and quite a few things that cannot be done interactively.

The basic setting



Example: **Max.asm**



Note: For now, it is not necessary to understand either the Hack machine language or the Max program. It is only important to grasp the program's logic. But if you're interested, we give a language overview on the right.

```
// Computes M[2]=max(M[0],M[1]) where M stands for RAM
   @0
   D=M              // D = M[0]
   @1
   D=D-M            // D = D - M[1]
   @FIRST_IS_GREATER
   D;JGT            // If D>0 goto FIRST_IS_GREATER
   @1
   D=M              // D = M[1]
   @SECOND_IS_GREATER
   0;JMP            // Goto SECOND_IS_GREATER
(FIRST_IS_GREATER)
   @0
   D=M              // D=first number
(SECOND_IS_GREATER)
   @2
   M=D              // M[2]=D (greater number)
(INFINITE_LOOP)
   @INFINITE_LOOP   // Infinite loop (our standard
   0;JMP            // way to terminate programs).
```

Hack language at a glance:

- **(label)** // defines a label
- **@xxx** // sets the **A** register
  // to xxx's value
- The other commands are self-explanatory; Jump directives like **JGT** and **JMP** mean "Jump to the address currently stored in the **A** register"
- Before any command involving a RAM location (**M**), the **A** register must be set to the desired RAM address (**@address**)
- Before any command involving a jump, the **A** register must be set to the desired ROM address (**@label**).

Sample test script: **Max.tst**



```
// Load the program and set up:
load Max.asm,
output-file Max.out,
compare-to  Max.cmp,
output-list RAM[0]%D2.6.2
            RAM[1]%D2.6.2
            RAM[2]%D2.6.2;

// Test 1: max(15,32)
set RAM[0] 15,
set RAM[1] 32;
repeat 14 {
  ticktock;
}
output;  // to the Max.out file

// Test 2: max(47,22)
set PC 0, // Reset prog. counter
set RAM[0] 47,
set RAM[1] 22;
repeat 14 {
  ticktock;
}
output;

// test 3: max(12,12)
// Etc.
```

The scripting language has commands for:

- Loading programs
- Setting up output and compare files
- Writing values into RAM locations
- Writing values into registers
- Executing the next command ("`ticktack`")
- Looping ("`repeat`")
- And more (see Appendix B).

Notes:

- As it turns out, the Max program requires 14 cycles to complete its execution
- All relevant files (`.asm`, `.tst`, `.cmp`) must be present in the same directory.

Output

RAM[0]	RAM[1]	RAM[2]
15	32	32
47	22	47

Using test scripts



Using test scripts



Using test scripts



The default script (and a deeper understanding of the CPU emulator logic)




Part V:
Debugging

Breakpoints: a powerful debugging tool

The CPU emulator continuously keeps track of:

- **`A:`** value of the A register
- **`D:`** value of the D register
- **`PC:`** value of the Program Counter
- **`RAM[i]:`** value of any RAM location
- **`time:`** number of elapsed machine cycles

Breakpoints:

- A breakpoint is a pair <variable, value> where variable is one of {**`A`**, **`D`**, **`PC`**, **`RAM[i]`**, **`time`**} and **`i`** is between 0 and 32K.
- Breakpoints can be declared either interactively, or via script commands.
- For each declared breakpoint, when the variable reaches the value, the emulator pauses the program's execution with a proper message.

Breakpoints declaration



Breakpoints declaration



Breakpoints usage



Postscript: Maurice Wilkes (computer pioneer) discovers debugging:

As soon as we started programming, we found to our surprise that it wasn't as easy to get programs right as we had thought. Debugging had to be discovered. I can remember the exact instant when I realized that a large part of my life from then on was going to be spent in finding mistakes in my own programs.

(Maurice Wilkes, 1949).