



MICROSOFT WINDOWS 10

不同的系统版本，有着不同的封装方式，封装过程中包含：“语言包：添加、关联、删除”、“驱动：添加、删除”、“累积更新：添加、删除”、“InBox Apps：添加、更新、标记”等。

在这背后藏着很多的隐藏故事，想解开这些，你准备好开始尝试封装了吗？

摘要

- 章节 1 部署映像
- 章节 2 报告
- 章节 3 常见问题
- 章节 4 已知问题

章节 1	部署映像	第 6 页
A.	先决条件	第 6 页
II	ISO 工具	第 6 页
III	要求	第 6 页
1.	系统安装包	第 6 页
2.	语言包	第 7 页
2.1.	学习	第 7 页
2.2.	语言包：下载	第 10 页
IV	Windows 安全中心	第 10 页
V	命令行	第 11 页
B.	语言包：提取	第 11 页
II	语言包：准备	第 11 页
III	语言包：提取方案	第 11 页
IV	执行提取命令	第 12 页
C.	自定义部署映像	第 17 页
II	自定义部署映像：Install.wim	第 17 页
1.	查看 Install.wim 详细信息	第 18 页
2.	指定挂载路径：Install.wim	第 18 页
3.	开始挂载 Install.wim	第 18 页
3.1.	自定义部署映像：WinRE.wim	第 18 页
3.1.1.	查看 WinRE.wim 详细信息	第 18 页
3.1.2.	指定挂载路径：WinRE.wim	第 18 页
3.1.3.	开始挂载 WinRE.wim	第 18 页
3.1.4.	语言包	第 19 页
3.1.4.1.	语言包：添加	第 19 页

3.1.4.2.	脱机映像语言：更改	第 20 页
3.1.4.2.1.	更改默认语言、区域设置和其他国际设置	第 20 页
3.1.4.2.2.	查看可用的语言设置	第 21 页
3.1.4.3.	语言包：删除	第 21 页
3.1.4.4.	组件：映像中已安装的所有包	第 23 页
3.1.5.	累积更新	第 23 页
3.1.5.1.	添加	第 23 页
3.1.5.2.	删除	第 23 页
3.1.5.3.	固化更新	第 24 页
3.1.5.3.1.	固化更新后清理组件	第 24 页
3.1.6.	驱动	第 24 页
3.1.7.	保存映像	第 24 页
3.1.8.	卸载映像	第 24 页
3.1.9.	重建 WinRE.wim 后，可缩小文件大小	第 24 页
3.1.10.	备份 WinRE.wim	第 25 页
3.1.11.	替换 Install.wim 映像内的 WinRE.wim	第 25 页
4.	语言包	第 26 页
4.1.	语言包：添加	第 26 页
4.2.	脱机映像语言：更改	第 32 页
4.2.1.	更改默认语言、区域设置和其他国际设置	第 32 页
4.2.2.	查看可用的语言设置	第 32 页
4.3.	语言包：删除	第 32 页
4.4.	组件：映像中已安装的所有包	第 34 页
5.	InBox Apps	第 35 页

5.1.	学习	第 35 页
5.2.	InBox Apps: 预安装应用程序	第 35 页
5.3.	InBox Apps: 已安装	第 37 页
5.4.	删除已安装的所有预应用程序	第 37 页
5.5.	区域标记: 了解	第 37 页
5.6.	区域标记: 添加方式	第 38 页
5.7.	InBox Apps: 安装	第 41 页
5.8.	区域标记: 删除	第 48 页
5.9.	InBox Apps: 优化	第 49 页
6.	累积更新	第 49 页
6.1.	功能启用包	第 49 页
6.2.	初始版本	第 49 页
6.3.	其它版本	第 51 页
6.4.	固化更新	第 52 页
6.4.1.	固化更新后清理组件	第 52 页
7.	驱动	第 52 页
8.	部署引擎: 添加	第 52 页
9.	健康	第 52 页
10.	替换 WinRE.wim	第 53 页
11.	保存映像	第 53 页
12.	卸载映像	第 53 页
13.	重建 Install.wim 后可缩小文件大小	第 53 页
14.	如何批量替换 Install.wim 里的所有索引号里的 WinRE.wim	第 54 页
14.1.	获取 WimLib	第 54 页
14.2.	如何在 Install.wim 里提取和更新 WinRE.wim	第 54 页
III	自定义部署映像: boot.wim	第 55 页

1.	查看 Boot.wim 详细信息	第 55 页
2.	指定挂载路径: Boot.wim	第 55 页
3.	开始挂载 Boot.wim	第 55 页
4.	语言包	第 55 页
4.1.	语言包: 添加	第 56 页
4.2.	脱机映像语言: 更改	第 57 页
4.2.1.	更改默认语言、区域设置和其他国际设置	第 57 页
4.2.2.	查看可用的语言设置	第 57 页
4.3.	语言包: 删除	第 57 页
4.4.	组件: 映像中已安装的所有包	第 60 页
4.5.	语言包: 同步到 ISO 安装程序	第 60 页
4.6.	重新生成 Lang.ini	第 60 页
4.6.1.	重新生成已挂载目录 lang.ini	第 60 页
4.6.2.	重新生成 lang.ini 后, 同步到安装程序	第 60 页
5.	累积更新	第 61 页
5.1.	添加	第 61 页
5.2.	删除	第 61 页
5.3.	固化更新	第 61 页
5.3.1.	固化更新后清理组件	第 61 页
6.	驱动	第 61 页
7.	保存映像	第 61 页
8.	卸载映像	第 61 页
IV	部署引擎	第 61 页
1.	添加方式	第 62 页
2.	部署引擎: 进阶	第 65 页

D.	ISO	第 67 页
II	生成 ISO	第 67 页
章节 2	报告	第 68 页
II	报告：不同版本	第 68 页
III	语言安装包适用于：Install.wim	第 70 页
IV	语言安装包适用于：WinRE.wim	第 71 页
V	语言安装包适用于：Boot.wim	第 72 页
章节 3	常见问题	第 73 页
II	清理所有挂载到	第 73 页
III	修复挂载出现异常的问题	第 74 页
IV	清理目录	第 74 页
章节 4	已知问题	第 74 页

章节 1 部署映像

A. 先决条件

II ISO 工具

准备一款可编辑 ISO 文件的软件，例如：[PowerISO](#)、[DAEMON Tools](#)、[ISO Workshop](#)；

III 要求

1. 系统安装包

关键词：[迭代](#)、[跨版本](#)、[大版本](#)、[累积更新](#)、[初始版本](#)

1.1. 说明

- 1.1.1. 每版本更新时请重新制作镜像，例如从 21H1 跨越到 22H2 时，应避免出现其它兼容性问题请勿在旧镜像基础上制作；
- 1.1.2. 该条例已经在某些 OEM 厂商，通过各种形式向封装师明确传达了该法令，不允许直接从迭代版本里直接升级；
- 1.1.3. 制作中请使用“初始版本”、“开发者版”制作。微软官方文档里曾短暂的出现过在制作中必须使用初始版本，后来这句在官方文档里却被删除了；
- 1.1.4. 安装语言包后，必须重新添加累积更新（可同一版本号），不添加累积更新会出现“乱码”、“界面闪退”等问题。
- 1.1.5. 进化过程：Windows 10 22H2, Build 19045.2006 + KB5027215 = OS Build 19045.3086

1.2. 准备下载初始版本或开发者版本

- 1.2.1. [en-us_windows_10_business_editions_version_22h2_x64_dvd_8cf17b79.iso](#)
- 1.2.2. [en-us_windows_10_business_editions_version_22h2_x86_dvd_186a68c3.iso](#)
- 1.2.3. [en-us_windows_10_consumer_editions_version_22h2_x64_dvd_8da72ab3.iso](#)
- 1.2.4. [en-us_windows_10_consumer_editions_version_22h2_x86_dvd_90883feb.iso](#)
- 1.2.5. [en-us_windows_10_iot_enterprise_version_22h2_arm64_dvd_39566b6b.iso](#)
- 1.2.6. [en-us_windows_10_iot_enterprise_version_22h2_x64_dvd_51cc370f.iso](#)
- 1.2.7. [en-us_windows_10_business_editions_version_21h2_x64_dvd_ce067768.iso](#)
- 1.2.8. [en-us_windows_10_business_editions_version_21h2_x86_dvd_8aba314e.iso](#)
- 1.2.9. [en-us_windows_10_consumer_editions_version_21h2_x64_dvd_6cfdb144.iso](#)
- 1.2.10. [en-us_windows_10_consumer_editions_version_21h2_x86_dvd_31755f1b.iso](#)
- 1.2.11. [en-us_windows_10_enterprise_ltsc_2021_x64_dvd_d289cf96.iso](#)
- 1.2.12. [en-us_windows_10_enterprise_ltsc_2021_x86_dvd_9f4aa95f.iso](#)

- 1.2.13. [en-us_windows_10_iot_enterprise_ltsc_2021_x64_dvd_257ad90f.iso](#)
- 1.3. 示例下载 [en-us_windows_10_business_editions_version_22h2_x64_dvd_8cf17b79.iso](#) 后，解压到：[D:\en-us_windows_10_business_editions_version_22h2_x64_dvd_8cf17b79](#)
- 1.4. 解压完成后，将目录 [en-us_windows_10_business_editions_version_22h2_x64_dvd_8cf17b79](#) 更改为 [D:\OS_10](#)
- 1.5. 所有脚本、所有路径，已默认设置为 [D:\OS_10](#) 为映像来源。
- 1.6. 安装配置
- 1.6.1. 学习：[Windows 安装版配置和产品 ID 文件 \(EI.cfg 和 PID.txt\)](#)
- 1.6.2. 已知问题
- 1.6.2.1. 没有 Ei.cfg 时，ISO 引导安装，选择某些版本时会报错，提示：[Windows 找不到 Microsoft 软件许可条款。请确保安装源有效。然后重新启动安装。](#)
- 1.6.2.2. 如何解决，添加 ei.cfg 到 [D:\OS_11\Sources](#) 里，创建 ei.cfg：
- ```
@

[Channel]

volume

[VL]

1

"@ | Out-File -FilePath "D:\OS_11\sources\EI.CFG" -Encoding Ascii
```

## 2. 语言包

### 2.1. 学习

阅读时，请了解“蓝色”重要突出部分。

- 2.1.1. [语言概述](#)
- 2.1.2. [将语言添加到 Windows 10 映像](#)
- 2.1.3. [语言和区域按需功能 \(FOD\)](#)
- 2.1.3.1. 字体
- 添加语言包时，触发了对应的区域时，需添加所需的字体功能，下载“[所有可用语言 FOD 的列表](#)”了解更多。
  - 在“语言包：提取”时，已加入自动识别功能，可了解函数：[Function Match\\_Required\\_Fonts](#)



2.1.3.2. 区域关联

区域关联是什么？

- 映像语言仅英文版时，添加 zh-HK 语言包后，映像语言不会新增，应先安装 zh-TW 后，再安装 zh-HK 即可获得对应的关联。

已知区域关联：

2.1.3.2.1. 区域：ar-sa，可选关联区域：en-US，关联安装包：

- 2.1.3.2.1.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-Package~31bf3856ad364e35~amd64~~.cab
- 2.1.3.2.1.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.2. 区域：bg-bg，可选关联区域：en-US，关联安装包：

- 2.1.3.2.2.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-Package~31bf3856ad364e35~amd64~~.cab
- 2.1.3.2.2.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.3. 区域：da-dk，可选关联区域：en-US，关联安装包：

- 2.1.3.2.3.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-Package~31bf3856ad364e35~amd64~~.cab
- 2.1.3.2.3.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.4. 区域：el-gr，可选关联区域：en-US，关联安装包：

- 2.1.3.2.4.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-Package~31bf3856ad364e35~amd64~~.cab
- 2.1.3.2.4.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.5. 区域：fr-ca，可选关联区域：en-US、fr-fr，关联安装包：

- 2.1.3.2.5.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-Package~31bf3856ad364e35~amd64~~.cab
- 2.1.3.2.5.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-Package~31bf3856ad364e35~amd64~~.cab
- 2.1.3.2.5.3. Microsoft-Windows-LanguageFeatures-Basic-fr-fr-Package~31bf3856ad364e35~amd64~~.cab
- 2.1.3.2.5.4. Microsoft-Windows-LanguageFeatures-Handwriting-fi-fi-

Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.6. 区域: [he-il](#), 可选关联区域: [en-US](#), 关联安装包:

2.1.3.2.6.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.6.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.7. 区域: [ru-ru](#), 可选关联区域: [en-US](#), 关联安装包:

2.1.3.2.7.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.7.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.8. 区域: [th-th](#), 可选关联区域: [en-US](#), 关联安装包:

2.1.3.2.8.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.8.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.9. 区域: [uk-ua](#), 可选关联区域: [en-US](#), 关联安装包:

2.1.3.2.9.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.9.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.10. 区域: [zh-TW](#), 可选关联区域: [zh-HK](#), 关联安装包:

2.1.3.2.10.1. Microsoft-Windows-LanguageFeatures-Basic-zh-hk-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.10.2. Microsoft-Windows-LanguageFeatures-Speech-zh-hk-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.10.3. Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-hk-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.3. 其它区域特定的要求

触发已知区域时, 需添加特定的“程序包”。

2.1.3.3.1. 区域: [zh-TW](#), 程序包: [Microsoft-Windows-InternationalFeatures-Taiwan-  
Package~31bf3856ad364e35~amd64~~.cab](#)

说明：对台湾日期格式设置要求的补充支持。将为位于台湾的客户提供包。

建议：仅在运送到台湾市场的设备上预安装。未在设备上安装此功能会导致对使用台湾日历的任何 API 调用失败。

存在争议：

- 在测试中发现，微软官方原版 Windows 10 里并未发现原版映像里安装此程序包，但是在建议项里有已知问题，到底是遵循与微软官方原版一致，由封装师自由选择安装与否。

2.2. 语言包：下载

[https://software-download.microsoft.com/download/pr/19041.1.191206-1406.vb\\_release\\_CLIENTLANGPACKDVD\\_OEM\\_MULTI.iso](https://software-download.microsoft.com/download/pr/19041.1.191206-1406.vb_release_CLIENTLANGPACKDVD_OEM_MULTI.iso)

2.3. 功能包：下载

ARM64: [https://software-static.download.prss.microsoft.com/pr/download/19041.1.191206-1406.vb\\_release\\_arm64fre\\_FOD-PACKAGES\\_OEM\\_PT1\\_arm64fre\\_MULTI.iso](https://software-static.download.prss.microsoft.com/pr/download/19041.1.191206-1406.vb_release_arm64fre_FOD-PACKAGES_OEM_PT1_arm64fre_MULTI.iso)

X64: [https://software-download.microsoft.com/download/pr/19041.1.191206-1406.vb\\_release\\_amd64fre\\_FOD-PACKAGES\\_OEM\\_PT1\\_amd64fre\\_MULTI.iso](https://software-download.microsoft.com/download/pr/19041.1.191206-1406.vb_release_amd64fre_FOD-PACKAGES_OEM_PT1_amd64fre_MULTI.iso)

X86: [https://software-static.download.prss.microsoft.com/pr/download/19041.1.191206-1406.vb\\_release\\_x86fre\\_FOD-PACKAGES\\_OEM\\_PT1\\_x86fre\\_MULTI.iso](https://software-static.download.prss.microsoft.com/pr/download/19041.1.191206-1406.vb_release_x86fre_FOD-PACKAGES_OEM_PT1_x86fre_MULTI.iso)

3. InBox Apps

[https://software-static.download.prss.microsoft.com/dbazure/888969d5-f34g-4e03-ac9d-1f9786c66749/19041.3031.230508-1728.vb\\_release\\_svc\\_prod3\\_amd64fre\\_InboxApps.iso](https://software-static.download.prss.microsoft.com/dbazure/888969d5-f34g-4e03-ac9d-1f9786c66749/19041.3031.230508-1728.vb_release_svc_prod3_amd64fre_InboxApps.iso)

IV Windows 安全中心

- 在处理封装任务时，将产生大量的临时文件，安装 InBox Apps 里的应用时会释放大量的安装文件；
- 开启 Windows 安全中心会扫描文件、会占用大量的 CPU。
- 测试中：未关闭前耗时 1 小时 22 分，关闭后耗时 20 分钟。

如何关闭：

绿色为命令行，按住 Windows 键并按 R 键启动“运行”。

- 打开“Windows 安全中心”或运行：`windowsdefender:`
- 选择“病毒和威胁防护”或运行：`windowsdefender://threat`
- 找到“病毒和威胁防护设置”，点击“管理设置”或运行：`windowsdefender://threatsettings`，建议您关闭部分功能：

3.1. 实时保护

- 3.2. 云提供的保护
- 3.3. 自动提交样本
- 3.4. 篡改防护

4. 未处于封装时，建议您开启 Windows 安全中心。

V 命令行

- 1. 可选“Terminal ”或“PowerShell ISE”，未安装“Terminal”，请前往 <https://github.com/microsoft/terminal/releases> 后下载；
- 2. 以管理员身份打开“Terminal”或“PowerShell ISE”，设置 PowerShell 执行策略：绕过，PS 命令行：  
  
Set-ExecutionPolicy -ExecutionPolicy Bypass -Force
- 3. 在本文中，绿色部分属于 PS 命令行，请复制后，粘贴到“Terminal”对话框，按回车键（Enter）后开始运行；
- 4. 有 .ps1 时，点击文件右键，选择以 PowerShell 运行，或复制路径，粘贴到“Terminal ”或“PowerShell ISE”里运行，带冒号的路径，在命令行添加 & 字符，示例：& "D:\Yi.Solutions\\_Encapsulation\\_SIP.ps1"

B. 语言包：提取

II 语言包：准备

- 1. 语言包：挂载  
  
挂载 19041.1.191206-1406.vb\_release\_CLIENTLANGPACKDVD\_OEM\_MULTI.iso 或解压到任意位置；
- 2. 功能包：挂载  
  
请正确选择架构版本，提取错误的语言包，安装会报错误。  
  
ARM64: 19041.1.191206-1406.vb\_release\_arm64fre\_FOD-PACKAGES\_OEM\_PT1\_arm64fre\_MULTI.iso  
  
X64: 19041.1.191206-1406.vb\_release\_amd64fre\_FOD-PACKAGES\_OEM\_PT1\_amd64fre\_MULTI.iso  
  
X86: 19041.1.191206-1406.vb\_release\_x86fre\_FOD-PACKAGES\_OEM\_PT1\_x86fre\_MULTI.iso

III 语言包：提取方案

- 1. 添加  
  
1.1. 语言名称：简体中文 - 中国，区域：zh-CN，适用范围：Install.Wim，Boot.Wim，WinRE.Wim
- 2. 删除  
  
2.1. 语言名称：英语 - 美国，区域：en-US，适用范围：Install.Wim，Boot.Wim，WinRE.Wim

3. 架构: x64

IV 执行提取命令

- Auto = 自动搜索本地所有磁盘，默认；
- 自定义路径，例如指定为 E 盘: \$ISO = "E:\"
- Extract.ps1
  - \Expand\Extract.ps1
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/Extract.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/Extract.ps1)

• 复制代码

```
$ISO = "Auto"

$SaveTo = "D:\OS_10_Custom"

$Extract_language_Pack = @(

 @{ Tag = "zh-CN"; Arch = "AMD64"; Act = "Add"; Scope = @("Install\Install"; "Install\WinRE"; "Boot\Boot") }

 @{ Tag = "en-US"; Arch = "AMD64"; Act = "Del"; Scope = @("Install\Install"; "Install\WinRE"; "Boot\Boot") }

)

Function Extract_Language

{

 param($NewArch, $Act, $NewLang, $Expand)

 Function Match_Required_Fonts

 {

 param($Lang)

 $Fonts = @(

 @{ Match = @("as", "ar-SA", "ar", "ar-AE", "ar-BH", "ar-DJ", "ar-DZ", "ar-EG", "ar-ER", "ar-IL", "ar-IQ", "ar-JO", "ar-KM", "ar-KW", "ar-LB", "ar-
LY", "ar-MA", "ar-MR", "ar-OM", "ar-PS", "ar-QA", "ar-SD", "ar-SO", "ar-SS", "ar-SY", "ar-TD", "ar-TN", "ar-YE", "arz-Arab", "ckb-Arab", "fa", "fa-
AF", "fa-IR", "glk-Arab", "ha-Arab", "ks-Arab", "ks-Arab-IN", "ku-Arab", "ku-Arab-IQ", "mzn-Arab", "pa-Arab", "pa-Arab-PK", "pnb-Arab", "prs",
"prs-AF", "prs-Arab", "ps", "ps-AF", "sd-Arab", "sd-Arab-PK", "tk-Arab", "ug", "ug-Arab", "ug-CN", "ur", "ur-IN", "ur-PK", "uz-Arab", "uz-Arab-AF");
Name = "Arab"; }

 @{ Match = @("bn-IN", "as-IN", "bn", "bn-BD", "bpy-Beng"); Name = "Beng"; }

 @{ Match = @("da-dk", "iu-Cans", "iu-Cans-CA"); Name = "Cans"; }

 @{ Match = @("chr-Cher-US", "chr-Cher"); Name = "Cher"; }

 @{ Match = @("hi-IN", "bh-Deva", "brx", "brx-Deva", "brx-IN", "hi", "ks-Deva", "mai", "mr", "mr-IN", "ne", "ne-IN", "ne-NP", "new-Deva", "pi-
Deva", "sa", "sa-Deva", "sa-IN"); Name = "Deva"; }

 @{ Match = @("am", "am-ET", "byn", "byn-ER", "byn-Ethi", "ti", "ti-ER", "ti-ET", "tig", "tig-ER", "tig-Ethi", "ve-Ethi", "wal", "wal-ET", "wal-
Ethi"); Name = "Ethi"; }

 @{ Match = @("gu", "gu-IN"); Name = "Gujr"; }
```

```
@{ Match = @"(pa", "pa-IN", "pa-Guru"); Name = "Guru"; }

@{ Match = @"(zh-CN", "cmn-Hans", "gan-Hans", "hak-Hans", "wu-Hans", "yue-Hans", "zh-gan-Hans", "zh-hak-Hans", "zh-Hans", "zh-SG", "zh-wu-Hans", "zh-yue-Hans"); Name = "Hans"; }

@{ Match = @"(zh-TW", "cmn-Hant", "hak-Hant", "lzh-Hant", "zh-hak-Hant", "zh-Hant", "zh-HK", "zh-lzh-Hant", "zh-MO", "zh-yue-Hant"); Name = "Hant"; }

@{ Match = @"(he", "he-IL", "yi"); Name = "Hebr"; }

@{ Match = @"(ja", "ja-JP"); Name = "Jpan"; }

@{ Match = @"(km", "km-KH"); Name = "Khmr"; }

@{ Match = @"(kn", "kn-IN"); Name = "Knda"; }

@{ Match = @"(ko", "ko-KR"); Name = "Kore"; }

@{ Match = @"(de-de", "lo", "lo-LA"); Name = "Lao"; }

@{ Match = @"(ml", "ml-IN"); Name = "Mlym"; }

@{ Match = @"(or", "or-IN"); Name = "Orya"; }

@{ Match = @"(si", "si-LK"); Name = "Sinh"; }

@{ Match = @"(tr-tr", "arc-Syrc", "syr", "syr-SY", "syr-Syrc"); Name = "Syrc"; }

@{ Match = @"(ta", "ta-IN", "ta-LK", "ta-MY", "ta-SG"); Name = "Taml"; }

@{ Match = @"(te", "te-IN"); Name = "Telu"; }

@{ Match = @"(th", "th-TH"); Name = "Thai"; }

)

ForEach ($item in $Fonts) {

 if (($item.Match) -Contains $Lang) {

 return $item.Name

 }

}

return "Not_matched"

}

Function Match_Other_Region_Specific_Requirements

{

 param($Lang)

 $RegionSpecific = @(

 @{ Match = @"(zh-TW"); Name = "Taiwan"; }

)

 ForEach ($item in $RegionSpecific) {

 if (($item.Match) -Contains $Lang) {

 return $item.Name

 }

 }

}
```

```

 }

}

return "Skip_specific_packages"

}

Function Extract_Process

{

 param($Package, $Name, $NewSaveTo)

 $NewSaveTo = "$($SaveTo)\$($NewSaveTo)\Language\$($Act)\$($NewLang)"

 New-Item -Path $NewSaveTo -ItemType Directory -ErrorAction SilentlyContinue | Out-Null

 if ($ISO -eq "Auto"){

 Get-PSDrive -PSProvider FileSystem -ErrorAction SilentlyContinue | ForEach-Object {

 ForEach ($item in $Package){

 $TempFilePath = Join-Path -Path $_.Root -ChildPath $item -ErrorAction SilentlyContinue

 if (Test-Path $TempFilePath -PathType Leaf){

 Write-host "`n Find: " -NoNewLine; Write-host $TempFilePath -ForegroundColor Green

 Write-host " Copy to: " -NoNewLine; Write-host $NewSaveTo

 Copy-Item -Path $TempFilePath -Destination $NewSaveTo -Force

 }

 }

 }

 } else {

 ForEach ($item in $Package){

 $TempFilePath = Join-Path -Path $ISO -ChildPath $item -ErrorAction SilentlyContinue

 Write-host "`n Find: " -NoNewline; Write-host $TempFilePath -ForegroundColor Green

 if (Test-Path $TempFilePath -PathType Leaf){

 Write-host " Copy to: " -NoNewLine; Write-host $NewSaveTo

 Copy-Item -Path $TempFilePath -Destination $NewSaveTo -Force

 } else {

 Write-host " Not found"

 }

 }

 }

 Write-host "`n Verify the language pack file"

 ForEach ($item in $Package){

```

```

$Path = "$($NewSaveTo)\$([IO.Path]::GetFileName($item))"

if (Test-Path $Path -PathType Leaf) {

 Write-host " Discover: " -NoNewLine; Write-host $Path -ForegroundColor Green

} else {

 Write-host " Not found: " -NoNewLine; Write-host $Path -ForegroundColor Red

}

}

}

}

$AdvLanguage = @(

@{

 Path = "Install\Install"

 Rule = @(

 "Microsoft-Windows-LanguageFeatures-Fonts-{DiyLang}-Package~31bf3856ad364e35~AMD64~~.cab"

 "{ARCHC}\langpacks\Microsoft-Windows-Client-Language-Pack_x64_{Lang}.cab"

 "Microsoft-Windows-LanguageFeatures-Basic-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

 "Microsoft-Windows-LanguageFeatures-Handwriting-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

 "Microsoft-Windows-LanguageFeatures-OCR-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

 "Microsoft-Windows-LanguageFeatures-Speech-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

 "Microsoft-Windows-LanguageFeatures-TextToSpeech-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

 "Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

 "Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

 "Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~{ARCH}~{Lang}~.cab"

 "Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~{ARCH}~{Lang}~.cab"

 "Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

 "Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

 "Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

 "Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

 "Microsoft-Windows-Printing-WFS-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

 "Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

 "Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

 "Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

 "Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

 "Microsoft-Windows-InternationalFeatures-{Specific}-Package~31bf3856ad364e35~amd64~~.cab"

)

}

```



```
}

@{

 Path = "Install\WinRE"

 Rule = @(

 "Windows Preinstallation Environment\x64\WinPE_OCs\WinPE-FontSupport-{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\lp.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-securestartup_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-atbroker_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-audiocore_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-audiodrivers_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-enhancedstorage_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-narrator_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-scripting_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-speech-tts_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-srh_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-srt_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-wds-tools_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-wmi_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-appxpackaging_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-storagewmi_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-wifi_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-rejuv_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-opcservices_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-hta_{Lang}.cab"

)

}

@{

 Path = "Boot\Boot"

 Rule = @(

 "Windows Preinstallation Environment\x64\WinPE_OCs\WinPE-FontSupport-{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\lp.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\WinPE-Setup_{Lang}.cab"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\WINPE-SETUP-CLIENT_{Lang}.CAB"

 "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-securestartup_{Lang}.cab"

)

}
```

```

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-atbroker_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiocore_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiodrivers_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-enhancedstorage_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-narrator_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-scripting_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-speech-tts_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srh_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srt_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wds-tools_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wmi_{Lang}.cab"

)

}

)

$NewFonts = Match_Required_Fonts -Lang $NewLang

$SpecificPackage = Match_Other_Region_Specific_Requirements -Lang $NewLang

$NewArchC = $NewArch.Replace("AMD64", "x64")

Foreach ($item in $Expand) {

 $Language = @()

 Foreach ($itemList in $AdvLanguage) {

 if ($itemList.Path -eq $item) {

 Foreach ($PrintLang in $itemList.Rule) {

 $Language += "$($PrintLang)".Replace("{Lang}", $NewLang).Replace("{DiyLang}", $NewFonts).Replace("{Specific}",
$SpecificPackage).Replace("{ARCH}", $NewArch).Replace("{ARCHC}", $NewArchC)

 }

 Extract_Process -NewSaveTo $itemList.Path -Package $Language -Name $item

 }

 }

}

}

}

Foreach ($item in $Extract_language_Pack) { Extract_Language -Act $item.Act -NewLang $item.Tag -NewArch $item.Arch -Expand
$item.Scope }

```

## C. 自定义部署映像

### II 自定义部署映像：Install.wim

1. 查看 Install.wim 详细信息

映像名称、映像描述、映像大小、架构、版本、索引号等；

```
$ViewFile = "D:\OS_10\Sources\Install.wim"

Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex }
```

循环操作区域，开始，

2. 指定挂载 Install 路径

```
New-Item -Path "D:\OS_10_Custom\Install\Install\Mount" -ItemType directory -ea SilentlyContinue
```

3. 开始挂载 Install.wim

默认索引号：1

```
Mount-WindowsImage -ImagePath "D:\OS_10\sources\install.wim" -Index "1" -Path "D:\OS_10_Custom\Install\Install\Mount"
```

处理 Install.wim 映像内的文件，可选项，开始，

3.1. 自定义部署映像：WinRE.wim

注意：

- WinRE.wim 属于 Install.wim 映像内的文件；
- Install.wim 有多个索引号时，仅处理任意一个 WinRE.wim 即可；
- 同步至所有索引号即可减少 Install.wim 体积，学习“如何批量替换 Install.wim 里的所有索引号里的 WinRE.wim”。

3.1.1. 查看 WinRE.wim 详细信息

映像名称、映像描述、映像大小、架构、版本、索引号等；

```
$ViewFile = "D:\OS_10_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"

Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex }
```

3.1.2. 指定挂载 WinRE.wim 路径

```
New-Item -Path "D:\OS_10_Custom\Install\WinRE\Mount" -ItemType directory -ea SilentlyContinue
```

3.1.3. 开始挂载 WinRE.wim

默认索引号：1

```
Mount-WindowsImage -ImagePath
"D:\OS_10_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim" -Index "1" -Path
"D:\OS_10_Custom\Install\WinRE\Mount"
```

3.1.4. 语言包

- 自动安装语言包：获取“组件：映像中已安装的所有包”后进行匹配，匹配到对应的名称后，再安装本地对应的语言包文件，查看报告 “[语言安装包适用于 WinRE.wim](#)” 。
- 添加语言时，须对应不同的架构版本，未对应时，添加过程中报错等提示。

3.1.4.1. 语言包：添加

- WinRE.Instl.lang.ps1
  - [\Expand\Install\WinRE\WinRE.Instl.lang.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/Install/WinRE/WinRE.Instl.lang.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/Install/WinRE/WinRE.Instl.lang.ps1)

- 复制代码

```
$Mount = "D:\OS_10_Custom\Install\WinRE\Mount"

$Sources = "D:\OS_10_Custom\Install\WinRE\Language\Add\zh-CN"

$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

 $Initl_install_Language_Component += $_.PackageName

}

Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\WinPE-FontSupport-zh-CN.cab"

$Language = @(

 @{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }

 @{ Match = "*SecureStartup*"; File = "winpe-securestartup_zh-CN.cab"; }

 @{ Match = "*ATBroker*"; File = "winpe-atbroker_zh-CN.cab"; }

 @{ Match = "*AudioCore*"; File = "winpe-audiocore_zh-CN.cab"; }

 @{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_zh-CN.cab"; }

 @{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_zh-CN.cab"; }

 @{ Match = "*Narrator*"; File = "winpe-narrator_zh-CN.cab"; }

 @{ Match = "*scripting*"; File = "winpe-scripting_zh-CN.cab"; }

 @{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_zh-CN.cab"; }

 @{ Match = "*srh*"; File = "winpe-srh_zh-CN.cab"; }

 @{ Match = "*srt*"; File = "winpe-srt_zh-CN.cab"; }
```

```
@{ Match = "*wds-tools*"; File = "winpe-wds-tools_zh-CN.cab"; }

@{ Match = "*-WMI-Package*"; File = "winpe-wmi_zh-CN.cab"; }

@{ Match = "*WinPE-AppxPackaging*"; File = "winpe-appxpackaging_zh-CN.cab"; }

@{ Match = "*StorageWMI*"; File = "winpe-storagewmi_zh-CN.cab"; }

@{ Match = "*WiFi*"; File = "winpe-wifi_zh-CN.cab"; }

@{ Match = "*rejuv*"; File = "winpe-rejuv_zh-CN.cab"; }

@{ Match = "*opcservices*"; File = "winpe-opcservices_zh-CN.cab"; }

@{ Match = "*hta*"; File = "winpe-hta_zh-CN.cab"; }

)

ForEach ($Rule in $Language) {

 Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host " $('-' * 80)"

 ForEach ($Component in $InitL_install_Language_Component) {

 if ($Component -like "*$($Rule.Match)*") {

 Write-host " Component name: " -NoNewline; Write-host $Component -ForegroundColor Green

 Write-host " Language pack file: " -NoNewline; Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

 Write-Host " Installing ".PadRight(22) -NoNewline

 try {

 Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" | Out-Null

 Write-host "Finish" -ForegroundColor Green

 } catch {

 Write-host "Failed" -ForegroundColor Red

 Write-host " $($_) " -ForegroundColor Red

 }

 break

 }

 }

}
```

#### 3.1.4.2. 脱机映像语言：更改

##### 3.1.4.2.1. 更改默认语言、区域设置和其他国际设置

区域：zh-CN

```
Dism /Image:"D:\OS_10_Custom\Install\WinRE\Mount" /Set-AllIntl:zh-CN
```

3.1.4.2.2. 查看可用的语言设置

```
Dism /Image:"D:\OS_10_Custom\Install\WinRE\Mount" /Get-Intl
```

3.1.4.3. 语言包：删除，可选

- 添加语言后，如果要部署到非英语区域，可通过删除英语语言组件来节省空间。删除语言时，请按与添加语言组件相反的顺序卸载语言组件。
- 添加中文后，反向删除“英语 - 美国”，区域：en-US，需提前提取语言包
- WinRE.Del.Specified.lang.Tag.ps1
  - \Expand\Install\WinRE\WinRE.Del.Specified.lang.Tag.ps1
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/Install/WinRE/WinRE.Del.Specified.lang.Tag.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/Install/WinRE/WinRE.Del.Specified.lang.Tag.ps1)

- 复制代码

```
$Lang = "en-US"

$Mount = "D:\OS_10_Custom\Install\WinRE\Mount"

$Sources = "D:\OS_10_Custom\Install\WinRE\Language\Del\en-US"

$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

 $Initl_install_Language_Component += $_.PackageName

}

$Language = @(

 @{ Match = "*windowsupdate*"; File = "winpe-windowsupdate_$($Lang).cab"; }

 @{ Match = "*appxdeployment*"; File = "winpe-appxdeployment_$($Lang).cab"; }

 @{ Match = "*hta*"; File = "winpe-hta_$($Lang).cab"; }

 @{ Match = "*opcservices*"; File = "winpe-opcservices_$($Lang).cab"; }

 @{ Match = "*rejuv*"; File = "winpe-rejuv_$($Lang).cab"; }

 @{ Match = "*WiFi*"; File = "winpe-wifi_$($Lang).cab"; }

 @{ Match = "*StorageWMI*"; File = "winpe-storagewmi_$($Lang).cab"; }

 @{ Match = "*WinPE-AppxPackaging*"; File = "winpe-appxpackaging_$($Lang).cab"; }

 @{ Match = "*-WMI-Package*"; File = "winpe-wmi_$($Lang).cab"; }

 @{ Match = "*wds-tools*"; File = "winpe-wds-tools_$($Lang).cab"; }

 @{ Match = "*srt*"; File = "winpe-srt_$($Lang).cab"; }

 @{ Match = "*srh*"; File = "winpe-srh_$($Lang).cab"; }

 @{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_$($Lang).cab"; }
```

```

@{ Match = "*scripting*"; File = "winpe-scripting_$(Lang).cab"; }

@{ Match = "*Narrator*"; File = "winpe-narrator_$(Lang).cab"; }

@{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_$(Lang).cab"; }

@{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_$(Lang).cab"; }

@{ Match = "*AudioCore*"; File = "winpe-audiocore_$(Lang).cab"; }

@{ Match = "*ATBroker*"; File = "winpe-atbroker_$(Lang).cab"; }

@{ Match = "*SecureStartup*"; File = "winpe-securestartup_$(Lang).cab"; }

@{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }

)

ForEach ($Rule in $Language) {

 Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host " $($-' * 80)"

 ForEach ($Component in $Initl_install_Language_Component) {

 if ($Component -like "*$($Rule.Match)*$(Lang)*") {

 Write-host " Component name: " -NoNewline

 Write-host $Component -ForegroundColor Green

 Write-host " Language pack file: " -NoNewline

 Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

 Write-Host " Deleting ".PadRight(22) -NoNewline

 try {

 Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" -
ErrorAction SilentlyContinue | Out-Null

 Write-host "Finish" -ForegroundColor Green

 } catch {

 Write-host "Failed" -ForegroundColor Red

 Write-host " $_" -ForegroundColor Red

 }

 break

 }

 }

}

$InitlClearLanguagePackage = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

 if ($_.PackageName -like "*$(Lang)*") {

 $InitlClearLanguagePackage += $_.PackageName

 }

}

```

```
}

if ($InitlClearLanguagePackage.count -gt 0) {

 ForEach ($item in $InitlClearLanguagePackage) {

 Write-Host "`n $($item)" -ForegroundColor Green

 Write-Host " Deleting".PadRight(22) -NoNewline

 try {

 Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction
 SilentlyContinue | Out-Null

 Write-host "Finish" -ForegroundColor Green

 } catch {

 Write-host "Failed" -ForegroundColor Red

 Write-host " $($_) " -ForegroundColor Red

 }

 }

}

}
```

3.1.4.4. 组件：映像中已安装的所有包

3.1.4.4.1. 查看

```
Get-WindowsPackage -Path "D:\OS_10_Custom\Install\WinRE\Mount" | Out-GridView
```

3.1.4.4.2. 导出到 Csv

```
$SaveTo = "D:\OS_10_Custom\Install\WinRE\Report.$(Get-Date -Format
"yyyyMMddHHmmss").csv"

Get-WindowsPackage -Path "D:\OS_10_Custom\Install\WinRE\Mount" | Export-CSV -
NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green
```

3.1.5. 累积更新，可选

准备可用的累积更新文件，请更改示例文件名：[KB\\_WinRE.cab](#)

3.1.5.1. 添加

```
$KBPath = "D:\OS_10_Custom\Install\WinRE\Update\KB_WinRE.cab"

Add-WindowsPackage -Path "D:\OS_10_Custom\Install\WinRE\Mount" -PackagePath $KBPath
```

3.1.5.2. 删除



```
$KBPath = "D:\OS_10_Custom\Install\WinRE\Update\KB_WinRE.cab"

Remove-WindowsPackage -Path "D:\OS_10_Custom\Install\WinRE\Mount" -PackagePath $KBPath
```

#### 3.1.5.3. 固化更新，可选项

固化后不可卸载，固化时将清理恢复映像并重置任何被取代的组件的基础。

```
Dism /image:"D:\OS_10_Custom\Install\WinRE\Mount" /cleanup-image /StartComponentCleanup
/ResetBase
```

##### 3.1.5.3.1. 固化更新后清理组件，可选项

```
$Mount = "D:\OS_10_Custom\Install\WinRE\Mount"

Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {

 if ($_.PackageState -eq "Superseded"){

 Write-Host " $($_.PackageName)" -ForegroundColor Green

 Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-
Null

 }

}
```

#### 3.1.6. 驱动

#### 3.1.7. 保存映像

```
Save-WindowsImage -Path "D:\OS_10_Custom\Install\WinRE\Mount"
```

#### 3.1.8. 卸载映像

关闭所有可能正在访问映像中文件的应用程序，包括文件资源管理器。

```
Dismount-WindowsImage -Path "D:\OS_10_Custom\Install\WinRE\Mount" -Discard
```

#### 3.1.9. 重建 WinRE.wim 后，可缩小文件大小

- [WinRE.Rebuild.ps1](#)
  - [\Expand\Install\WinRE\WinRE.Rebuild.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/Install/WinRE/WinRE.Rebuild.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/Install/WinRE/WinRE.Rebuild.ps1)
- 复制代码

```
$FileName = "D:\OS_10_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"
```

```
Get-WindowsImage -ImagePath $Filename -ErrorAction SilentlyContinue | ForEach-Object {
```

```

Write-Host " Image name: " -NoNewLine

Write-Host $_.ImageName -ForegroundColor Yellow

Write-Host " The index number: " -NoNewLine

Write-Host $_.ImageIndex -ForegroundColor Yellow

Write-Host "`n Rebuild".PadRight(28) -NoNewLine

Export-WindowsImage -SourceImagePath $Filename -SourceIndex $_.ImageIndex -DestinationImagePath
"$(($FileName).New" -CompressionType max

Write-Host "Finish`n" -ForegroundColor Green
}

if (Test-Path "$(($FileName).New" -PathType Leaf) {

Remove-Item -Path $Filename

Move-Item -Path "$(($FileName).New" -Destination $Filename

Write-Host "Finish" -ForegroundColor Green

} else {

Write-host "Failed" -ForegroundColor Red

}

```

#### 3.1.10. 备份 WinRE.wim

- WinRE.Backup.ps1
  - [\Expand\Install\WinRE\WinRE.Backup.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/Install/WinRE/WinRE.Backup.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/Install/WinRE/WinRE.Backup.ps1)
- 复制代码

```

$WimLibPath = "D:\OS_10_Custom\Install\Install\Update\WinLib"

$FileName = "D:\OS_10_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"

New-Item -Path $WimLibPath -ItemType Directory -ea SilentlyContinue

Copy-Item -Path $FileName -Destination $WimLibPath -Force

```

#### 3.1.11. 替换 Install.wim 映像内的 WinRE.wim

- 每次挂载 Install.wim 后“[替换 WinRE.wim](#)”；
- 学习“[获取 Install.wim 所有索引号后并替换旧的 WinRE.wim](#)”。

处理 Install.wim 映像内的文件，结束。

#### 4. 语言包

- 自动安装语言包：获取“组件：映像中已安装的所有包”后进行匹配，匹配到对应的名称后，再安装本地对应的语言包文件，查看报告“[语言安装包适用于 Install.wim](#)”。
- 添加语言时，须对应不同的架构版本，未对应时，添加过程中报错等提示。

##### 4.1. 语言包：添加

- Install.Instl.lang.ps1
  - [\Expand\Install\Install.Instl.lang.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/Install/Install.Instl.lang.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/Install/Install.Instl.lang.ps1)

- 复制代码

```
Function Language_Install

{

 param($Mount, $Sources, $Lang)

 $Initl_install_Language_Component = @()

 if (Test-Path $Mount -PathType Container) {

 Get-WindowsPackage -Path $Mount | ForEach-Object { $Initl_install_Language_Component += $_.PackageName }

 } else {

 Write-Host "Not mounted: $($Mount)"

 return

 }

 $Script:Init_Folder_All_File = @()

 if (Test-Path "$($Sources)\$($Lang)" -PathType Container) {

 Get-ChildItem -Path $Sources -Recurse -Include "*.cab" -ErrorAction SilentlyContinue | ForEach-Object {

 $Script:Init_Folder_All_File += $_.FullName

 }

 Write-host "`n Available language pack installation files"

 if ($Script:Init_Folder_All_File.Count -gt 0) {

 ForEach ($item in $Script:Init_Folder_All_File) {

 Write-host " $($item)"

 }

 } else {

 Write-host "There are no language pack files locally"
```

```
 return

 }

} else {

 Write-Host "Path does not exist: $($Sources)\$($Lang)"

 return

}

$Script:Init_Folder_All_File_Match_Done = @()

$Script:Init_Folder_All_File_Exclude = @()

$Script:Search_File_Order = @(

 @{

 Name = "Fonts"

 Description = "Fonts"

 Rule = @(

 @{ Match_Name = "*Fonts*"; IsMatch = "No"; Capability = ""; }

)

 }

 @{

 Name = "Basic"

 Description = "Basic"

 Rule = @(

 @{ Match_Name = "*LanguageFeatures-Basic*"; IsMatch = "Yes"; Capability = "Language.Basic~~~$($Lang)~0.0.1.0"; }

 @{ Match_Name = "*Client*Language*Pack*"; IsMatch = "Yes"; Capability = "Language.Basic~~~$($Lang)~0.0.1.0"; }

)

 }

 @{

 Name = "OCR"

 Description = "Optical character recognition"

 Rule = @(

 @{ Match_Name = "*LanguageFeatures-OCR*"; IsMatch = "Yes"; Capability = "Language.OCR~~~$($Lang)~0.0.1.0"; }

)

 }

 @{

 Name = "Handwriting"

 Description = "Handwriting recognition"
```

```

Rule = @(

 @{ Match_Name = "*LanguageFeatures-Handwriting*"; IsMatch = "Yes"; Capability =
"Language.Handwriting~~~${$Lang}~0.0.1.0"; }

)

}

@{

 Name = "TextToSpeech"

 Description = "Text-to-speech"

 Rule = @(

 @{ Match_Name = "*LanguageFeatures-TextToSpeech*"; IsMatch = "Yes"; Capability =
"Language.TextToSpeech~~~${$Lang}~0.0.1.0"; }

)

}

@{

 Name = "Speech"

 Description = "Speech recognition"

 Rule = @(

 @{ Match_Name = "*LanguageFeatures-Speech*"; IsMatch = "Yes"; Capability =
"Language.Speech~~~${$Lang}~0.0.1.0"; }

)

}

@{

 Name = "RegionSpecific"

 Description = "Other region-specific requirements"

 Rule = @(

 @{ Match_Name = "*InternationalFeatures*"; IsMatch = "No"; Capability = ""; }

)

}

@{

 Name = "Retail"

 Description = "Retail demo experience"

 Rule = @(

 @{ Match_Name = "*RetailDemo*"; IsMatch = "Yes"; Capability = ""; }

)

}

@{

```

```

Name = "Features_On_Demand"

Description = "Features on demand"

Rule = @(

 @{ Match_Name = "*InternetExplorer*"; IsMatch = "Yes"; Capability = ""; }

 @{ Match_Name = "*MSPaint*amd64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.MSPaint~~~~0.0.1.0"; }

 @{ Match_Name = "*MSPaint*wow64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.MSPaint~~~~0.0.1.0"; }

 @{ Match_Name = "*Notepad*amd64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.Notepad~~~~0.0.1.0"; }

 @{ Match_Name = "*Notepad*wow64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.Notepad~~~~0.0.1.0"; }

 @{ Match_Name = "*MediaPlayer*amd64*"; IsMatch = "Yes"; Capability =
"Media.WindowsMediaPlayer~~~~0.0.12.0"; }

 @{ Match_Name = "*MediaPlayer*wow64*"; IsMatch = "Yes"; Capability =
"Media.WindowsMediaPlayer~~~~0.0.12.0"; }

 @{ Match_Name = "*PowerShell-ISE-FOD-Package*amd64*"; IsMatch = "Yes"; Capability =
"Microsoft.Windows.PowerShell.ISE~~~~0.0.1.0"; }

 @{ Match_Name = "*PowerShell-ISE-FOD-Package*wow64*"; IsMatch = "Yes"; Capability =
"Microsoft.Windows.PowerShell.ISE~~~~0.0.1.0"; }

 @{ Match_Name = "*Printing*PMCPPC*amd64*"; IsMatch = "Yes"; Capability =
"Print.Management.Console~~~~0.0.1.0"; }

 @{ Match_Name = "*Printing*WFS*amd64*"; IsMatch = "Yes"; Capability = "Print.Management.Console~~~~0.0.1.0"; }

 @{ Match_Name = "*StepsRecorder*amd64*"; IsMatch = "Yes"; Capability = "App.StepsRecorder~~~~0.0.1.0"; }

 @{ Match_Name = "*StepsRecorder*wow64*"; IsMatch = "Yes"; Capability = "App.StepsRecorder~~~~0.0.1.0"; }

 @{ Match_Name = "*WordPad*amd64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.WordPad~~~~0.0.1.0"; }

 @{ Match_Name = "*WordPad*wow64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.WordPad~~~~0.0.1.0"; }

 @{ Match_Name = "*WMIC*FoD*Package*amd64*"; IsMatch = "Yes"; Capability = "WMIC~~~~"; }

 @{ Match_Name = "*WMIC*FoD*Package*wow64*"; IsMatch = "Yes"; Capability = "WMIC~~~~"; }

)

}

)

ForEach ($item in $Script:Search_File_Order) { New-Variable -Name "Init_File_Type_$(($item.Name))" -Value @() -Force }

ForEach ($Wildcard in $Script:Init_Folder_All_File) {

 ForEach ($item in $Script:Search_File_Order) {

 ForEach ($NewRule in $item.Rule) {

 if ($Wildcard -like "*$(($NewRule.Match_Name))*") {

 Write-host "`n Fuzzy matching: " -NoNewline; Write-host $NewRule.Match_Name -ForegroundColor Green

 Write-host " Language pack file: " -NoNewline; Write-host $Wildcard -ForegroundColor Green

 $OSDefaultUser = (Get-Variable -Name "Init_File_Type_$(($item.Name))" -ErrorAction SilentlyContinue).Value
 }
 }
 }
}

```

```

 $TempSave = @{{ Match_Name = $NewRule.Match_Name; Capability = $NewRule.Capability; FileName =
$Wildcard }

 $new = $OSDefaultUser + $TempSave

 if ($NewRule.IsMatch -eq "Yes") {

 ForEach ($Component in $Init_install_Language_Component) {

 if ($Component -like "*${$NewRule.Match_Name}*") {

 Write-host " Component name: " -NoNewline; Write-host $Component -ForegroundColor Green

 New-Variable -Name "Init_File_Type_${item.Name}" -Value $new -Force

 $Script:Init_Folder_All_File_Match_Done += $Wildcard

 break

 }

 }

 } else {

 Write-host " Do not match, install directly" -ForegroundColor Yellow

 New-Variable -Name "Init_File_Type_${item.Name}" -Value $new -Force

 $Script:Init_Folder_All_File_Match_Done += $Wildcard

 }

 }

}

Write-host "`n Grouping is complete, pending installation" -ForegroundColor Yellow

Write-host " $('-' * 80)"

ForEach ($Wildcard in $Script:Search_File_Order) {

 $OSDefaultUser = (Get-Variable -Name "Init_File_Type_${Wildcard.Name}" -ErrorAction SilentlyContinue).Value

 Write-host "`n ${Wildcard.Description} (${$OSDefaultUser.Count} item)"

 if ($OSDefaultUser.Count -gt 0) {

 ForEach ($item in $OSDefaultUser) {

 Write-host " ${item.FileName}" -ForegroundColor Green

 }

 } else {

 Write-host " Not available" -ForegroundColor Red

 }

}

Write-host "`n Not matched, no longer installed" -ForegroundColor Yellow

```

```

Write-host " $('-' * 80)"

ForEach ($item in $Script:Init_Folder_All_File){

 if ($Script:Init_Folder_All_File_Match_Done -notcontains $item) {

 $Script:Init_Folder_All_File_Exclude += $item

 Write-host " $($item)" -ForegroundColor Red

 }

}

Write-host "`n Install" -ForegroundColor Yellow

Write-host " $('-' * 80)"

ForEach ($WildCard in $Script:Search_File_Order){

 $OSDefaultUser = (Get-Variable -Name "Init_File_Type_{$WildCard.Name}" -ErrorAction SilentlyContinue).Value

 Write-host "`n $($WildCard.Description) ($($OSDefaultUser.Count) item);" ; Write-host " $('-' * 80)"

 if ($OSDefaultUser.Count -gt 0) {

 ForEach ($item in $OSDefaultUser) {

 Write-host " Language pack file: " -NoNewline; Write-host $item.FileName -ForegroundColor Green

 Write-Host " Installing".PadRight(22) -NoNewline

 if (Test-Path $item.FileName -PathType Leaf) {

 try{

 Add-WindowsPackage -Path $Mount -PackagePath $item.FileName | Out-Null

 Write-host "Finish`n" -ForegroundColor Green

 } catch {

 Write-host "Failed" -ForegroundColor Red

 Write-host " $($_) " -ForegroundColor Red

 }

 } else {

 Write-host "Does not exist`n"

 }

 }

 } else {

 Write-host " Not available`n" -ForegroundColor Red

 }

}

Language_Install -Mount "D:\OS_10_Custom\Install\Install\Mount" -Sources
"D:\OS_10_Custom\Install\Install\Language\Add" -Lang "zh-CN"

```



#### 4.2. 脱机映像语言：更改

- 从 Windows 11 开始，DISM 设置的默认系统 UI 语言在所有版本中保持不变（家庭版除外）。对于所有商业版，在开箱即用体验 (OOBE) 期间选择的语言会设置为系统首选 UI 语言，Windows 将以此语言显示；对于家庭版，在 OOBE 期间选择的语言将继续用作默认系统 UI 语言。
- 从 Windows 10 版本 2004 开始，如果将基于 .appx 的语言体验包 (LXP) 支持的语言作为参数传递，则该语言将设置为系统首选 UI 语言，其父语言将设置为默认系统 UI 语言。在以前的版本中，仅支持基于 .cab 的语言包。

##### 4.2.1. 更改默认语言、区域设置和其他国际设置

区域：zh-CN

```
Dism /Image:"D:\OS_10_Custom\Install\Install\Mount" /Set-AllIntl:"zh-CN"
```

##### 4.2.2. 查看可用的语言设置

```
Dism /Image:"D:\OS_10_Custom\Install\Install\Mount" /Get-Intl
```

#### 4.3. 语言包：删除，可选

- 添加语言后，如果要部署到非英语区域，可通过删除英语语言组件来节省空间。删除语言时，请按与添加语言组件相反的顺序卸载语言组件。
- 添加中文后，反向删除“英语 - 美国”，区域：en-US，需提前提取语言包
- Install.Del.Specified.lang.Tag.ps1
  - \Expand\Install\Install.Del.Specified.lang.Tag.ps1
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/Install/Install/Install.Del.Specified.lang.Tag.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/Install/Install/Install.Del.Specified.lang.Tag.ps1)
- 复制代码

```
$Lang = "en-US"
```

```
$Mount = "D:\OS_10_Custom\Install\Install\Mount"
```

```
$Sources = "D:\OS_10_Custom\Install\Install\Language\Del\en-US"
```

```
$Initl_install_Language_Component = @()
```

```
Get-WindowsPackage -Path $Mount | ForEach-Object {
```

```
 $Initl_install_Language_Component += $_.PackageName
```

```
}
```

```
$Language = @(
```

```
 @{ Match = "*WordPad*wow64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~wow64~$($Lang)~.cab"; }
```

```

 @{ Match = "*WordPad*amd64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~amd64~$(Lang)~.cab"; }

 @{ Match = "*WMIC*FoD*Package*wow64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

 @{ Match = "*WMIC*FoD*Package*amd64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

 @{ Match = "*StepsRecorder*wow64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

 @{ Match = "*StepsRecorder*amd64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~amd64~$(Lang)~.cab"; }

 @{ Match = "*Printing*PMCPPC*amd64*"; File = "Microsoft-Windows-Printing-PMCPPC-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

 @{ Match = "*PowerShell*wow64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

 @{ Match = "*PowerShell*amd64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~amd64~$(Lang)~.cab"; }

 @{ Match = "*MediaPlayer*wow64*"; File = "Microsoft-Windows-MediaPlayer-Package-wow64-$(Lang).cab"; }

 @{ Match = "*MediaPlayer*amd64*"; File = "Microsoft-Windows-MediaPlayer-Package-AMD64-$(Lang).cab"; }

 @{ Match = "*Notepad*wow64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

 @{ Match = "*Notepad*amd64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

 @{ Match = "*InternetExplorer*"; File = "Microsoft-Windows-InternetExplorer-Optional-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

 @{ Match = "*TextToSpeech*"; File = "Microsoft-Windows-LanguageFeatures-TextToSpeech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

 @{ Match = "*LanguageFeatures-Speech*"; File = "Microsoft-Windows-LanguageFeatures-Speech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

 @{ Match = "*OCR*"; File = "Microsoft-Windows-LanguageFeatures-OCR-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

 @{ Match = "*Handwriting*"; File = "Microsoft-Windows-LanguageFeatures-Handwriting-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

 @{ Match = "*LanguageFeatures-Basic*"; File = "Microsoft-Windows-LanguageFeatures-Basic-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

 @{ Match = "*Client-LanguagePack-Package*"; File = "Microsoft-Windows-Client-Language-Pack_x64_$(Lang).cab"; }
)

 ForEach ($Rule in $Language) {

 Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host " $('-' * 80)"

 ForEach ($Component in $InitL_install_Language_Component) {

 if ($Component -like "*$($Rule.Match)*$(Lang)*") {

 Write-host " Component name: " -NoNewline; Write-host $Component -ForegroundColor Green
 }
 }
 }
}

```

```

Write-host " Language pack file: " -NoNewline; Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

Write-Host " Deleting ".PadRight(22) -NoNewline

try {

 Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" -ErrorAction SilentlyContinue |
Out-Null

 Write-host "Finish" -ForegroundColor Green

} catch {

 Write-host "Failed" -ForegroundColor Red

 Write-host " $($_) " -ForegroundColor Red

}

break

}

}

}

$InitlClearLanguagePackage = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

 if ($_.PackageName -like "*$($Lang)*") {

 $InitlClearLanguagePackage += $_.PackageName

 }

}

if ($InitlClearLanguagePackage.count -gt 0) {

 ForEach ($item in $InitlClearLanguagePackage) {

 Write-Host "`n $($item)" -ForegroundColor Green

 Write-Host " Deleting ".PadRight(22) -NoNewline

 try {

 Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction SilentlyContinue | Out-Null

 Write-host "Finish" -ForegroundColor Green

 } catch {

 Write-host "Failed" -ForegroundColor Red

 Write-host " $($_) " -ForegroundColor Red

 }

 }

}

}

```

#### 4.4. 组件：映像中已安装的所有包

4.4.1. 查看

```
Get-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" | Out-GridView
```

4.4.2. 导出到 Csv

```
$SaveTo = "D:\OS_10_Custom\Install\Install\Report.$(Get-Date -Format "yyyyMMddHHmmss").csv"

Get-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" | Export-CSV -NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green
```

5. InBox Apps

5.1. 学习

5.1.1. DISM 应用包（.appx 或 .appxbundle）服务命令行选项

5.2. InBox Apps：预安装应用程序

- 编组缩写
  - 群组 A: Windows 10 Education, Windows 10 Enterprise, Windows 10 Pro, Windows 10 Pro Education, Windows 10 Pro for Workstations, Windows 10 Home, Windows 10 Home Single Language, Windows 10 IoT Enterprise
  - 群组 B: Windows 10 Education N, Windows 10 Enterprise N, Windows 10 Pro N, Windows 10 Pro Education N, Windows 10 Pro N for Workstations, Windows 10 Home N

|     | 名称                             | 产品 ID        | 编组   |
|-----|--------------------------------|--------------|------|
| 1.  | Microsoft.HEIFImageExtension   | 9PMMSR1CGPWG | A    |
| 2.  | Microsoft.MixedReality.Portal  | 9NG1H8B3ZC7M | A    |
| 3.  | Microsoft.SkypeApp             | 9WZDNCRFJ364 | A    |
| 4.  | Microsoft.VP9VideoExtensions   | 9N4D0MSMP0PT | A    |
| 5.  | Microsoft.WebMediaExtensions   | 9N5TDP8VCMHS | A    |
| 6.  | Microsoft.WebplImageExtension  | 9PG2DK419DRG | A    |
| 7.  | Microsoft.WindowsSoundRecorder | 9WZDNCRFHWKN | A    |
| 8.  | Microsoft.Xbox.TCUI            | 9NKNC0LD5NN6 | A    |
| 9.  | Microsoft.XboxGamingOverlay    | 9NZKPSTSNW4P | A    |
| 10. | Microsoft.ZuneMusic            | 9WZDNCRFJ3PT | A    |
| 11. | Microsoft.ZuneVideo            | 9WZDNCRFJ3P2 | A    |
| 12. | Microsoft.UI.Xaml.2.0          |              | A, B |
| 13. | Microsoft.UI.Xaml.2.1          |              | A, B |
| 14. | Microsoft.UI.Xaml.2.3          |              | A, B |

|     |                                        |               |      |
|-----|----------------------------------------|---------------|------|
| 15. | Microsoft.Advertising.Xaml             |               | A, B |
| 16. | Microsoft.NET.Native.Framework.1.7     |               | A, B |
| 17. | Microsoft.NET.Native.Framework.2.2     |               | A, B |
| 18. | Microsoft.NET.Native.Runtime.1.7       |               | A, B |
| 19. | Microsoft.NET.Native.Runtime.2.2       |               | A, B |
| 20. | Microsoft.VCLibs.140.00                |               | A, B |
| 21. | Microsoft.VCLibs.140.00.UWPDesktop     |               | A, B |
| 22. | Services.Store.Engagement              |               | A, B |
| 23. | Microsoft.Cortana                      | 9NFFX4SZZ23L  | A, B |
| 24. | Microsoft.BingWeather                  | 9WZDNCRFJ3Q2  | A, B |
| 25. | Microsoft.DesktopAppInstaller          | 9NBLGGH4NNS1  | A, B |
| 26. | Microsoft.GetHelp                      | 9PKDZBMV1H3T  | A, B |
| 27. | Microsoft.Getstarted                   | 9WZDNCRD TBJJ | A, B |
| 28. | Microsoft.Microsoft3DViewer            | 9NBLGGH42THS  | A, B |
| 29. | Microsoft.MicrosoftOfficeHub           | 9WZDNCRD29V9  | A, B |
| 30. | Microsoft.MicrosoftSolitaireCollection | 9WZDNCRFHWD2  | A, B |
| 31. | Microsoft.MicrosoftStickyNotes         | 9NBLGGH4QGHW  | A, B |
| 32. | Microsoft.MSPaint                      | 9NBLGGH4QGHW  | A, B |
| 33. | Microsoft.Office.OneNote               | XPFFZHVQWWLHB | A, B |
| 34. | Microsoft.People                       | 9NBLGGH10PG8  | A, B |
| 35. | Microsoft.ScreenSketch                 | 9MZ95KL8MR0L  | A, B |
| 36. | Microsoft.Wallet                       | 9NBLGGH52CKV  | A, B |
| 37. | Microsoft.StorePurchaseApp             | 9NBLGGH4LS1F  | A, B |
| 38. | Microsoft.Windows.Photos               | 9WZDNCRFJBH4  | A, B |
| 39. | Microsoft.WindowsAlarms                | 9WZDNCRFJ3PR  | A, B |
| 40. | Microsoft.WindowsCalculator            | 9WZDNCRFHVN5  | A, B |
| 41. | Microsoft.WindowsCamera                | 9WZDNCRFJBBG  | A, B |
| 42. | Microsoft.Windows.CommunicationsApps   | 9WZDNCRFHVQM  | A, B |
| 43. | Microsoft.WindowsFeedbackHub           | 9NBLGGH4R32N  | A, B |
| 44. | Microsoft.WindowsMaps                  | 9WZDNCRD TBBV | A, B |
| 45. | Microsoft.WindowsStore                 | 9WZDNCRFJBMP  | A, B |
| 46. | Microsoft.XboxApp                      | 9MV0B5HZVK9Z  | A, B |
| 47. | Microsoft.XboxGameOverlay              | 9NBLGGH537C2  | A, B |
| 48. | Microsoft.XboxIdentityProvider         | 9WZDNCRD1HKW  | A, B |

|     |                                   |              |      |
|-----|-----------------------------------|--------------|------|
| 49. | Microsoft.XboxSpeechToTextOverlay | 9P086NHDNB9W | A, B |
| 50. | Microsoft.YourPhone               | 9NMPJ99VJBWV | A, B |

5.3. InBox Apps：已安装

5.3.1. 查看

```
Get-AppXProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" | Out-GridView
```

5.3.2. 导出到 Csv

```
$SaveTo = "D:\OS_10_Custom\Install\Install\Report.$(Get-Date -Format "yyyyMMddHHmmss").csv"

Get-AppXProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" | Export-CSV -NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green
```

5.4. 删除已安装的所有预应用程序

- Install.InBox.Appx.Clear.all.ps1
  - [\Expand\Install\Install.InBox.Appx.Clear.all.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/Install/Install.InBox.Appx.Clear.all.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/Install/Install.InBox.Appx.Clear.all.ps1)

• 复制代码

```
Get-AppXProvisionedPackage -path "D:\OS_10_Custom\Install\Install\Mount" -ErrorAction SilentlyContinue | ForEach-Object {

 Write-host "`n $($_.DisplayName)"

 Write-Host " Deleting ".PadRight(22) -NoNewline

 try {

 Remove-AppxProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackageName $_.PackageName -ErrorAction SilentlyContinue | Out-Null

 Write-host "Finish" -ForegroundColor Green

 } catch {

 Write-host "Failed" -ForegroundColor Red

 }

}
```

5.5. 区域标记：了解

了解区域标记前，先了解 ZuneMusic 应用程序可用的语言列表：[en-us](#), en-gb, as-in, az-latn-az, bs-latn-ba, bn-in, cs-cz, cy-gb, ar-sa, de-de, af-za, am-et, da-dk, el-gr, es-es, es-mx, ca-es, ca-es-valencia, eu-es, fi-fi, bg-bg, ga-ie, et-ee, gl-es, gu-in, gd-

gb, fil-ph, fr-ca, fr-fr, hy-am, fa-ir, hu-hu, id-id, it-it, ja-jp, hr-hr, ka-ge, is-is, he-il, hi-in, kk-kz, lo-la, km-kh, lt-lt, kn-in, kok-in, ko-kr, mk-mk, lv-lv, ms-my, mi-nz, mr-in, mt-mt, ne-np, nl-nl, nb-no, ml-in, nn-no, lb-lu, or-in, ro-ro, sk-sk, ru-ru, pl-pl, quz-pe, pt-br, pt-pt, sq-al, ta-in, th-th, sv-se, pa-in, sr-cyrl-ba, sr-cyrl-rs, sr-latn-rs, ur-pk, ug-cn, tr-tr, uk-ua, tt-ru, **zh-cn**, vi-vn, uz-latn-uz, sl-si, zh-tw, te-in

查看脱机映像已安装的语言

Dism /Image:"D:\OS\_10\_Custom\Install\Install\Mount" /Get-Intl

查看结果已安装的语言：**en-US**、**zh-CN**，在安装 ZuneMusic 应用时，安装程序会匹配“已安装的语言”，自动过滤未安装的语言列表，这就是区域标记。

5.6. 区域标记：添加方式

5.6.1. 执行“语言包：添加”

5.6.2. 安装“本地语言体验包（LXPs）”

微软官方向 Windows 10 提供了本地语言体验包（LXPS）安装文件，Windows 11 不再提供，想获取：

5.6.2.1. 使用“Windows 本地语言体验包（LXPs）下载器”下载

了解：<https://github.com/ilikeyi/LXPs>

下载后保存到：**D:\OS\_10\_Custom\Install\Install\InBox.Appx**，文件格式：  
**LanguageExperiencePack.zh-CN.Neutral.Appx**

5.6.2.2. 手动下载

5.6.2.2.1. 区域

| 区域                    | 产品 ID         | 区域                 | 产品 ID        |
|-----------------------|---------------|--------------------|--------------|
| <b>en-US</b>          | C9PDSCC711RVF | <b>af-za</b>       | 9PDW16B5HMXR |
| <b>am-et</b>          | 9NGL4R61W3PL  | <b>ar-sa</b>       | 9N4S78P86PKX |
| <b>as-in</b>          | 9NTJLXMX35J   | <b>az-latn-az</b>  | 9P5TFKZHQ5K8 |
| <b>be-by</b>          | 9MXPBGNNDW3L  | <b>bg-bg</b>       | 9MX54588434F |
| <b>bn-bd</b>          | 9PH7TKVXGGM8  | <b>bn-in</b>       | 9P1M44L7W84T |
| <b>bs-latn-ba</b>     | 9MVFKLJ10MFL  | <b>ca-es</b>       | 9P6JMKJQZ9S7 |
| <b>ca-es-valencia</b> | 9P9K3WMFSW90  | <b>chr-cher-us</b> | 9MX15485N3RK |
| <b>cs-cz</b>          | 9P3WXZ1KTM7C  | <b>cy-gb</b>       | 9NKJ9TBML4HB |
| <b>da-dk</b>          | 9NDMT2VKSNL1  | <b>de-de</b>       | 9P6CT0SLW589 |
| <b>el-gr</b>          | 9N586B13PBLD  | <b>en-gb</b>       | 9NT52VQ39BVN |

|            |              |             |              |
|------------|--------------|-------------|--------------|
| es-es      | 9NWVGWLHPB1Z | es-mx       | 9N8MCM1X3928 |
| et-ee      | 9NFBHFMCR30L | eu-es       | 9NMCHQHZ37HZ |
| fa-ir      | 9NGS7DD4QS21 | fi-fi       | 9MW3PQ7SD3QK |
| fil-ph     | 9NWM2KGTDSSS | fr-ca       | 9MTP2VP0VL92 |
| fr-fr      | 9NHMG4BJKMDG | ga-ie       | 9P0L5Q848KXT |
| gd-gb      | 9P1DBPF36BF3 | gl-es       | 9NXRNBRNJN9B |
| gu-in      | 9P2HMSWDJDQ1 | ha-latn-ng  | 9N1L95DBGRG3 |
| he-il      | 9NB6ZFND5HCQ | hi-in       | 9NZC3GRX8LD3 |
| hr-hr      | 9NW01VND4LTW | hu-hu       | 9MWN3C58HL87 |
| hy-am      | 9NKM28TM6P67 | id-id       | 9P4X3N4SDK8P |
| ig-ng      | 9PG4ZFJ48JSX | is-is       | 9NTHJR7TQXX1 |
| it-it      | 9P8PQWNS6VJX | ja-jp       | 9N1W692FV4S1 |
| ka-ge      | 9P60JZL05WGH | kk-kz       | 9PHV179R97LV |
| km-kh      | 9PGKTS4JS531 | kn-in       | 9NC6DB7N95F9 |
| kok-in     | 9MV3P55CMZ6P | ko-kr       | 9N4TXPCVRNGF |
| ku-arab-iq | 9P1C18QL3D7H | ky-kg       | 9P7D3JJGZM48 |
| lb-lu      | 9N0ST1WBZ9D9 | lo-la       | 9N8X352G5NZV |
| lt-lt      | 9NWWD891H6HN | lv-lv       | 9N5CQDPH6SQT |
| mi-nz      | 9P2GDFB3JPSX | mk-mk       | 9P1X6XB1K3RN |
| ml-in      | 9NWDTV8FFV7L | mn-mn       | 9PG1DHC4VTZW |
| mr-in      | 9MWXCKHJVR1J | ms-my       | 9NPXL8ZSDDQ7 |
| mt-mt      | 9PDG96SQ6BN8 | nb-no       | 9N6J0M5DHCK0 |
| ne-np      | 9P7CHPLWDQVN | nl-nl       | 9PF1C9NB5PRV |
| nn-no      | 9PK7KM3Z06KH | nso-za      | 9NS49QLX5CDV |
| or-in      | 9NTHCXCXSJDH | pa-arab-pk  | 9NJRL03WH6FM |
| pa-in      | 9NSNC0ZJX69B | pl-pl       | 9NC5HW94R0LD |
| prs-af     | 9P3NGC6X5ZQC | pt-br       | 9P8LBDM4FW35 |
| pt-pt      | 9P7X8QJ7FL0X | quc-latn-gt | 9P2V6MNNQZ0B |
| quz-pe     | 9NHTX8NVQ04K | ro-ro       | 9MWXGPJ5PJ3H |
| ru-ru      | 9NMJCX77QKPX | rw-rw       | 9NFW0M20H9WG |
| sd-arab-pk | 9NB9JSCXW9X5 | si-lk       | 9NVF9QSLGTL0 |
| sk-sk      | 9N7LSNN099WB | sl-si       | 9NV27L34J4ST |
| sq-al      | 9MWLRGNMDGK7 | sr-cyrl-ba  | 9MXGN7V65C7B |
| sr-cyrl-rs | 9PPD6CCK9K5H | sr-latn-rs  | 9NBZ0SJDPPVT |



|            |              |       |              |
|------------|--------------|-------|--------------|
| sv-se      | 9P0HSNX08177 | sw-ke | 9NFF2M19DQ55 |
| ta-in      | 9PDZB1WT1B34 | te-in | 9PMQJJGF63FW |
| tg-cyrl-tj | 9MZHLBPPT2HC | th-th | 9MSTWFRL0LR4 |
| ti-et      | 9NC8C9RDNK2S | tk-tm | 9NKHQ4GL6VLT |
| tn-za      | 9NFSXM123DHT | tr-tr | 9NL1D3T5HG9R |
| tt-ru      | 9NV90Q1X1ZR2 | ug-cn | 9P52C5D7VL5S |
| uk-ua      | 9PPPMZRSGHR8 | ur-pk | 9NDWFTFW12BQ |
| uz-latn-uz | 9P5P2T5P5L9S | vi-vn | 9P0W68X0XZPT |
| wo-sn      | 9NH3SW1CR90F | xh-za | 9NW3QWSLQD17 |
| yo-ng      | 9NGM3VPPZS5V | zh-cn | 9NRMNT6GMZ7  |
| zh-tw      | 9PCJ4DHCQ1JQ | zu-za | 9NNRM7KT5NB0 |

下载区域: zh-CN, 应用程序 ID: 9NRMNT6GMZ70, 商店连接:  
<https://www.microsoft.com/store/productId/9NRMNT6GMZ70>

5.6.2.2.2. 打开网站: <https://store.rg-adguard.net>

5.6.2.2.2.1. 搜索关键词:  
  
<https://www.microsoft.com/store/productId/9NRMNT6GMZ70>

5.6.2.2.2.2. 网页内搜索 22621 内容, 搜索结果:  
  
[Microsoft.LanguageExperiencePackzh-CN\\_22621.\\*.neutral\\_\\_8wekyb3d8bbwe.appx](#)

5.6.2.2.2.3. 下载后保存到 D:\OS\_10\_Custom\Install\Install\InBox.Appx 目录里,  
重命名: [LanguageExperiencePack.zh-cn.Neutral.Appx](#)

5.6.2.3. 执行安装命令安装本地语言体验包 (LXPs)

了解区域标记添加方式后, 获得 [LanguageExperiencePack.zh-cn.Neutral](#) 后, 执行安装命令:  
  
`Add-AppxProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath "D:\OS_10_Custom\Install\Install\InBox.appx\LanguageExperiencePack.zh-cn.Neutral.appx" -SkipLicense`

5.6.2.4. InBox Apps: 已安装的应用程序包

5.6.2.4.1. 查看  
  
`Get-AppXProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" | Out-GridView`

#### 5.6.2.4.2. 导出出 Csv

```
$SaveTo = "D:\OS_10_Custom\Install\Install\Report.$(Get-Date -Format
"yyyyMMddHHmmss").csv"

Get-AppXProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" |
Export-CSV -NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green
```

### 5.7. InBox Apps：安装

#### 5.7.1. 挂载或解压 InBox Apps 安装文件

挂载 [19041.3031.230508-1728.vb\\_release\\_svc\\_prod3\\_amd64fre\\_InboxApps.iso](#) 或解压到任意位置；

#### 5.7.2. 执行安装命令后安装 InBox Apps 到： Install.wim

- [Auto](#) = 自动搜索本地所有磁盘，默认；
- 自定义路径，例如指定为 F 盘： [\\$ISO = "F:\packages"](#)
- Install.Inst.InBox.Appx.ps1
  - [\Expand\Install\Install.Inst.InBox.Appx.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/Install/Install.Inst.InBox.Appx.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/Install/Install.Inst.InBox.Appx.ps1)
- 复制代码

```
$ISO = "Auto"

$Mount = "D:\OS_10_Custom\Install\Install\Mount"

try {

 Write-host "`n Offline image version: " -NoNewline

 $Current_Edition_Version = (Get-WindowsEdition -Path $Mount).Edition

 Write-Host $Current_Edition_Version -ForegroundColor Green

} catch {

 Write-Host "Error" -ForegroundColor Red

 Write-Host " $($_) " -ForegroundColor Yellow

 return

}

$Pre_Config_Rules = @(

 @{

 Name = @("Core"; "CoreN"; "CoreSingleLanguage");
```

```

Apps = @(

 "Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.HEIFImageExtension"; "Microsoft.HEVCVideoExtension";
"Microsoft.SecHealthUI"; "Microsoft.VP9VideoExtensions"; "Microsoft.WebpImageExtension";
"Microsoft.WindowsStore"; "Microsoft.GamingApp"; "Microsoft.Sticky.Notes"; "Microsoft.Paint";
"Microsoft.PowerAutomateDesktop"; "Microsoft.ScreenSketch"; "Microsoft.WindowsNotepad";
"Microsoft.WindowsTerminal"; "Clipchamp.Clipchamp"; "Microsoft.Solitaire.Collection";
"Microsoft.WindowsAlarms"; "Microsoft.WindowsFeedbackHub"; "Microsoft.WindowsMaps";
"Microsoft.ZuneMusic"; "Microsoft.BingNews"; "Microsoft.DesktopAppInstaller"; "Microsoft.WindowsCamera";
"Microsoft.Getstarted"; "Microsoft.Cortana"; "Microsoft.BingWeather"; "Microsoft.GetHelp";
"Microsoft.MicrosoftOfficeHub"; "Microsoft.People"; "Microsoft.StorePurchaseApp"; "Microsoft.Todos";
"Microsoft.WebMediaExtensions"; "Microsoft.Windows.Photos"; "Microsoft.WindowsCalculator";
"Microsoft.Windows.CommunicationsApps"; "Microsoft.WindowsSoundRecorder"; "Microsoft.Xbox.TCUI";
"Microsoft.XboxGameOverlay"; "Microsoft.XboxGamingOverlay"; "Microsoft.XboxIdentityProvider";
"Microsoft.XboxSpeechToTextOverlay";

"Microsoft.YourPhone"; "Microsoft.ZuneVideo"; "MicrosoftCorporationII.QuickAssist";
"MicrosoftWindows.Client.WebExperience"; "Microsoft.RawImageExtension";
"MicrosoftCorporationII.MicrosoftFamily";

)

}

@{

 Name = @("Education"; "Professional"; "ProfessionalEducation"; "ProfessionalWorkstation"; "Enterprise";
"IoTEnterprise"; "ServerRdsh");

 Apps = @(

 "Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.HEIFImageExtension"; "Microsoft.HEVCVideoExtension";
"Microsoft.SecHealthUI"; "Microsoft.VP9VideoExtensions"; "Microsoft.WebpImageExtension";
"Microsoft.WindowsStore"; "Microsoft.GamingApp"; "Microsoft.Sticky.Notes"; "Microsoft.Paint";
"Microsoft.PowerAutomateDesktop"; "Microsoft.ScreenSketch"; "Microsoft.WindowsNotepad";
"Microsoft.WindowsTerminal"; "Clipchamp.Clipchamp"; "Microsoft.Solitaire.Collection";
"Microsoft.WindowsAlarms"; "Microsoft.WindowsFeedbackHub"; "Microsoft.WindowsMaps";
"Microsoft.ZuneMusic"; "Microsoft.BingNews"; "Microsoft.DesktopAppInstaller"; "Microsoft.WindowsCamera";
"Microsoft.Getstarted"; "Microsoft.Cortana"; "Microsoft.BingWeather"; "Microsoft.GetHelp";
"Microsoft.MicrosoftOfficeHub"; "Microsoft.People"; "Microsoft.StorePurchaseApp"; "Microsoft.Todos";
"Microsoft.WebMediaExtensions"; "Microsoft.Windows.Photos"; "Microsoft.WindowsCalculator";
"Microsoft.Windows.CommunicationsApps"; "Microsoft.WindowsSoundRecorder"; "Microsoft.Xbox.TCUI";
"Microsoft.XboxGameOverlay"; "Microsoft.XboxGamingOverlay"; "Microsoft.XboxIdentityProvider";
"Microsoft.XboxSpeechToTextOverlay"; "Microsoft.YourPhone"; "Microsoft.ZuneVideo";
"MicrosoftCorporationII.QuickAssist"; "MicrosoftWindows.Client.WebExperience";
"Microsoft.RawImageExtension";

)

}

@{

 Name = @("EnterpriseN"; "EnterpriseGN"; "EnterpriseSN"; "ProfessionalN"; "EducationN";
"ProfessionalWorkstationN"; "ProfessionalEducationN"; "CloudN"; "CloudEN"; "CloudEditionN";
"CloudEditionLN"; "StarterN");

```

```

Apps = @(

 "Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.SecHealthUI"; "Microsoft.WindowsStore";
"Microsoft.Sticky.Notes"; "Microsoft.Paint"; "Microsoft.PowerAutomateDesktop"; "Microsoft.ScreenSketch";
"Microsoft.WindowsNotepad"; "Microsoft.WindowsTerminal"; "Clipchamp.Clipchamp";
"Microsoft.Solitaire.Collection"; "Microsoft.WindowsAlarms"; "Microsoft.WindowsFeedbackHub";
"Microsoft.WindowsMaps"; "Microsoft.BingNews"; "Microsoft.DesktopAppInstaller";
"Microsoft.WindowsCamera"; "Microsoft.Getstarted"; "Microsoft.Cortana"; "Microsoft.BingWeather";
"Microsoft.GetHelp"; "Microsoft.MicrosoftOfficeHub"; "Microsoft.People"; "Microsoft.StorePurchaseApp";
"Microsoft.Todos"; "Microsoft.Windows.Photos"; "Microsoft.WindowsCalculator";
"Microsoft.Windows.CommunicationsApps"; "Microsoft.XboxGameOverlay"; "Microsoft.XboxIdentityProvider";
"Microsoft.XboxSpeechToTextOverlay"; "Microsoft.YourPhone"; "MicrosoftCorporationII.QuickAssist";
"MicrosoftWindows.Client.WebExperience";

)

}

)

$Allow_Install_App = @()

ForEach ($item in $Pre_Config_Rules) {

 if ($item.Name -contains $Current_Edition_Version) {

 Write-host "`n Match to: "-NoNewline

 Write-host $Current_Edition_Version -ForegroundColor Green

 $Allow_Install_App = $item.Apps

 break

 }

}

Write-host "`n The app to install ($($Allow_Install_App.Count) item)" -ForegroundColor Yellow

Write-host " $('-' * 80)"

ForEach ($item in $Allow_Install_App) {

 Write-host " $($item)" -ForegroundColor Green

}

$InBoxApps = @(

 @{ Name = "Microsoft.UI.Xaml.2.3"; File = "Microsoft.UI.Xaml.x64.2.3.appx"; License = ""; }

 @{ Name = "Microsoft.UI.Xaml.2.4"; File = "Microsoft.UI.Xaml.x64.2.4.appx"; License = ""; }

 @{ Name = "Microsoft.UI.Xaml.2.7"; File = "Microsoft.UI.Xaml.x64.2.7.appx"; License = ""; }

 @{ Name = "Microsoft.NET.Native.Framework.2.2"; File = "Microsoft.NET.Native.Framework.x64.2.2.appx";
License = ""; }

 @{ Name = "Microsoft.NET.Native.Runtime.2.2"; File = "Microsoft.NET.Native.Runtime.x64.2.2.appx"; License =
""; }

 @{ Name = "Microsoft.VCLibs.140.00"; File = "Microsoft.VCLibs.x64.14.00.appx"; License = ""; }

```

```
@{ Name = "Microsoft.VCLibs.140.00.UWPDesktop"; File = "Microsoft.VCLibs.x64.14.00.UWPDesktop.appx";
License = ""; }

@{ Name = "Microsoft.WindowsStore"; File = "Microsoft.WindowsStore_8wekyb3d8bbwe.msixbundle"; License
= "Microsoft.WindowsStore_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.HEIFImageExtension"; File =
"Microsoft.HEIFImageExtension_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.HEIFImageExtension_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.HEVCVideoExtension"; File =
"Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.x64.appx"; License =
"Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.x64.xml"; }

@{ Name = "Microsoft.SecHealthUI"; File = "Microsoft.SecHealthUI_8wekyb3d8bbwe.x64.appx"; License =
"Microsoft.SecHealthUI_8wekyb3d8bbwe.x64.xml"; }

@{ Name = "Microsoft.VP9VideoExtensions"; File = "Microsoft.VP9VideoExtensions_8wekyb3d8bbwe.x64.appx";
License = "Microsoft.VP9VideoExtensions_8wekyb3d8bbwe.x64.xml"; }

@{ Name = "Microsoft.WebplImageExtension"; File =
"Microsoft.WebplImageExtension_8wekyb3d8bbwe.x64.appx"; License =
"Microsoft.WebplImageExtension_8wekyb3d8bbwe.x64.xml"; }

@{ Name = "Microsoft.GamingApp"; File = "Microsoft.GamingApp_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.GamingApp_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.Sticky.Notes"; File = "Microsoft.MicrosoftStickyNotes_8wekyb3d8bbwe.msixbundle";
License = "Microsoft.MicrosoftStickyNotes_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.Paint"; File = "Microsoft.Paint_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.Paint_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.PowerAutomateDesktop"; File =
"Microsoft.PowerAutomateDesktop_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.PowerAutomateDesktop_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.ScreenSketch"; File = "Microsoft.ScreenSketch_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.ScreenSketch_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.WindowsNotepad"; File = "Microsoft.WindowsNotepad_8wekyb3d8bbwe.msixbundle";
License = "Microsoft.WindowsNotepad_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.WindowsTerminal"; File = "Microsoft.WindowsTerminal_8wekyb3d8bbwe.msixbundle";
License = "Microsoft.WindowsTerminal_8wekyb3d8bbwe.xml"; }

@{ Name = "Clipchamp.Clipchamp"; File = "Clipchamp.Clipchamp_yxz26nhyzhsrt.msixbundle"; License =
"Clipchamp.Clipchamp_yxz26nhyzhsrt.xml"; }

@{ Name = "Microsoft.Solitaire.Collection"; File =
"Microsoft.MicrosoftSolitaireCollection_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.MicrosoftSolitaireCollection_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.WindowsAlarms"; File = "Microsoft.WindowsAlarms_8wekyb3d8bbwe.msixbundle";
License = "Microsoft.WindowsAlarms_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.WindowsFeedbackHub"; File =
"Microsoft.WindowsFeedbackHub_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.WindowsFeedbackHub_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.WindowsMaps"; File = "Microsoft.WindowsMaps_8wekyb3d8bbwe.msixbundle"; License
= "Microsoft.WindowsMaps_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.ZuneMusic"; File = "Microsoft.ZuneMusic_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.ZuneMusic_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "MicrosoftCorporationII.MicrosoftFamily"; File =
"MicrosoftCorporationII.MicrosoftFamily_8wekyb3d8bbwe.msixbundle"; License =
"MicrosoftCorporationII.MicrosoftFamily_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.BingNews"; File = "Microsoft.BingNews_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.BingNews_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.DesktopAppInstaller"; File =
"Microsoft.DesktopAppInstaller_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.DesktopAppInstaller_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.WindowsCamera"; File = "Microsoft.WindowsCamera_8wekyb3d8bbwe.msixbundle";
License = "Microsoft.WindowsCamera_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.Getstarted"; File = "Microsoft.Getstarted_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.Getstarted_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.Cortana"; File = "Microsoft.CortanaApp_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.CortanaApp_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.BingWeather"; File = "Microsoft.BingWeather_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.BingWeather_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.GetHelp"; File = "Microsoft.GetHelp_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.GetHelp_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.MicrosoftOfficeHub"; File =
"Microsoft.MicrosoftOfficeHub_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.MicrosoftOfficeHub_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.People"; File = "Microsoft.People_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.People_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.StorePurchaseApp"; File = "Microsoft.StorePurchaseApp_8wekyb3d8bbwe.appxbundle";
License = "Microsoft.StorePurchaseApp_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.Todos"; File = "Microsoft.Todos_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.Todos_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.WebMediaExtensions"; File =
"Microsoft.WebMediaExtensions_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.WebMediaExtensions_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.Windows.Photos"; File = "Microsoft.Windows.Photos_8wekyb3d8bbwe.appxbundle";
License = "Microsoft.Windows.Photos_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.WindowsCalculator"; File =
"Microsoft.WindowsCalculator_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.WindowsCalculator_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.Windows.CommunicationsApps"; File =
"Microsoft.WindowsCommunicationsApps_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.WindowsCommunicationsApps_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.WindowsSoundRecorder"; File =
"Microsoft.WindowsSoundRecorder_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.WindowsSoundRecorder_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.Xbox.TCUI"; File = "Microsoft.Xbox.TCUI_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.Xbox.TCUI_8wekyb3d8bbwe.xml"; }
```

```

 @{ Name = "Microsoft.XboxGameOverlay"; File = "Microsoft.XboxGameOverlay_8wekyb3d8bbwe.appxbundle";
License = "Microsoft.XboxGameOverlay_8wekyb3d8bbwe.xml"; }

 @{ Name = "Microsoft.XboxGamingOverlay"; File =
"Microsoft.XboxGamingOverlay_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.XboxGamingOverlay_8wekyb3d8bbwe.xml"; }

 @{ Name = "Microsoft.XboxIdentityProvider"; File =
"Microsoft.XboxIdentityProvider_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.XboxIdentityProvider_8wekyb3d8bbwe.xml"; }

 @{ Name = "Microsoft.XboxSpeechToTextOverlay"; File =
"Microsoft.XboxSpeechToTextOverlay_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.XboxSpeechToTextOverlay_8wekyb3d8bbwe.xml"; }

 @{ Name = "Microsoft.YourPhone"; File = "Microsoft.YourPhone_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.YourPhone_8wekyb3d8bbwe.xml"; }

 @{ Name = "Microsoft.ZuneVideo"; File = "Microsoft.ZuneVideo_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.ZuneVideo_8wekyb3d8bbwe.xml"; }

 @{ Name = "MicrosoftCorporationII.QuickAssist"; File =
"MicrosoftCorporationII.QuickAssist_8wekyb3d8bbwe.appxbundle"; License =
"MicrosoftCorporationII.QuickAssist_8wekyb3d8bbwe.xml"; }

 @{ Name = "MicrosoftWindows.Client.WebExperience"; File =
"MicrosoftWindows.Client.WebExperience_cw5n1h2txyewy.appxbundle"; License =
"MicrosoftWindows.Client.WebExperience_cw5n1h2txyewy.xml"; }

 @{ Name = "Microsoft.RawImageExtension"; File =
"Microsoft.RawImageExtension_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.RawImageExtension_8wekyb3d8bbwe.xml"; }

)

```

```
Function Install_Appx
```

```

{

 param($File, $License)

 Write-host " $('-' * 80)"

 Write-host " Installing: " -NoNewline; Write-host $File -ForegroundColor Yellow

 if (Test-Path -Path $File -PathType Leaf) {

 if (Test-Path -Path $License -PathType Leaf) {

 Write-host " License: " -NoNewline; Write-host $License -ForegroundColor Yellow

 Write-host " With License".PadRight(22) -NoNewline -ForegroundColor Green

 Write-host " Installing".PadRight(22) -NoNewline

 try {

 Add-AppxProvisionedPackage -Path $Mount -PackagePath $File -LicensePath $License -ErrorAction
SilentlyContinue | Out-Null

 Write-Host "Done" -ForegroundColor Green

 } catch {

 Write-Host "Failed" -ForegroundColor Red
 }
 }
 }
}

```



```

 Write-Host " $($_) " -ForegroundColor Yellow

 }

} else {

 Write-host " No License".PadRight(22) -NoNewline -ForegroundColor Red

 Write-host " Installing".PadRight(22) -NoNewline

 try {

 Add-AppxProvisionedPackage -Path $Mount -PackagePath $File -SkipLicense -ErrorAction
SilentlyContinue | Out-Null

 Write-Host "Done" -ForegroundColor Green

 } catch {

 Write-Host "Failed" -ForegroundColor Red

 Write-Host " $($_) " -ForegroundColor Yellow

 }

}

} else {

 Write-host " The installation package does not exist" -ForegroundColor Red

}

}

ForEach ($Rule in $InBoxApps) {

 Write-host "`n Name: " -NoNewline

 Write-host $Rule.Name -ForegroundColor Yellow

 Write-host " $('-' * 80)"

 if($Allow_Install_App -contains $Rule.Name) {

 Write-host " Search for apps: " -NoNewline

 Write-host $Rule.File -ForegroundColor Yellow

 Write-host " Search for License: " -NoNewline

 Write-host $Rule.File -ForegroundColor Yellow

 if ($ISO -eq "Auto") {

 Get-PSDrive -PSProvider FileSystem -ErrorAction SilentlyContinue | ForEach-Object {

 $AppPath = Join-Path -Path $_.Root -ChildPath "packages\$($Rule.File)" -ErrorAction SilentlyContinue

 $LicensePath = Join-Path -Path $_.Root -ChildPath "packages\$($Rule.License)" -ErrorAction
SilentlyContinue

 if (Test-Path $AppPath -PathType Leaf) {

 Write-host " $('-' * 80)"

 Write-host " Discover apps: " -NoNewLine; Write-host $AppPath -ForegroundColor Green

```



```

 if (Test-Path $LicensePath -PathType Leaf) {; Write-host " Discover License: " -NoNewLine

 Write-host $LicensePath -ForegroundColor Green

 } else {

 Write-host " License: " -NoNewLine

 Write-host "Not found" -ForegroundColor Red

 }

 Install_Appx -File $AppPath -License $LicensePath

 return

 }

}

} else {

 Install_Appx -File "$($ISO)\${$Rule.File}" -License "$($ISO)\${$Rule.License}"

}

} else {

 Write-host " Skip the installation" -ForegroundColor Red

}

}

```

#### 5.8. 区域标记：删除

- 完成安装 InBox Apps 应用后，区域标记已不再重要，可删除或不删除，删除“本地语言体验包（LXPs），简体中文 - 中国）”，区域标记：zh-CN，可更改为其它区域标记。
- Install.Clear.Flag.ps1
  - [\Expand\Install\Install.Clear.Flag.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/Install/Install.Clear.Flag.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/Install/Install.Clear.Flag.ps1)
- 复制代码

```

$Lang = "zh-CN"

Get-AppXProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" | Foreach-object {

 if ($_.DisplayName -Like "*LanguageExperiencePack*${$Lang}*") {

 Write-host " ${$_.DisplayName}"

 Write-Host " Deleting ".PadRight(22) -NoNewline

 try {

 Remove-AppxProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackageName $_.PackageName -ErrorAction SilentlyContinue | Out-Null

```

```
Write-host "Finish" -ForegroundColor Green

} catch {

Write-host "Failed" -ForegroundColor Red

}

}

}

}
```

#### 5.9. InBox Apps：优化

在安装应用后，应优化预配 Appx 包，通过用硬链接替换相同的文件来减少应用的磁盘使用量，仅针对脱机映像。

```
Dism /Image:"D:\OS_10_Custom\Install\Install\Mount" /Optimize-ProvisionedAppxPackages
```

### 6. 累积更新

- 不同版本、旧版本升级到最新版时，需优先添加“功能启用包”后才能添加最新版累积更新；
- 添加语言包后，可安装与初始版本相同的累积更新，以解决安装后未刷新“组件：映像中已安装的所有包”状态的已知问题；
- 为保持最新，推荐您下载最新版。

#### 6.1. 功能启用包

- 学习：[KB5015684：使用启用包对 Windows 10 版本 22H2 的特别推荐更新](#)
- 注意：[使用 Windows 10 22H2 19045.2006 相同版本和以上版本号时，可跳过功能启用包。](#)
- 制作 Windows 10 版本 2004、20H2、21H1、21H2 时，需提前安装“功能启用包”后才能安装 19045.\* 的累积更新，  
下载后保存到：[D:\OS\\_10\\_Custom\Install\Install\Update](#)，根据架构选择下载：

##### 6.1.1. x64，默认

- 直连下载

[https://catalog.s.download.windowsupdate.com/c/upgr/2022/07/windows10.0-kb5015684-x64\\_523c039b86ca98f2d818c4e6706e2cc94b634c4a.msu](https://catalog.s.download.windowsupdate.com/c/upgr/2022/07/windows10.0-kb5015684-x64_523c039b86ca98f2d818c4e6706e2cc94b634c4a.msu)

- 安装

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5015684-x64_523c039b86ca98f2d818c4e6706e2cc94b634c4a.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

##### 6.1.2. x86

- 直连下载

[https://catalog.s.download.windowsupdate.com/c/upgr/2022/07/windows10.0-kb5015684-x86\\_556015f4260dd75ca30b3e84484ea5b3ec97fa08.msu](https://catalog.s.download.windowsupdate.com/c/upgr/2022/07/windows10.0-kb5015684-x86_556015f4260dd75ca30b3e84484ea5b3ec97fa08.msu)

- 安装

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5015684-x86_556015f4260dd75ca30b3e84484ea5b3ec97fa08.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

#### 6.1.3. Arm64

- 直连下载

[https://catalog.s.download.windowsupdate.com/c/upgr/2022/07/windows10.0-kb5015684-arm64\\_a4cc6e95084da14adb972e1d67cf573a244ed7a3.msu](https://catalog.s.download.windowsupdate.com/c/upgr/2022/07/windows10.0-kb5015684-arm64_a4cc6e95084da14adb972e1d67cf573a244ed7a3.msu)

- 安装

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5015684-arm64_a4cc6e95084da14adb972e1d67cf573a244ed7a3.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

### 6.2. 初始版本

累积更新 KB5017308 已无法从 <https://www.catalog.update.microsoft.com/Search.aspx?q=KB5017308> 里搜索到，通过直连方式下载后保存到：D:\OS\_10\_Custom\Install\Install\Update，根据架构选择下载：

#### 6.2.1. x64, 默认

- 直连下载

[https://catalog.s.download.windowsupdate.com/c/msdownload/update/software/secu/2022/09/windows10.0-kb5017308-x64\\_2027053968a06948b45d139d95475ab4feee5654.msu](https://catalog.s.download.windowsupdate.com/c/msdownload/update/software/secu/2022/09/windows10.0-kb5017308-x64_2027053968a06948b45d139d95475ab4feee5654.msu)

- 安装

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5017308-x64_2027053968a06948b45d139d95475ab4feee5654.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

#### 6.2.2. x86

- 直连下载

[https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/secu/2022/09/windows10.0-kb5017308-x86\\_ec788348202c33b871c8af028d045debd273576c.msu](https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/secu/2022/09/windows10.0-kb5017308-x86_ec788348202c33b871c8af028d045debd273576c.msu)

- 安装

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5017308-x86_ec788348202c33b871c8af028d045debd273576c.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

6.2.3. Arm64

- 直连下载

[https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/secu/2022/09/windows10.0-kb5017308-arm64\\_1ca51a0b3abdab7ee891bd1e1e6d3f03bc15e324.msu](https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/secu/2022/09/windows10.0-kb5017308-arm64_1ca51a0b3abdab7ee891bd1e1e6d3f03bc15e324.msu)

- 安装

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5017308-arm64_1ca51a0b3abdab7ee891bd1e1e6d3f03bc15e324.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

6.3. 其它版本

查阅“[Windows 10 版本信息](#)”，例如下载累积更新：[KB5032278](#)，前往下载页面：

<https://www.catalog.update.microsoft.com/Search.aspx?q=KB5032278>，下载后保存到：

[D:\OS\\_10\\_Custom\Install\Install\Update](#)，或通过直连下载，根据架构选择下载：

6.3.1. x64, 默认

- 直连下载

[https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/updt/2023/11/windows10.0-kb5032278-x64\\_3a2b384f690eaa92c5030c535ac4a7e47c71a635.msu](https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/updt/2023/11/windows10.0-kb5032278-x64_3a2b384f690eaa92c5030c535ac4a7e47c71a635.msu)

- 添加

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5032278-x64_3a2b384f690eaa92c5030c535ac4a7e47c71a635.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

6.3.2. x86

- 直连下载

[https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/updt/2023/11/windows10.0-kb5032278-x86\\_21e1e1c12d0f763d7c6e3ac6c3d7f8c6461e0004.msu](https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/updt/2023/11/windows10.0-kb5032278-x86_21e1e1c12d0f763d7c6e3ac6c3d7f8c6461e0004.msu)

- 添加

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5032278-
x86_21e1e1c12d0f763d7c6e3ac6c3d7f8c6461e0004.msu"

Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

#### 6.3.3. Arm64

- 直连下载

[https://catalog.s.download.windowsupdate.com/c/msdownload/update/software/updt/2023/11/windows10.0-kb5032278-arm64\\_54422d085c9d2c64ca0ff6e88ace3ec9f8860b6a.msu](https://catalog.s.download.windowsupdate.com/c/msdownload/update/software/updt/2023/11/windows10.0-kb5032278-arm64_54422d085c9d2c64ca0ff6e88ace3ec9f8860b6a.msu)

- 添加

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5032278-
arm64_54422d085c9d2c64ca0ff6e88ace3ec9f8860b6a.msu"

Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

#### 6.4. 固化更新，可选项

固化后不可卸载，固化时将清理恢复映像并重置任何被取代的组件的基础。

```
Dism /Image:"D:\OS_10_Custom\Install\Install\Mount" /cleanup-image /StartComponentCleanup /ResetBase
```

##### 6.4.1. 固化更新后清理组件，可选项

```
$Mount = "D:\OS_10_Custom\Install\Install\Mount"

Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {

 if ($_.PackageState -eq "Superseded"){

 Write-Host " $($_.PackageName)" -ForegroundColor Green

 Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null

 }

}
```

#### 7. 驱动，可选

#### 8. 部署引擎：添加，可选

- 了解“[部署引擎](#)”，如果添加到 ISO 安装介质，可跳过添加到已挂载；
- 如果添加部署引擎到已挂载里，请继续在当前位置执行下一步。

#### 9. 健康

保存前应检查是否损坏，健康状态异常时，中止保存

```
Repair-WindowsImage -Path "D:\OS_10_Custom\Install\Install\Mount" -ScanHealth
```

#### 10. 替换 WinRE.wim

已批量替换 Install.wim 里的所有索引号里的 WinRE.wim 请跳过该步骤。

```
$WinRE = "D:\OS_10_Custom\Install\Install\Update\Winlib\WinRE.wim"
```

```
$CopyTo = "D:\OS_10_Custom\Install\Install\Mount\Windows\System32\Recovery"
```

```
Copy-Item -Path $WinRE -Destination $CopyTo -Force
```

#### 11. 保存映像

```
Save-WindowsImage -Path "D:\OS_10_Custom\Install\Install\Mount"
```

#### 12. 卸载映像

关闭所有可能正在访问映像中文件的应用程序，包括文件资源管理器。

```
Dismount-WindowsImage -Path "D:\OS_10_Custom\Install\Install\Mount" -Discard
```

循环操作区域，结束。

#### 13. 重建 Install.wim 后可缩小文件大小

- Install.Rebuild.wim.ps1
  - [\Expand\Install\Install.Rebuild.wim.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/Install/Install.Rebuild.wim.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/Install/Install.Rebuild.wim.ps1)
- 复制代码

```
$InstallWim = "D:\OS_10\sources\install.wim"
```

```
Get-WindowsImage -ImagePath $InstallWim -ErrorAction SilentlyContinue | ForEach-Object {
```

```
 Write-Host " Image name: " -NoNewline
```

```
 Write-Host $_.ImageName -ForegroundColor Yellow
```

```
 Write-Host " The index number: " -NoNewline
```

```
 Write-Host $_.ImageIndex -ForegroundColor Yellow
```

```
 Write-Host "`n Under reconstruction".PadRight(28) -NoNewline
```

```
 Export-WindowsImage -SourceImagePath $InstallWim -SourceIndex $_.ImageIndex -DestinationImagePath "$($InstallWim).New" -
 CompressionType max | Out-Null
```

```
 Write-Host "Finish`n" -ForegroundColor Green
```

```

}

if (Test-Path "$($InstallWim).New" -PathType Leaf) {

 Remove-Item -Path $InstallWim

 Move-Item -Path "$($InstallWim).New" -Destination $InstallWim

 Write-Host "Finish" -ForegroundColor Green

} else {

 Write-host "Failed" -ForegroundColor Red

}

```

#### 14. 如何批量替换 Install.wim 里的所有索引号里的 WinRE.wim

##### 14.1. 获取 WimLib

前往 <https://wimlib.net> 官方网站后，选择不同的版本：arm64, x64, x86，下载完成后解压到：D:\Wimlib

##### 14.2. 如何在 Install.wim 里提取和更新 WinRE.wim

###### 14.2.1. 从 Install.wim 里提取 WinRE.wim 文件 Install.wim

- Install.WinRE.Replace.wim.ps1
  - [\Expand\Install\Install.WinRE.Replace.wim.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/Install/Install.WinRE.Replace.wim.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/Install/Install.WinRE.Replace.wim.ps1)

- 复制代码

```

$Arguments = @(

 "extract",

 "D:\OS_10\sources\install.wim", "1",

 "\Windows\System32\Recovery\Winre.wim",

 "--dest-dir=""D:\OS_10_Custom\Install\Install\Update\Winlib""""

)

New-Item -Path "D:\OS_10_Custom\Install\Install\Update\Winlib" -ItemType Directory -ea SilentlyContinue

Start-Process -FilePath "d:\wimlib\wimlib-image.exe" -ArgumentList $Arguments -wait -nonewwindow

```

###### 14.2.2. 获取 Install.wim 所有索引号后并替换旧的 WinRE.wim

- Install.WinRE.Replace.wim.ps1
  - [\Expand\Install\Install.WinRE.Replace.wim.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/Install/Install.WinRE.Replace.wim.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/Install/Install.WinRE.Replace.wim.ps1)

- 复制代码

```
Get-WindowsImage -ImagePath "D:\OS_10\sources\install.wim" -ErrorAction SilentlyContinue | ForEach-Object {

 Write-Host " Image name: " -NoNewline; Write-Host $_.ImageName -ForegroundColor Yellow

 Write-Host " The index number: " -NoNewline; Write-Host $_.ImageIndex -ForegroundColor Yellow

 Write-Host "`n Replacement "

 $Arguments = @(

 "update",

 "D:\OS_10\sources\install.wim", $_.ImageIndex,

 "--command=""add 'D:\OS_10_Custom\Install\Install\Update\Winlib\WinRE.wim'
 '\Windows\System32\Recovery\WinRe.wim'"""

)

 Start-Process -FilePath "d:\wimlib\wimlib-imagex.exe" -ArgumentList $Arguments -wait -nonewwindow

 Write-Host " Finish`n" -ForegroundColor Green

}
```

### III 自定义部署映像：boot.wim

#### 1. 查看 Boot.wim 文件信息

映像名称、映像描述、映像大小、架构、版本、索引号等；

```
$ViewFile = "D:\OS_10\Sources\Boot.wim"

Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex }
```

#### 2. 指定挂载 Boot.wim 路径

```
New-Item -Path "D:\OS_10_Custom\Boot\Boot\Mount" -ItemType directory -ea SilentlyContinue
```

#### 3. 开始挂载 Boot.wim

默认索引号：2

```
Mount-WindowsImage -ImagePath "D:\OS_10\sources\boot.wim" -Index "2" -Path "D:\OS_10_Custom\Boot\Boot\Mount"
```

#### 4. 语言包

- 自动安装语言包：获取“组件：映像中已安装的所有包”后进行匹配，匹配到对应的名称后，再安装本地对应的语言包文件，查看报告“[语言安装包适用于 Boot.wim](#)”。



- 添加语言时，须对应不同的架构版本，未对应时，添加过程中报错等提示。

#### 4.1. 语言包：添加

- Boot.Instl.lang.ps1
  - [\Expand\Boot\Boot.Instl.lang.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/Boot/Boot.Instl.lang.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/Boot/Boot.Instl.lang.ps1)

- 复制代码

```
$Mount = "D:\OS_10_Custom\Boot\Boot\Mount"

$Sources = "D:\OS_10_Custom\Boot\Boot\Language\Add\zh-CN"

$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

 $Initl_install_Language_Component += $_.PackageName

}

Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\WinPE-FontSupport-zh-CN.cab"

$Language = @(

 @{ Match = "*WinPE*Setup*Client*Package*"; File = "WINPE-SETUP-CLIENT_zh-CN.CAB"; }

 @{ Match = "*WinPE*Setup*Package*"; File = "WinPE-Setup_zh-CN.cab"; }

 @{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }

 @{ Match = "*SecureStartup*"; File = "winpe-securestartup_zh-CN.cab"; }

 @{ Match = "*ATBroker*"; File = "winpe-atbroker_zh-CN.cab"; }

 @{ Match = "*AudioCore*"; File = "winpe-audiocore_zh-CN.cab"; }

 @{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_zh-CN.cab"; }

 @{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_zh-CN.cab"; }

 @{ Match = "*Narrator*"; File = "winpe-narrator_zh-CN.cab"; }

 @{ Match = "*scripting*"; File = "winpe-scripting_zh-CN.cab"; }

 @{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_zh-CN.cab"; }

 @{ Match = "*srh*"; File = "winpe-srh_zh-CN.cab"; }

 @{ Match = "*srt*"; File = "winpe-srt_zh-CN.cab"; }

 @{ Match = "*wds-tools*"; File = "winpe-wds-tools_zh-CN.cab"; }

 @{ Match = "*-WMI-Package*"; File = "winpe-wmi_zh-CN.cab"; }

)

ForEach ($Rule in $Language) {

 Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host " $('-' * 80)"
```

```

ForEach ($Component in $InitL_install_Language_Component) {

 if ($Component -like "*$($Rule.Match)*") {

 Write-host " Component name: " -NoNewline; Write-host $Component -ForegroundColor Green

 Write-host " Language pack file: " -NoNewline; Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

 Write-Host " Installing ".PadRight(22) -NoNewline

 try {

 Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" | Out-Null

 Write-host "Finish" -ForegroundColor Green

 } catch {

 Write-host "Failed" -ForegroundColor Red

 Write-host " $($_) " -ForegroundColor Red

 }

 break

 }

}

}

```

## 4.2. 脱机映像语言：更改

### 4.2.1. 更改默认语言、区域设置和其他国际设置

区域标记：**zh-CN**

```
Dism /Image:"D:\OS_10_Custom\Boot\Boot\Mount" /Set-AllIntl:zh-CN
```

### 4.2.2. 查看可用的语言设置

```
Dism /Image:"D:\OS_10_Custom\Boot\Boot\Mount" /Get-Intl
```

## 4.3. 语言包：删除，可选

- 添加语言后，如果要部署到非英语区域，可通过删除英语语言组件来节省空间。删除语言时，请按与添加语言组件相反的顺序卸载语言组件。
- 添加中文后，反向删除“**英语 - 美国**”，区域：**en-US**，需提前提取语言包
- Boot.Del.Specified.lang.Tag.ps1
  - [\Expand\Boot\Boot.Del.Specified.lang.Tag.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/Boot/Boot/Boot.Del.Specified.lang.Tag.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/Boot/Boot/Boot.Del.Specified.lang.Tag.ps1)

- 复制代码

```
$Lang = "en-US"

$Mount = "D:\OS_10_Custom\Boot\Boot\Mount"

$Sources = "D:\OS_10_Custom\Boot\Boot\Language\Del\en-US"

$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

 $Initl_install_Language_Component += $_.PackageName

}

$Language = @(

 @{ Match = "*WordPad*wow64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~wow64~$($Lang)~.cab"; }

 @{ Match = "*WordPad*amd64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~amd64~$($Lang)~.cab"; }

 @{ Match = "*WMIC*FoD*Package*wow64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~wow64~$($Lang)~.cab"; }

 @{ Match = "*WMIC*FoD*Package*amd64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~AMD64~$($Lang)~.cab"; }

 @{ Match = "*StepsRecorder*wow64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~wow64~$($Lang)~.cab"; }

 @{ Match = "*StepsRecorder*amd64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~amd64~$($Lang)~.cab"; }

 @{ Match = "*Printing*PMCPPC*amd64*"; File = "Microsoft-Windows-Printing-PMCPPC-FoD-
Package~31bf3856ad364e35~AMD64~$($Lang)~.cab"; }

 @{ Match = "*PowerShell*wow64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~wow64~$($Lang)~.cab"; }

 @{ Match = "*PowerShell*amd64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~amd64~$($Lang)~.cab"; }

 @{ Match = "*MediaPlayer*wow64*"; File = "Microsoft-Windows-MediaPlayer-Package-wow64-$($Lang).cab"; }

 @{ Match = "*MediaPlayer*amd64*"; File = "Microsoft-Windows-MediaPlayer-Package-AMD64-$($Lang).cab"; }

 @{ Match = "*Notepad*wow64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~wow64~$($Lang)~.cab"; }

 @{ Match = "*Notepad*amd64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~AMD64~$($Lang)~.cab"; }

 @{ Match = "*InternetExplorer*"; File = "Microsoft-Windows-InternetExplorer-Optional-
Package~31bf3856ad364e35~AMD64~$($Lang)~.cab"; }

 @{ Match = "*TextToSpeech*"; File = "Microsoft-Windows-LanguageFeatures-TextToSpeech-$($Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

 @{ Match = "*LanguageFeatures-Speech*"; File = "Microsoft-Windows-LanguageFeatures-Speech-$($Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

 @{ Match = "*OCR*"; File = "Microsoft-Windows-LanguageFeatures-OCR-$($Lang)-
```

```
Package~31bf3856ad364e35~amd64~~.cab"; }

 @{ Match = "*Handwriting*"; File = "Microsoft-Windows-LanguageFeatures-Handwriting-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

 @{ Match = "*LanguageFeatures-Basic*"; File = "Microsoft-Windows-LanguageFeatures-Basic-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

 @{ Match = "*Client-LanguagePack-Package*"; File = "Microsoft-Windows-Client-Language-Pack_x64_$(Lang).cab"; }

)

ForEach ($Rule in $Language) {

 Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host " $('-' * 80)"

 ForEach ($Component in $Initl_install_Language_Component) {

 if ($Component -like "*$(Rule.Match)*$(Lang)*") {

 Write-host " Component name: " -NoNewline; Write-host $Component -ForegroundColor Green

 Write-host " Language pack file: " -NoNewline; Write-host "$($Sources)\$(Rule.File)" -ForegroundColor Green

 Write-Host " Deleting ".PadRight(22) -NoNewline

 try {

 Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$(Rule.File)" -ErrorAction SilentlyContinue | Out-Null

 Write-host "Finish" -ForegroundColor Green

 } catch {

 Write-host "Failed" -ForegroundColor Red

 Write-host " $($_) " -ForegroundColor Red

 }

 break

 }

 }

}

$InitlClearLanguagePackage = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

 if ($_.PackageName -like "*$(Lang)*") {

 $InitlClearLanguagePackage += $_.PackageName

 }

}

if ($InitlClearLanguagePackage.count -gt 0) {

 ForEach ($item in $InitlClearLanguagePackage) {

 Write-Host "`n $($item)" -ForegroundColor Green

 Write-Host " Deleting ".PadRight(22) -NoNewline
```

```
try{

 Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction SilentlyContinue | Out-Null

 Write-host "Finish" -ForegroundColor Green

} catch {

 Write-host "Failed" -ForegroundColor Red

 Write-host " $($_) " -ForegroundColor Red

}

}

}
```

4.4. 组件：映像中已安装的所有包

4.4.1. 查看

```
Get-WindowsPackage -Path "D:\OS_10_Custom\Boot\Boot\Mount" | Out-GridView
```

4.4.2. 导出到 Csv

```
$SaveTo = "D:\OS_10_Custom\Boot\Boot\Report.${(Get-Date -Format "yyyyMMddHHmmss")}.csv"

Get-WindowsPackage -Path "D:\OS_10_Custom\Boot\Boot\Mount" | Export-CSV -NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green
```

4.5. 语言包：同步到 ISO 安装程序

```
Copy-Item -Path "D:\OS_10_Custom\Boot\Boot\Mount\sources\zh-CN" -Destination "D:\OS_10\sources\zh-CN" -Recurse -Force
```

4.6. 重新生成 Lang.ini

重新生成后，可调整“安装界面”，选择“语言”时的顺序，打开 lang.ini，默认首选值 = 3，非默认值 = 2。

4.6.1. 重新生成已挂载目录 lang.ini

重新生成的 Lang.ini 文件位置： [D:\en-us\\_windows\\_server\\_2022\\_x64\\_dvd\\_620d7eac\\_Custom\Boot\Boot\Mount\Sources\lang.ini](#)

```
Dism /image:"D:\OS_10_Custom\Boot\Boot\Mount" /gen-langini /distribution:"D:\OS_10_Custom\Boot\Boot\Mount"
```

4.6.2. 重新生成 lang.ini 后，同步到安装程序

重新生成的 Lang.ini 文件位置： [D:\en-us\\_windows\\_server\\_2022\\_x64\\_dvd\\_620d7eac\Sources\lang.ini](#)

```
Dism /image:"D:\OS_10_Custom\Boot\Boot\Mount" /gen-langini /distribution:"D:\OS_10"
```

5. 累积更新，可选

准备可用的累积更新文件，请更改示例文件名：KB\_Boot.cab

5.1. 添加

```
$KBPath = "D:\OS_10_Custom\Boot\Boot\Update\KB_Boot.cab"

Add-WindowsPackage -Path "D:\OS_10_Custom\Boot\Boot\Mount" -PackagePath $KBPath
```

5.2. 删除

```
$KBPath = "D:\OS_10_Custom\Boot\Boot\Update\KB_Boot.cab"

Remove-WindowsPackage -Path "D:\OS_10_Custom\Boot\Boot\Mount" -PackagePath $KBPath
```

5.3. 固化更新，可选项

固化后不可卸载，固化时将清理恢复映像并重置任何被取代的组件的基础。

```
Dism /image:"D:\OS_10_Custom\Boot\Boot\Mount" /cleanup-image /StartComponentCleanup /ResetBase
```

5.3.1. 固化更新后清理组件，可选项

```
$Mount = "D:\OS_10_Custom\Boot\Boot\Mount"

Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {

 if ($_.PackageState -eq "Superseded") {

 Write-Host " $($_.PackageName)" -ForegroundColor Green

 Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null

 }

}
```

6. 驱动，可选

7. 保存映像

```
Save-WindowsImage -Path "D:\OS_10_Custom\Boot\Boot\Mount"
```

8. 卸载映像

关闭所有可能正在访问映像中文件的应用程序，包括文件资源管理器。

```
Dismount-WindowsImage -Path "D:\OS_10_Custom\Boot\Boot\Mount" -Discard
```

- 了解“自动添加 Windows 系统已安装的语言”，学习：<https://github.com/ilikeyi/Multilingual>，如何下载：
  - 进入网站后，点击“代码”，“下载压缩包”，下载完成后得到 `main.zip` 压缩包文件。
  - 前往 <https://github.com/ilikeyi/Multilingual/releases> 下载页面，选择可用版本：1.1.1.1，选择下载源代码格式：zip，下载完成后得到 `Multilingual-1.1.1.1.zip` 压缩包文件；
- 将已下载的 `main.zip` 或 `Multilingual-1.1.1.1.zip`，解压到：D:\Multilingual-1.1.1.1，重命名：D:\Multilingual
- 学习“无人值守 Windows 安装参考”，通过无人值守来干预安装过程。

1. 添加方式

1.1. 添加到 ISO 安装介质

1.1.1. 无人值守

1.1.1.1. 添加到：`[ISO]:\Autounattend.xml`

引导 ISO 安装时，Autounattend.xml 干预 WinPE 安装程序。

复制 `D:\Multilingual\_Learn\Unattend\Mul.Unattend.xml` 到 `D:\OS_10\Autounattend.xml`

```
Copy-Item "D:\Multilingual_Learn\Unattend\Mul.Unattend.xml" -Destination
"D:\OS_10\Autounattend.xml" -Force
```

1.1.1.2. 添加到：`[ISO]:\Sources\Unattend.xml`

挂载或解压 ISO 时，运行 `[ISO]:\Setup.exe` 安装程序后，`[ISO]:\Sources\Unattend.xml` 将干预安装过程。

复制 `D:\Multilingual\_Learn\Unattend\Mul.Unattend.xml` 到 `D:\OS_10\Sources\Unattend.xml`

```
Copy-Item "D:\Multilingual_Learn\Unattend\Mul.Unattend.xml" -Destination
"D:\OS_10\Sources\Unattend.xml" -Force
```

1.1.1.3. 添加到：`[ISO]:\sources\$OEM$\$$\Panther\unattend.xml`

安装过程中复制到系统盘里，复制到：`{系统盘}:\Windows\Panther\unattend.xml`

1.1.1.3.1. 创建 \$OEM\$ 路径

```
New-Item -Path "D:\OS_10\sources\`OEM\`$$\Panther" -ItemType Directory
```

1.1.1.3.2. 复制

复制 `D:\Multilingual\_Learn\Unattend\Mul.Unattend.xml` 到  
`D:\OS_10\Sources\$OEM$\Panther\Unattend.xml`

```
Copy-Item "D:\Multilingual\Learn\Unattend\Mul.Unattend.xml" -Destination
"D:\OS_10\sources\`OEM\`$$\Panther\Unattend.xml" -Force
```

1.1.2. 部署引擎：添加

添加“自动添加 Windows 系统已安装的语言”到 D:\OS\_10\sources\\$OEM\$\\$1\Yi\Engine 目录里。

1.1.2.1. 部署引擎：复制

复制 D:\Multilingual\Engine 到 D:\OS\_10\Sources\\$OEM\$\\$1\Yi\Engine

```
Copy-Item "D:\Multilingual\Engine" -Destination "D:\OS_10\sources\`OEM\`$1\Yi\Engine" -Recurse -
Force
```

1.1.2.2. 部署引擎：自定义部署标记

```
$Flag = @(

 "Is_Mark_Sync" # 允许全盘搜索并同步部署标记

 # 先决部署

 # "Auto_Update" # 允许自动更新

 # "Use_UTF8" # Beta 版：使用 Unicode UTF-8 提供全球语言支持

 "Disable_Network_Location_Wizard" # 网络位置向导

 "Disable_Cleanup_Appx_Tasks" # Appx 清理维护任务

 "Disable_Cleanup_On_Demand_Language" # 阻止清理未使用的按需功能语言包

 "Disable_Cleanup_Unsed_Language" # 阻止清理未使用的语言包

 "Prerequisites_Reboot" # 重新启动计算机

 # 完成首次部署

 # "Popup_Engine" # 允许首次弹出部署引擎主界面

 # "Allow_First_Pre_Experience" # 允许首次预体验，按计划

 "Reset_Execution_Policy" # 恢复 PowerShell 执行策略：受限

 "Clear_Solutions" # 删除整个解决方案

 "Clear_Engine" # 删除部署引擎，保留其它

 # "First_Experience_Reboot" # 重新启动计算机

)

ForEach ($item in $Flag) {
```



```
Write-host " $($item)" -ForegroundColor Green

New-Item -Path "D:\OS_10\sources\`OEM\`$1\Yi\Engine\Deploy\Allow" -ItemType Directory -
ErrorAction SilentlyContinue | Out-Null

Out-File -FilePath "D:\OS_10\sources\`OEM\`$1\Yi\Engine\Deploy\Allow\$(item)" -Encoding utf8 -
ErrorAction SilentlyContinue

}
```

1.2. 添加到已挂载

通过“自定义部署映像：Install.wim”，执行“开始挂载 Install.wim”，挂载到：D:\OS\_10\_Custom\Install\Install\Mount

1.2.1. 无人值守

复制 D:\Multilingual\\_Learn\Unattend\Mul.Unattend.xml 到  
D:\OS\_10\_Custom\Install\Install\Mount\Panther\Unattend.xml

```
Copy-Item "D:\Multilingual_Learn\Unattend\Mul.Unattend.xml" -Destination
"D:\OS_10_Custom\Install\Install\Mount\Panther" -Force
```

1.2.2. 部署引擎

添加“自动添加 Windows 系统已安装的语言”到 D:\OS\_10\_Custom\Install\Install\Mount\Yi\Engine 目录里。

1.2.2.1. 部署引擎：复制

复制 D:\Multilingual\Engine 到 D:\OS\_10\_Custom\Install\Install\Mount\Yi\Engine

```
Copy-Item "D:\Multilingual\Engine" -Destination "D:\OS_10_Custom\Install\Install\Mount\Yi\Engine" -
Recurse -Force
```

1.2.2.2. 部署引擎：自定义部署标记

```
$Flag = @(

 "Is_Mark_Sync" # 允许全盘搜索并同步部署标记

 # 先决部署

 # "Auto_Update" # 允许自动更新

 # "Use_UTF8" # Beta 版：使用 Unicode UTF-8 提供全球语言支持

 "Disable_Network_Location_Wizard" # 网络位置向导

 "Disable_Cleanup_Appx_Tasks" # Appx 清理维护任务

 "Disable_Cleanup_On_Demand_Language" # 阻止清理未使用的按需功能语言包
```

```
"Disable_Cleanup_Unsed_Language" # 阻止清理未使用的语言包

"Prerequisites_Reboot" # 重新启动计算机

完成首次部署

"Popup_Engine" # 允许首次弹出部署引擎主界面

"Allow_First_Pre_Experience" # 允许首次预体验，按计划

"Reset_Execution_Policy" # 恢复 PowerShell 执行策略：受限

"Clear_Solutions" # 删除整个解决方案

"Clear_Engine" # 删除部署引擎，保留其它

"First_Experience_Reboot" # 重新启动计算机

)

ForEach ($item in $Flag) {

 Write-host " $($item)" -ForegroundColor Green

 New-Item -Path "D:\OS_10_Custom\Install\Install\Mount\Yi\Engine\Deploy\Allow" -ItemType Directory -
 ErrorAction SilentlyContinue | Out-Null

 Out-File -FilePath "D:\OS_10_Custom\Install\Install\Mount\Yi\Engine\Deploy\Allow\${$item}" -Encoding
 utf8 -ErrorAction SilentlyContinue

}
```

## 2. 部署引擎：进阶

### 2.1. 部署引擎：添加过程中

在复制部署引擎后，可添加部署标记来干预安装过程。

### 2.2. 无人值守方案

自定义无人值守时，以下文件存在时请同步修改：

- [D:\OS\\_10\Autounattend.xml](#)
- [D:\OS\\_10\Sources\Unattend.xml](#)
- [D:\OS\\_10\sources\\\$\OEM\\$\\\$\\\$Panther\unattend.xml](#)
- [D:\OS\\_10\\_Custom\Install\Install\Mount\Panther\Unattend.xml](#)

#### 2.2.1. 多语言或单语

多语言时，单语时，可互相切换，替换时，请替换文件里所有相同的。

2.2.1.1. 多语言

```
<UILanguage>%OSDUILanguage%</UILanguage>

<InputLocale>%OSDInputLocale%</InputLocale>

<SystemLocale>%OSDSysLocale%</SystemLocale>

<UILanguage>%OSDUILanguage%</UILanguage>

<UILanguageFallback>%OSDUILanguageFallback%</UILanguageFallback>

<UserLocale>%OSDUserLocale%</UserLocale>
```

2.2.1.2. 单语

单语需指定区域，例如指定区域：zh-CN

```
<UILanguage>zh-CN</UILanguage>

<InputLocale>zh-CN</InputLocale>

<SystemLocale>zh-CN</SystemLocale>

<UILanguage>zh-CN</UILanguage>

<UILanguageFallback>zh-CN</UILanguageFallback>

<UserLocale>zh-CN</UserLocale>
```

2.2.2. 用户方案

默认使用自建用户 Administrator 并自动登录，可通过修改以下配置切换：自建、自定义用户。

2.2.2.1. 自建用户 Administrator

默认使用自建用户：Administrator 并自动登录，插入到 <OOBE> 和 </OOBE> 之间。

```
<UserAccounts>

 <LocalAccounts>

 <LocalAccount wcm:action="add">

 <Password>

 <Value></Value>

 <PlainText>true</PlainText>

 </Password>

 <Description>Administrator</Description>

 <DisplayName>Administrator</DisplayName>

 <Group>Administrators</Group>

 <Name>Administrator</Name>
```

```
</LocalAccount>

</LocalAccounts>

</UserAccounts>

<AutoLogon>

 <Password>

 <Value></Value>

 <PlainText>true</PlainText>

 </Password>

 <Enabled>true</Enabled>

 <Username>Administrator</Username>

</AutoLogon>
```

2.2.2.2. 自定义用户

设置自定义用户后，安装系统完成后，在 OOB 里，可选择本地、在线用户等设置。

2.2.2.2.1. 删除

用户名：从开始处删除 <UserAccounts> 到 </UserAccounts>

自动登录：从开始处删除 <AutoLogon> 到 </AutoLogon>

2.2.2.2.2. 替换

从开始处 <OOBE> 到 </OOBE>

```
<OOBE>

 <ProtectYourPC>3</ProtectYourPC>

 <HideEULAPage>true</HideEULAPage>

 <HideWirelessSetupInOOBE>true</HideWirelessSetupInOOBE>

</OOBE>
```

D. ISO

II 生成 ISO

1. 下载 OScding

根据架构选择 OScding 版本，下载后保存到：D:\，保存在其它路径请输入 OScding.exe 绝对路径；

1.1. x64

[https://github.com/ilikeyi/solutions/raw/main/\\_Software/Oscding/amd64/oscdimg.exe](https://github.com/ilikeyi/solutions/raw/main/_Software/Oscding/amd64/oscdimg.exe)

1.2. x86

[https://github.com/ilikeyi/solutions/raw/main/\\_Software/Oscding/x86/oscdimg.exe](https://github.com/ilikeyi/solutions/raw/main/_Software/Oscding/x86/oscdimg.exe)

1.3. arm64

[https://github.com/ilikeyi/solutions/raw/main/\\_Software/Oscding/arm64/oscdimg.exe](https://github.com/ilikeyi/solutions/raw/main/_Software/Oscding/arm64/oscdimg.exe)

2. 使用 oscding 命令行生成一个 ISO 文件，保存到：D:\Win11.iso

- ISO.ps1
  - [\Expand\ISO.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Attachment/OS.10/22H2/Expand/ISO.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.10/22H2/Expand/ISO.ps1)

- 复制代码

```
$Oscding = "D:\Oscding.exe"

$ISO = "D:\OS_10"

$Volume = "OS_10"

$SaveTo = "D:\OS_10.iso"

$Arguments = @("-m", "-o", "-u2", "-udfver102", "-l" "$($Volume)", "-bootdata:2#p0,e,b" "$($ISO)\boot\etfsboot.com" "#pEF,e,b" "$($ISO)\efi\microsoft\boot\efisys.bin", $ISO, $SaveTo)

Start-Process -FilePath $Oscding -ArgumentList $Arguments -wait -nonewwindow
```

章节 2 报告

- 编组缩写：
  - 群组 A: Windows 10 Education, Windows 10 Enterprise, Windows 10 Pro Education, Windows 10 Pro for Workstations, Windows 10 IoT Enterprise
  - 群组 B: Windows 10 Education N, Windows 10 Enterprise N, Windows 10 Pro, Windows 10 Pro N, Windows 10 Pro Education N, Windows 10 Pro N for Workstations
  - 群组 C: Windows 10 Home, Windows 10 Home Single Language
  - 群组 D: Windows 10 家庭版 N

II 不同版本

- |    |                                                                                         |      |
|----|-----------------------------------------------------------------------------------------|------|
| 1. | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~amd64~~10.0.19041.2006           | A, C |
| 2. | Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~~10.0.19041.1806   | A, B |
|    | Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.1 |      |

3.	Microsoft-Windows-Printing-WFS-FoD-Package~31bf3856ad364e35~amd64~~10.0.19041.2006	A, B, C, D
	Microsoft-Windows-Printing-WFS-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.906	
4.	Microsoft-OneCore-ApplicationModel-Sync-Desktop-FOD-Package~31bf3856ad364e35~amd64~~10.0.19041.1949	A, B, C, D
5.	Microsoft-OneCore-DirectX-Database-FOD-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
6.	Microsoft-Windows-Client-LanguagePack-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.2006	A, B, C, D
7.	Microsoft-Windows-FodMetadata-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
8.	Microsoft-Windows-Foundation-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
9.	Microsoft-Windows-Hello-Face-Migration-Package~31bf3856ad364e35~amd64~~10.0.19041.1889	A, B, C, D
10.	Microsoft-Windows-Hello-Face-Package~31bf3856ad364e35~amd64~~10.0.19041.1889	A, B, C, D
11.	Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~~11.0.19041.1566	A, B, C, D
12.	Microsoft-Windows-LanguageFeatures-Basic-en-us-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
13.	Microsoft-Windows-LanguageFeatures-Handwriting-en-us-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
14.	Microsoft-Windows-LanguageFeatures-OCR-en-us-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
15.	Microsoft-Windows-LanguageFeatures-Speech-en-us-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
16.	Microsoft-Windows-LanguageFeatures-TextToSpeech-en-us-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
17.	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~amd64~~10.0.19041.746	A, B, C, D
	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.1	A, B, C, D
18.	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~~10.0.19041.1	A, B, C, D
	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.19041.1	A, B, C, D
19.	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~amd64~~10.0.19041.1865	A, B, C, D
	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.488	A, B, C, D
20.	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~~10.0.19041.1	A, B, C, D
	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.19041.1	A, B, C, D
21.	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.1	A, B, C, D
22.	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~~10.0.19041.1	A, B, C, D
	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~en-US~10.0.19041.1	A, B, C, D
23.	Microsoft-Windows-QuickAssist-Package~31bf3856ad364e35~amd64~~10.0.19041.1949	A, B, C, D
24.	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~~10.0.19041.746	A, B, C, D
	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.1	A, B, C, D
25.	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~~10.0.19041.1	A, B, C, D
	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~en-US~10.0.19041.1	A, B, C, D
26.	Microsoft-Windows-TabletPCMath-Package~31bf3856ad364e35~amd64~~10.0.19041.1865	A, B, C, D
27.	Microsoft-Windows-UserExperience-Desktop-Package~31bf3856ad364e35~amd64~~10.0.19041.1741	A, B, C, D

28.	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~~10.0.19041.1682	A, B, C, D
	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.1	A, B, C, D
29.	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~~10.0.19041.1	A, B, C, D
	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.19041.1	A, B, C, D
30.	OpenSSH-Client-Package~31bf3856ad364e35~amd64~~10.0.19041.964	A, B, C, D
31.	Package_for_DotNetRollup~31bf3856ad364e35~amd64~~10.0.4556.3	A, B, C, D
32.	Package_for_KB5015684~31bf3856ad364e35~amd64~~19041.1799.1.2	A, B, C, D
33.	Package_for_RollupFix~31bf3856ad364e35~amd64~~19041.2006.1.7	A, B, C, D
34.	Package_for_ServicingStack_1704~31bf3856ad364e35~amd64~~19041.1704.1.4	A, B, C, D
35.	Package_for_ServicingStack_1940~31bf3856ad364e35~amd64~~19041.1940.1.0	A, B, C, D

III 语言安装包适用于：Install.wim

1.	Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B
	Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
2.	Microsoft-Windows-LanguageFeatures-Fonts-Hans-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-Fonts-Hans-Package~31bf3856ad364e35~amd64~~10.0.19041.1	
3.	Microsoft-Windows-Client-Language-Pack_x64_zh-CN.cab	A, B, C, D
	Microsoft-Windows-Client-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
4.	Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~zh-CN~11.0.19041.1	
5.	Microsoft-Windows-LanguageFeatures-Basic-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-Basic-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.19041.1	
6.	Microsoft-Windows-LanguageFeatures-Handwriting-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-Handwriting-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.19041.1	
7.	Microsoft-Windows-LanguageFeatures-OCR-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-OCR-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.19041.1	
8.	Microsoft-Windows-LanguageFeatures-Speech-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-Speech-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.19041.1	
9.	Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.19041.1	
10.	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
11.	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.19041.1	

12.	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
13.	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.19041.1	
14.	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
15.	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.19041.1	
16.	Microsoft-Windows-Printing-WFS-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-Printing-WFS-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
17.	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
18.	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~zh-CN~10.0.19041.1	
19.	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
20.	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.19041.1	

IV 语言安装包适用于：WinRE.wim

1.	WinPE-FontSupport-zh-CN.cab	
	Microsoft-Windows-WinPE-FontSupport-ZH-CN-Package~31bf3856ad364e35~amd64~~10.0.19041.1	
2.	lp.cab	
	Microsoft-Windows-WinPE-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
3.	winpe-appxpackaging_zh-CN.cab	
	Microsoft-Windows-WinPE-AppxPackaging-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
4.	winpe-atbroker_zh-CN.cab	
	WinPE-ATBroker-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
5.	winpe-audiocore_zh-CN.cab	
	WinPE-AudioCore-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
6.	winpe-audiodrivers_zh-CN.cab	
	WinPE-AudioDrivers-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
7.	winpe-enhancedstorage_zh-CN.cab	
	WinPE-EnhancedStorage-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	



8.

winpe-hta\_zh-CN.cab

WinPE-HTA-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
9.

winpe-narrator\_zh-CN.cab

WinPE-Narrator-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
10.

winpe-opcservices\_zh-CN.cab

WinPE-OpcServices-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
11.

winpe-rejuv\_zh-CN.cab

WinPE-Rejuv-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
12.

winpe-scripting\_zh-CN.cab

WinPE-Scripting-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
13.

winpe-securestartup\_zh-CN.cab

WinPE-SecureStartup-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
14.

winpe-speech-tts\_zh-CN.cab

WinPE-Speech-TTS-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
15.

winpe-srh\_zh-CN.cab

WinPE-SRH-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
16.

winpe-srt\_zh-CN.cab

WinPE-SRT-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
17.

winpe-storagewmi\_zh-CN.cab

WinPE-StorageWMI-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
18.

winpe-wds-tools\_zh-CN.cab

WinPE-WDS-Tools-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
19.

winpe-wifi\_zh-CN.cab

WinPE-WiFi-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
20.

winpe-wmi\_zh-CN.cab

WinPE-WMI-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1

V

语言安装包适用于：Boot.wim

1.

WinPE-FontSupport-zh-CN.cab

Microsoft-Windows-WinPE-FontSupport-ZH-CN-Package~31bf3856ad364e35~amd64~~10.0.19041.1
2.

lp.cab

Microsoft-Windows-WinPE-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
3.

winpe-atbroker\_zh-CN.cab

WinPE-ATBroker-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1

4.

winpe-audiocore\_zh-CN.cab

WinPE-AudioCore-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
5.

winpe-audiodrivers\_zh-CN.cab

WinPE-AudioDrivers-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
6.

winpe-enhancedstorage\_zh-CN.cab

WinPE-EnhancedStorage-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
7.

winpe-narrator\_zh-CN.cab

WinPE-Narrator-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
8.

winpe-scripting\_zh-CN.cab

WinPE-Scripting-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
9.

winpe-securestartup\_zh-CN.cab

WinPE-SecureStartup-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
10.

WINPE-SETUP-CLIENT\_zh-CN.CAB

WinPE-Setup-Client-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
11.

WinPE-Setup\_zh-CN.cab

WinPE-Setup-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
12.

winpe-speech-tts\_zh-CN.cab

WinPE-Speech-TTS-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
13.

winpe-srh\_zh-CN.cab

WinPE-SRH-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
14.

winpe-srt\_zh-CN.cab

WinPE-SRT-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
15.

winpe-wds-tools\_zh-CN.cab

WinPE-WDS-Tools-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
16.

winpe-wmi\_zh-CN.cab

WinPE-WMI-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1

章节 3

常见问题

II

清理所有挂载到

关闭所有可能正在访问映像中文件的应用程序，包括文件资源管理器。

Dismount-WindowsImage -Path "D:\OS\_10\_Custom\Install\Install\Mount" -Discard

Dismount-WindowsImage -Path "D:\OS\_10\_Custom\Install\WinRE\Mount" -Discard

Dismount-WindowsImage -Path "D:\OS\_10\_Custom\Boot\Boot\Mount" -Discard

III 修复挂载出现异常的问题

1. 查看已挂载

```
Get-WindowsImage -Mounted
```

2. 删除保存在注册表里的 DISM 挂载记录

```
Remove-Item -Path "HKLM:\SOFTWARE\Microsoft\WIMMount\Mounted Images*" -Force -Recurse -ErrorAction SilentlyContinue | Out-Null
```

3. 删除与已损坏的已装载映像关联的所有资源。

```
Clear-WindowsCorruptMountPoint
```

```
Dism /cleanup-wim
```

IV 清理目录

```
Remove-Item "D:\OS_10_Custom" -Force -Recurse
```

```
Remove-Item "D:\OS_10\Sources\`OEM" -Force -Recurse
```

```
Remove-Item -Path "D:\OS_10\Autounattend.xml" -Force
```

```
Remove-Item -Path "D:\OS_10\Sources\Unattend.xml" -Force
```

章节 4 已知问题

暂无



作者: Yi

网站: <https://fengyi.tel>

邮箱: [775159955@qq.com](mailto:775159955@qq.com), [ilikeyi@outlook.com](mailto:ilikeyi@outlook.com)

文档版本: 1.0

文档模型: 完整版

更新日期: 2024 - 4

建议或反馈: <https://github.com/ilikeyi/solutions/issues>