



## MICROSOFT WINDOWS 10

Different system versions have different packaging methods. The packaging process includes: "Language pack: add, associate, delete", "Drive: add, delete", "Cumulative update: add, delete", "InBox Apps: add, Update, mark" etc.

There are many hidden stories hidden behind this. If you want to unlock these, are you ready to start trying to encapsulate them?

### Summary

Chapter 1	Deployment image
Chapter 2	Report
Chapter 3	Common problem
Chapter 4	Known issues

Table of contents

Chapter 1	Deployment image	Page 5
A.	Prerequisites	Page 5
II	ISO tools	Page 5
III	Requirements	Page 5
1.	System installation package	Page 5
2.	Language pack	Page 6
2.1.	Learn	Page 6
2.2.	Language pack: Download	Page 9
2.3.	Feature pack: Download	Page 9
3.	InBox Apps	Page 9
IV	Windows Security	Page 9
V	Command line	Page 10
B.	Language Pack: Extract	Page 10
II	Language pack: Ready	Page 10
III	Language pack: Scheme	Page 10
IV	Execute the extract command	Page 10
C.	Customize the deployment image	Page 16
II	Custom deployment image Install.wim	Page 16
1.	View Install.wim details	Page 16
2.	Specify the path to mount Install.wim	Page 16
3.	Start mounting Install.wim	Page 16
3.1.	Custom deployment image WinRE.wim	Page 17
3.1.1.	View WinRE.wim details	Page 17
3.1.2.	Specify the path to mount WinRE.wim	Page 17
3.1.3.	Start mounting WinRE.wim	Page 17
3.1.4.	Language pack: WinRE	Page 17
3.1.4.1.	Language pack: add	Page 17
3.1.4.2.	Offline image language: change	Page 19
3.1.4.2.1.	Change default language, regional settings, and other international settings	Page 19
3.1.4.2.2.	View available language settings	Page 19

3.1.4.3.	Language packs: Removed .....	Page 19
3.1.4.4.	Components: All packages installed in the image .....	Page 21
3.1.5.	Cumulative updates .....	Page 22
3.1.5.1.	Add .....	Page 22
3.1.5.2.	Delete .....	Page 22
3.1.5.3.	Solid update .....	Page 22
3.1.5.3.1.	Clean components after curing and updating .....	Page 22
3.1.6.	Drive .....	Page 22
3.1.7.	Save image .....	Page 22
3.1.8.	Unmount image .....	Page 22
3.1.9.	After rebuilding WinRE.wim, the file size can be reduced .....	Page 23
3.1.10.	Backup WinRE.wim .....	Page 23
3.1.11.	Replace WinRE.wim within the Install.wim image .....	Page 24
4.	Language pack .....	Page 24
4.1.	Language pack: add .....	Page 24
4.2.	Offline image language: change .....	Page 30
4.2.1.	Change default language, regional settings, and other international settings .....	Page 30
4.2.2.	View available language settings .....	Page 30
4.3.	Language packs: Removed .....	Page 30
4.4.	Components: All packages installed in the image .....	Page 33
5.	InBox Apps .....	Page 33
5.1.	Learn .....	Page 33
5.2.	InBox Apps: Pre-install the application .....	Page 33
5.3.	InBox Apps: Installed .....	Page 35
5.4.	Remove all installed pre-applications .....	Page 35
5.5.	Region tag: Understanding .....	Page 36
5.6.	Region tag: adding method .....	Page 36
5.7.	InBox Apps: Install .....	Page 39
5.8.	Region tag: delete .....	Page 46
5.9.	InBox Apps: optimization .....	Page 47

6.	Cumulative updates .....	Page 47
6.1.	Feature enablement package .....	Page 47
6.2.	Initial version .....	Page 48
6.3.	Other versions .....	Page 49
6.4.	Solidify Updated .....	Page 50
7.	Drive .....	Page 50
8.	Deployment engine: Add .....	Page 50
9.	Health .....	Page 50
10.	Replace WinRE.wim .....	Page 50
11.	Save image: Install.wim .....	Page 51
12.	Unmount image: Install.wim .....	Page 51
13.	Rebuilding Install.wim reduces file size .....	Page 51
14.	How to batch replace WinRE.wim in all index numbers in Install.wim .....	Page 51
14.1.	Obtain WimLib .....	Page 51
14.2.	How to extract and update WinRE.wim in Install.wim .....	Page 52
III	Custom deployment image boot.wim .....	Page 53
1.	View Boot.wim details .....	Page 53
2.	Specify the path to mount Boot.wim .....	Page 53
3.	Start mounting Boot.wim .....	Page 53
4.	Language pack: Boot .....	Page 53
4.1.	Language pack: Add .....	Page 53
4.2.	Offline image language: change .....	Page 54
4.2.1.	Change default language, regional settings, and other international settings .....	Page 54
4.2.2.	View available language settings .....	Page 55
4.3.	Language pack: Removed .....	Page 55
4.4.	Components: All packages installed in the image .....	Page 57
4.5.	Language: Repair .....	Page 57
4.6.	Language packs: sync to ISO installer .....	Page 58
4.7.	Regenerate Lang.ini .....	Page 58
4.7.1.	Regenerate the mounted directory lang.ini .....	Page 58
4.7.2.	After regenerating lang.ini, sync to the installer .....	Page 58

5.	Cumulative updates .....	Page 58
5.1.	Add .....	Page 58
5.2.	Delete .....	Page 58
5.3.	Solid update .....	Page 58
5.3.1.	Clean components after curing and updating .....	Page 59
6.	Drive .....	Page 59
7.	Save image: Boot.wim .....	Page 59
8.	Unmount image: Boot.wim .....	Page 59
IV	Deployment engine .....	Page 59
1.	Add method .....	Page 59
2.	Deployment Engine: Advanced .....	Page 62
D.	Generate ISO .....	Page 64
Chapter 2	Report .....	Page 65
II	Reports: Different versions .....	Page 65
III	Report: Language installation packages apply to Install.wim .....	Page 67
IV	Report: Language installation packages apply to WinRE.wim .....	Page 68
V	Report: Language installation packages apply to Boot.wim .....	Page 70
Chapter 3	Common problem .....	Page 65
II	Clean all mounts to .....	Page 71
III	Fix the problem of abnormal mounting .....	Page 71
IV	Clean directories .....	Page 71
Chapter 4	Known issues .....	Page 72

## Chapter 1 Deployment image

### A. Prerequisites

#### II ISO tools

Use a software that can edit ISO files, such as: [PowerISO](#), [DAEMON Tools](#), [ISO Workshop](#);

#### III Requirements

##### 1. System installation package

Keywords: [iteration](#), [cross-version](#), [major version](#), [cumulative update](#), [initial release](#)

##### 1.1. illustrate

- 1.1.1. Please remake the image when each version is updated, for example, when crossing from 21H1 to 22H2, avoid other compatibility problems, and do not make the image based on the old image;
- 1.1.2. The regulation has been clearly communicated to packagers in various forms by some OEMs, and direct upgrades from iterative versions are not allowed;
- 1.1.3. Please use "Initial Version" and "Developer Edition" for production. There was a brief appearance in the official Microsoft documentation that the initial version must be used in production, but this sentence was later deleted in the official documentation;
- 1.1.4. After installing the language pack, you must re-add the cumulative update (the same version number), and if you do not add the cumulative update, problems such as "garbled characters" and "interface flashback" will occur.
- 1.1.5. Evolutionary process: Windows 10 22H2, Build 19045.2006 + KB5027215 = OS Build 19045.3086

##### 1.2. Prepare to download the initial or developer version

- 1.2.1. [en-us\\_windows\\_10\\_business\\_editions\\_version\\_22h2\\_x64\\_dvd\\_8cf17b79.iso](#)
- 1.2.2. [en-us\\_windows\\_10\\_business\\_editions\\_version\\_22h2\\_x86\\_dvd\\_186a68c3.iso](#)
- 1.2.3. [en-us\\_windows\\_10\\_consumer\\_editions\\_version\\_22h2\\_x64\\_dvd\\_8da72ab3.iso](#)
- 1.2.4. [en-us\\_windows\\_10\\_consumer\\_editions\\_version\\_22h2\\_x86\\_dvd\\_90883feb.iso](#)
- 1.2.5. [en-us\\_windows\\_10\\_iot\\_enterprise\\_version\\_22h2\\_arm64\\_dvd\\_39566b6b.iso](#)
- 1.2.6. [en-us\\_windows\\_10\\_iot\\_enterprise\\_version\\_22h2\\_x64\\_dvd\\_51cc370f.iso](#)
- 1.2.7. [en-us\\_windows\\_10\\_business\\_editions\\_version\\_21h2\\_x64\\_dvd\\_ce067768.iso](#)
- 1.2.8. [en-us\\_windows\\_10\\_business\\_editions\\_version\\_21h2\\_x86\\_dvd\\_8aba314e.iso](#)
- 1.2.9. [en-us\\_windows\\_10\\_consumer\\_editions\\_version\\_21h2\\_x64\\_dvd\\_6cfdb144.iso](#)
- 1.2.10. [en-us\\_windows\\_10\\_consumer\\_editions\\_version\\_21h2\\_x86\\_dvd\\_31755f1b.iso](#)
- 1.2.11. [en-us\\_windows\\_10\\_enterprise\\_ltsc\\_2021\\_x64\\_dvd\\_d289cf96.iso](#)
- 1.2.12. [en-us\\_windows\\_10\\_enterprise\\_ltsc\\_2021\\_x86\\_dvd\\_9f4aa95f.iso](#)

1.2.13. [en-us\\_windows\\_10\\_iot\\_enterprise\\_ltsc\\_2021\\_x64\\_dvd\\_257ad90f.iso](#)

1.3. After the sample download [en-us\\_windows\\_10\\_business\\_editions\\_version\\_22h2\\_x64\\_dvd\\_8cf17b79.iso](#), Unzip to: [D:\en-us\\_windows\\_10\\_business\\_editions\\_version\\_22h2\\_x64\\_dvd\\_8cf17b79](#)

1.4. After decompression is complete, change the directory [en-us\\_windows\\_10\\_business\\_editions\\_version\\_22h2\\_x64\\_dvd\\_8cf17b79](#) change to [D:\OS\\_10](#)

1.5. All scripts and all paths are set to [D:\OS\\_10](#) as the image source.

1.6. Installation configuration

1.6.1. Learn: [Windows Setup Edition Configuration and Product ID Files \( Ei.cfg and PID.txt \)](#)

1.6.2. Known issues

1.6.2.1. When there is no Ei.cfg, ISO boot installation will report an error when selecting certain versions, prompting: **Windows cannot find the Microsoft Software License terms. Make sure the installation sources are valid and restart the installation.**

1.6.2.2. How to solve it? Add ei.cfg to D:\OS\_10\Sources and create ei.cfg:

@"

[Channel]

volume

[VL]

1

"@ | Out-File -FilePath "D:\OS\_10\sources\EI.CFG" -Encoding Ascii

2. Language pack

2.1. Learn

As you read, please understand the important highlights of "Blue".

2.1.1. [Languages overview](#)

2.1.2. [Add languages to a Windows 10 image](#)

2.1.3. [Language and region Features on Demand \(FOD\)](#)

2.1.3.1. Fonts

- When adding a language pack, when the corresponding region is triggered, the required font functions need to be added, download "[List of all available language FODs](#)" learn more.
- In "Language Pack: Extract", the automatic recognition function has been added, and you can understand the functions: [Function Match\\_Required\\_Fonts](#)

2.1.3.2. Regional association

What are regional connections?

- When the image language is only in English, after adding the [zh-HK](#) language pack, the image

language will not be added. You should install [zh-TW](#) first, and then install [zh-HK](#) to obtain the corresponding association.

Known regional associations:

2.1.3.2.1. Region: [ar-sa](#), Optional associated areas: [en-US](#), associated installation package:

2.1.3.2.1.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.1.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.2. Region: [bg-bg](#), Optional associated areas: [en-US](#), associated installation package:

2.1.3.2.2.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.2.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.3. Region: [da-dk](#), Optional associated areas: [en-US](#), associated installation package:

2.1.3.2.3.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.3.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.4. Region: [el-gr](#), Optional associated areas: [en-US](#), associated installation package:

2.1.3.2.4.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.4.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.5. Region: [fr-ca](#), Optional associated areas: [en-US](#), [fr-fr](#), associated installation package:

2.1.3.2.5.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.5.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.5.3. Microsoft-Windows-LanguageFeatures-Basic-fr-fr-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.5.4. Microsoft-Windows-LanguageFeatures-Handwriting-fi-fi-  
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.6. Region: [he-il](#), Optional associated areas: [en-US](#), associated installation package:

2.1.3.2.6.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-  
Package~31bf3856ad364e35~amd64~~.cab



2.1.3.2.6.2.	Microsoft-Windows-LanguageFeatures-OCR-en-us- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.7.	Region: <b>ru-ru</b> , Optional associated areas: <b>en-US</b> , associated installation package:
2.1.3.2.7.1.	Microsoft-Windows-LanguageFeatures-Basic-es-us- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.7.2.	Microsoft-Windows-LanguageFeatures-OCR-en-us- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.8.	Region: <b>th-th</b> , Optional associated areas: <b>en-US</b> , associated installation package:
2.1.3.2.8.1.	Microsoft-Windows-LanguageFeatures-Basic-es-us- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.8.2.	Microsoft-Windows-LanguageFeatures-OCR-en-us- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.9.	Region: <b>uk-ua</b> , Optional associated areas: <b>en-US</b> , associated installation package:
2.1.3.2.9.1.	Microsoft-Windows-LanguageFeatures-Basic-es-us- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.9.2.	Microsoft-Windows-LanguageFeatures-OCR-en-us- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.10.	Region: <b>zh-TW</b> , Optional associated areas: <b>zh-HK</b> , associated installation package:
2.1.3.2.10.1.	Microsoft-Windows-LanguageFeatures-Basic-zh-hk- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.10.2.	Microsoft-Windows-LanguageFeatures-Speech-zh-hk- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.10.3.	Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-hk- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.3.	Other region-specific requirements
When triggering a known area, a specific "package" needs to be added.	
2.1.3.3.1.	Region: <b>zh-TW</b>
	Package: <b>Microsoft-Windows-InternationalFeatures-Taiwan- Package~31bf3856ad364e35~amd64~~.cab</b>
	Description: Supplemental support for Taiwan date formatting requirements. Package will be provided to customers located in Taiwan.
	Recommendation: Preinstall only on devices shipping to the Taiwan market. Not installing this capability on devices causes any API calls to that use the Taiwan calendar to fail.

THERE IS CONTROVERSY:

- During the test, it was found that this package was not installed in the original image of Microsoft's official original Windows 10. However, there are known issues in the recommended items. In the end, it is consistent with the official Microsoft original version, and the packager can freely choose to install it or not.

## 2.2. Language pack: Download

[https://software-download.microsoft.com/download/pr/19041.1.191206-1406.vb\\_release\\_CLIENTLANGPACKDVD\\_OEM\\_MULTI.iso](https://software-download.microsoft.com/download/pr/19041.1.191206-1406.vb_release_CLIENTLANGPACKDVD_OEM_MULTI.iso)

## 2.3. Feature pack: Download

ARM64: [https://software-static.download.prss.microsoft.com/pr/download/19041.1.191206-1406.vb\\_release\\_arm64fre\\_FOD-PACKAGES\\_OEM\\_PT1\\_arm64fre\\_MULTI.iso](https://software-static.download.prss.microsoft.com/pr/download/19041.1.191206-1406.vb_release_arm64fre_FOD-PACKAGES_OEM_PT1_arm64fre_MULTI.iso)

X64: [https://software-download.microsoft.com/download/pr/19041.1.191206-1406.vb\\_release\\_amd64fre\\_FOD-PACKAGES\\_OEM\\_PT1\\_amd64fre\\_MULTI.iso](https://software-download.microsoft.com/download/pr/19041.1.191206-1406.vb_release_amd64fre_FOD-PACKAGES_OEM_PT1_amd64fre_MULTI.iso)

X86: [https://software-static.download.prss.microsoft.com/pr/download/19041.1.191206-1406.vb\\_release\\_x86fre\\_FOD-PACKAGES\\_OEM\\_PT1\\_x86fre\\_MULTI.iso](https://software-static.download.prss.microsoft.com/pr/download/19041.1.191206-1406.vb_release_x86fre_FOD-PACKAGES_OEM_PT1_x86fre_MULTI.iso)

## 3. InBox Apps

[https://software-static.download.prss.microsoft.com/dbazure/888969d5-f34g-4e03-ac9d-1f9786c66749/19041.3031.230508-1728.vb\\_release\\_svc\\_prod3\\_amd64fre\\_InboxApps.iso](https://software-static.download.prss.microsoft.com/dbazure/888969d5-f34g-4e03-ac9d-1f9786c66749/19041.3031.230508-1728.vb_release_svc_prod3_amd64fre_InboxApps.iso)

## IV Windows Security

- When processing the encapsulation task, a large number of temporary files will be generated, and a large number of installation files will be released when installing the application in InBox Apps;
- Turning on Windows Security scans files and takes up a lot of CPU.
- In test: 1 hour and 22 minutes before shutdown, 20 minutes after shutdown.

How to close:

With the command line in green, hold down the Windows key and press R to launch Run.

1. Open Windows Security or run: `windowsdefender`;
2. Select "Virus & Threat Protection" or Run: `windowsdefender://threat`
3. Find "Virus & Threat Protection Settings", click "Manage Settings" or Run: `windowsdefender://threatsettings`, we recommend that you turn off some features:
  - 3.1. Real-time protection
  - 3.2. Cloud=delivered protection
  - 3.3. Automatic sample submission
  - 3.4. Tamper Protection
4. When you're not encapsulated, we recommend that you turn on Windows Security.

## V Command line

1. Optional "Terminal" or "PowerShell ISE", if "Terminal" is not installed, please go to: <https://github.com/microsoft/terminal/releases> After downloading;
2. Open "Terminal" or "PowerShell ISE" as administrator, it is recommended to set the PowerShell execution policy: bypass, PS command line:  
  
`Set-ExecutionPolicy -ExecutionPolicy Bypass -Force`
3. In this article, PS command line, green part, please copy it, paste it into the "Terminal" dialog box, press Enter and start running;
4. When there is `.ps1`, right-click the file and select Run with PowerShell, or copy the path and paste it into Terminal to run, the path with a colon, add the & character in the command line, example: `& "D:\Yi.Solutions\Encapsulation\SIP.ps1"`

## B. Language Pack: Extract

### II Language pack: Ready

1. Language pack: Mount

Mount `19041.1.191206-1406.vb_release_CLIENTLANGPACKDVD_OEM_MULTI.iso` or unzipped to any location;

2. Feature pack: Mount

Please select the schema version correctly, extract the wrong language pack, and the installation will report an error.

ARM64: `19041.1.191206-1406.vb_release_arm64fre_FOD-PACKAGES_OEM_PT1_arm64fre_MULTI.iso`

X64: `19041.1.191206-1406.vb_release_amd64fre_FOD-PACKAGES_OEM_PT1_amd64fre_MULTI.iso`

X86: `19041.1.191206-1406.vb_release_x86fre_FOD-PACKAGES_OEM_PT1_x86fre_MULTI.iso`

### III Language pack: Scheme

1. Add

1.1. Language name: `Simplified Chinese - China`, Region: `zh-CN`, Scope of application: `Install.Wim`, `Boot.Wim`, `WinRE.Wim`

2. Delete

2.1. Language name: `English - United States`, Region: `en-US`, Scope of application: `Install.Wim`, `Boot.Wim`, `WinRE.Wim`

3. Architecture: `x64`

### IV Execute the extract command

- `Auto` = automatically search all local disks, default;
- Customize the path, for example, specify the E drive: `$ISO = "E:\"`
- `Extract.ps1`
  - `\Expand\Extract.ps1`
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging/tutorial/OS.10/22H2/Expand/Extract.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging/tutorial/OS.10/22H2/Expand/Extract.ps1)

- Copy the code

```
$ISO = "Auto"

$SaveTo = "D:\OS_10_Custom"

$Extract_language_Pack = @(

    @{ Tag = "zh-CN"; Arch = "AMD64"; Act = "Add"; Scope = @("Install\Install"; "Install\WinRE"; "Boot\Boot") }

    @{ Tag = "en-US"; Arch = "AMD64"; Act = "Del"; Scope = @( "Install\Install"; "Install\WinRE"; "Boot\Boot" ) }

)

Function Extract_Language

{

    param($NewArch, $Act, $NewLang, $Expand)

    Function Match_Required_Fonts

    {

        param($Lang)

        $Fonts = @(

            @{ Match = @("as", "ar-SA", "ar", "ar-AE", "ar-BH", "ar-DJ", "ar-DZ", "ar-EG", "ar-ER", "ar-IL", "ar-IQ", "ar-JO", "ar-KM", "ar-KW", "ar-LB", "ar-LY",
            "ar-MA", "ar-MR", "ar-OM", "ar-PS", "ar-QA", "ar-SD", "ar-SO", "ar-SS", "ar-SY", "ar-TD", "ar-TN", "ar-YE", "arz-Arab", "ckb-Arab", "fa", "fa-AF", "fa-IR",
            "glk-Arab", "ha-Arab", "ks-Arab", "ks-Arab-IN", "ku-Arab", "ku-Arab-IQ", "mzn-Arab", "pa-Arab", "pa-Arab-PK", "pnb-Arab", "prs", "prs-AF", "prs-Arab",
            "ps", "ps-AF", "sd-Arab", "sd-Arab-PK", "tk-Arab", "ug", "ug-Arab", "ug-CN", "ur", "ur-IN", "ur-PK", "uz-Arab", "uz-Arab-AF"); Name = "Arab"; }

            @{ Match = @("bn-IN", "as-IN", "bn", "bn-BD", "bpy-Beng"); Name = "Beng"; }

            @{ Match = @("da-dk", "iu-Cans", "iu-Cans-CA"); Name = "Cans"; }

            @{ Match = @("chr-Cher-US", "chr-Cher"); Name = "Cher"; }

            @{ Match = @("hi-IN", "bh-Deva", "brx", "brx-Deva", "brx-IN", "hi", "ks-Deva", "mai", "mr", "mr-IN", "ne", "ne-IN", "ne-NP", "new-Deva", "pi-Deva",
            "sa", "sa-Deva", "sa-IN"); Name = "Deva"; }

            @{ Match = @("am", "am-ET", "byn", "byn-ER", "byn-Ethi", "ti", "ti-ER", "ti-ET", "tig", "tig-ER", "tig-Ethi", "ve-Ethi", "wal", "wal-ET", "wal-Ethi");
            Name = "Ethi"; }

            @{ Match = @("gu", "gu-IN"); Name = "Gujr"; }

            @{ Match = @("pa", "pa-IN", "pa-Guru"); Name = "Guru"; }

            @{ Match = @("zh-CN", "cmn-Hans", "gan-Hans", "hak-Hans", "wuu-Hans", "yue-Hans", "zh-gan-Hans", "zh-hak-Hans", "zh-Hans", "zh-SG", "zh-
            wuu-Hans", "zh-yue-Hans"); Name = "Hans"; }

            @{ Match = @("zh-TW", "cmn-Hant", "hak-Hant", "lzh-Hant", "zh-hak-Hant", "zh-Hant", "zh-HK", "zh-lzh-Hant", "zh-MO", "zh-yue-Hant"); Name =
            "Hant"; }

            @{ Match = @("he", "he-IL", "yi"); Name = "Hebr"; }

            @{ Match = @("ja", "ja-JP"); Name = "Jpan"; }

            @{ Match = @("km", "km-KH"); Name = "Khmr"; }

            @{ Match = @("kn", "kn-IN"); Name = "Knda"; }

            @{ Match = @("ko", "ko-KR"); Name = "Kore"; }

            @{ Match = @("de-de", "lo", "lo-LA"); Name = "Lao"; }
```

```

    @{ Match = @"(ml", "ml-IN"); Name = "Mlym"; }

    @{ Match = @"(or", "or-IN"); Name = "Orya"; }

    @{ Match = @"(si", "si-LK"); Name = "Sinh"; }

    @{ Match = @"(tr-tr", "arc-Sync", "syr", "syr-SY", "syr-Sync"); Name = "Sync"; }

    @{ Match = @"(ta", "ta-IN", "ta-LK", "ta-MY", "ta-SG"); Name = "Taml"; }

    @{ Match = @"(te", "te-IN"); Name = "Telu"; }

    @{ Match = @"(th", "th-TH"); Name = "Thai"; }

)

ForEach ($item in $Fonts) {

    if (($item.Match) -Contains $Lang) {

        return $item.Name

    }

}

return "Not_matched"

}

Function Match_Other_Region_Specific_Requirements

{

    param($Lang)

    $RegionSpecific = @(

        @{ Match = @"(zh-TW"); Name = "Taiwan"; }

    )

    ForEach ($item in $RegionSpecific) {

        if (($item.Match) -Contains $Lang) {

            return $item.Name

        }

    }

    return "Skip_specific_packages"

}

Function Extract_Process

{

    param($Package, $Name, $NewSaveTo)

    $NewSaveTo = "$($SaveTo)\$($NewSaveTo)\Language\$($Act)\$($NewLang)"

    New-Item -Path $NewSaveTo -ItemType Directory -ErrorAction SilentlyContinue | Out-Null

    if ($ISO -eq "Auto") {

```

```

Get-PSDrive -PSProvider FileSystem -ErrorAction SilentlyContinue | ForEach-Object {

    ForEach ($item in $Package) {

        $TempFilePath = Join-Path -Path $_.Root -ChildPath $item -ErrorAction SilentlyContinue

        if (Test-Path $TempFilePath -PathType Leaf) {

            Write-host "`n  Find: " -NoNewLine; Write-host $TempFilePath -ForegroundColor Green

            Write-host "  Copy to: " -NoNewLine; Write-host $NewSaveTo

            Copy-Item -Path $TempFilePath -Destination $NewSaveTo -Force

        }

    }

}

} else {

    ForEach ($item in $Package) {

        $TempFilePath = Join-Path -Path $ISO -ChildPath $item -ErrorAction SilentlyContinue

        Write-host "`n  Find: " -NoNewline; Write-host $TempFilePath -ForegroundColor Green

        if (Test-Path $TempFilePath -PathType Leaf) {

            Write-host "  Copy to: " -NoNewLine; Write-host $NewSaveTo

            Copy-Item -Path $TempFilePath -Destination $NewSaveTo -Force

        } else {

            Write-host "  Not found"

        }

    }

}

Write-host "`n  Verify the language pack file"

ForEach ($item in $Package) {

    $Path = "$($NewSaveTo)\${[IO.Path]::GetFileName($item)}"

    if (Test-Path $Path -PathType Leaf) {

        Write-host "  Discover: " -NoNewLine; Write-host $Path -ForegroundColor Green

    } else {

        Write-host "  Not found: " -NoNewLine; Write-host $Path -ForegroundColor Red

    }

}

}

$AdvLanguage = @(

    @{

```

```
Path = "Install\Install"

Rule = @(

    "Microsoft-Windows-LanguageFeatures-Fonts-{DiyLang}-Package~31bf3856ad364e35~AMD64~~.cab"

    "{ARCHC}\langpacks\Microsoft-Windows-Client-Language-Pack_x64_{Lang}.cab"

    "Microsoft-Windows-LanguageFeatures-Basic-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

    "Microsoft-Windows-LanguageFeatures-Handwriting-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

    "Microsoft-Windows-LanguageFeatures-OCR-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

    "Microsoft-Windows-LanguageFeatures-Speech-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

    "Microsoft-Windows-LanguageFeatures-TextToSpeech-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

    "Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

    "Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

    "Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~{ARCH}~{Lang}~.cab"

    "Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~{ARCH}~{Lang}~.cab"

    "Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

    "Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

    "Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

    "Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

    "Microsoft-Windows-Printing-WFS-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

    "Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

    "Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

    "Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

    "Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

    "Microsoft-Windows-InternationalFeatures-{Specific}-Package~31bf3856ad364e35~amd64~~.cab"

)

}

@{

    Path = "Install\WinRE"

    Rule = @(

        "Windows Preinstallation Environment\x64\WinPE_OC\WinPE-FontSupport-{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\lp.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-securestartup_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-atbroker_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiocore_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiodrivers_{Lang}.cab"
```

```

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-enhancedstorage_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-narrator_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-scripting_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-speech-tts_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srh_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srt_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wds-tools_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wmi_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-appxpackaging_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-storagewmi_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wifi_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-rejuv_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-opcservices_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-hta_{Lang}.cab"

)

}

@{

Path = "Boot\Boot"

Rule = @(

"Windows Preinstallation Environment\x64\WinPE_OC\WinPE-FontSupport-{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\lp.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\WinPE-Setup_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\WINPE-SETUP-CLIENT_{Lang}.CAB"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-securestartup_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-atbroker_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiocore_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiodrivers_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-enhancedstorage_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-narrator_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-scripting_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-speech-tts_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srh_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srt_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wds-tools_{Lang}.cab"

```



```

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-wmi_{Lang}.cab"

    )

}

)

$NewFonts = Match_Required_Fonts -Lang $NewLang

$SpecificPackage = Match_Other_Region_Specific_Requirements -Lang $NewLang

$NewArchC = $NewArch.Replace("AMD64", "x64")

Foreach ($item in $Expand) {

    $Language = @()

    Foreach ($itemList in $AdvLanguage) {

        if ($itemList.Path -eq $item) {

            Foreach ($PrintLang in $itemList.Rule) {

                $Language += "$($PrintLang)".Replace("{Lang}", $NewLang).Replace("{DiyLang}", $NewFonts).Replace("{Specific}",
$SpecificPackage).Replace("{ARCH}", $NewArch).Replace("{ARCHC}", $NewArchC)

            }

            Extract_Process -NewSaveTo $itemList.Path -Package $Language -Name $item

        }

    }

}

}

}

Foreach ($item in $Extract_language_Pack) { Extract_Language -Act $item.Act -NewLang $item.Tag -NewArch $item.Arch -Expand $item.Scope }

```

## C. Customize the deployment image

### II Custom deployment image Install.wim

#### 1. View Install.wim details

Image name, image description, image size, architecture, version, index number, etc.

```
$ViewFile = "D:\OS_10\Sources\Install.wim"
```

```
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex }
```

#### LOOP OPERATING AREA, START,

#### 2. Specify the path to mount Install.wim

```
New-Item -Path "D:\OS_10_Custom\Install\Install\Mount" -ItemType directory -ea SilentlyContinue
```

#### 3. Start mounting Install.wim

Default index number: 1

```
Mount-WindowsImage -ImagePath "D:\OS_10\sources\install.wim" -Index "1" -Path "D:\OS_10_Custom\Install\Install\Mount"
```

#### PROCESS FILES WITHIN THE INSTALL.WIM IMAGE, OPTIONALLY, START,

##### 3.1. Custom deployment image WinRE.wim

###### WARNING:

- WinRE.wim is a file within the Install.wim image;
- When Install.wim has multiple index numbers, only process any WinRE.wim;
- Synchronize to all index numbers to reduce the size of Install.wim, learn "[How to batch replace WinRE.wim in all index numbers in Install.wim](#)".

##### 3.1.1. View WinRE.wim details

Image name, image description, image size, architecture, version, index number, etc.

```
$ViewFile = "D:\OS_10_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"
```

```
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index  
$_.ImageIndex }
```

##### 3.1.2. Specify the path to mount WinRE.wim

```
New-Item -Path "D:\OS_10_Custom\Install\WinRE\Mount" -ItemType directory -ea SilentlyContinue
```

##### 3.1.3. Start mounting WinRE.wim

Default index number: 1

```
Mount-WindowsImage -ImagePath "D:\OS_10_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim" -  
Index "1" -Path "D:\OS_10_Custom\Install\WinRE\Mount"
```

##### 3.1.4. Language pack: WinRE

- Automatically install language packs: Get "Component: All installed packages in the image" and match them. After matching the corresponding names, install the local corresponding language pack files, View the report "[Language installation package for WinRE.wim](#)".
- When adding languages, different schema versions must be corresponded, and if not, errors are reported during the addition process.

##### 3.1.4.1. Language pack: add

- WinRE.Instl.lang.ps1
  - [\Expand\Install\WinRE\WinRE.Instl.lang.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/WinRE/WinRE.Instl.lang.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/WinRE/WinRE.Instl.lang.ps1)
- Copy the code

```
$Mount = "D:\OS_10_Custom\Install\WinRE\Mount"

$Sources = "D:\OS_10_Custom\Install\WinRE\Language\Add\zh-CN"

$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    $Initl_install_Language_Component += $_.PackageName

}

Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\WinPE-FontSupport-zh-CN.cab"

$Language = @(

    @{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }

    @{ Match = "*SecureStartup*"; File = "winpe-securestartup_zh-CN.cab"; }

    @{ Match = "*ATBroker*"; File = "winpe-atbroker_zh-CN.cab"; }

    @{ Match = "*AudioCore*"; File = "winpe-audiocore_zh-CN.cab"; }

    @{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_zh-CN.cab"; }

    @{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_zh-CN.cab"; }

    @{ Match = "*Narrator*"; File = "winpe-narrator_zh-CN.cab"; }

    @{ Match = "*scripting*"; File = "winpe-scripting_zh-CN.cab"; }

    @{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_zh-CN.cab"; }

    @{ Match = "*srh*"; File = "winpe-srh_zh-CN.cab"; }

    @{ Match = "*srt*"; File = "winpe-srt_zh-CN.cab"; }

    @{ Match = "*wds-tools*"; File = "winpe-wds-tools_zh-CN.cab"; }

    @{ Match = "*-WMI-Package*"; File = "winpe-wmi_zh-CN.cab"; }

    @{ Match = "*WinPE-AppxPackaging*"; File = "winpe-appxpackaging_zh-CN.cab"; }

    @{ Match = "*StorageWMI*"; File = "winpe-storagewmi_zh-CN.cab"; }

    @{ Match = "*WiFi*"; File = "winpe-wifi_zh-CN.cab"; }

    @{ Match = "*rejuv*"; File = "winpe-rejuv_zh-CN.cab"; }

    @{ Match = "*opcservices*"; File = "winpe-opcservices_zh-CN.cab"; }

    @{ Match = "*hta*"; File = "winpe-hta_zh-CN.cab"; }

)

ForEach ($Rule in $Language) {

    Write-host "`n  Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "*$($Rule.Match)*") {

            Write-host "    Component name: " -NoNewline; Write-host $Component -ForegroundColor Green

            Write-host "    Language pack file: " -NoNewline; Write-host "$($Sources)\$($Rule.File)" -
ForegroundColor Green
```

```

Write-Host " Installing".PadRight(22) -NoNewline

try{

    Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" | Out-Null

    Write-host "Finish" -ForegroundColor Green

} catch {

    Write-host "Failed" -ForegroundColor Red

    Write-host " $($_) " -ForegroundColor Red

}

break

}

}

}

```

#### 3.1.4.2. Offline image language: change

##### 3.1.4.2.1. Change default language, regional settings, and other international settings

Region: zh-CN

```
Dism /Image:"D:\OS_10_Custom\Install\WinRE\Mount" /Set-AllIntl:"zh-CN"
```

##### 3.1.4.2.2. View available language settings

```
Dism /Image:"D:\OS_10_Custom\Install\WinRE\Mount" /Get-Intl
```

#### 3.1.4.3. Language packs: Removed

- After you add languages, if you want to deploy to a non-English locale, you can save space by removing the English language component. When you remove a language, uninstall the language components in the reverse order in which you added them.
- After adding the Chinese, delete "English - United States" in reverse, the Region tag: en-US, you need to extract the language pack in advance
- WinRE.Del.Specified.lang.Tag.ps1
  - [\Expand\Install\WinRE\WinRE.Del.Specified.lang.Tag.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging/tutorial/OS.10/22H2/Expand/Install/WinRE/WinRE.Del.Specified.lang.Tag.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging/tutorial/OS.10/22H2/Expand/Install/WinRE/WinRE.Del.Specified.lang.Tag.ps1)

- Copy the code

```
$Lang = "en-US"
```

```
$Mount = "D:\OS_10_Custom\Install\WinRE\Mount"
```

```
$Sources = "D:\OS_10_Custom\Install\WinRE\Language\Del\en-US"
```

```
$Initl_install_Language_Component = @()
```

```
Get-WindowsPackage -Path $Mount | ForEach-Object { $Initl_install_Language_Component +=
$_.PackageName }

$Language = @(

    @{ Match = "*windowsupdate*"; File = "winpe-windowsupdate_$(Lang).cab"; }

    @{ Match = "*appxdeployment*"; File = "winpe-appxdeployment_$(Lang).cab"; }

    @{ Match = "*hta*"; File = "winpe-hta_$(Lang).cab"; }

    @{ Match = "*opcservices*"; File = "winpe-opcservices_$(Lang).cab"; }

    @{ Match = "*rejuv*"; File = "winpe-rejuv_$(Lang).cab"; }

    @{ Match = "*WiFi*"; File = "winpe-wifi_$(Lang).cab"; }

    @{ Match = "*StorageWMI*"; File = "winpe-storagewmi_$(Lang).cab"; }

    @{ Match = "*WinPE-AppxPackaging*"; File = "winpe-appxpackaging_$(Lang).cab"; }

    @{ Match = "*-WMI-Package*"; File = "winpe-wmi_$(Lang).cab"; }

    @{ Match = "*wds-tools*"; File = "winpe-wds-tools_$(Lang).cab"; }

    @{ Match = "*srt*"; File = "winpe-srt_$(Lang).cab"; }

    @{ Match = "*srh*"; File = "winpe-srh_$(Lang).cab"; }

    @{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_$(Lang).cab"; }

    @{ Match = "*scripting*"; File = "winpe-scripting_$(Lang).cab"; }

    @{ Match = "*Narrator*"; File = "winpe-narrator_$(Lang).cab"; }

    @{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_$(Lang).cab"; }

    @{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_$(Lang).cab"; }

    @{ Match = "*AudioCore*"; File = "winpe-audiocore_$(Lang).cab"; }

    @{ Match = "*ATBroker*"; File = "winpe-atbroker_$(Lang).cab"; }

    @{ Match = "*SecureStartup*"; File = "winpe-securestartup_$(Lang).cab"; }

    @{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }

)

ForEach ($Rule in $Language) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "*$($Rule.Match)*$(Lang)*") {

            Write-host "  Component name: " -NoNewline; Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline; Write-host "$($Sources)\$($Rule.File)" -
ForegroundColor Green

            Write-Host "  Deleting ".PadRight(22) -NoNewline

            try {

                Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" -ErrorAction
SilentlyContinue | Out-Null
```

```

        Write-host "Finish" -ForegroundColor Green

    } catch {

        Write-host "Failed" -ForegroundColor Red

        Write-host "  $($_) " -ForegroundColor Red

    }

    break

}

}

}

$InitlClearLanguagePackage = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    if ($_.PackageName -like "*${$Lang}*") {

        $InitlClearLanguagePackage += $_.PackageName

    }

}

if ($InitlClearLanguagePackage.count -gt 0) {

    ForEach ($item in $InitlClearLanguagePackage) {

        Write-Host "`n  $($item)" -ForegroundColor Green

        Write-Host "    Deleting ".PadRight(22) -NoNewline

        try{

            Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction SilentlyContinue |
Out-Null

            Write-host "Finish" -ForegroundColor Green

        } catch {

            Write-host "Failed" -ForegroundColor Red

            Write-host "  $($_) " -ForegroundColor Red

        }

    }

}

```

#### 3.1.4.4. Components: All packages installed in the image

##### 3.1.4.4.1. View

```
Get-WindowsPackage -Path "D:\OS_10_Custom\Install\WinRE\Mount" | Out-GridView
```

##### 3.1.4.4.2. Export to csv

```
$SaveTo = "D:\OS_10_Custom\Install\WinRE\Report.$(Get-Date -Format
"yyyyMMddHHmmss").csv"

Get-WindowsPackage -Path "D:\OS_10_Custom\Install\WinRE\Mount" | Export-CSV -
NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green
```

### 3.1.5. Cumulative updates

To prepare the cumulative updates file available, change the example file name: **KB\_WinRE.cab**

#### 3.1.5.1. Add

```
$KBPath = "D:\OS_10_Custom\Install\WinRE\Update\KB_WinRE.cab"

Add-WindowsPackage -Path "D:\OS_10_Custom\Install\WinRE\Mount" -PackagePath $KBPath
```

#### 3.1.5.2. Delete

```
$KBPath = "D:\OS_10_Custom\Install\WinRE\Update\KB_WinRE.cab"

Remove-WindowsPackage -Path "D:\OS_10_Custom\Install\WinRE\Mount" -PackagePath $KBPath
```

#### 3.1.5.3. Solid update

It cannot be uninstalled after curing, which cleans the recovery image and resets the basis of any superseded components.

```
Dism /image:"D:\OS_10_Custom\Install\WinRE\Mount" /cleanup-image /StartComponentCleanup
/ResetBase
```

##### 3.1.5.3.1. Clean components after curing and updating

```
$Mount = "D:\OS_10_Custom\Install\WinRE\Mount"

Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {

    if ($_.PackageState -eq "Superseded"){

        Write-Host "  $($_.PackageName)" -ForegroundColor Green

        Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null

    }

}
```

### 3.1.6. Drive

### 3.1.7. Save image

```
Save-WindowsImage -Path "D:\OS_10_Custom\Install\WinRE\Mount"
```

### 3.1.8. Unmount image

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowsImage -Path "D:\OS_10_Custom\Install\WinRE\Mount" -Discard
```

#### 3.1.9. After rebuilding WinRE.wim, the file size can be reduced

- WinRE.Rebuild.ps1
  - [\Install\WinRE\WinRE.Rebuild.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/WinRE/WinRE.Rebuild.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/WinRE/WinRE.Rebuild.ps1)

- Copy the code

```
$FileName = "D:\OS_10_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"

Get-WindowsImage -ImagePath $Filename -ErrorAction SilentlyContinue | ForEach-Object {

    Write-Host "  Image name: " -NoNewline

    Write-Host $_.ImageName -ForegroundColor Yellow

    Write-Host "  The index number: " -NoNewline

    Write-Host $_.ImageIndex -ForegroundColor Yellow

    Write-Host "`n  Rebuild".PadRight(28) -NoNewline

    Export-WindowsImage -SourceImagePath $Filename -SourceIndex $_.ImageIndex -DestinationImagePath
"$($FileName).New" -CompressionType max

    Write-Host "Finish`n" -ForegroundColor Green

}

if (Test-Path "$($FileName).New" -PathType Leaf) {

    Remove-Item -Path $Filename

    Move-Item -Path "$($FileName).New" -Destination $Filename

    Write-Host "Finish" -ForegroundColor Green

} else {

    Write-host "Failed" -ForegroundColor Red

}
```

#### 3.1.10. Backup WinRE.wim

- WinRE.Backup.ps1
  - [\Expand\Install\WinRE\WinRE.Backup.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/WinRE/WinRE.Backup.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/WinRE/WinRE.Backup.ps1)

- Copy the code



```
$WimLibPath = "D:\OS_10_Custom\Install\Install\Update\Winlib"
```

```
$FileName = "D:\OS_10_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"
```

```
New-Item -Path $WimLibPath -ItemType Directory -ea SilentlyContinue
```

```
Copy-Item -Path $FileName -Destination $WimLibPath -Force
```

#### 3.1.11. Replace WinRE.wim within the Install.wim image

- After each mount Install.wim "[Replace WinRE.wim](#)";
- Learn "[Get all index numbers of Install.wim and replace the old WinRE.wim](#)".

[Process the files in the Install.wim image and end.](#)

### 4. Language pack

- Automatically install language packs: Get "Component: All installed packages in the image" and match them. After matching the corresponding names, install the local corresponding language pack files, View the report "[Language installation package for Install.wim](#)".
- When adding languages, different schema versions must be corresponded, and if not, errors are reported during the addition process.

#### 4.1. Language pack: add

- Install.Instl.lang.ps1
  - [\Expand\Install\Install.Instl.lang.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging/tutorial/OS.10/22H2/Expand/Install/Install.Instl.lang.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging/tutorial/OS.10/22H2/Expand/Install/Install.Instl.lang.ps1)

- Copy the code

```
Function Language_Install
```

```
{
```

```
param($Mount, $Sources, $Lang)
```

```
$InitL_install_Language_Component = @()
```

```
if (Test-Path $Mount -PathType Container) {
```

```
Get-WindowsPackage -Path $Mount | ForEach-Object { $InitL_install_Language_Component += $_.PackageName }
```

```
} else {
```

```
Write-Host "Not mounted: $($Mount)"
```

```
return
```

```
}
```

```
$Script:Init_Folder_All_File = @()
```

```
if (Test-Path "$($Sources)\$($Lang)" -PathType Container) {
```

```

Get-ChildItem -Path $Sources -Recurse -Include "*.cab" -ErrorAction SilentlyContinue | ForEach-Object {

    $Script:Init_Folder_All_File += $_.FullName

}

Write-host "`n  Available language pack installation files"

if ($Script:Init_Folder_All_File.Count -gt 0){

    ForEach ($item in $Script:Init_Folder_All_File) {

        Write-host "  $($item)"

    }

} else {

    Write-host "There are no language pack files locally"

    return

}

} else {

    Write-Host "Path does not exist: $($Sources)\$($Lang)"

    return

}

$Script:Init_Folder_All_File_Match_Done = @()

$Script:Init_Folder_All_File_Exclude = @()

$Script:Search_File_Order = @(

    @{

        Name = "Fonts"

        Description = "Fonts"

        Rule = @(

            @{ Match_Name = "*Fonts*"; IsMatch = "No"; Capability = ""; }

        )

    }

    @{

        Name = "Basic"

        Description = "Basic"

        Rule = @(

            @{ Match_Name = "*LanguageFeatures-Basic*"; IsMatch = "Yes"; Capability = "Language.Basic~~~$($Lang)~0.0.1.0"; }

            @{ Match_Name = "*Client*Language*Pack*"; IsMatch = "Yes"; Capability = "Language.Basic~~~$($Lang)~0.0.1.0"; }

        )

    }

)

```

```

@{

    Name = "OCR"

    Description = "Optical character recognition"

    Rule = @(

        @{ Match_Name = "*LanguageFeatures-OCR*"; IsMatch = "Yes"; Capability = "Language.OCR~~~${$Lang}~0.0.1.0"; }

    )

}

@{

    Name = "Handwriting"

    Description = "Handwriting recognition"

    Rule = @(

        @{ Match_Name = "*LanguageFeatures-Handwriting*"; IsMatch = "Yes"; Capability =
"Language.Handwriting~~~${$Lang}~0.0.1.0"; }

    )

}

@{

    Name = "TextToSpeech"

    Description = "Text-to-speech"

    Rule = @(

        @{ Match_Name = "*LanguageFeatures-TextToSpeech*"; IsMatch = "Yes"; Capability =
"Language.TextToSpeech~~~${$Lang}~0.0.1.0"; }

    )

}

@{

    Name = "Speech"

    Description = "Speech recognition"

    Rule = @(

        @{ Match_Name = "*LanguageFeatures-Speech*"; IsMatch = "Yes"; Capability = "Language.Speech~~~${$Lang}~0.0.1.0"; }

    )

}

@{

    Name = "RegionSpecific"

    Description = "Other region-specific requirements"

    Rule = @(

        @{ Match_Name = "*InternationalFeatures*"; IsMatch = "No"; Capability = ""; }

    )

}

```

```

    )

}

@{

    Name = "Retail"

    Description = "Retail demo experience"

    Rule = @(

        @{ Match_Name = "*RetailDemo*"; IsMatch = "Yes"; Capability = ""; }

    )

}

@{

    Name = "Features_On_Demand"

    Description = "Features on demand"

    Rule = @(

        @{ Match_Name = "*InternetExplorer*"; IsMatch = "Yes"; Capability = ""; }

        @{ Match_Name = "*MSPaint*amd64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.MSPaint~~~~0.0.1.0"; }

        @{ Match_Name = "*MSPaint*wow64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.MSPaint~~~~0.0.1.0"; }

        @{ Match_Name = "*Notepad*amd64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.Notepad~~~~0.0.1.0"; }

        @{ Match_Name = "*Notepad*wow64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.Notepad~~~~0.0.1.0"; }

        @{ Match_Name = "*MediaPlayer*amd64*"; IsMatch = "Yes"; Capability = "Media.WindowsMediaPlayer~~~~0.0.12.0"; }

        @{ Match_Name = "*MediaPlayer*wow64*"; IsMatch = "Yes"; Capability = "Media.WindowsMediaPlayer~~~~0.0.12.0"; }

        @{ Match_Name = "*PowerShell-ISE-FOD-Package*amd64*"; IsMatch = "Yes"; Capability =
"Microsoft.Windows.PowerShell.ISE~~~~0.0.1.0"; }

        @{ Match_Name = "*PowerShell-ISE-FOD-Package*wow64*"; IsMatch = "Yes"; Capability =
"Microsoft.Windows.PowerShell.ISE~~~~0.0.1.0"; }

        @{ Match_Name = "*Printing*PMCPPC*amd64*"; IsMatch = "Yes"; Capability = "Print.Management.Console~~~~0.0.1.0"; }

        @{ Match_Name = "*Printing*WFS*amd64*"; IsMatch = "Yes"; Capability = "Print.Management.Console~~~~0.0.1.0"; }

        @{ Match_Name = "*StepsRecorder*amd64*"; IsMatch = "Yes"; Capability = "App.StepsRecorder~~~~0.0.1.0"; }

        @{ Match_Name = "*StepsRecorder*wow64*"; IsMatch = "Yes"; Capability = "App.StepsRecorder~~~~0.0.1.0"; }

        @{ Match_Name = "*WordPad*amd64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.WordPad~~~~0.0.1.0"; }

        @{ Match_Name = "*WordPad*wow64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.WordPad~~~~0.0.1.0"; }

        @{ Match_Name = "*WMIC*FoD*Package*amd64*"; IsMatch = "Yes"; Capability = "WMIC~~~~"; }

        @{ Match_Name = "*WMIC*FoD*Package*wow64*"; IsMatch = "Yes"; Capability = "WMIC~~~~"; }

    )

}

)

```

```

ForEach ($item in $Script:Search_File_Order) { New-Variable -Name "Init_File_Type_$( $item.Name )" -Value @() -Force }

ForEach ($Wildcard in $Script:Init_Folder_All_File) {

    ForEach ($item in $Script:Search_File_Order) {

        ForEach ($NewRule in $item.Rule) {

            if ($Wildcard -like "*$( $NewRule.Match_Name )*") {

                Write-host "`n  Fuzzy matching: " -NoNewline; Write-host $NewRule.Match_Name -ForegroundColor Green

                Write-host "  Language pack file: " -NoNewline; Write-host $Wildcard -ForegroundColor Green

                $OSDefaultUser = (Get-Variable -Name "Init_File_Type_$( $item.Name )" -ErrorAction SilentlyContinue).Value

                $TempSave = @{ Match_Name = $NewRule.Match_Name; Capability = $NewRule.Capability; FileName = $Wildcard }

                $new = $OSDefaultUser + $TempSave

                if ($NewRule.IsMatch -eq "Yes") {

                    ForEach ($Component in $InitL_install_Language_Component) {

                        if ($Component -like "*$( $NewRule.Match_Name )*") {

                            Write-host "  Component name: " -NoNewline; Write-host $Component -ForegroundColor Green

                            New-Variable -Name "Init_File_Type_$( $item.Name )" -Value $new -Force

                            $Script:Init_Folder_All_File_Match_Done += $Wildcard

                            break

                        }

                    }

                } else {

                    Write-host "  Do not match, install directly" -ForegroundColor Yellow

                    New-Variable -Name "Init_File_Type_$( $item.Name )" -Value $new -Force

                    $Script:Init_Folder_All_File_Match_Done += $Wildcard

                }

            }

        }

    }

}

Write-host "`n  Grouping is complete, pending installation" -ForegroundColor Yellow

Write-host "  $('.' * 80)"

ForEach ($Wildcard in $Script:Search_File_Order) {

    $OSDefaultUser = (Get-Variable -Name "Init_File_Type_$( $Wildcard.Name )" -ErrorAction SilentlyContinue).Value

```

```

Write-host "`n $($Wildcard.Description) ( $($OSDefaultUser.Count) item )"

if ($OSDefaultUser.Count -gt 0) {

    ForEach ($item in $OSDefaultUser) {

        Write-host " $($item.FileName)" -ForegroundColor Green

    }

} else {

    Write-host " Not available" -ForegroundColor Red

}

}

Write-host "`n Not matched, no longer installed" -ForegroundColor Yellow

Write-host " $('-' * 80)"

ForEach ($item in $Script:Init_Folder_All_File) {

    if ($Script:Init_Folder_All_File_Match_Done -notcontains $item) {

        $Script:Init_Folder_All_File_Exclude += $item

        Write-host " $($item)" -ForegroundColor Red

    }

}

Write-host "`n Install" -ForegroundColor Yellow

Write-host " $('-' * 80)"

ForEach ($Wildcard in $Script:Search_File_Order) {

    $OSDefaultUser = (Get-Variable -Name "Init_File_Type_{$Wildcard.Name}" -ErrorAction SilentlyContinue).Value

    Write-host "`n $($Wildcard.Description) ( $($OSDefaultUser.Count) item )"; Write-host " $('-' * 80)"

    if ($OSDefaultUser.Count -gt 0) {

        ForEach ($item in $OSDefaultUser) {

            Write-host " Language pack file: " -NoNewline; Write-host $item.FileName -ForegroundColor Green

            Write-Host " Installing ".PadRight(22) -NoNewline

            if (Test-Path $item.FileName -PathType Leaf) {

                try {

                    Add-WindowsPackage -Path $Mount -PackagePath $item.FileName | Out-Null

                    Write-host "Finish`n" -ForegroundColor Green

                } catch {

                    Write-host "Failed" -ForegroundColor Red

                    Write-host " ${_}" -ForegroundColor Red

                }

            }

        }

    }

}

```

```

    } else {

        Write-host "Does not exist`n"

    }

}

} else {

    Write-host "  Not available`n" -ForegroundColor Red

}

}

}

}

Language_Install -Mount "D:\OS_10_Custom\Install\Install\Mount" -Sources "D:\OS_10_Custom\Install\Install\Language\Add" -
Lang "zh-CN"

```

#### 4.2. Offline image language: change

- Starting Windows 11, the [default System UI Language](#) set by DISM is left unaltered on all editions except for Home edition. For [all commercial editions](#) the language chosen during the Out-of-Box Experience (OOBE) is set as the [System Preferred UI language](#) and Windows will be displayed in this language and for Home edition the language chosen at OOBE will continue to be the default System UI Language.
- As of Windows 10, version 2004, if an .appx-based Language Experience Pack (LXP) backed language is passed as an argument then the language will be set as the System Preferred UI language and its parent language will be set as the Default System UI language. In prior versions only .cab based language packs were supported.

##### 4.2.1. Change default language, regional settings, and other international settings

Region: [zh-CN](#)

```
Dism /Image:"D:\OS_10_Custom\Install\Install\Mount" /Set-AllIntl:zh-CN
```

##### 4.2.2. View available language settings

```
Dism /Image:"D:\OS_10_Custom\Install\Install\Mount" /Get-Intl
```

#### 4.3. Language packs: Removed

- After you add languages, if you want to deploy to a non-English locale, you can save space by removing the English language component. When you remove a language, uninstall the language components in the reverse order in which you added them.
- After adding the Chinese, delete "[English - United States](#)" in reverse, the Region tag: [en-US](#), you need to extract the language pack in advance
- Install.Del.Specified.lang.Tag.ps1
  - [\Expand\Install\Install.Del.Specified.lang.Tag.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging/tutorial/OS.10/22H2/Expand/Install/Install.Del.Specified.lang.Tag.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging/tutorial/OS.10/22H2/Expand/Install/Install.Del.Specified.lang.Tag.ps1)
- Copy the code

```

$Lang = "en-US"

$Mount = "D:\OS_10_Custom\Install\Install\Mount"

$Sources = "D:\OS_10_Custom\Install\Install\Language\Del\en-US"

$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    $Initl_install_Language_Component += $_.PackageName

}

$Language = @(

    @{ Match = "*WordPad*wow64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~wow64~$(($Lang)~.cab"; }

    @{ Match = "*WordPad*amd64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~amd64~$(($Lang)~.cab"; }

    @{ Match = "*WMIC*FoD*Package*wow64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~wow64~$(($Lang)~.cab"; }

    @{ Match = "*WMIC*FoD*Package*amd64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~AMD64~$(($Lang)~.cab"; }

    @{ Match = "*StepsRecorder*wow64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~wow64~$(($Lang)~.cab"; }

    @{ Match = "*StepsRecorder*amd64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~amd64~$(($Lang)~.cab"; }

    @{ Match = "*Printing*PMCPPC*amd64*"; File = "Microsoft-Windows-Printing-PMCPPC-FoD-
Package~31bf3856ad364e35~AMD64~$(($Lang)~.cab"; }

    @{ Match = "*PowerShell*wow64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~wow64~$(($Lang)~.cab"; }

    @{ Match = "*PowerShell*amd64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~amd64~$(($Lang)~.cab"; }

    @{ Match = "*MediaPlayer*wow64*"; File = "Microsoft-Windows-MediaPlayer-Package-wow64-$(($Lang).cab"; }

    @{ Match = "*MediaPlayer*amd64*"; File = "Microsoft-Windows-MediaPlayer-Package-AMD64-$(($Lang).cab"; }

    @{ Match = "*Notepad*wow64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~wow64~$(($Lang)~.cab"; }

    @{ Match = "*Notepad*amd64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~AMD64~$(($Lang)~.cab"; }

    @{ Match = "*InternetExplorer*"; File = "Microsoft-Windows-InternetExplorer-Optional-
Package~31bf3856ad364e35~AMD64~$(($Lang)~.cab"; }

    @{ Match = "*TextToSpeech*"; File = "Microsoft-Windows-LanguageFeatures-TextToSpeech-$(($Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "*LanguageFeatures-Speech*"; File = "Microsoft-Windows-LanguageFeatures-Speech-$(($Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "*OCR*"; File = "Microsoft-Windows-LanguageFeatures-OCR-$(($Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

```



```

        @{ Match = "*Handwriting*"; File = "Microsoft-Windows-LanguageFeatures-Handwriting-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*LanguageFeatures-Basic*"; File = "Microsoft-Windows-LanguageFeatures-Basic-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*Client-LanguagePack-Package*"; File = "Microsoft-Windows-Client-Language-Pack_x64_$(Lang).cab"; }

    )

    ForEach ($Rule in $Language) {

        Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host " $('-' * 80)"

        ForEach ($Component in $Initl_install_Language_Component) {

            if ($Component -like "*$(Rule.Match)*$(Lang)*") {

                Write-host " Component name: " -NoNewline

                Write-host $Component -ForegroundColor Green

                Write-host " Language pack file: " -NoNewline

                Write-host "$($Sources)\$(Rule.File)" -ForegroundColor Green

                Write-Host " Deleting ".PadRight(22) -NoNewline

                try {

                    Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$(Rule.File)" -ErrorAction SilentlyContinue | Out-Null

                    Write-host "Finish" -ForegroundColor Green

                } catch {

                    Write-host "Failed" -ForegroundColor Red

                    Write-host " $($_) " -ForegroundColor Red

                }

                break

            }

        }

    }

    $InitlClearLanguagePackage = @()

    Get-WindowsPackage -Path $Mount | ForEach-Object {

        if ($_.PackageName -like "*$(Lang)*") {

            $InitlClearLanguagePackage += $_.PackageName

        }

    }

    if ($InitlClearLanguagePackage.count -gt 0) {

        ForEach ($item in $InitlClearLanguagePackage) {

            Write-Host "`n $($item)" -ForegroundColor Green

```

```
Write-Host " Deleting ".PadRight(22) -NoNewline

try{

    Remove-AppxProvisionedPackage -Path $Mount -PackageName $Item -ErrorAction SilentlyContinue | Out-Null

    Write-host "Finish" -ForegroundColor Green

} catch {

    Write-host "Failed" -ForegroundColor Red

    Write-host " $($_) " -ForegroundColor Red

}

}

}
```

4.4. Components: All packages installed in the image

4.4.1. View

```
Get-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" | Out-GridView
```

4.4.2. Export to csv

```
$SaveTo = "D:\OS_10_Custom\Install\Install\Report.$(Get-Date -Format "yyyyMMddHHmmss").csv"

Get-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" | Export-CSV -NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green
```

5. InBox Apps

5.1. Learn

5.1.1. DISM App Package (.appx or .appxbundle) Servicing Command-Line Options

5.2. InBox Apps: Pre-install the application

- Group abbreviations
  - Group A: Core, CoreSingleLanguage, Education, Professional, ProfessionalEducation, ProfessionalWorkstation, Enterprise, IoTEnterprise, ServerRdsh
  - Group B: EnterpriseN, EnterpriseGN, EnterpriseSN, ProfessionalN, CoreN, EducationN, ProfessionalWorkstationN, ProfessionalEducationN, CloudN, CloudEN, CloudEditionN, CloudEditionLN, StarterN

	Name	Products ID	Grouping
1.	Microsoft.HEIFImageExtension	9PMMSR1CGPWG	A
2.	Microsoft.MixedReality.Portal	9NG1H8B3ZC7M	A
3.	Microsoft.SkypeApp	9WZDNCRFJ364	A

4.	Microsoft.VP9VideoExtensions	9N4D0MSMP0PT	A
5.	Microsoft.WebMediaExtensions	9N5TDP8VCMHS	A
6.	Microsoft.WebpImageExtension	9PG2DK419DRG	A
7.	Microsoft.WindowsSoundRecorder	9WZDNCRFWKN	A
8.	Microsoft.Xbox.TCUI	9NKNC0LD5NN6	A
9.	Microsoft.XboxGamingOverlay	9NZKPSTSNW4P	A
10.	Microsoft.ZuneMusic	9WZDNCRFJ3PT	A
11.	Microsoft.ZuneVideo	9WZDNCRFJ3P2	A
12.	Microsoft.UI.Xaml.2.0		A, B
13.	Microsoft.UI.Xaml.2.1		A, B
14.	Microsoft.UI.Xaml.2.3		A, B
15.	Microsoft.Advertising.Xaml		A, B
16.	Microsoft.NET.Native.Framework.1.7		A, B
17.	Microsoft.NET.Native.Framework.2.2		A, B
18.	Microsoft.NET.Native.Runtime.1.7		A, B
19.	Microsoft.NET.Native.Runtime.2.2		A, B
20.	Microsoft.VCLibs.140.00		A, B
21.	Microsoft.VCLibs.140.00.UWPDesktop		A, B
22.	Services.Store.Engagement		A, B
23.	Microsoft.Cortana	9NFFX4SZZ23L	A, B
24.	Microsoft.BingWeather	9WZDNCRFJ3Q2	A, B
25.	Microsoft.DesktopAppInstaller	9NBLGGH4NNS1	A, B
26.	Microsoft.GetHelp	9PKDZBMV1H3T	A, B
27.	Microsoft.Getstarted	9WZDNCRDTBJJ	A, B
28.	Microsoft.Microsoft3DViewer	9NBLGGH42THS	A, B
29.	Microsoft.MicrosoftOfficeHub	9WZDNCRD29V9	A, B
30.	Microsoft.MicrosoftSolitaireCollection	9WZDNCRFHWD2	A, B
31.	Microsoft.MicrosoftStickyNotes	9NBLGGH4QGHW	A, B
32.	Microsoft.MSPaint	9NBLGGH4QGHW	A, B

33.	Microsoft.Office.OneNote	XPFFZHVQGWWLHB	A, B
34.	Microsoft.People	9NBLGGH10PG8	A, B
35.	Microsoft.ScreenSketch	9MZ95KL8MR0L	A, B
36.	Microsoft.Wallet		A, B
37.	Microsoft.StorePurchaseApp	9NBLGGH4LS1F	A, B
38.	Microsoft.Windows.Photos	9WZDNCRFJBH4	A, B
39.	Microsoft.WindowsAlarms	9WZDNCRFJ3PR	A, B
40.	Microsoft.WindowsCalculator	9WZDNCRFHVN5	A, B
41.	Microsoft.WindowsCamera	9WZDNCRFJBBG	A, B
42.	Microsoft.Windows.CommunicationsApps	9WZDNCRFHVQM	A, B
43.	Microsoft.WindowsFeedbackHub	9NBLGGH4R32N	A, B
44.	Microsoft.WindowsMaps	9WZDNCRDTBVB	A, B
45.	Microsoft.WindowsStore	9WZDNCRFJBMP	A, B
46.	Microsoft.XboxApp	9MV0B5HZVK9Z	A, B
47.	Microsoft.XboxGameOverlay	9NBLGGH537C2	A, B
48.	Microsoft.XboxIdentityProvider	9WZDNCRD1HKW	A, B
49.	Microsoft.XboxSpeechToTextOverlay	9P086NHDB9W	A, B
50.	Microsoft.YourPhone	9NMPJ99VJBWV	A, B

5.3. InBox Apps: Installed

5.3.1. View

```
Get-AppXProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" | Out-GridView
```

5.3.2. Export to Csv

```
$SaveTo = "D:\OS_10_Custom\Install\Install\Report.${(Get-Date -Format "yyyyMMddHHmmss")}.csv"
```

```
Get-AppXProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" | Export-CSV -NoType -Path $SaveTo
```

```
Write-host $SaveTo -ForegroundColor Green
```

5.4. Remove all installed pre-applications

- Install.InBox.Appx.Clear.all.ps1
  - \Expand\Install\Install.InBox.Appx.Clear.all.ps1
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging/tutorial/OS.10/22H2/Expand/Install/Install.InBox.Appx](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging/tutorial/OS.10/22H2/Expand/Install/Install.InBox.Appx)

[.Clear.all.ps1](#)

- Copy the code

```
Get-AppXProvisionedPackage -path "D:\OS_10_Custom\Install\Install\Mount" -ErrorAction SilentlyContinue | ForEach-Object {  
  
    Write-host "`n $($_.DisplayName)"; Write-Host "  Deleting ".PadRight(22) -NoNewline  
  
    try {  
  
        Remove-AppxProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackageName $_.PackageName -  
ErrorAction SilentlyContinue | Out-Null  
  
        Write-host "Finish" -ForegroundColor Green  
  
    } catch {  
  
        Write-host "Failed" -ForegroundColor Red  
  
    }  
  
}
```

#### 5.5. Region tag: Understanding

Before understanding zone tags, first understand the list of languages available in the ZuneMusic app: [en-us](#), en-gb, as-in, az-latn-az, bs-latn-ba, bn-in, cs-cz, cy-gb, ar-sa, de-de, af-za, am-et, da-dk, el-gr, es-es, es-mx, ca-es, ca-es-valencia, eu-es, fi-fi, bg-bg, ga-ie, et-ee, gl-es, gu-in, gd-gb, fil-ph, fr-ca, fr-fr, hy-am, fa-ir, hu-hu, id-id, it-it, ja-jp, hr-hr, ka-ge, is-is, he-il, hi-in, kk-kz, lo-la, km-kh, lt-lt, kn-in, kok-in, ko-kr, mk-mk, lv-lv, ms-my, mi-nz, mr-in, mt-mt, ne-np, nl-nl, nb-no, ml-in, nn-no, lb-lu, or-in, ro-ro, sk-sk, ru-ru, pl-pl, quz-pe, pt-br, pt-pt, sq-al, ta-in, th-th, sv-se, pa-in, sr-cyrl-ba, sr-cyrl-rs, sr-latn-rs, ur-pk, ug-cn, tr-tr, uk-ua, tt-ru, [zh-cn](#), vi-vn, uz-latn-uz, sl-si, zh-tw, te-in

View installed languages for offline images

```
Dism /Image:"D:\OS_10_Custom\Install\Install\Mount" /Get-Intl
```

View results for installed languages: [en-US](#), [zh-CN](#), When installing the ZuneMusic app, the installer will match "Installed Languages" and automatically filter the list of uninstalled languages, This is the area tag.

#### 5.6. Region tag: adding method

##### 5.6.1. Execute "Language Pack: Add"

##### 5.6.2. Install “Local Language Experience Packages (LXPs)”

Microsoft officially provides the Local Language Experience Package (LXPS) installation file for Windows 10. It will no longer be provided for Windows 11. Want to get:

##### 5.6.2.1. Download using the Windows Local Language Experience Packs (LXPs) Downloader

learn: <https://github.com/ilikeyi/LXPs>

After downloading, save to: [D:\OS\\_10\\_Custom\Install\Install\InBox.Appx](#)

File format: [LanguageExperiencePack.zh-CN.Neutral.Appx](#)

5.6.2.2. Manual download

5.6.2.2.1. Region

Region	Products ID	Region	Products ID
en-US	C9PDSCC711RVF	af-za	9PDW16B5HMXR
am-et	9NGL4R61W3PL	ar-sa	9N4S78P86PKX
as-in	9NTJLXMX35J	az-latn-az	9P5TFKZH5K8
be-by	9MXPBGNNNDW3L	bg-bg	9MX54588434F
bn-bd	9PH7TKVXGGM8	bn-in	9P1M44L7W84T
bs-latn-ba	9MVFKLJ10MFL	ca-es	9P6JMKJQZ9S7
ca-es-valencia	9P9K3WMFSW90	chr-cher-us	9MX15485N3RK
cs-cz	9P3WXZ1KTM7C	cy-gb	9NKJ9TBM4HB
da-dk	9NDMT2VKS1L	de-de	9P6CT0SLW589
el-gr	9N586B13PBLD	en-gb	9NT52VQ39BVN
es-es	9NWVGWLHPB1Z	es-mx	9N8MCM1X3928
et-ee	9NFBHFMCR30L	eu-es	9NMCHQHZ37HZ
fa-ir	9NGS7DD4QS21	fi-fi	9MW3PQ7SD3QK
fil-ph	9NWM2KGTSSS	fr-ca	9MTP2VP0VL92
fr-fr	9NHMG4BJKMDG	ga-ie	9P0L5Q848KXT
gd-gb	9P1DBPF36BF3	gl-es	9NXXRNBXN9B
gu-in	9P2HMSWDJDQ1	ha-latn-ng	9N1L95DBGRG3
he-il	9NB6ZFND5HCQ	hi-in	9NZC3GRX8LD3
hr-hr	9NW01VND4LTW	hu-hu	9MWN3C58HL87
hy-am	9NKM28TM6P67	id-id	9P4X3N4SDK8P
ig-ng	9PG4ZFJ48JSX	is-is	9NTHJR7TQXX1
it-it	9P8PQWNS6VJX	ja-jp	9N1W692FV4S1
ka-ge	9P60JZL05WGH	kk-kz	9PHV179R97LV
km-kh	9PGKTS4JS531	kn-in	9NC6DB7N95F9
kok-in	9MV3P55CMZ6P	ko-kr	9N4TXPCVRNGF
ku-arab-iq	9P1C18QL3D7H	ky-kg	9P7D3JJGZM48
lb-lu	9N0ST1WBZ9D9	lo-la	9N8X352G5NZV
lt-lt	9NWW891H6HN	lv-lv	9N5CQDPH6SQT
mi-nz	9P2GDFB3JPSX	mk-mk	9P1X6XB1K3RN
ml-in	9NWDTV8FFV7L	mn-mn	9PG1DHC4VTZW
mr-in	9MWXCKHJVR1J	ms-my	9NPXL8ZSDDQ7

mt-mt	9PDG96SQ6BN8	nb-no	9N6J0M5DHCK0
ne-np	9P7CHPLWDQVN	nl-nl	9PF1C9NB5PRV
nn-no	9PK7KM3Z06KH	nso-za	9NS49QLX5CDV
or-in	9NTHCXCXSJDH	pa-arab-pk	9NJRL03WH6FM
pa-in	9NSNC0ZJX69B	pl-pl	9NC5HW94R0LD
prs-af	9P3NGC6X5ZQC	pt-br	9P8LBDM4FW35
pt-pt	9P7X8QJ7FL0X	quc-latn-gt	9P2V6MNNQZ0B
quz-pe	9NHTX8NVQ04K	ro-ro	9MWXGPJ5PJ3H
ru-ru	9NMJCX77QKPX	rw-rw	9NFW0M20H9WG
sd-arab-pk	9NB9JSCXW9X5	si-lk	9NVF9QSLGTL0
sk-sk	9N7LSNN099WB	sl-si	9NV27L34J4ST
sq-al	9MWLRGNMDGK7	sr-cyrl-ba	9MXGN7V65C7B
sr-cyrl-rs	9PPD6CCK9K5H	sr-latn-rs	9NBZ0SJDPPVT
sv-se	9P0HSNX08177	sw-ke	9NFF2M19DQ55
ta-in	9PDZB1WT1B34	te-in	9PMQJJGF63FW
tg-cyrl-tj	9MZHLBPPT2HC	th-th	9MSTWFRL0LR4
ti-et	9NC8C9RDNK2S	tk-tm	9NKHQ4GL6VLT
tn-za	9NFSXM123DHT	tr-tr	9NL1D3T5HG9R
tt-ru	9NV90Q1X1ZR2	ug-cn	9P52C5D7VL5S
uk-ua	9PPPMZRSGHR8	ur-pk	9NDWFTFW12BQ
uz-latn-uz	9P5P2T5P5L9S	vi-vn	9P0W68X0XZPT
wo-sn	9NH3SW1CR90F	xh-za	9NW3QWSLQD17
yo-ng	9NGM3VPPZS5V	zh-cn	9NRMNT6GMZ7
zh-tw	9PCJ4DHCQ1JQ	zu-za	9NNRM7KT5NB0

Download Region: zh-CN, application ID: 9NRMNT6GMZ70, Store link:  
<https://www.microsoft.com/store/productId/9NRMNT6GMZ70>

5.6.2.2.2. Open the website: <https://store.rg-adguard.net>

5.6.2.2.2.1. Search keywords:  
  
<https://www.microsoft.com/store/productId/9NRMNT6GMZ70>

5.6.2.2.2.2. Search 22621 content in the web page, search results:  
[Microsoft.LanguageExperiencePackzh-CN\\_22621.\\*](#).  
[neutral\\_\\_8wekyb3d8bbwe.appx](#)

5.6.2.2.3. After downloading, save it to the

D:\OS\_10\_Custom\Install\Install\InBox.Appx directory and rename it:  
LanguageExperiencePack.zh-cn.Neutral.Appx

5.6.2.3. Execute the installation command to install the local language experience package (LXPs)

After understanding how to add zone tags, obtain LanguageExperiencePack.zh-cn.Neutral, execute the installation command:

```
Add-AppxProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath  
"D:\OS_10_Custom\Install\Install\InBox.appx\LanguageExperiencePack.zh-cn.Neutral.appx" -SkipLicense
```

5.6.2.4. InBox Apps: An installed application package

5.6.2.4.1. View

```
Get-AppXProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" | Out-  
GridView
```

5.6.2.4.2. Export to Csv

```
$SaveTo = "D:\OS_10_Custom\Install\Install\Report.$(Get-Date -Format  
"yyyyMMddHHmmss").csv"
```

```
Get-AppXProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" | Export-  
CSV -NoType -Path $SaveTo
```

```
Write-host $SaveTo -ForegroundColor Green
```

5.7. InBox Apps: Install

5.7.1. Mount or decompress the InBox Apps installation file

Mount 19041.3031.230508-1728.vb\_release\_svc\_prod3\_amd64fre\_InboxApps.iso or extract to any location;

5.7.2. After executing the installation command, install InBox Apps to: Install.wim

- Auto = Automatically search all local disks, default;
- Custom path, e.g. specify F drive: \$ISO = "F:\packages"
- Install.Inst.InBox.Appx.ps1
  - \Expand\Install\Install.Inst.InBox.Appx.ps1
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/Install.Inst.InBox.Appx.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/Install.Inst.InBox.Appx.ps1)

- Copy the code

```
$ISO = "Auto"
```

```
$Mount = "D:\OS_10_Custom\Install\Install\Mount"
```

```
try{
```



```

Write-host "`n Offline image version: " -NoNewline

$Current_Edition_Version = (Get-WindowsEdition -Path $Mount).Edition

Write-Host $Current_Edition_Version -ForegroundColor Green

} catch {

Write-Host "Error" -ForegroundColor Red

Write-Host " $($_) " -ForegroundColor Yellow

return

}

$Pre_Config_Rules = @(

@{

Name = @( "Core"; "CoreN"; "CoreSingleLanguage"; )

Apps = @(

"Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.HEIFImageExtension"; "Microsoft.HEVCVideoExtension";
"Microsoft.SecHealthUI"; "Microsoft.VP9VideoExtensions"; "Microsoft.WebpImageExtension";
"Microsoft.WindowsStore"; "Microsoft.GamingApp"; "Microsoft.Sticky.Notes"; "Microsoft.Paint";
"Microsoft.PowerAutomateDesktop"; "Microsoft.ScreenSketch"; "Microsoft.WindowsNotepad";
"Microsoft.WindowsTerminal"; "Clipchamp.Clipchamp"; "Microsoft.Solitaire.Collection"; "Microsoft.WindowsAlarms";
"Microsoft.WindowsFeedbackHub"; "Microsoft.WindowsMaps"; "Microsoft.ZuneMusic"; "Microsoft.BingNews";
"Microsoft.DesktopAppInstaller"; "Microsoft.WindowsCamera"; "Microsoft.Getstarted"; "Microsoft.Cortana";
"Microsoft.BingWeather"; "Microsoft.GetHelp"; "Microsoft.MicrosoftOfficeHub"; "Microsoft.People";
"Microsoft.StorePurchaseApp"; "Microsoft.Todos"; "Microsoft.WebMediaExtensions"; "Microsoft.Windows.Photos";
"Microsoft.WindowsCalculator"; "Microsoft.Windows.CommunicationsApps"; "Microsoft.WindowsSoundRecorder";
"Microsoft.Xbox.TCUI"; "Microsoft.XboxGameOverlay"; "Microsoft.XboxGamingOverlay";
"Microsoft.XboxIdentityProvider"; "Microsoft.XboxSpeechToTextOverlay"; "Microsoft.YourPhone";
"Microsoft.ZuneVideo"; "MicrosoftCorporationII.QuickAssist"; "MicrosoftWindows.Client.WebExperience";
"Microsoft.RawImageExtension"; "MicrosoftCorporationII.MicrosoftFamily";

)

}

@{

Name = @( "Education"; "Professional"; "ProfessionalEducation"; "ProfessionalWorkstation"; "Enterprise";
"IoTEnterprise"; "ServerRdsh"; )

Apps = @(

"Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.HEIFImageExtension"; "Microsoft.HEVCVideoExtension";
"Microsoft.SecHealthUI"; "Microsoft.VP9VideoExtensions"; "Microsoft.WebpImageExtension";
"Microsoft.WindowsStore"; "Microsoft.GamingApp"; "Microsoft.Sticky.Notes"; "Microsoft.Paint";
"Microsoft.PowerAutomateDesktop"; "Microsoft.ScreenSketch"; "Microsoft.WindowsNotepad";
"Microsoft.WindowsTerminal"; "Clipchamp.Clipchamp"; "Microsoft.Solitaire.Collection"; "Microsoft.WindowsAlarms";
"Microsoft.WindowsFeedbackHub"; "Microsoft.WindowsMaps"; "Microsoft.ZuneMusic"; "Microsoft.BingNews";
"Microsoft.DesktopAppInstaller"; "Microsoft.WindowsCamera"; "Microsoft.Getstarted"; "Microsoft.Cortana";
"Microsoft.BingWeather"; "Microsoft.GetHelp"; "Microsoft.MicrosoftOfficeHub"; "Microsoft.People";
"Microsoft.StorePurchaseApp"; "Microsoft.Todos"; "Microsoft.WebMediaExtensions"; "Microsoft.Windows.Photos";

```

```

"Microsoft.WindowsCalculator"; "Microsoft.Windows.CommunicationsApps"; "Microsoft.WindowsSoundRecorder";
"Microsoft.Xbox.TCUI"; "Microsoft.XboxGameOverlay"; "Microsoft.XboxGamingOverlay";
"Microsoft.XboxIdentityProvider"; "Microsoft.XboxSpeechToTextOverlay"; "Microsoft.YourPhone";
"Microsoft.ZuneVideo"; "MicrosoftCorporationII.QuickAssist"; "MicrosoftWindows.Client.WebExperience";
"Microsoft.RawImageExtension";

    )

}

@{

    Name = @( "EnterpriseN"; "EnterpriseGN"; "EnterpriseSN"; "ProfessionalN"; "EducationN";
"ProfessionalWorkstationN"; "ProfessionalEducationN"; "CloudN"; "CloudEN"; "CloudEditionN"; "CloudEditionLN";
"StarterN"; )

    Apps = @(

        "Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.SecHealthUI"; "Microsoft.WindowsStore";
"Microsoft.Sticky.Notes"; "Microsoft.Paint"; "Microsoft.PowerAutomateDesktop"; "Microsoft.ScreenSketch";
"Microsoft.WindowsNotepad"; "Microsoft.WindowsTerminal"; "Clipchamp.Clipchamp";
"Microsoft.Solitaire.Collection"; "Microsoft.WindowsAlarms"; "Microsoft.WindowsFeedbackHub";
"Microsoft.WindowsMaps"; "Microsoft.BingNews"; "Microsoft.DesktopAppInstaller"; "Microsoft.WindowsCamera";
"Microsoft.Getstarted"; "Microsoft.Cortana"; "Microsoft.BingWeather"; "Microsoft.GetHelp";
"Microsoft.MicrosoftOfficeHub"; "Microsoft.People"; "Microsoft.StorePurchaseApp"; "Microsoft.Todos";
"Microsoft.Windows.Photos"; "Microsoft.WindowsCalculator"; "Microsoft.Windows.CommunicationsApps";
"Microsoft.XboxGameOverlay"; "Microsoft.XboxIdentityProvider"; "Microsoft.XboxSpeechToTextOverlay";
"Microsoft.YourPhone"; "MicrosoftCorporationII.QuickAssist"; "MicrosoftWindows.Client.WebExperience";

    )

}

)

$Allow_Install_App = @()

ForEach ($item in $Pre_Config_Rules) {

    if ($item.Name -contains $Current_Edition_Version) {

        Write-host "`n  Match to: "-NoNewline

        Write-host $Current_Edition_Version -ForegroundColor Green

        $Allow_Install_App = $item.Apps

        break

    }

}

Write-host "`n  The app to install ( $($Allow_Install_App.Count) item )" -ForegroundColor Yellow

Write-host "  $('-' * 80)"

ForEach ($item in $Allow_Install_App) {

    Write-host "  $($item)" -ForegroundColor Green

}

```

```

$InBoxApps = @(

    @{ Name = "Microsoft.UI.Xaml.2.3"; File = "Microsoft.UI.Xaml.x64.2.3.appx"; License = ""; }

    @{ Name = "Microsoft.UI.Xaml.2.4"; File = "Microsoft.UI.Xaml.x64.2.4.appx"; License = ""; }

    @{ Name = "Microsoft.UI.Xaml.2.7"; File = "Microsoft.UI.Xaml.x64.2.7.appx"; License = ""; }

    @{ Name = "Microsoft.NET.Native.Framework.2.2"; File = "Microsoft.NET.Native.Framework.x64.2.2.appx"; License =
""; }

    @{ Name = "Microsoft.NET.Native.Runtime.2.2"; File = "Microsoft.NET.Native.Runtime.x64.2.2.appx"; License = ""; }

    @{ Name = "Microsoft.VCLibs.140.00"; File = "Microsoft.VCLibs.x64.14.00.appx"; License = ""; }

    @{ Name = "Microsoft.VCLibs.140.00.UWPDesktop"; File = "Microsoft.VCLibs.x64.14.00.UWPDesktop.appx";
License = ""; }

    @{ Name = "Microsoft.WindowsStore"; File = "Microsoft.WindowsStore_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.WindowsStore_8wekyb3d8bbwe.xml"; }

    @{ Name = "Microsoft.HEIFImageExtension"; File = "Microsoft.HEIFImageExtension_8wekyb3d8bbwe.appxbundle";
License = "Microsoft.HEIFImageExtension_8wekyb3d8bbwe.xml"; }

    @{ Name = "Microsoft.HEVCVideoExtension"; File = "Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.x64.appx";
License = "Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.x64.xml"; }

    @{ Name = "Microsoft.SecHealthUI"; File = "Microsoft.SecHealthUI_8wekyb3d8bbwe.x64.appx"; License =
"Microsoft.SecHealthUI_8wekyb3d8bbwe.x64.xml"; }

    @{ Name = "Microsoft.VP9VideoExtensions"; File = "Microsoft.VP9VideoExtensions_8wekyb3d8bbwe.x64.appx";
License = "Microsoft.VP9VideoExtensions_8wekyb3d8bbwe.x64.xml"; }

    @{ Name = "Microsoft.WebplImageExtension"; File = "Microsoft.WebplImageExtension_8wekyb3d8bbwe.x64.appx";
License = "Microsoft.WebplImageExtension_8wekyb3d8bbwe.x64.xml"; }

    @{ Name = "Microsoft.GamingApp"; File = "Microsoft.GamingApp_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.GamingApp_8wekyb3d8bbwe.xml"; }

    @{ Name = "Microsoft.Sticky.Notes"; File = "Microsoft.MicrosoftStickyNotes_8wekyb3d8bbwe.msixbundle"; License
= "Microsoft.MicrosoftStickyNotes_8wekyb3d8bbwe.xml"; }

    @{ Name = "Microsoft.Paint"; File = "Microsoft.Paint_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.Paint_8wekyb3d8bbwe.xml"; }

    @{ Name = "Microsoft.PowerAutomateDesktop"; File =
"Microsoft.PowerAutomateDesktop_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.PowerAutomateDesktop_8wekyb3d8bbwe.xml"; }

    @{ Name = "Microsoft.ScreenSketch"; File = "Microsoft.ScreenSketch_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.ScreenSketch_8wekyb3d8bbwe.xml"; }

    @{ Name = "Microsoft.WindowsNotepad"; File = "Microsoft.WindowsNotepad_8wekyb3d8bbwe.msixbundle";
License = "Microsoft.WindowsNotepad_8wekyb3d8bbwe.xml"; }

    @{ Name = "Microsoft.WindowsTerminal"; File = "Microsoft.WindowsTerminal_8wekyb3d8bbwe.msixbundle";
License = "Microsoft.WindowsTerminal_8wekyb3d8bbwe.xml"; }

    @{ Name = "Clipchamp.Clipchamp"; File = "Clipchamp.Clipchamp_yxz26nhyzhsrt.msixbundle"; License =
"Clipchamp.Clipchamp_yxz26nhyzhsrt.xml"; }

    @{ Name = "Microsoft.Solitaire.Collection"; File =
"Microsoft.MicrosoftSolitaireCollection_8wekyb3d8bbwe.msixbundle"; License =
"Microsoft.MicrosoftSolitaireCollection_8wekyb3d8bbwe.xml"; }

```

```
@{ Name = "Microsoft.WindowsAlarms"; File = "Microsoft.WindowsAlarms_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.WindowsAlarms_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.WindowsFeedbackHub"; File =  
"Microsoft.WindowsFeedbackHub_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.WindowsFeedbackHub_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.WindowsMaps"; File = "Microsoft.WindowsMaps_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.WindowsMaps_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.ZuneMusic"; File = "Microsoft.ZuneMusic_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.ZuneMusic_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "MicrosoftCorporationII.MicrosoftFamily"; File =  
"MicrosoftCorporationII.MicrosoftFamily_8wekyb3d8bbwe.msixbundle"; License =  
"MicrosoftCorporationII.MicrosoftFamily_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.BingNews"; File = "Microsoft.BingNews_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.BingNews_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.DesktopAppInstaller"; File = "Microsoft.DesktopAppInstaller_8wekyb3d8bbwe.msixbundle";  
License = "Microsoft.DesktopAppInstaller_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.WindowsCamera"; File = "Microsoft.WindowsCamera_8wekyb3d8bbwe.msixbundle"; License  
= "Microsoft.WindowsCamera_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.Getstarted"; File = "Microsoft.Getstarted_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.Getstarted_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.Cortana"; File = "Microsoft.CortanaApp_8wekyb3d8bbwe.appxbundle"; License =  
"Microsoft.CortanaApp_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.BingWeather"; File = "Microsoft.BingWeather_8wekyb3d8bbwe.appxbundle"; License =  
"Microsoft.BingWeather_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.GetHelp"; File = "Microsoft.GetHelp_8wekyb3d8bbwe.appxbundle"; License =  
"Microsoft.GetHelp_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.MicrosoftOfficeHub"; File = "Microsoft.MicrosoftOfficeHub_8wekyb3d8bbwe.appxbundle";  
License = "Microsoft.MicrosoftOfficeHub_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.People"; File = "Microsoft.People_8wekyb3d8bbwe.appxbundle"; License =  
"Microsoft.People_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.StorePurchaseApp"; File = "Microsoft.StorePurchaseApp_8wekyb3d8bbwe.appxbundle";  
License = "Microsoft.StorePurchaseApp_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.Todos"; File = "Microsoft.Todos_8wekyb3d8bbwe.appxbundle"; License =  
"Microsoft.Todos_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.WebMediaExtensions"; File = "Microsoft.WebMediaExtensions_8wekyb3d8bbwe.appxbundle";  
License = "Microsoft.WebMediaExtensions_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.Windows.Photos"; File = "Microsoft.Windows.Photos_8wekyb3d8bbwe.appxbundle"; License  
= "Microsoft.Windows.Photos_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.WindowsCalculator"; File = "Microsoft.WindowsCalculator_8wekyb3d8bbwe.appxbundle";  
License = "Microsoft.WindowsCalculator_8wekyb3d8bbwe.xml"; }
```

```
@{ Name = "Microsoft.Windows.CommunicationsApps"; File =  
"Microsoft.WindowsCommunicationsApps_8wekyb3d8bbwe.appxbundle"; License =  
"Microsoft.WindowsCommunicationsApps_8wekyb3d8bbwe.xml"; }
```

```

        @{ Name = "Microsoft.WindowsSoundRecorder"; File =
"Microsoft.WindowsSoundRecorder_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.WindowsSoundRecorder_8wekyb3d8bbwe.xml"; }

        @{ Name = "Microsoft.Xbox.TCUI"; File = "Microsoft.Xbox.TCUI_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.Xbox.TCUI_8wekyb3d8bbwe.xml"; }

        @{ Name = "Microsoft.XboxGameOverlay"; File = "Microsoft.XboxGameOverlay_8wekyb3d8bbwe.appxbundle";
License = "Microsoft.XboxGameOverlay_8wekyb3d8bbwe.xml"; }

        @{ Name = "Microsoft.XboxGamingOverlay"; File = "Microsoft.XboxGamingOverlay_8wekyb3d8bbwe.appxbundle";
License = "Microsoft.XboxGamingOverlay_8wekyb3d8bbwe.xml"; }

        @{ Name = "Microsoft.XboxIdentityProvider"; File = "Microsoft.XboxIdentityProvider_8wekyb3d8bbwe.appxbundle";
License = "Microsoft.XboxIdentityProvider_8wekyb3d8bbwe.xml"; }

        @{ Name = "Microsoft.XboxSpeechToTextOverlay"; File =
"Microsoft.XboxSpeechToTextOverlay_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.XboxSpeechToTextOverlay_8wekyb3d8bbwe.xml"; }

        @{ Name = "Microsoft.YourPhone"; File = "Microsoft.YourPhone_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.YourPhone_8wekyb3d8bbwe.xml"; }

        @{ Name = "Microsoft.ZuneVideo"; File = "Microsoft.ZuneVideo_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.ZuneVideo_8wekyb3d8bbwe.xml"; }

        @{ Name = "MicrosoftCorporationII.QuickAssist"; File =
"MicrosoftCorporationII.QuickAssist_8wekyb3d8bbwe.appxbundle"; License =
"MicrosoftCorporationII.QuickAssist_8wekyb3d8bbwe.xml"; }

        @{ Name = "MicrosoftWindows.Client.WebExperience"; File =
"MicrosoftWindows.Client.WebExperience_cw5n1h2txyewy.appxbundle"; License =
"MicrosoftWindows.Client.WebExperience_cw5n1h2txyewy.xml"; }

        @{ Name = "Microsoft.RawImageExtension"; File = "Microsoft.RawImageExtension_8wekyb3d8bbwe.appxbundle";
License = "Microsoft.RawImageExtension_8wekyb3d8bbwe.xml"; }

    )

Function Install_Appx

{

    param ( $File, $License )

    Write-host "  $('-' * 80)"

    Write-host "  Installing: " -NoNewline; Write-host $File -ForegroundColor Yellow

    if (Test-Path -Path $File -PathType Leaf) {

        if (Test-Path -Path $License -PathType Leaf) {

            Write-host "    License: " -NoNewline; Write-host $License -ForegroundColor Yellow

            Write-host "    With License".PadRight(22) -NoNewline -ForegroundColor Green

            Write-host "    Installing".PadRight(22) -NoNewline

            try {

                Add-AppxProvisionedPackage -Path $Mount -PackagePath $File -LicensePath $License -ErrorAction
SilentlyContinue | Out-Null

                Write-Host "Done" -ForegroundColor Green

```

```

    } catch {

        Write-Host "Failed" -ForegroundColor Red

        Write-Host "  $($_) " -ForegroundColor Yellow

    }

} else {

    Write-host "  No License".PadRight(22) -NoNewline -ForegroundColor Red

    Write-host "  Installing".PadRight(22) -NoNewline

    try {

        Add-AppxProvisionedPackage -Path $Mount -PackagePath $File -SkipLicense -ErrorAction SilentlyContinue | Out-Null

        Write-Host "Done" -ForegroundColor Green

    } catch {

        Write-Host "Failed" -ForegroundColor Red

        Write-Host "  $($_) " -ForegroundColor Yellow

    }

}

} else {

    Write-host "  The installation package does not exist" -ForegroundColor Red

}

}

ForEach ($Rule in $InBoxApps) {

    Write-host "`n  Name: " -NoNewline

    Write-host $Rule.Name -ForegroundColor Yellow

    Write-host "  $('-' * 80)"

    if($Allow_Install_App -contains $Rule.Name) {

        Write-host "  Search for apps: " -NoNewline

        Write-host $Rule.File -ForegroundColor Yellow

        Write-host "  Search for License: " -NoNewline

        Write-host $Rule.File -ForegroundColor Yellow

        if ($ISO -eq "Auto") {

            Get-PSDrive -PSProvider FileSystem -ErrorAction SilentlyContinue | ForEach-Object {

                $AppPath = Join-Path -Path $_.Root -ChildPath "packages\$($Rule.File)" -ErrorAction SilentlyContinue

                $LicensePath = Join-Path -Path $_.Root -ChildPath "packages\$($Rule.License)" -ErrorAction SilentlyContinue

                if (Test-Path $AppPath -PathType Leaf) {

                    Write-host "  $('-' * 80)"

```

```

        Write-host " Discover apps: " -NoNewLine; Write-host $AppPath -ForegroundColor Green

        if (Test-Path $LicensePath -PathType Leaf) {

            Write-host " Discover License: " -NoNewLine; Write-host $LicensePath -ForegroundColor Green

        } else {

            Write-host " License: " -NoNewLine; Write-host "Not found" -ForegroundColor Red

        }

        Install_Appx -File $AppPath -License $LicensePath

        return

    }

}

} else {

    Install_Appx -File "$($ISO)\$($Rule.File)" -License "$($ISO)\$($Rule.License)"

}

} else {

    Write-host " Skip the installation" -ForegroundColor Red

}

}

```

#### 5.8. Region tag: delete

- After completing the installation of the InBox Apps application, the Region tag is no longer important and can be deleted or not deleted. Delete "Local Language Experience Package (LXPs), Simplified Chinese - China)" and uniquely identify the Region tag: **zh-CN**, can be changed to other Region tag.
- Install.Clear.Flag.ps1
  - [\Expand\Install\Install.Clear.Flag.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/Install.Clear.Flag.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/Install.Clear.Flag.ps1)

- Copy the code

```

$Lang = "zh-CN"

Get-AppXProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" | Foreach-object {

    if ($_.DisplayName -Like "*LanguageExperiencePack*${$Lang}*") {

        Write-host " ${$_DisplayName}"; Write-Host " Deleting ".PadRight(22) -NoNewline

        try {

            Remove-AppxProvisionedPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackageName $_.PackageName -
            ErrorAction SilentlyContinue | Out-Null

            Write-host "Finish" -ForegroundColor Green
        }
    }
}

```

```

    } catch {

        Write-host "Failed" -ForegroundColor Red

    }

}

}

```

#### 5.9. InBox Apps: optimization

After the app is installed, provisioning the Appx package should be optimized to reduce the app's disk usage by replacing identical files with hard links, only for offline images.

```
Dism /Image:"D:\OS_10_Custom\Install\Install\Mount" /Optimize-ProvisionedAppxPackages
```

### 6. Cumulative updates

- When upgrading different versions or old versions to the latest version, you need to add the "Function Enablement Package" first before adding the latest cumulative update;
- After adding a language pack, you can install the same cumulative update as the initial version to resolve a known issue where the "Components: All packages installed in the image" status is not refreshed after installation;
- To stay up to date, it is recommended that you download the latest version.

#### 6.1. Feature enablement package

- Learn: [KB5015684: Featured update to Windows 10, version 22H2 by using an enablement package](#)
- Note: When using the same version as Windows 10 22H2 19045.2006 and above, the feature enablement package can be skipped.
- When making Windows 10 versions 2004, 20H2, 21H1, and 21H2, you need to install the "Feature Enablement Package" in advance before you can install the cumulative update of 19045.\*. After downloading, save it to: [D:\OS\\_10\\_Custom\Install\Install\Update](#), select according to the architecture download:

##### 6.1.1. x64, default

- Direct download

[https://catalog.s.download.windowsupdate.com/c/upgr/2022/07/windows10.0-kb5015684-x64\\_523c039b86ca98f2d818c4e6706e2cc94b634c4a.msu](https://catalog.s.download.windowsupdate.com/c/upgr/2022/07/windows10.0-kb5015684-x64_523c039b86ca98f2d818c4e6706e2cc94b634c4a.msu)

- Install

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5015684-x64_523c039b86ca98f2d818c4e6706e2cc94b634c4a.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

##### 6.1.2. x86

- Direct download

<https://catalog.s.download.windowsupdate.com/c/upgr/2022/07/windows10.0-kb5015684->



[x86\\_556015f4260dd75ca30b3e84484ea5b3ec97fa08.msu](#)

- Install

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5015684-x86_556015f4260dd75ca30b3e84484ea5b3ec97fa08.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

#### 6.1.3. Arm64

- Direct download

[https://catalog.s.download.windowsupdate.com/c/upgr/2022/07/windows10.0-kb5015684-arm64\\_a4cc6e95084da14adb972e1d67cf573a244ed7a3.msu](https://catalog.s.download.windowsupdate.com/c/upgr/2022/07/windows10.0-kb5015684-arm64_a4cc6e95084da14adb972e1d67cf573a244ed7a3.msu)

- Install

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5015684-arm64_a4cc6e95084da14adb972e1d67cf573a244ed7a3.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

### 6.2. Initial version

Cumulative update KB5017308 cannot be searched from <https://www.catalog.update.microsoft.com/Search.aspx?q=KB5017308>. Download it through direct connection and save it to: [D:\OS\\_10\\_Custom\Install\Install\Update](#), choose to download according to the architecture:

#### 6.2.1. x64, default

- Direct download

[https://catalog.s.download.windowsupdate.com/c/msdownload/update/software/secu/2022/09/windows10.0-kb5017308-x64\\_2027053968a06948b45d139d95475ab4feee5654.msu](https://catalog.s.download.windowsupdate.com/c/msdownload/update/software/secu/2022/09/windows10.0-kb5017308-x64_2027053968a06948b45d139d95475ab4feee5654.msu)

- Install

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5017308-x64_2027053968a06948b45d139d95475ab4feee5654.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

#### 6.2.2. x86

- Direct download

[https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/secu/2022/09/windows10.0-kb5017308-x86\\_ec788348202c33b871c8af028d045debd273576c.msu](https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/secu/2022/09/windows10.0-kb5017308-x86_ec788348202c33b871c8af028d045debd273576c.msu)

- Install

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5017308-
```

```
x86_ec788348202c33b871c8af028d045debd273576c.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

#### 6.2.3. Arm64

- Direct download

[https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/secu/2022/09/windows10.0-kb5017308-arm64\\_1ca51a0b3abdab7ee891bd1e1e6d3f03bc15e324.msu](https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/secu/2022/09/windows10.0-kb5017308-arm64_1ca51a0b3abdab7ee891bd1e1e6d3f03bc15e324.msu)

- Install

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5017308-arm64_1ca51a0b3abdab7ee891bd1e1e6d3f03bc15e324.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

#### 6.3. Other versions

Check "[Windows 10 version information](#)", for example, download the cumulative update: [KB5032278](#), go to the download page: <https://www.catalog.update.microsoft.com/Search.aspx?q=KB5032278>, and save it to: `D:\OS_10_Custom\Install\Install\Update`, or download through direct connection, select download according to the architecture:

##### 6.3.1. x64, default

- Direct download

[https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/updt/2023/11/windows10.0-kb5032278-x64\\_3a2b384f690eaa92c5030c535ac4a7e47c71a635.msu](https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/updt/2023/11/windows10.0-kb5032278-x64_3a2b384f690eaa92c5030c535ac4a7e47c71a635.msu)

- Add to

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5032278-x64_3a2b384f690eaa92c5030c535ac4a7e47c71a635.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

##### 6.3.2. x86

- Direct download

[https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/updt/2023/11/windows10.0-kb5032278-x86\\_21e1e1c12d0f763d7c6e3ac6c3d7f8c6461e0004.msu](https://catalog.s.download.windowsupdate.com/d/msdownload/update/software/updt/2023/11/windows10.0-kb5032278-x86_21e1e1c12d0f763d7c6e3ac6c3d7f8c6461e0004.msu)

- Add to

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5032278-x86_21e1e1c12d0f763d7c6e3ac6c3d7f8c6461e0004.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

##### 6.3.3. Arm64

- Direct download

[https://catalog.s.download.windowsupdate.com/c/msdownload/update/software/updt/2023/11/windows10-kb5032278-arm64\\_54422d085c9d2c64ca0ff6e88ace3ec9f8860b6a.msu](https://catalog.s.download.windowsupdate.com/c/msdownload/update/software/updt/2023/11/windows10-kb5032278-arm64_54422d085c9d2c64ca0ff6e88ace3ec9f8860b6a.msu)

- Add to

```
$KBPath = "D:\OS_10_Custom\Install\Install\Update\windows10.0-kb5032278-arm64_54422d085c9d2c64ca0ff6e88ace3ec9f8860b6a.msu"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Install\Install\Mount" -PackagePath $KBPath
```

#### 6.4. Solidify Updated

It cannot be uninstalled after curing, which cleans the recovery image and resets the basis of any superseded components.

```
Dism /Image:"D:\OS_10_Custom\Install\Install\Mount" /cleanup-image /StartComponentCleanup /ResetBase
```

##### 6.4.1. Clean components after curing and updating

```
$Mount = "D:\OS_10_Custom\Install\Install\Mount"
```

```
Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {
```

```
    if ($_.PackageState -eq "Superseded") {
```

```
        Write-Host "  $($_.PackageName)" -ForegroundColor Green
```

```
        Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null
```

```
    }
```

```
}
```

#### 7. Drive

#### 8. Deployment engine: Add

- Learn "Deployment Engine", if added to ISO installation media, can skip adding to mounted.
- After adding the deployment engine, continue at the current location.

#### 9. Health

Before saving, check whether it is damaged. If the health status is abnormal, stop saving.

```
Repair-WindowsImage -Path "D:\OS_10_Custom\Install\Install\Mount" -ScanHealth
```

#### 10. Replace WinRE.wim

WinRE.wim in all index numbers in Install.wim has been replaced in batches. Please skip this step.

```
$WinRE = "D:\OS_10_Custom\Install\Install\Update\Winlib\WinRE.wim"
```

```
$CopyTo = "D:\OS_10_Custom\Install\Install\Mount\Windows\System32\Recovery"
```

```
Copy-Item -Path $WinRE -Destination $CopyTo -Force
```

11. Save image: Install.wim

```
Save-WindowImage -Path "D:\OS_10_Custom\Install\Install\Mount"
```

12. Unmount image: Install.wim

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowImage -Path "D:\OS_10_Custom\Install\Install\Mount" -Discard
```

LOOP OPERATING AREA, END.

13. Rebuilding Install.wim reduces file size

- Install.Rebuild.wim.ps1
  - [\Expand\Install\Install.Rebuild.wim.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/Install.Rebuild.wim.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/Install.Rebuild.wim.ps1)

- Copy the code

```
$InstallWim = "D:\OS_10\sources\install.wim"
```

```
Get-WindowImage -ImagePath $InstallWim -ErrorAction SilentlyContinue | ForEach-Object {
```

```
    Write-Host "  Image name: " -NoNewline; Write-Host $_.ImageName -ForegroundColor Yellow
```

```
    Write-Host "  The index number: " -NoNewline; Write-Host $_.ImageIndex -ForegroundColor Yellow
```

```
    Write-Host "`n  Under reconstruction".PadRight(28) -NoNewline
```

```
    Export-WindowImage -SourceImagePath $InstallWim -SourceIndex $_.ImageIndex -DestinationImagePath "$($InstallWim).New" -  
    CompressionType max | Out-Null
```

```
    Write-Host "Finish`n" -ForegroundColor Green
```

```
}
```

```
if (Test-Path "$($InstallWim).New" -PathType Leaf) {
```

```
    Remove-Item -Path $InstallWim
```

```
    Move-Item -Path "$($InstallWim).New" -Destination $InstallWim
```

```
    Write-Host "Finish" -ForegroundColor Green
```

```
} else {
```

```
    Write-host "Failed" -ForegroundColor Red
```

```
}
```

14. How to batch replace WinRE.wim in all index numbers in Install.wim

14.1. Obtain WimLib

After going to the official website of <https://wimlib.net>, select a different version: [arm64](#), [x64](#), [x86](#), and extract it to: [D:Wimlib](#) after downloading

## 14.2. How to extract and update WinRE.wim in Install.wim

### 14.2.1. Extract the WinRE.wim file Install.wim from Install.wim

- Install.WinRE.Extract.ps1
  - [\Expand\Install\Install.WinRE.Extract.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/Install.WinRE.Extract.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/Install.WinRE.Extract.ps1)

- Copy the code

```
$Arguments = @(
    "extract",
    "D:\OS_10\sources\install.wim", "1",
    "\Windows\System32\Recovery\Winre.wim",
    "--dest-dir=""D:\OS_10_Custom\Install\Install\Update\Winlib""
)

New-Item -Path "D:\OS_10_Custom\Install\Install\Update\Winlib" -ItemType Directory -ea SilentlyContinue

Start-Process -FilePath "d:\wimlib\wimlib-image.exe" -ArgumentList $Arguments -wait -nonewwindow
```

### 14.2.2. Get all index numbers of Install.wim and replace the old WinRE.wim

- Install.WinRE.Replace.wim.ps1
  - [\Expand\Install\Install.WinRE.Replace.wim.ps1](#)
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/Install.WinRE.Replace.wim.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.10/22H2/Expand/Install/Install.WinRE.Replace.wim.ps1)

- Copy the code

```
Get-WindowsImage -ImagePath "D:\OS_10\sources\install.wim" -ErrorAction SilentlyContinue | ForEach-Object {
    Write-Host "  Image name: " -NoNewline; Write-Host $_.ImageName -ForegroundColor Yellow

    Write-Host "  The index number: " -NoNewline; Write-Host $_.ImageIndex -ForegroundColor Yellow

    Write-Host "`n  Replacement "

    $Arguments = @(
        "update",
        "D:\OS_10\sources\install.wim", $_.ImageIndex,
        "--command=""add 'D:\OS_10_Custom\Install\Install\Update\Winlib\WinRE.wim'
        '\Windows\System32\Recovery\Winre.wim'""
    )

    Start-Process -FilePath "d:\wimlib\wimlib-image.exe" -ArgumentList $Arguments -wait -nonewwindow

    Write-Host "  Finish`n" -ForegroundColor Green
}
```

```
}
```

### III Custom deployment image boot.wim

#### 1. View Boot.wim details

Image name, image description, image size, architecture, version, index number, etc.

```
$ViewFile = "D:\OS_10\Sources\Boot.wim"
```

```
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex }
```

#### 2. Specify the path to mount Boot.wim

```
New-Item -Path "D:\OS_10_Custom\Boot\Boot\Mount" -ItemType directory -ea SilentlyContinue
```

#### 3. Start mounting Boot.wim

Default index number: 2

```
Mount-WindowsImage -ImagePath "D:\OS_10\sources\boot.wim" -Index "2" -Path "D:\OS_10_Custom\Boot\Boot\Mount"
```

#### 4. Language pack: Boot

- Automatically install language packs: Get "Component: All installed packages in the image" and match them. After matching the corresponding names, install the local corresponding language pack files, View the report "[Language installation package for Boot.wim](#)".
- When adding languages, different schema versions must be corresponded, and if not, errors are reported during the addition process.

##### 4.1. Language pack: Add

- Boot.Instl.lang.ps1

- [\Expand\Boot\Boot.Instl.lang.ps1](#)

- [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging/tutorial/OS.10/22H2/Expand/Boot/Boot.Instl.lang.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging/tutorial/OS.10/22H2/Expand/Boot/Boot.Instl.lang.ps1)

- Copy the code

```
$Mount = "D:\OS_10_Custom\Boot\Boot\Mount"
```

```
$Sources = "D:\OS_10_Custom\Boot\Boot\Language\Add\zh-CN"
```

```
$Initl_install_Language_Component = @()
```

```
Get-WindowsPackage -Path $Mount | ForEach-Object {
```

```
    $Initl_install_Language_Component += $_.PackageName
```

```
}
```

```
Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\WinPE-FontSupport-zh-CN.cab"
```

```
$Language = @(
```

```
    @{ Match = "*WinPE*Setup*Client*Package*"; File = "WINPE-SETUP-CLIENT_zh-CN.CAB"; }
```

```
    @{ Match = "*WinPE*Setup*Package*"; File = "WinPE-Setup_zh-CN.cab"; }
```

```

@{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }

@{ Match = "*SecureStartup*"; File = "winpe-securestartup_zh-CN.cab"; }

@{ Match = "*ATBroker*"; File = "winpe-atbroker_zh-CN.cab"; }

@{ Match = "*AudioCore*"; File = "winpe-audiocore_zh-CN.cab"; }

@{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_zh-CN.cab"; }

@{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_zh-CN.cab"; }

@{ Match = "*Narrator*"; File = "winpe-narrator_zh-CN.cab"; }

@{ Match = "*scripting*"; File = "winpe-scripting_zh-CN.cab"; }

@{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_zh-CN.cab"; }

@{ Match = "*srh*"; File = "winpe-srh_zh-CN.cab"; }

@{ Match = "*srt*"; File = "winpe-srt_zh-CN.cab"; }

@{ Match = "*wds-tools*"; File = "winpe-wds-tools_zh-CN.cab"; }

@{ Match = "*-WMI-Package*"; File = "winpe-wmi_zh-CN.cab"; }

)

ForEach ($Rule in $Language) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "*$($Rule.Match)*") {

            Write-host "  Component name: " -NoNewline; Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline; Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

            Write-Host "  Installing ".PadRight(22) -NoNewline

            try {

                Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" | Out-Null

                Write-host "Finish" -ForegroundColor Green

            } catch {

                Write-host "Failed" -ForegroundColor Red

                Write-host "  $($_) " -ForegroundColor Red

            }

            break

        }

    }

}

}

```

## 4.2. Offline image language: change

### 4.2.1. Change default language, regional settings, and other international settings

Region: zh-CN

```
Dism /Image:"D:\OS_10_Custom\Boot\Boot\Mount" /Set-AllIntl:"zh-CN"
```

#### 4.2.2. View available language settings

```
Dism /Image:"D:\OS_10_Custom\Boot\Boot\Mount" /Get-Intl
```

#### 4.3. Language pack: Removed

- After you add languages, if you want to deploy to a non-English locale, you can save space by removing the English language component. When you remove a language, uninstall the language components in the reverse order in which you added them.
- After adding the Chinese, delete "English - United States" in reverse, the Region tag: en-US, you need to extract the language pack in advance
- Boot.Del.Specified.lang.Tag.ps1
  - \Expand\Boot\Boot.Del.Specified.lang.Tag.ps1
  - [https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging/tutorial/OS.10/22H2/Expand/Boot/Boot.Del.Specified.lang.Tag.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging/tutorial/OS.10/22H2/Expand/Boot/Boot.Del.Specified.lang.Tag.ps1)

- Copy the code

```
$Lang = "en-US"
```

```
$Mount = "D:\OS_10_Custom\Boot\Boot\Mount"
```

```
$Sources = "D:\OS_10_Custom\Boot\Boot\Language\Del\en-US"
```

```
$Initl_install_Language_Component = @()
```

```
Get-WindowsPackage -Path $Mount | ForEach-Object { $Initl_install_Language_Component += $_.PackageName }
```

```
$Language = @(
```

```
    @{ Match = "*WordPad*wow64*"; File = "Microsoft-Windows-WordPad-FoD-  
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*WordPad*amd64*"; File = "Microsoft-Windows-WordPad-FoD-  
Package~31bf3856ad364e35~amd64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*WMIC*FoD*Package*wow64*"; File = "Microsoft-Windows-WMIC-FoD-  
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*WMIC*FoD*Package*amd64*"; File = "Microsoft-Windows-WMIC-FoD-  
Package~31bf3856ad364e35~AMD64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*StepsRecorder*wow64*"; File = "Microsoft-Windows-StepsRecorder-  
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*StepsRecorder*amd64*"; File = "Microsoft-Windows-StepsRecorder-  
Package~31bf3856ad364e35~amd64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*Printing*PMCPPC*amd64*"; File = "Microsoft-Windows-Printing-PMCPPC-FoD-  
Package~31bf3856ad364e35~AMD64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*PowerShell*wow64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-  
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }
```



```

        @{ Match = "*PowerShell*amd64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~amd64~$(Lang)~.cab"; }

        @{ Match = "*MediaPlayer*wow64*"; File = "Microsoft-Windows-MediaPlayer-Package-wow64-$(Lang).cab"; }

        @{ Match = "*MediaPlayer*amd64*"; File = "Microsoft-Windows-MediaPlayer-Package-AMD64-$(Lang).cab"; }

        @{ Match = "*Notepad*wow64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

        @{ Match = "*Notepad*amd64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*InternetExplorer*"; File = "Microsoft-Windows-InternetExplorer-Optional-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*TextToSpeech*"; File = "Microsoft-Windows-LanguageFeatures-TextToSpeech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*LanguageFeatures-Speech*"; File = "Microsoft-Windows-LanguageFeatures-Speech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*OCR*"; File = "Microsoft-Windows-LanguageFeatures-OCR-$(Lang)-Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*Handwriting*"; File = "Microsoft-Windows-LanguageFeatures-Handwriting-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*LanguageFeatures-Basic*"; File = "Microsoft-Windows-LanguageFeatures-Basic-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*Client-LanguagePack-Package*"; File = "Microsoft-Windows-Client-Language-Pack_x64_$(Lang).cab"; }

    )

    ForEach ($Rule in $Language) {

        Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

        ForEach ($Component in $Initl_install_Language_Component) {

            if ($Component -like "*$($Rule.Match)*$(Lang)*") {

                Write-host "  Component name: " -NoNewline

                Write-host $Component -ForegroundColor Green

                Write-host "  Language pack file: " -NoNewline

                Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

                Write-Host "  Deleting ".PadRight(22) -NoNewline

                try {

                    Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" -ErrorAction SilentlyContinue | Out-Null

                    Write-host "Finish" -ForegroundColor Green

                } catch {

                    Write-host "Failed" -ForegroundColor Red

                    Write-host "  $('_)" -ForegroundColor Red

                }

            }

            break
        }
    }
}

```

```

    }

}

}

$InitlClearLanguagePackage = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    if ($_.PackageName -like "*$($Lang)*") {

        $InitlClearLanguagePackage += $_.PackageName

    }

}

if ($InitlClearLanguagePackage.count -gt 0) {

    ForEach ($item in $InitlClearLanguagePackage) {

        Write-Host "`n $($item)" -ForegroundColor Green

        Write-Host "  Deleting ".PadRight(22) -NoNewline

        try {

            Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction SilentlyContinue | Out-Null

            Write-host "Finish" -ForegroundColor Green

        } catch {

            Write-host "Failed" -ForegroundColor Red

            Write-host "  $($_) " -ForegroundColor Red

        }

    }

}

```

#### 4.4. Components: All packages installed in the image

##### 4.4.1. View

```
Get-WindowsPackage -Path "D:\OS_10_Custom\Boot\Boot\Mount" | Out-GridView
```

##### 4.4.2. Export to csv

```

$SaveTo = "D:\OS_10_Custom\Boot\Boot\Report.$(Get-Date -Format "yyyyMMddHHmmss").csv"

Get-WindowsPackage -Path "D:\OS_10_Custom\Boot\Boot\Mount" | Export-CSV -NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green

```

#### 4.5. Language: Repair

##### 4.5.1. Extract

```
Open: D:\OS_10_Custom\Install\Install\Language\Add\zh-CN\Microsoft-Windows-Client-Language-Pack_x64_zh-CN.cab,
```

enter the directory: `Setup\sources\zh-cn\cli`, and copy the following files to the deskto:

4.5.1.1. `arunres.dll.mui`

4.5.1.2. `spwizres.dll.mui`

4.5.1.3. `w32uires.dll.mui`

4.5.2. Copy

Copy the extracted files to: `D:\OS_10_Custom\Boot\Boot\Mount\sources\zh-CN`

4.6. Language packs: sync to ISO installer

```
Copy-Item -Path "D:\OS_10_Custom\Boot\Boot\Mount\sources\zh-CN" -Destination "D:\OS_10\sources\zh-CN" -Recurse -Force
```

4.7. Regenerate Lang.ini

After regeneration, you can adjust the "Installation Interface", the order when selecting "Language", open lang.ini, the default preferred value = 3, non-default value = 2.

4.7.1. Regenerate the mounted directory lang.ini

Regenerated Lang.ini file location: `D:\en-us_windows_server_2022_x64_dvd_620d7eac_Custom\Boot\Boot\Mount\Sources\lang.ini`

```
Dism /image:"D:\OS_10_Custom\Boot\Boot\Mount" /gen-langini /distribution:"D:\OS_10_Custom\Boot\Boot\Mount"
```

4.7.2. After regenerating lang.ini, sync to the installer

Regenerated Lang.ini file location: `D:\en-us_windows_server_2022_x64_dvd_620d7eac\Sources\lang.ini`

```
Dism /image:"D:\OS_10_Custom\Boot\Boot\Mount" /gen-langini /distribution:"D:\OS_10"
```

5. Cumulative updates

To prepare the cumulative updates file available, change the example file name: `KB_Boot.cab`

5.1. Add

```
$KBPath = "D:\OS_10_Custom\Boot\Boot\Update\KB_Boot.cab"
```

```
Add-WindowsPackage -Path "D:\OS_10_Custom\Boot\Boot\Mount" -PackagePath $KBPath
```

5.2. Delete

```
$KBPath = "D:\OS_10_Custom\Boot\Boot\Update\KB_Boot.cab"
```

```
Remove-WindowsPackage -Path "D:\OS_10_Custom\Boot\Boot\Mount" -PackagePath $KBPath
```

5.3. Solid update

It cannot be uninstalled after curing, which cleans the recovery image and resets the basis of any superseded components.

```
Dism /image:"D:\OS_10_Custom\Boot\Boot\Mount" /cleanup-image /StartComponentCleanup /ResetBase
```

#### 5.3.1. Clean components after curing and updating

```
$Mount = "D:\OS_10_Custom\Boot\Boot\Mount"

Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {

    if ($_.PackageState -eq "Superseded") {

        Write-Host "  $($_.PackageName)" -ForegroundColor Green

        Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null

    }

}
```

#### 6. Drive

#### 7. Save image: Boot.wim

```
Save-WindowsImage -Path "D:\OS_10_Custom\Boot\Boot\Mount"
```

#### 8. Unmount image: Boot.wim

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowsImage -Path "D:\OS_10_Custom\Boot\Boot\Mount" -Discard
```

### IV Deployment engine

- Learn about "Automatically Adding Languages Installed in Windows Systems", learn: <https://github.com/ilikeyi/Multilingual>, how to download:
  - After entering the website, click "Code", "Download Compressed Package", and after the download is completed, you will get the [main.zip](#) compressed package file.
  - Go to the <https://github.com/ilikeyi/Multilingual/releases> download page, select the available version: [1.1.1.1](#), select the download source code format: zip, and get the [Multilingual-1.1.1.1.zip](#) compressed package file after the download is completed;
- Unzip the downloaded [main.zip](#) or [Multilingual-1.1.1.1.zip](#) to: [D:\Multilingual-1.1.1.1](#), and rename: [D:\Multilingual](#)
- Learn "[Unattended Windows Setup Reference](#)", Intervene in the installation process by leaving it unattended.

#### 1. Add method

##### 1.1. Add to ISO installation media

##### 1.1.1. Unattended

##### 1.1.1.1. Add to: [\[ISO\]:\Autounattend.xml](#)

Autounattend.xml interferes with the WinPE installer when booting an ISO installation.

Copy [D:\Multilingual\Learn\Unattend\Mul.Unattend.xml](#) to [D:\OS\\_10\Autounattend.xml](#)

```
Copy-Item "D:\Multilingual\Learn\Unattend\Mul.Unattend.xml" -Destination "D:\OS_10\Autounattend.xml" -Force
```

1.1.1.2. Add to: [ISO]:\Sources\Unattend.xml

When mounting or unpacking an ISO, after running the [ISO]:\Setup.exe installer, [ISO]:\Sources\Unattend.xml will intervene in the installation process.

Copy D:\Multilingual\Learn\Unattend\Mul.Unattend.xml to D:\OS\_10\Sources\Unattend.xml

```
Copy-Item "D:\Multilingual\Learn\Unattend\Mul.Unattend.xml" -Destination  
"D:\OS_10\Sources\Unattend.xml" -Force
```

1.1.1.3. Add to: [ISO]:\sources\\$OEM\$\\$\$\Panther\unattend.xml

Copy it to the system disk during the installation process, copy to: {system disk}\Windows\Panther\unattend.xml

1.1.1.3.1. Create \$OEM\$ path

```
New-Item -Path "D:\OS_10\sources\`$OEM$\`$$\Panther" -ItemType Directory
```

1.1.1.3.2. Copy

Copy D:\Multilingual\Learn\Unattend\Mul.Unattend.xml to  
D:\OS\_10\Sources\\$OEM\$\Panther\Unattend.xml

```
Copy-Item "D:\Multilingual\Learn\Unattend\Mul.Unattend.xml" -Destination  
"D:\OS_10\sources\`$OEM$\`$$\Panther\Unattend.xml" -Force
```

1.1.2. Deployment engine: add

Add "Automatically add installed languages for Windows systems" to D:\OS\_10\sources\\$OEM\$\\$1\Yi\Engine in the directory.

1.1.2.1. Deployment Engine: Copy

Copy D:\Multilingual\Engine to D:\OS\_10\Sources\\$OEM\$\\$1\Yi\Engine

```
Copy-Item "D:\Multilingual\Engine" -Destination "D:\OS_10\sources\`$OEM$\`$1\Yi\Engine" -Recurse -  
Force
```

1.1.2.2. Deployment engine: custom deployment tags

```
$Flag = @(
```

```
"Is_Mark_Sync" # Allow global search and synchronization of deployment tags
```

```
# Prerequisite deployment
```

```
# "Auto_Update" # Allow automatic updates
```

```
# "Use_UTF8" # Beta: Global language support using Unicode UTF-8
```

```
"Disable_Network_Location_Wizard" # Network Location Wizard
```

```
"Disable_Cleanup_Appx_Tasks" # Appx Cleanup and maintenance tasks
```

```
"Disable_Cleanup_On_Demand_Language" # Prevent cleanup of unused on-demand feature language  
packs
```

```
"Disable_Cleanup_Unsed_Language" # Prevent cleaning of unused language packs
```

```

"Prerequisites_Reboot" # Restart your computer

# Complete first deployment

# "Popup_Engine" # Allow the deployment engine main interface to pop up for the first time

# "Allow_First_Pre_Experience" # Allow first preview, as planned

"Reset_Execution_Policy" # Restore PowerShell execution policy: Restricted

"Clear_Solutions" # Delete the entire solution

"Clear_Engine" # Delete the deployment engine and keep the others

# "First_Experience_Reboot" # Restart your computer

)

ForEach ($Item in $Flag) {

    Write-host " $($Item)" -ForegroundColor Green

    New-Item -Path "D:\OS_10\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow" -ItemType Directory -
    ErrorAction SilentlyContinue | Out-Null

    Out-File -FilePath "D:\OS_10\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow\${$Item}" -Encoding utf8 -
    ErrorAction SilentlyContinue

}

```

## 1.2. Add to mounted

Through "[Customized deployment image: Install.wim](#)", execute "[Start mounting Install.wim](#)" and mount to:  
[D:\OS\\_10\\_Custom\Install\Install\Mount](#)

### 1.2.1. Unattended

Copy [D:\Multilingual\\\_Learn\Unattend\Mul.Unattend.xml](#) to  
[D:\OS\\_10\\_Custom\Install\Install\Mount\Panther\Unattend.xml](#)

```

Copy-Item "D:\Multilingual\_Learn\Unattend\Mul.Unattend.xml" -Destination
"D:\OS_10_Custom\Install\Install\Mount\Panther" -Force

```

### 1.2.2. Deployment engine: add

Add "[Automatically add languages installed on Windows systems](#)" to the  
[D:\OS\\_10\\_Custom\Install\Install\Mount\Yi\Engine](#) directory.

#### 1.2.2.1. Deployment Engine: Copy

Copy [D:\Multilingual\Engine](#) to [D:\OS\\_10\\_Custom\Install\Install\Mount\Yi\Engine](#)

```

Copy-Item "D:\Multilingual\Engine" -Destination "D:\OS_10_Custom\Install\Install\Mount\Yi\Engine" -
Recurse -Force

```

#### 1.2.2.2. Deployment engine: custom deployment tags

```

$Flag = @(

```

```

"Is_Mark_Sync" # Allow global search and synchronization of deployment tags

# Prerequisite deployment

# "Auto_Update" # Allow automatic updates

# "Use_UTF8" # Beta: Global language support using Unicode UTF-8

"Disable_Network_Location_Wizard" # Network Location Wizard

"Disable_Cleanup_Appx_Tasks" # Appx Cleanup and maintenance tasks

"Disable_Cleanup_On_Demand_Language" # Prevent cleanup of unused on-demand feature language
packs

"Disable_Cleanup_Unsed_Language" # Prevent cleaning of unused language packs

"Prerequisites_Reboot" # Restart your computer

# Complete first deployment

# "Popup_Engine" # Allow the deployment engine main interface to pop up for the first time

# "Allow_First_Pre_Experience" # Allow first preview, as planned

"Reset_Execution_Policy" # Restore PowerShell execution policy: Restricted

"Clear_Solutions" # Delete the entire solution

"Clear_Engine" # Delete the deployment engine and keep the others

# "First_Experience_Reboot" # Restart your computer

)

ForEach ($item in $Flag) {

    Write-host " $($item)" -ForegroundColor Green

    New-Item -Path "D:\OS_10\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow" -ItemType Directory -
ErrorAction SilentlyContinue | Out-Null

    Out-File -FilePath "D:\OS_10\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow\$( $item)" -Encoding utf8 -
ErrorAction SilentlyContinue

}

```

## 2. Deployment Engine: Advanced

### 2.1. Deployment engine: adding process

After copying the deployment engine, you can add deployment tags to intervene in the installation process.

### 2.2. Unattended solution

When the customization is unattended, please modify it simultaneously if the following files exist:

- [D:\OS\\_10\Autounattend.xml](#)
- [D:\OS\\_10\Sources\Unattend.xml](#)
- [D:\OS\\_10\sources\\\$OEM\\$\\\$\\$\Panther\unattend.xml](#)
- [D:\OS\\_10\\_Custom\Install\Install\Mount\Panther\Unattend.xml](#)

### 2.2.1. Multilingual or monolingual

In multi-language and monolingual, you can switch between each other. When replacing, please replace all the same ones in the file.

#### 2.2.1.1. Multi-language

```
<UILanguage>%OSDUILanguage%</UILanguage>

<InputLocale>%OSDInputLocale%</InputLocale>

<SystemLocale>%OSDSystemLocale%</SystemLocale>

<UILanguage>%OSDUILanguage%</UILanguage>

<UILanguageFallback>%OSDUILanguageFallback%</UILanguageFallback>

<UserLocale>%OSDUserLocale%</UserLocale>
```

#### 2.2.1.2. Monolingual

A single language needs to specify a Region tag, for example, specify a Region tag: **zh-CN**

```
<UILanguage>zh-CN</UILanguage>

<InputLocale>zh-CN</InputLocale>

<SystemLocale>zh-CN</SystemLocale>

<UILanguage>zh-CN</UILanguage>

<UILanguageFallback>zh-CN</UILanguageFallback>

<UserLocale>zh-CN</UserLocale>
```

### 2.2.2. User plan

By default, the self-created user **Administrator** is used and logged in automatically. It can be switched by modifying the following configuration: self-created or customized user.

#### 2.2.2.1. Self-created user Administrator

By default, the self-created user: **Administrator** is used and logged in automatically, inserted between **<OOBE>** and **</OOBE>**.

```
<UserAccounts>

<LocalAccounts>

<LocalAccount wcm:action="add">

<Password>

<Value></Value>

<PlainText>true</PlainText>

</Password>

<Description>Administrator</Description>
```



```

        <DisplayName>Administrator</DisplayName>

        <Group>Administrators</Group>

        <Name>Administrator</Name>

    </LocalAccount>

</LocalAccounts>

</UserAccounts>

<AutoLogon>

    <Password>

        <Value></Value>

        <PlainText>true</PlainText>

    </Password>

    <Enabled>true</Enabled>

    <Username>Administrator</Username>

</AutoLogon>

```

#### 2.2.2.2. Custom user

After setting up a custom user and installing the system, in OOBE, you can choose settings such as local and online users.

##### 2.2.2.2.1. Delete

Username: Removed from start `<UserAccounts>` to `</UserAccounts>`

Autologin: Remove from start `<AutoLogon>` to `</AutoLogon>`

##### 2.2.2.2.2. Replace

From the beginning `<OOBE>` to `</OOBE>`

```
<OOBE>
```

```
    <ProtectYourPC>3</ProtectYourPC>
```

```
    <HideEULAPage>true</HideEULAPage>
```

```
    <HideWirelessSetupInOOBE>true</HideWirelessSetupInOOBE>
```

```
</OOBE>
```

## D. Generate ISO

### 1. Download OScdimg

Select the Oscding version according to the architecture, and save it to: `D:\` after downloading. To save in other paths, please enter the absolute path of OScdimg.exe;

- 1.1.

x64

[https://github.com/ilikeyi/solutions/raw/main/\\_Software/Oscdimg/amd64/oscdimg.exe](https://github.com/ilikeyi/solutions/raw/main/_Software/Oscdimg/amd64/oscdimg.exe)
- 1.2.

x86

[https://github.com/ilikeyi/solutions/raw/main/\\_Software/Oscdimg/x86/oscdimg.exe](https://github.com/ilikeyi/solutions/raw/main/_Software/Oscdimg/x86/oscdimg.exe)
- 1.3.

arm64

[https://github.com/ilikeyi/solutions/raw/main/\\_Software/Oscdimg/arm64/oscdimg.exe](https://github.com/ilikeyi/solutions/raw/main/_Software/Oscdimg/arm64/oscdimg.exe)

2. Use the oscdimg command line to generate an ISO file and save it to: D:\OS\_10.iso
- ISO.ps1

○ \Expand\ISO.ps1

[https://github.com/ilikeyi/solutions/blob/main/\\_Learn/Packaging/tutorial/OS.10/22H2/Expand/ISO.ps1](https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging/tutorial/OS.10/22H2/Expand/ISO.ps1)
- Copy the code

```
$Oscdimg = "D:\Oscdimg.exe"

$ISO = "D:\OS_10"

$Volume = "OS_10"

$SaveTo = "D:\OS_10.iso"

$Arguments = @("-m", "-o", "-u2", "-udfver102", "-l"`${$Volume}`"", "-bootdata:2#p0,e,b"`${$ISO}\boot\etfsboot.com`""#pEF,e,b"`${$ISO}\efi\microsoft\boot\efisys.bin`"", $ISO, $SaveTo)

Start-Process -FilePath $Oscdimg -ArgumentList $Arguments -wait -nonewwindow
```

Chapter 2

Report

- Group abbreviations:
- Group A: Windows 10 Education, Windows 10 Enterprise, Windows 10 Pro Education, Windows 10 Pro for Workstations, Windows 10 IoT Enterprise

• Group B: Windows 10 Education N, Windows 10 Enterprise N, Windows 10 Pro, Windows 10 Pro N, Windows 10 Pro Education N, Windows 10 Pro N for Workstations

• Group C: Windows 10 Home, Windows 10 Home Single Language

• Group D: Windows 10 Home N

II

Reports: Different versions

1.

Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~amd64~~10.0.19041.2006

A, C
2.

Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~~10.0.19041.1806

A, B

Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.1
3.

Microsoft-Windows-Printing-WFS-FoD-Package~31bf3856ad364e35~amd64~~10.0.19041.2006

A, B, C, D

	Microsoft-Windows-Printing-WFS-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.906	
4.	Microsoft-OneCore-ApplicationModel-Sync-Desktop-FOD-Package~31bf3856ad364e35~amd64~~10.0.19041.1949	A, B, C, D
5.	Microsoft-OneCore-DirectX-Database-FOD-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
6.	Microsoft-Windows-Client-LanguagePack-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.2006	A, B, C, D
7.	Microsoft-Windows-FodMetadata-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
8.	Microsoft-Windows-Foundation-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
9.	Microsoft-Windows-Hello-Face-Migration-Package~31bf3856ad364e35~amd64~~10.0.19041.1889	A, B, C, D
10.	Microsoft-Windows-Hello-Face-Package~31bf3856ad364e35~amd64~~10.0.19041.1889	A, B, C, D
11.	Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~~11.0.19041.1566	A, B, C, D
12.	Microsoft-Windows-LanguageFeatures-Basic-en-us-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
13.	Microsoft-Windows-LanguageFeatures-Handwriting-en-us-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
14.	Microsoft-Windows-LanguageFeatures-OCR-en-us-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
15.	Microsoft-Windows-LanguageFeatures-Speech-en-us-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
16.	Microsoft-Windows-LanguageFeatures-TextToSpeech-en-us-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
17.	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~amd64~~10.0.19041.746	A, B, C, D
	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.1	A, B, C, D
18.	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~~10.0.19041.1	A, B, C, D
	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.19041.1	A, B, C, D
19.	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~amd64~~10.0.19041.1865	A, B, C, D
	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.488	A, B, C, D
20.	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~~10.0.19041.1	A, B, C, D
	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.19041.1	A, B, C, D
21.	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~~10.0.19041.1	A, B, C, D
	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.1	A, B, C, D
22.	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~~10.0.19041.1	A, B, C, D
	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~en-US~10.0.19041.1	A, B, C, D
23.	Microsoft-Windows-QuickAssist-Package~31bf3856ad364e35~amd64~~10.0.19041.1949	A, B, C, D
24.	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~~10.0.19041.746	A, B, C, D
	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.1	A, B, C, D
25.	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~~10.0.19041.1	A, B, C, D
	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~en-US~10.0.19041.1	A, B, C, D
26.	Microsoft-Windows-TabletPCMath-Package~31bf3856ad364e35~amd64~~10.0.19041.1865	A, B, C, D
27.	Microsoft-Windows-UserExperience-Desktop-Package~31bf3856ad364e35~amd64~~10.0.19041.1741	A, B, C, D
28.	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~~10.0.19041.1682	A, B, C, D

	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.19041.1	A, B, C, D
29.	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~~10.0.19041.1	A, B, C, D
	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.19041.1	A, B, C, D
30.	OpenSSH-Client-Package~31bf3856ad364e35~amd64~~10.0.19041.964	A, B, C, D
31.	Package_for_DotNetRollup~31bf3856ad364e35~amd64~~10.0.4556.3	A, B, C, D
32.	Package_for_KB5015684~31bf3856ad364e35~amd64~~19041.1799.1.2	A, B, C, D
33.	Package_for_RollupFix~31bf3856ad364e35~amd64~~19041.2006.1.7	A, B, C, D
34.	Package_for_ServicingStack_1704~31bf3856ad364e35~amd64~~19041.1704.1.4	A, B, C, D
35.	Package_for_ServicingStack_1940~31bf3856ad364e35~amd64~~19041.1940.1.0	A, B, C, D

III Report: Language installation packages apply to Install.wim

1.	Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B
	Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
2.	Microsoft-Windows-LanguageFeatures-Fonts-Hans-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-Fonts-Hans-Package~31bf3856ad364e35~amd64~~10.0.19041.1	
3.	Microsoft-Windows-Client-Language-Pack_x64_zh-CN.cab	A, B, C, D
	Microsoft-Windows-Client-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
4.	Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~zh-CN~11.0.19041.1	
5.	Microsoft-Windows-LanguageFeatures-Basic-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-Basic-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.19041.1	
6.	Microsoft-Windows-LanguageFeatures-Handwriting-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-Handwriting-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.19041.1	
7.	Microsoft-Windows-LanguageFeatures-OCR-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-OCR-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.19041.1	
8.	Microsoft-Windows-LanguageFeatures-Speech-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-Speech-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.19041.1	
9.	Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.19041.1	
10.	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	

11.	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.19041.1	
12.	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
13.	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.19041.1	
14.	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
15.	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.19041.1	
16.	Microsoft-Windows-Printing-WFS-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-Printing-WFS-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
17.	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
18.	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~zh-CN~10.0.19041.1	
19.	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1	
20.	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.19041.1	

IV Report: Language installation packages apply to WinRE.wim

1.	WinPE-FontSupport-zh-CN.cab
	Microsoft-Windows-WinPE-FontSupport-ZH-CN-Package~31bf3856ad364e35~amd64~~10.0.19041.1
2.	lp.cab
	Microsoft-Windows-WinPE-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
3.	winpe-appxpackaging_zh-CN.cab
	Microsoft-Windows-WinPE-AppxPackaging-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
4.	winpe-atbroker_zh-CN.cab

- WinPE-ATBroker-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
5. winpe-audiocore\_zh-CN.cab
- WinPE-AudioCore-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
6. winpe-audiodrivers\_zh-CN.cab
- WinPE-AudioDrivers-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
7. winpe-enhancedstorage\_zh-CN.cab
- WinPE-EnhancedStorage-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
8. winpe-hta\_zh-CN.cab
- WinPE-HTA-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
9. winpe-narrator\_zh-CN.cab
- WinPE-Narrator-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
10. winpe-opcservices\_zh-CN.cab
- WinPE-OpcServices-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
11. winpe-rejuv\_zh-CN.cab
- WinPE-Rejuv-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
12. winpe-scripting\_zh-CN.cab
- WinPE-Scripting-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
13. winpe-securestartup\_zh-CN.cab
- WinPE-SecureStartup-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
14. winpe-speech-tts\_zh-CN.cab
- WinPE-Speech-TTS-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
15. winpe-srh\_zh-CN.cab
- WinPE-SRH-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
16. winpe-srt\_zh-CN.cab
- WinPE-SRT-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
17. winpe-storagewmi\_zh-CN.cab
- WinPE-StorageWMI-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1
18. winpe-wds-tools\_zh-CN.cab
- WinPE-WDS-Tools-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1

19. winpe-wifi\_zh-CN.cab

[WinPE-WiFi-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1](#)

20. winpe-wmi\_zh-CN.cab

[WinPE-WMI-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1](#)

V Report: Language installation packages apply to Boot.wim

1. WinPE-FontSupport-zh-CN.cab

[Microsoft-Windows-WinPE-FontSupport-ZH-CN-Package~31bf3856ad364e35~amd64~~10.0.19041.1](#)

2. lp.cab

[Microsoft-Windows-WinPE-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1](#)

3. winpe-atbroker\_zh-CN.cab

[WinPE-ATBroker-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1](#)

4. winpe-audiocore\_zh-CN.cab

[WinPE-AudioCore-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1](#)

5. winpe-audiodrivers\_zh-CN.cab

[WinPE-AudioDrivers-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1](#)

6. winpe-enhancedstorage\_zh-CN.cab

[WinPE-EnhancedStorage-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1](#)

7. winpe-narrator\_zh-CN.cab

[WinPE-Narrator-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1](#)

8. winpe-scripting\_zh-CN.cab

[WinPE-Scripting-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1](#)

9. winpe-securestartup\_zh-CN.cab

[WinPE-SecureStartup-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1](#)

10. WINPE-SETUP-CLIENT\_zh-CN.CAB

[WinPE-Setup-Client-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1](#)

11. WinPE-Setup\_zh-CN.cab

[WinPE-Setup-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1](#)

12. winpe-speech-tts\_zh-CN.cab

WinPE-Speech-TTS-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1

13. winpe-srh\_zh-CN.cab

WinPE-SRH-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1

14. winpe-srt\_zh-CN.cab

WinPE-SRT-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1

15. winpe-wds-tools\_zh-CN.cab

WinPE-WDS-Tools-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1

16. winpe-wmi\_zh-CN.cab

WinPE-WMI-Package~31bf3856ad364e35~amd64~zh-CN~10.0.19041.1

Chapter 3 Common problem

II Clean all mounts to

Close any applications that may be accessing files in the image, including File Explorer.

Dismount-WindowsImage -Path "D:\OS\_10\_Custom\Install\Install\Mount" -Discard

Dismount-WindowsImage -Path "D:\OS\_10\_Custom\Install\WinRE\Mount" -Discard

Dismount-WindowsImage -Path "D:\OS\_10\_Custom\Boot\Boot\Mount" -Discard

III Fix the problem of abnormal mounting

1. View mounted

Get-WindowsImage -Mounted

2. Delete the DISM mount record saved in the registry

Remove-Item -Path "HKLM:\SOFTWARE\Microsoft\WIMMount\Mounted Images\\*" -Force -Recurse -ErrorAction SilentlyContinue

3. Delete all resources associated with the corrupted mounted image

Clear-WindowsCorruptMountPoint

Dism /cleanup-wim

IV Clean directories

Remove-Item "D:\OS\_10\_Custom" -Force -Recurse

Remove-Item "D:\OS\_10\Sources\`\$OEM\$" -Force -Recurse

Remove-Item -Path "D:\OS\_10\Autounattend.xml" -Force

Remove-Item -Path "D:\OS\_10\Sources\Unattend.xml" -Force



Chapter 4      Known issues

None yet



Author: Yi

Website: <https://fengyi.tel>

Email: [775159955@qq.com](mailto:775159955@qq.com), [ilikeyi@outlook.com](mailto:ilikeyi@outlook.com)

Document version: 1.0

Documentation model: Full version

Translation: Chinese to English version

Updated: 2024 - 4

Suggestions or feedback: <https://github.com/ilikeyi/solutions/issues>