

WINDOWS 11 22H2

Different system versions have different packaging methods. The packaging process includes: "Language pack: add, associate, delete", "Driver: add, delete", "Cumulative update: add, delete", "InBox Appx: add, Update, mark" etc.

There are many hidden stories hidden behind this. If you want to unlock these, are you ready to start trying to encapsulate them?

TABLE OF CONTENTS

One.

Deployment image

A.

Prerequisites

B.

Language Pack: Extraction

C.

Customize the deployment image

D.

ISO

One.

Common problem

Two.

Known issues

Three.

Components: All packages installed in the image, Comparison

ONE. DEPLOYMENT IMAGE

A.

Prerequisites

II

ISO tools

Use a software that can edit ISO files, such as: [PowerISO](#), [DAEMON Tools](#), [ISO Workshop](#);

III

Get related packages

Learn "[Attachment: OS](#)" and view the "[Windows 11](#)" item.

1.

System installation package

1.1.

Prepare: [en-us_windows_11_business_editions_version_22h2_x64_dvd_17a08ce3.iso](#)

1.2.

Unzip to: [D:\en-us_windows_11_business_editions_version_22h2_x64_dvd_17a08c](#)

1.3.

After decompression is complete, change the directory [en-us_windows_11_business_editions_version_22h2_x64_dvd_17a08c](#) change to [D:\OS11](#)

1.4.

All scripts and all paths are set to [D:\OS11](#) as the image source.

2.

Language pack

2.1.

Learn

1.1.1.

[Add languages to a Windows 11 image](#)

1.1.2.

[Language and region Features on Demand \(FOD\)](#)

1.1.2.1.

Regional association

What are regional connections?

- When the image language is only in English, after adding the [zh-HK](#) language pack, the image language will not be added. You should install [zh-TW](#) first, and then install [zh-HK](#) to obtain the corresponding association.
- Please refer to Microsoft's official original version: Windows 10, Windows 11 Traditional Chinese version.

Known regional associations:

1.1.2.1.1. Region: [zh-TW](#) , Optional associated areas: [zh-HK](#)

1.1.2.2. **Fonts**

When adding a language pack, when the corresponding region is triggered, the required font functions need to be added, download "[List of all available language FODs](#)" learn more.

In "[Language Pack: Extraction](#)", the automatic recognition function has been added, and you can understand the functions: [Function Match_Required_Fonts](#)

1.1.2.3. **Other region-specific requirements**

1.1.2.3.1. Region: [zh-TW](#), Package: [Microsoft-Windows-InternationalFeatures-Taiwan-Package~31bf3856ad364e35~amd64~~.cab](#)

Description: [Supplemental support for Taiwan date formatting requirements. Package will be provided to customers located in Taiwan.](#)

Recommendation: [Preinstall only on devices shipping to the Taiwan market. Not installing this capability on devices causes any API calls to that use the Taiwan calendar to fail.](#)

When triggering a known area, a specific "package" needs to be added.

THERE IS CONTROVERSY:

- During the test, it was found that this package was not installed in the original image of Microsoft's official original Windows 10 and Windows 11. However, there are known issues in the recommended items. In the end, it is consistent with the official Microsoft original version, and the packager can freely choose to install it. or not.

2.2. **Language pack: Download**

[22621.1.220506-1250.ni_release_amd64fre_CLIENT_LOF_PACKAGES_OEM.iso](#)

2.3. **Language pack: Fixed**

Select any website and open:

- <https://uupdump.net>
- <https://uup.ee>

2.3.1. After opening, search for keywords: [22621.382](#), select from the search results: [Windows 11, version 22H2 \(22621.382\) amd64](#)

- 2.3.2. After opening, select "[All files](#)";
- 2.3.3. Search the green part in the "[All Files](#)" page and download:
 - 2.3.3.1. Applies to: Install.wim (1 item)
 - 2.3.3.1.1. [Media](#)
 - 2.3.3.2. Applies to: WinRE.wim, none yet
 - 2.3.3.3. Applies to: Boot.wim, none yet
- 2.3.4. After downloading all the files, scroll to the bottom of the page, download and run "[Generate Rename Script \(Windows\)](#)"
- 2.4. Use ISO editing software, edit [22621.1.220506-1250.ni_release_amd64fre_CLIENT_LOF_PACKAGES_OEM.iso](#), and add the downloaded file to the [\[ISO\]:\LanguagesAndOptionalFeatures](#) directory;

3. **InBox Apps**

- 3.1. Download: [22621.1778.230511-2102.ni_release_svc_prod3_amd64fre_InboxApps.iso](#)
- 3.2. Download: [22621.1.220506-1250.ni_release_amd64fre_InboxApps.iso](#) finally, extract the following files and save them to the desktop:
 - 3.2.1. [Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.x64.appx](#)
 - 3.2.2. [Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.x64.xml](#)
- 3.3. Use the ISO editing tool to edit [22621.1778.230511-2102.ni_release_svc_prod3_amd64fre_InboxApps.iso](#) and add the extracted files to the [\[ISO\]:\packages](#) directory;

IV When running the PS command line:

1. Optional "Terminal" or "PowerShell ISE", if "Terminal" is not installed, please go to: <https://github.com/microsoft/terminal/releases> After downloading;
2. Open "Terminal" or "PowerShell ISE" as administrator, it is recommended to set the PowerShell execution policy: bypass, PS command line:


```
Set-ExecutionPolicy -ExecutionPolicy Bypass -Force
```
3. In this article, PS command line, green part, please copy it, paste it into the "Terminal" dialog box, press Enter and start running;
4. When there is [.ps1](#), right-click the file and select Run with PowerShell, or copy the path and paste it into Terminal to run.

B. **Language Pack: Extraction**

II **Prepare the language pack**

Mount [22621.1.220506-1250.ni_release_amd64fre_CLIENT_LOF_PACKAGES_OEM.iso](#) or unzipped to any location;

III **Extract language pack scheme**

1. **Add**

1.1. Language name: **Simplified Chinese - China**, Regio: **zh-CN**, Scope of application: **Install.Wim**, **Boot.Wim**, **WinRE.Wim**

2. **Delete**

2.1. Language name: **English - United States**, Regio: **en-US**, Scope of application: **Install.Wim**, **Boot.Wim**, **WinRE.Wim**

IV **Execute the extract command**

- **Auto** = automatically search all local disks, default;
- Customize the path, for example, specify the E drive: **\$ISO = "E:\"**

Copy the code or view the source file: **Extract.ps1** ([Local](#), [Github](#))

```
$ISO = "Auto"
$SaveTo = "D:\OS11_Custom"
$Extract_language_Pack = @(
    @{ Tag = "zh-CN"; Act = "Add"; Scope = @( "Install\Install"; "Install\WinRE"; "Boot\Boot" ) }
    @{ Tag = "en-US"; Act = "Del"; Scope = @( "Install\Install"; "Install\WinRE"; "Boot\Boot" ) }
)

Function Extract_Language
{
    param( $Act, $NewLang, $Expand )

    Function Match_Required_Fonts
    {
        param( $Lang )

        $Fonts = @(
            @{ Match = @("as", "ar-SA", "ar", "ar-AE", "ar-BH", "ar-DJ", "ar-DZ", "ar-EG", "ar-ER", "ar-IL", "ar-IQ", "ar-JO", "ar-KM", "ar-KW", "ar-LB", "ar-
LY", "ar-MA", "ar-MR", "ar-OM", "ar-PS", "ar-QA", "ar-SD", "ar-SO", "ar-SS", "ar-SY", "ar-TD", "ar-TN", "ar-YE", "arz-Arab", "ckb-Arab", "fa", "fa-AF",
"fa-IR", "glk-Arab", "ha-Arab", "ks-Arab", "ks-Arab-IN", "ku-Arab", "ku-Arab-IQ", "mzn-Arab", "pa-Arab", "pa-Arab-PK", "pnb-Arab", "prs", "prs-AF",
"prs-Arab", "ps", "ps-AF", "sd-Arab", "sd-Arab-PK", "tk-Arab", "ug", "ug-Arab", "ug-CN", "ur", "ur-IN", "ur-PK", "uz-Arab", "uz-Arab-AF"); Name =
"Arab"; }
            @{ Match = @("bn-IN", "as-IN", "bn", "bn-BD", "bpy-Beng"); Name = "Beng"; }
            @{ Match = @("da-dk", "iu-Cans", "iu-Cans-CA"); Name = "Cans"; }
            @{ Match = @("chr-Cher-US", "chr-Cher"); Name = "Cher"; }
            @{ Match = @("hi-IN", "bh-Deva", "brx", "brx-Deva", "brx-IN", "hi", "ks-Deva", "mai", "mr", "mr-IN", "ne", "ne-IN", "ne-NP", "new-Deva", "pi-
Deva", "sa", "sa-Deva", "sa-IN"); Name = "Deva"; }
            @{ Match = @("am", "am-ET", "byn", "byn-ER", "byn-Ethi", "ti", "ti-ER", "ti-ET", "tig", "tig-ER", "tig-Ethi", "ve-Ethi", "wal", "wal-ET", "wal-Ethi");
Name = "Ethi"; }
            @{ Match = @("gu", "gu-IN"); Name = "Gujr"; }
            @{ Match = @("pa", "pa-IN", "pa-Guru"); Name = "Guru"; }
            @{ Match = @("zh-CN", "cmn-Hans", "gan-Hans", "hak-Hans", "wuu-Hans", "yue-Hans", "zh-gan-Hans", "zh-hak-Hans", "zh-Hans", "zh-SG",
"zh-wuu-Hans", "zh-yue-Hans"); Name = "Hans"; }
            @{ Match = @("zh-TW", "cmn-Hant", "hak-Hant", "lzh-Hant", "zh-hak-Hant", "zh-Hant", "zh-HK", "zh-lzh-Hant", "zh-MO", "zh-yue-Hant");
Name = "Hant"; }
            @{ Match = @("he", "he-IL", "yi"); Name = "Hebr"; }
            @{ Match = @("ja", "ja-JP"); Name = "Jpan"; }
            @{ Match = @("km", "km-KH"); Name = "Khmr"; }
```

```

@{ Match = @("kn", "kn-IN"); Name = "Knda"; }
@{ Match = @("ko", "ko-KR"); Name = "Kore"; }
@{ Match = @("de-de", "lo", "lo-LA"); Name = "Lao"; }
@{ Match = @("ml", "ml-IN"); Name = "Mlym"; }
@{ Match = @("or", "or-IN"); Name = "Orya"; }
@{ Match = @("si", "si-LK"); Name = "Sinh"; }
@{ Match = @("tr-tr", "arc-Syrc", "syr", "syr-SY", "syr-Syrc"); Name = "Syrc"; }
@{ Match = @("ta", "ta-IN", "ta-LK", "ta-MY", "ta-SG"); Name = "Taml"; }
@{ Match = @("te", "te-IN"); Name = "Telu"; }
@{ Match = @("th", "th-TH"); Name = "Thai"; }
)

```

```

ForEach ($item in $Fonts) {
    if (($item.Match) -Contains $Lang) {
        return $item.Name
    }
}

```

```

return "Not_matched"
}

```

Function Match_Other_Region_Specific_Requirements

```

{
    param( $Lang )

    $Fonts = @(
        @{ Match = @("zh-TW"); Name = "Taiwan"; }
    )
}

```

```

ForEach ($item in $Fonts) {
    if (($item.Match) -Contains $Lang) {
        return $item.Name
    }
}

```

```

return "Skip_specific_packages"
}

```

Function Extract_Process

```

{
    param( $Package, $Name, $NewSaveTo )

    $NewSaveTo = "$($SaveTo)\$($NewSaveTo)\Language\$($Act)\$($NewLang)"
    New-Item -Path $NewSaveTo -ItemType Directory -ErrorAction SilentlyContinue | Out-Null

    if ($ISO -eq "Auto"){
        Get-PSDrive -PSProvider FileSystem -ErrorAction SilentlyContinue | ForEach-Object {
            ForEach ($item in $Package) {
                $TempFilePath = Join-Path -Path $_.Root -ChildPath $item -ErrorAction SilentlyContinue

                if (Test-Path $TempFilePath -PathType Leaf) {
                    Write-host "`n Find: " -NoNewLine; Write-host $TempFilePath -ForegroundColor Green
                    Write-host " Copy to: " -NoNewLine; Write-host $NewSaveTo
                    Copy-Item -Path $TempFilePath -Destination $NewSaveTo -Force
                }
            }
        }
    } else {

```

```

ForEach ($item in $Package) {
    $TempFilePath = Join-Path -Path $ISO -ChildPath $item -ErrorAction SilentlyContinue

    Write-host "`n Find: " -NoNewLine; Write-host $TempFilePath -ForegroundColor Green
    if (Test-Path $TempFilePath -PathType Leaf) {
        Write-host " Copy to: " -NoNewLine; Write-host $NewSaveTo
        Copy-Item -Path $TempFilePath -Destination $NewSaveTo -Force
    } else {
        Write-host " Not found"
    }
}

Write-host "`n Verify the language pack file"
ForEach ($item in $Package) {
    $Path = "$($NewSaveTo)\${[IO.Path]::GetFileName($item)}"

    if (Test-Path $Path -PathType Leaf) {
        Write-host " Discover: " -NoNewLine; Write-host $Path -ForegroundColor Green
    } else {
        Write-host " Not found: " -NoNewLine; Write-host $Path -ForegroundColor Red
    }
}

$AdvLanguage = @(
    @{
        Path = "Install\Install"
        Rule = @(
            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Fonts-{DiyLang}-Package~31bf3856ad364e35~AMD64~~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-Client-Language-Pack_x64_{Lang}.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Basic-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Handwriting-{Lang}-
Package~31bf3856ad364e35~AMD64~~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-OCR-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Speech-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-TextToSpeech-{Lang}-
Package~31bf3856ad364e35~AMD64~~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-MediaPlayer-Package-AMD64-{Lang}.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-MediaPlayer-Package-wow64-{Lang}.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~{Lang}~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"
            "LanguagesAndOptionalFeatures\Microsoft-Windows-InternationalFeatures-{Specific}-Package~31bf3856ad364e35~amd64~~.cab"
        )
    }
)
@{
    Path = "Install\WinRE"
    Rule = @(

```

```

"Windows Preinstallation Environment\x64\WinPE_OC\WinPE-FontSupport-{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\lp.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-securestartup_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-atbroker_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiocore_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiodrivers_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-enhancedstorage_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-narrator_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-scripting_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-speech-tts_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srh_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srt_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wds-tools_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wmi_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-appxdeployment_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-appxpackaging_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-storagewmi_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wifi_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-windowsupdate_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-rejuv_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-opcservices_{Lang}.cab"
"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-hta_{Lang}.cab"
)
}
@{
    Path = "Boot\Boot"

    Rule = @(
        "Windows Preinstallation Environment\x64\WinPE_OC\WinPE-FontSupport-{Lang}.cab"
        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\lp.cab"
        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\WinPE-Setup_{Lang}.cab"
        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\WINPE-SETUP-CLIENT_{Lang}.CAB"
        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-securestartup_{Lang}.cab"
        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-atbroker_{Lang}.cab"
        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiocore_{Lang}.cab"
        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiodrivers_{Lang}.cab"
        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-enhancedstorage_{Lang}.cab"
        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-narrator_{Lang}.cab"
        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-scripting_{Lang}.cab"
        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-speech-tts_{Lang}.cab"
        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srh_{Lang}.cab"
        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srt_{Lang}.cab"
        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wds-tools_{Lang}.cab"
        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wmi_{Lang}.cab"
    )
}
)

$NewFonts = Match_Required_Fonts -Lang $NewLang
$SpecificPackage = Match_Other_Region_Specific_Requirements -Lang $NewLang

Foreach ($item in $Expand) {
    $Language = @()

    Foreach ($itemList in $AdvLanguage) {
        if ($itemList.Path -eq $item) {
            Foreach ($PrintLang in $itemList.Rule) {
                $Language += "$($PrintLang)".Replace("{Lang}", $NewLang).Replace("{DiyLang}", $NewFonts).Replace("{Specific}", $SpecificPackage)
            }
        }
    }
}

```

```

        Extract_Process -NewSaveTo $ItemList.Path -Package $Language -Name $item
    }
}
}
}

ForEach ($item in $Extract_language_Pack) {
    Extract_Language -Act $item.Act -NewLang $item.Tag -Expand $item.Scope
}

```

C. Customize the deployment image

II Custom deployment image: Install.wim

1. View Install.wim details

Image name, image description, image size, architecture, version, index number, etc.

```

$ViewFile = "D:\OS11\Sources\Install.wim"
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object {
    Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex
}

```

LOOP OPERATING AREA, START,

2. Specify the path to mount Install.wim

```
New-Item -Path "D:\OS11_Custom\Install\Install\Mount" -ItemType directory -ea SilentlyContinue
```

3. Start mounting Install.wim

Default index number: 1

```
Mount-WindowsImage -ImagePath "D:\OS11\sources\install.wim" -Index "1" -Path "D:\OS11_Custom\Install\Install\Mount"
```

PROCESS FILES WITHIN THE INSTALL.WIM IMAGE, OPTIONALLY, START,

3.1. Custom deployment image: WinRE.wim

WARNING:

- WinRE.wim is a file within the Install.wim image;
- When Install.wim has multiple index numbers, only process any WinRE.wim;
- Synchronize to all index numbers to reduce the size of Install.wim; learn "[How to batch replace WinRE.wim in all index numbers in Install.wim](#)".

3.1.1. View WinRE.wim details

Image name, image description, image size, architecture, version, index number, etc.

```

$ViewFile = "D:\OS11_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object {
    Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex
}

```


3.1.2. Specify the path to mount WinRE.wim

```
New-Item -Path "D:\OS11_Custom\Install\WinRE\Mount" -ItemType directory -ea SilentlyContinue
```

3.1.3. Start mounting WinRE.wim

Default index number: 1

```
Mount-WindowsImage -ImagePath "D:\OS11_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"
-Index "1" -Path "D:\OS11_Custom\Install\WinRE\Mount"
```

3.1.4. Language pack

Automatically install language packs: Get "Component: All installed packages in the image" and match them. After matching the corresponding names, install the local corresponding language pack files.

3.1.4.1. Language pack: add

Copy the code or view the source file: [WinRE.Instl.lang.ps1](#) ([Local](#), [Github](#))

```
$Mount = "D:\OS11_Custom\Install\WinRE\Mount"
$Sources = "D:\OS11_Custom\Install\WinRE\Language\Add\zh-CN"

$Initl_install_Language_Component = @()
Get-WindowsPackage -Path $Mount | ForEach-Object {
    $Initl_install_Language_Component += $_.PackageName
}

Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\WinPE-FontSupport-zh-CN.cab"

$Language_List = @(
    @{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }
    @{ Match = "*SecureStartup*"; File = "winpe-securestartup_zh-CN.cab"; }
    @{ Match = "*ATBroker*"; File = "winpe-atbroker_zh-CN.cab"; }
    @{ Match = "*AudioCore*"; File = "winpe-audiocore_zh-CN.cab"; }
    @{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_zh-CN.cab"; }
    @{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_zh-CN.cab"; }
    @{ Match = "*Narrator*"; File = "winpe-narrator_zh-CN.cab"; }
    @{ Match = "*scripting*"; File = "winpe-scripting_zh-CN.cab"; }
    @{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_zh-CN.cab"; }
    @{ Match = "*srh*"; File = "winpe-srh_zh-CN.cab"; }
    @{ Match = "*srt*"; File = "winpe-srt_zh-CN.cab"; }
    @{ Match = "*wds-tools*"; File = "winpe-wds-tools_zh-CN.cab"; }
    @{ Match = "*-WMI-Package*"; File = "winpe-wmi_zh-CN.cab"; }
    @{ Match = "*WinPE-AppxPackaging*"; File = "winpe-appxpackaging_zh-CN.cab"; }
    @{ Match = "*StorageWMI*"; File = "winpe-storagewmi_zh-CN.cab"; }
    @{ Match = "*WiFi*"; File = "winpe-wifi_zh-CN.cab"; }
    @{ Match = "*rejuv*"; File = "winpe-rejuv_zh-CN.cab"; }
    @{ Match = "*opcservices*"; File = "winpe-opcservices_zh-CN.cab"; }
    @{ Match = "*hta*"; File = "winpe-hta_zh-CN.cab"; }
    @{ Match = "*windowsupdate*"; File = "winpe-windowsupdate_zh-CN.cab"; }
    @{ Match = "*appxdeployment*"; File = "winpe-appxdeployment_zh-CN.cab"; }
)

ForEach ($Rule in $Language_List) {
```

```

Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"
ForEach ($Component in $Initl_install_Language_Component) {
    if ($Component -like "*$($Rule.Match)*") {
        Write-host "    Component name: " -NoNewline
        Write-host $Component -ForegroundColor Green
        Write-host "    Language pack file: " -NoNewline
        Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

        Write-Host "    Installing ".PadRight(22) -NoNewline
        try {
            Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" | Out-Null
            Write-host "Finish" -ForegroundColor Green
        } catch {
            Write-host "Failed" -ForegroundColor Red
        }
        break
    }
}
}

```

3.1.4.2. Offline image language: change

3.1.4.2.1. Change default language, regional settings, and other international settings

Region: **zh-CN**

```
Dism /Image:"D:\OS11_Custom\Install\WinRE\Mount" /Set-AllIntl:"zh-CN"
```

3.1.4.2.2. View available language settings

```
Dism /Image:"D:\OS11_Custom\Install\WinRE\Mount" /Get-Intl
```

3.1.4.3. Language packs: Removed, optional

- After you add languages, if you want to deploy to a non-English locale, you can save space by removing the English language component. When you remove a language, uninstall the language components in the reverse order in which you added them.
- After adding the Chinese, delete "**English - United States**" in reverse, the Region tag: **en-US**, you need to extract the language pack in advance

Copy the code or view the source files: [WinRE.Del.Specified.lang.Tag.ps1](#) ([Local](#), [Github](#))

```

$Lang = "en-US"
$Mount = "D:\OS11_Custom\Install\WinRE\Mount"
$Sources = "D:\OS11_Custom\Install\WinRE\Language\Del\en-US"

$Initl_install_Language_Component = @()
Get-WindowsPackage -Path $Mount | ForEach-Object {
    $Initl_install_Language_Component += $_.PackageName
}

$Language = @(
    @{ Match = "*windowsupdate*"; File = "winpe-windowsupdate_$( $Lang ).cab"; }
    @{ Match = "*appxdeployment*"; File = "winpe-appxdeployment_$( $Lang ).cab"; }
    @{ Match = "*hta*"; File = "winpe-hta_$( $Lang ).cab"; }
)

```

```
@{ Match = "*opcservices*"; File = "winpe-opcservices_$(Lang).cab"; }
@{ Match = "*rejuv*"; File = "winpe-rejuv_$(Lang).cab"; }
@{ Match = "*WiFi*"; File = "winpe-wifi_$(Lang).cab"; }
@{ Match = "*StorageWMI*"; File = "winpe-storagewmi_$(Lang).cab"; }
@{ Match = "*WinPE-AppxPackaging*"; File = "winpe-appxpackaging_$(Lang).cab"; }
@{ Match = "*-WMI-Package*"; File = "winpe-wmi_$(Lang).cab"; }
@{ Match = "*wds-tools*"; File = "winpe-wds-tools_$(Lang).cab"; }
@{ Match = "*srt*"; File = "winpe-srt_$(Lang).cab"; }
@{ Match = "*srh*"; File = "winpe-srh_$(Lang).cab"; }
@{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_$(Lang).cab"; }
@{ Match = "*scripting*"; File = "winpe-scripting_$(Lang).cab"; }
@{ Match = "*Narrator*"; File = "winpe-narrator_$(Lang).cab"; }
@{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_$(Lang).cab"; }
@{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_$(Lang).cab"; }
@{ Match = "*AudioCore*"; File = "winpe-audiocore_$(Lang).cab"; }
@{ Match = "*ATBroker*"; File = "winpe-atbroker_$(Lang).cab"; }
@{ Match = "*SecureStartup*"; File = "winpe-securestartup_$(Lang).cab"; }
@{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }
)
```

```
ForEach ($Rule in $Language) {
    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"
    ForEach ($Component in $Initl_install_Language_Component) {
        if ($Component -like "*$(Rule.Match)*$(Lang)*") {
            Write-host "  Component name: " -NoNewline
            Write-host $Component -ForegroundColor Green
            Write-host "  Language pack file: " -NoNewline
            Write-host "$($Sources)\$(Rule.File)" -ForegroundColor Green

            Write-Host "  Deleting ".PadRight(22) -NoNewline
            try {
                Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$(Rule.File)" -ErrorAction
                SilentlyContinue | Out-Null
            } catch {
                Write-host "Finish" -ForegroundColor Green
            } catch {
                Write-host "Failed" -ForegroundColor Red
                Write-host "  $('_)" -ForegroundColor Red
            }
            break
        }
    }
}

$InitlClearLanguagePackage = @()
Get-WindowsPackage -Path $Mount | ForEach-Object {
    if ($_.PackageName -like "*$(Lang)*") {
        $InitlClearLanguagePackage += $_.PackageName
    }
}

if ($InitlClearLanguagePackage.count -gt 0) {
    ForEach ($item in $InitlClearLanguagePackage) {
        Write-Host "`n  $($item)" -ForegroundColor Green
        Write-Host "  Deleting ".PadRight(22) -NoNewline
        try {
            Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction SilentlyContinue
        } catch {
            Write-host "Finish" -ForegroundColor Green
        } catch {
            Write-host "Failed" -ForegroundColor Red
            Write-host "  $('_)" -ForegroundColor Red
        }
    }
}
```

```

        Write-host "Failed" -ForegroundColor Red
        Write-host "  $($_) " -ForegroundColor Red
    }
}
}

```

3.1.4.4. **Components: All packages installed in the image**

3.1.4.4.1. **View**

```
Get-WindowsPackage -Path "D:\OS11_Custom\Install\WinRE\Mount" | Out-GridView
```

3.1.4.4.2. **Export to csv**

```

$SaveTo = "D:\OS11_Custom\Install\WinRE\Report.$(Get-Date -Format
"yyyyMMddHHmmss").csv"
Get-WindowsPackage -Path "D:\OS11_Custom\Install\WinRE\Mount" | Export-CSV -
NoType -Path $SaveTo
Write-host $SaveTo -ForegroundColor Green

```

3.1.5. **Cumulative updates, optional**

To prepare the cumulative updates file available, change the example file name: `KB_WinRE.cab`

3.1.5.1. **Add**

```

$KBPath = "D:\OS11_Custom\Install\WinRE\Update\KB_WinRE.cab"
Add-WindowsPackage -Path "D:\OS11_Custom\Install\WinRE\Mount" -PackagePath $KBPath

```

3.1.5.2. **Delete**

```

$KBPath = "D:\OS11_Custom\Install\WinRE\Update\KB_WinRE.cab"
Remove-WindowsPackage -Path "D:\OS11_Custom\Install\WinRE\Mount" -PackagePath $KBPath

```

3.1.5.3. **Solid update, optional**

It cannot be uninstalled after curing, which cleans the recovery image and resets the basis of any superseded components.

```

Dism /image:"D:\OS11_Custom\Install\WinRE\Mount" /cleanup-image /StartComponentCleanup
/ResetBase

```

3.1.5.3.1. **Clean components after curing and updating, optional**

```

$Mount = "D:\OS11_Custom\Install\WinRE\Mount"
Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {
    if ($_.PackageState -eq "Superseded") {
        Write-Host "  $($_.PackageName)" -ForegroundColor Green
        Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null
    }
}

```

3.1.6. **Driver, optional**

3.1.7. **Save image**

```
Save-WindowsImage -Path "D:\OS11_Custom\Install\WinRE\Mount"
```

3.1.8. **Unmount image**

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowsImage -Path "D:\OS11_Custom\Install\WinRE\Mount" -Discard
```

3.1.9. **After rebuilding WinRE.wim, the file size can be reduced**

Copy the code or view the source file: [WinRE.Rebuild.ps1](#) ([Local](#), [Github](#))

```
$FileName = "D:\OS11_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"
Get-WindowsImage -ImagePath $Filename -ErrorAction SilentlyContinue | ForEach-Object {
    Write-Host " Image name: " -NoNewline
    Write-Host $_.ImageName -ForegroundColor Yellow
    Write-Host " The index number: " -NoNewline
    Write-Host $_.ImageIndex -ForegroundColor Yellow

    Write-Host "`n Rebuild".PadRight(28) -NoNewline
    Export-WindowsImage -SourceImagePath $Filename -SourceIndex $_.ImageIndex -DestinationImagePath
"$($FileName).New" -CompressionType max
    Write-Host "Finish`n" -ForegroundColor Green
}
if (Test-Path "$($FileName).New" -PathType Leaf) {
    Remove-Item -Path $Filename
    Move-Item -Path "$($FileName).New" -Destination $Filename
    Write-Host "Finish" -ForegroundColor Green
} else {
    Write-host "Failed" -ForegroundColor Red
}
```

3.1.10. **Backup WinRE.wim**

Copy the code or view the source file: [WinRE.Backup.ps1](#) ([Local](#), [Github](#))

```
$WimLibPath = "D:\OS11_Custom\Install\Install\Update\Winlib"
$FileName = "D:\OS11_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"
New-Item -Path $WimLibPath -ItemType Directory -ea SilentlyContinue
Copy-Item -Path $FileName -Destination $WimLibPath -Force
```

3.1.11. **Replace WinRE.wim within the Install.wim image**

- After each mount Install.wim "[Replace WinRE.wim](#)";
- Learn "[Get all index numbers of Install.wim and replace the old WinRE.wim](#)".

[Process the files in the Install.wim image and end.](#)

4. **Language pack**

Automatically install language packs: Get "Component: All installed packages in the image" and match them. After matching the

corresponding names, install the local corresponding language pack files.

4.1. Language pack: add

Copy the code or view the source file: [Install.Instl.lang.ps1](#) ([Local](#), [Github](#))

```
$Mount = "D:\OS11_Custom\Install\Install\Mount"
$Sources = "D:\OS11_Custom\Install\Install\Language\Add\zh-CN"

$Initl_install_Language_Component = @()
Get-WindowsPackage -Path $Mount | ForEach-Object {
    $Initl_install_Language_Component += $_.PackageName
}

Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\Microsoft-Windows-LanguageFeatures-Fonts-Hans-
Package~31bf3856ad364e35~amd64~~.cab"

$Language_List = @(
    @{ Match = "*Client-LanguagePack-Package*"; File = "Microsoft-Windows-Client-Language-Pack_x64_zh-CN.cab"; }
    @{ Match = "*LanguageFeatures-Basic*"; File = "Microsoft-Windows-LanguageFeatures-Basic-zh-CN-
Package~31bf3856ad364e35~amd64~~.cab"; }
    @{ Match = "*Handwriting*"; File = "Microsoft-Windows-LanguageFeatures-Handwriting-zh-CN-
Package~31bf3856ad364e35~amd64~~.cab"; }
    @{ Match = "*OCR*"; File = "Microsoft-Windows-LanguageFeatures-OCR-zh-CN-
Package~31bf3856ad364e35~amd64~~.cab"; }
    @{ Match = "*LanguageFeatures-Speech*"; File = "Microsoft-Windows-LanguageFeatures-Speech-zh-CN-
Package~31bf3856ad364e35~amd64~~.cab"; }
    @{ Match = "*TextToSpeech*"; File = "Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-CN-
Package~31bf3856ad364e35~amd64~~.cab"; }
    @{ Match = "*InternetExplorer*"; File = "Microsoft-Windows-InternetExplorer-Optional-
Package~31bf3856ad364e35~AMD64~zh-CN~.cab"; }
    @{ Match = "*Notepad*amd64*"; File = "Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~AMD64~zh-
CN~.cab"; }
    @{ Match = "*Notepad*wow64*"; File = "Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~wow64~zh-
CN~.cab"; }
    @{ Match = "*MediaPlayer*amd64*"; File = "Microsoft-Windows-MediaPlayer-Package-AMD64-zh-CN.cab"; }
    @{ Match = "*MediaPlayer*wow64*"; File = "Microsoft-Windows-MediaPlayer-Package-wow64-zh-CN.cab"; }
    @{ Match = "*PowerShell*amd64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~zh-
CN~.cab"; }
    @{ Match = "*PowerShell*wow64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~zh-
CN~.cab"; }
    @{ Match = "*Printing*PMCPPC*amd64*"; File = "Microsoft-Windows-Printing-PMCPPC-FoD-
Package~31bf3856ad364e35~AMD64~zh-CN~.cab"; }
    @{ Match = "*StepsRecorder*amd64*"; File = "Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~zh-
CN~.cab"; }
    @{ Match = "*StepsRecorder*wow64*"; File = "Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~zh-
CN~.cab"; }
    @{ Match = "*WMIC*FoD*Package*amd64*"; File = "Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~AMD64~zh-
CN~.cab"; }
    @{ Match = "*WMIC*FoD*Package*wow64*"; File = "Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~wow64~zh-
CN~.cab"; }
    @{ Match = "*WordPad*amd64*"; File = "Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~zh-
CN~.cab"; }
    @{ Match = "*WordPad*wow64*"; File = "Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~zh-
CN~.cab"; }
    @{ Match = "*Client*LanguagePack*zh-TW*"; File = "Microsoft-Windows-InternationalFeatures-Taiwan-
Package~31bf3856ad364e35~amd64~~.cab"; }
```

```

)

ForEach ($Rule in $Language_List) {
    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host " $('-' * 80)"
    ForEach ($Component in $Initl_install_Language_Component) {
        if ($Component -like "*$($Rule.Match)*") {
            Write-host " Component name: " -NoNewline
            Write-host $Component -ForegroundColor Green
            Write-host " Language pack file: " -NoNewline
            Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

            Write-Host " Installing ".PadRight(22) -NoNewline
            try {
                Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" | Out-Null
                Write-host "Finish" -ForegroundColor Green
            } catch {
                Write-host "Failed" -ForegroundColor Red
            }
            break
        }
    }
}
}

```

4.2. Offline image language: change

- Starting Windows 11, the [default System UI Language](#) set by DISM is left unaltered on all editions except for Home edition. For [all commercial editions](#) the language chosen during the Out-of-Box Experience (OOBE) is set as the [System Preferred UI language](#) and Windows will be displayed in this language and for Home edition the language chosen at OOBE will continue to be the default System UI Language.
- As of Windows 10, version 2004, if an .appx-based Language Experience Pack (LXP) backed language is passed as an argument then the language will be set as the System Preferred UI language and its parent language will be set as the Default System UI language. In prior versions only .cab based language packs were supported.

4.2.1. Change default language, regional settings, and other international settings

Region: [zh-CN](#)

```
Dism /Image:"D:\OS11_Custom\Install\Install\Mount" /Set-AllIntl:zh-CN
```

4.2.2. View available language settings

```
Dism /Image:"D:\OS11_Custom\Install\Install\Mount" /Get-Intl
```

4.3. Language packs: Removed, optional

- After you add languages, if you want to deploy to a non-English locale, you can save space by removing the English language component. When you remove a language, uninstall the language components in the reverse order in which you added them.
- After adding the Chinese, delete "[English - United States](#)" in reverse, the Region tag: [en-US](#), you need to extract the language pack in advance

Copy the code or view the source files: [Install.Del.Specified.lang.Tag.ps1](#) ([Local](#), [Github](#))

```
$Lang = "en-US"

$Mount = "D:\OS11_Custom\Install\Install\Mount"

$Sources = "D:\OS11_Custom\Install\Install\Language\Del\en-US"

$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    $Initl_install_Language_Component += $_.PackageName

}

$Language = @(

    @{ Match = "*WordPad*wow64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~wow64~$(($Lang)~.cab"; }

    @{ Match = "*WordPad*amd64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~amd64~$(($Lang)~.cab"; }

    @{ Match = "*WMIC*FoD*Package*wow64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~wow64~$(($Lang)~.cab"; }

    @{ Match = "*WMIC*FoD*Package*amd64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~AMD64~$(($Lang)~.cab"; }

    @{ Match = "*StepsRecorder*wow64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~wow64~$(($Lang)~.cab"; }

    @{ Match = "*StepsRecorder*amd64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~amd64~$(($Lang)~.cab"; }

    @{ Match = "*Printing*PMCPPC*amd64*"; File = "Microsoft-Windows-Printing-PMCPPC-FoD-
Package~31bf3856ad364e35~AMD64~$(($Lang)~.cab"; }

    @{ Match = "*PowerShell*wow64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~wow64~$(($Lang)~.cab"; }

    @{ Match = "*PowerShell*amd64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~amd64~$(($Lang)~.cab"; }

    @{ Match = "*MediaPlayer*wow64*"; File = "Microsoft-Windows-MediaPlayer-Package-wow64-$(($Lang).cab"; }

    @{ Match = "*MediaPlayer*amd64*"; File = "Microsoft-Windows-MediaPlayer-Package-AMD64-$(($Lang).cab"; }

    @{ Match = "*Notepad*wow64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~wow64~$(($Lang)~.cab"; }

    @{ Match = "*Notepad*amd64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~AMD64~$(($Lang)~.cab"; }

    @{ Match = "*InternetExplorer*"; File = "Microsoft-Windows-InternetExplorer-Optional-
Package~31bf3856ad364e35~AMD64~$(($Lang)~.cab"; }

    @{ Match = "*TextToSpeech*"; File = "Microsoft-Windows-LanguageFeatures-TextToSpeech-$(($Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "*LanguageFeatures-Speech*"; File = "Microsoft-Windows-LanguageFeatures-Speech-$(($Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "*OCR*"; File = "Microsoft-Windows-LanguageFeatures-OCR-$(($Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "*Handwriting*"; File = "Microsoft-Windows-LanguageFeatures-Handwriting-$(($Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "*LanguageFeatures-Basic*"; File = "Microsoft-Windows-LanguageFeatures-Basic-$(($Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "*Client-LanguagePack-Package*"; File = "Microsoft-Windows-Client-Language-Pack_x64_$(($Lang).cab"; }

)

ForEach ($Rule in $Language) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "*$($Rule.Match)*$(($Lang))*") {

            Write-host "  Component name: " -NoNewline

            Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline
```



```

Write-host "$($Sources)\ $($Rule.File)" -ForegroundColor Green
Write-Host "  Deleting ".PadRight(22) -NoNewline

try {
    Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\ $($Rule.File)" -ErrorAction SilentlyContinue | Out-Null

    Write-host "Finish" -ForegroundColor Green
} catch {
    Write-host "Failed" -ForegroundColor Red
    Write-host "  $($_) " -ForegroundColor Red
}
break
}
}
}

$InitlClearLanguagePackage = @()
Get-WindowsPackage -Path $Mount | ForEach-Object {
    if ($_.PackageName -like "* $($Lang)*") {
        $InitlClearLanguagePackage += $_.PackageName
    }
}

if ($InitlClearLanguagePackage.count -gt 0) {
    ForEach ($item in $InitlClearLanguagePackage) {
        Write-Host "`n  $($item)" -ForegroundColor Green
        Write-Host "  Deleting ".PadRight(22) -NoNewline
        try {
            Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction SilentlyContinue | Out-Null
            Write-host "Finish" -ForegroundColor Green
        } catch {
            Write-host "Failed" -ForegroundColor Red
            Write-host "  $($_) " -ForegroundColor Red
        }
    }
}
}

```

4.4. Components: All packages installed in the image

4.4.1. View

```
Get-WindowsPackage -Path "D:\OS11_Custom\Install\Install\Mount" | Out-GridView
```

4.4.2. Export to csv

```

$SaveTo = "D:\OS11_Custom\Install\Install\Report.$(Get-Date -Format "yyyyMMddHHmmss").csv"
Get-WindowsPackage -Path "D:\OS11_Custom\Install\Install\Mount" | Export-CSV -NoType -Path $SaveTo
Write-host $SaveTo -ForegroundColor Green

```

5. InBox Apps

5.1. Learn "Attachment: inBox Apps"

Learn about pre-installed apps for different operating systems, app store connections.

5.2. **InBox Apps: Installed**

5.2.1. **View**

```
Get-AppXProvisionedPackage -Path "D:\OS11_Custom\Install\Install\Mount" | Out-GridView
```

5.2.2. **Export to Csv**

```
$SaveTo = "D:\OS11_Custom\Install\Install\Report.$(Get-Date -Format "yyyyMMddHHmmss").csv"
Get-AppXProvisionedPackage -Path "D:\OS11_Custom\Install\Install\Mount" | Export-CSV -NoType -Path $SaveTo
Write-host $SaveTo -ForegroundColor Green
```

5.3. **Remove all installed pre-applications**

Copy the code or view the source file: [Install.InBox.Appx.Clear.all.ps1](#) ([Local](#), [Github](#))

```
Get-AppXProvisionedPackage -path "D:\OS11_Custom\Install\Install\Mount" -ErrorAction SilentlyContinue | ForEach-Object {
    Write-host "`n $($_.DisplayName)"; Write-Host " Deleting ".PadRight(22) -NoNewline
    try {
        Remove-AppxProvisionedPackage -Path "D:\OS11_Custom\Install\Install\Mount" -PackageName $_.PackageName -
ErrorAction SilentlyContinue | Out-Null
        Write-host "Finish" -ForegroundColor Green
    } catch {
        Write-host "Failed" -ForegroundColor Red
    }
}
```

5.4. **Region tag: Understanding**

Before understanding zone tags, first understand the list of languages available in the ZuneMusic app: [en-us](#), en-gb, as-in, az-latn-az, bs-latn-ba, bn-in, cs-cz, cy-gb, ar-sa, de-de, af-za, am-et, da-dk, el-gr, es-es, es-mx, ca-es, ca-es-valencia, eu-es, fi-fi, bg-bg, ga-ie, et-ee, gl-es, gu-in, gd-gb, fil-ph, fr-ca, fr-fr, hy-am, fa-ir, hu-hu, id-id, it-it, ja-jp, hr-hr, ka-ge, is-is, he-il, hi-in, kk-kz, lo-la, km-kh, lt-lt, kn-in, kok-in, ko-kr, mk-mk, lv-lv, ms-my, mi-nz, mr-in, mt-mt, ne-np, nl-nl, nb-no, ml-in, nn-no, lb-lu, or-in, ro-ro, sk-sk, ru-ru, pl-pl, quz-pe, pt-br, pt-pt, sq-al, ta-in, th-th, sv-se, pa-in, sr-cyrl-ba, sr-cyrl-rs, sr-latn-rs, ur-pk, ug-cn, tr-tr, uk-ua, tt-ru, [zh-cn](#), vi-vn, uz-latn-uz, sl-si, zh-tw, te-in

View installed languages for offline images

```
Dism /Image:"D:\OS11_Custom\Install\Install\Mount" /Get-Intl
```

View results for installed languages: [en-US](#), [zh-CN](#), When installing the ZuneMusic app, the installer will match "Installed Languages" and automatically filter the list of uninstalled languages, This is the area tag.

5.5. **Region tag: adding method**

5.5.1. Execute "[Language Pack:Add](#)"

5.5.2. Install “Local Language Experience Packages (LXPs)”

Microsoft officially provides the Local Language Experience Package (LXPS) installation file for Windows 10. It will no longer be provided for Windows 11. To obtain the offline installation package:

5.5.2.1. **Download using the Windows Local Language Experience Packs (LXPs) Downloader**

learn: <https://github.com/ilikeyi/LXPs>

After downloading, save to: D:\OS11_Custom\Install\Install\InBox.Appx, file
format:LanguageExperiencePack.zh-CN.Neutral.Appx

5.5.2.2. **Manual download**

5.5.2.2.1. **View "Attachment: LXPs"**

Waiting to download Local Language Experience Packs (LXPs) for "Simplified Chinese -
China", Region: zh-CN, application ID: 9NRMNT6GMZ70, Store link:
<https://www.microsoft.com/store/productId/9NRMNT6GMZ70>

5.5.2.2.2. **Open the website: https://store.rg-adguard.net**

5.5.2.2.2.1. Search keywords:

<https://www.microsoft.com/store/productId/9NRMNT6GMZ70>

5.5.2.2.2.2. Search 22621 content in the web page, search results:
[Microsoft.LanguageExperiencePackzh-CN_22621.*.neutral__8wekyb3d8bbwe.appx](#)

5.5.2.2.2.3. After downloading, save it to the
[D:\OS11_Custom\Install\Install\InBox.Appx](#) directory and rename it:
[LanguageExperiencePack.zh-cn.Neutral.Appx](#)

5.5.2.3. **Execute the installation command to install the local language experience package (LXPs)**

After understanding how to add zone tags, obtain [LanguageExperiencePack.zh-cn.Neutral](#), execute the
installation command:

```
Add-AppxProvisionedPackage -Path "D:\OS11_Custom\Install\Install\Mount" -PackagePath  
"D:\OS11_Custom\Install\Install\InBox.appx\LanguageExperiencePack.zh-cn.Neutral.appx" -  
SkipLicense
```

5.5.2.4. **InBox Apps: An installed application package**

5.5.2.4.1. **View**

```
Get-AppXProvisionedPackage -Path "D:\OS11_Custom\Install\Install\Mount" | Out-GridView
```

5.5.2.4.2. **Export to Csv**

```
$SaveTo = "D:\OS11_Custom\Install\Install\Report.$(Get-Date -Format  
"yyyyMMddHHmmss").csv"  
Get-AppXProvisionedPackage -Path "D:\OS11_Custom\Install\Install\Mount" | Export-CSV -  
NoType -Path $SaveTo  
Write-host $SaveTo -ForegroundColor Green
```

5.6. **InBox Apps: Install**

5.6.1. **Mount or decompress the InBox Apps installation file**

Mount [22621.1.220506-1250.ni_release_amd64fre_InboxApps.iso](#) or extract to any location;

5.6.2. After executing the installation command, install InBox Apps to: Install.wim

- **Auto** = Automatically search all local disks, default;
- Custom path, e.g. specify F drive: **\$ISO = "F:\packages"**

Copy the code or view the source file: [Install.Inst.InBox.Appx.ps1](#) ([Local](#), [Github](#))

```
$ISO = "Auto"

$Mount = "D:\OS11_Custom\Install\Install\Mount"

try {
    Write-host "`n  Offline image version: " -NoNewline
    $Current_Edition_Version = (Get-WindowsEdition -Path $Mount).Edition
    Write-Host $Current_Edition_Version -ForegroundColor Green
} catch {
    Write-Host "Error" -ForegroundColor Red
    Write-Host "  $($_) " -ForegroundColor Yellow
    return
}

$Pre_Config_Rules = @(
    @{
        Name = @(
            "Core"; "CoreN"; "CoreSingleLanguage";
        )
        Apps = @(
            "Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
            "Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
            "Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.HEIFImageExtension"; "Microsoft.HEVCVideoExtension";
            "Microsoft.SecHealthUI"; "Microsoft.VP9VideoExtensions"; "Microsoft.WebpImageExtension";
            "Microsoft.WindowsStore"; "Microsoft.GamingApp"; "Microsoft.Sticky.Notes"; "Microsoft.Paint";
            "Microsoft.PowerAutomateDesktop"; "Microsoft.ScreenSketch"; "Microsoft.WindowsNotepad";
            "Microsoft.WindowsTerminal"; "Clipchamp.Clipchamp"; "Microsoft.Solitaire.Collection"; "Microsoft.WindowsAlarms";
            "Microsoft.WindowsFeedbackHub"; "Microsoft.WindowsMaps"; "Microsoft.ZuneMusic"; "Microsoft.BingNews";
            "Microsoft.DesktopAppInstaller"; "Microsoft.WindowsCamera"; "Microsoft.Getstarted"; "Microsoft.Cortana";
            "Microsoft.BingWeather"; "Microsoft.GetHelp"; "Microsoft.MicrosoftOfficeHub"; "Microsoft.People";
            "Microsoft.StorePurchaseApp"; "Microsoft.Todos"; "Microsoft.WebMediaExtensions"; "Microsoft.Windows.Photos";
            "Microsoft.WindowsCalculator"; "Microsoft.Windows.CommunicationsApps"; "Microsoft.WindowsSoundRecorder";
            "Microsoft.Xbox.TCUI"; "Microsoft.XboxGameOverlay"; "Microsoft.XboxGamingOverlay";
            "Microsoft.XboxIdentityProvider"; "Microsoft.XboxSpeechToTextOverlay"; "Microsoft.YourPhone";
            "Microsoft.ZuneVideo"; "MicrosoftCorporationII.QuickAssist"; "MicrosoftWindows.Client.WebExperience";
            "Microsoft.RawImageExtension"; "MicrosoftCorporationII.MicrosoftFamily";
        )
    }
)

@{
    Name = @(
        "Education"; "Professional"; "ProfessionalEducation"; "ProfessionalWorkstation"; "Enterprise"; "IoTEnterprise";
        "ServerRdsh";
    )
    Apps = @(
        "Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
        "Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
        "Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.HEIFImageExtension"; "Microsoft.HEVCVideoExtension";
        "Microsoft.SecHealthUI"; "Microsoft.VP9VideoExtensions"; "Microsoft.WebpImageExtension";
        "Microsoft.WindowsStore"; "Microsoft.GamingApp"; "Microsoft.Sticky.Notes"; "Microsoft.Paint";
        "Microsoft.PowerAutomateDesktop"; "Microsoft.ScreenSketch"; "Microsoft.WindowsNotepad";
        "Microsoft.WindowsTerminal"; "Clipchamp.Clipchamp"; "Microsoft.Solitaire.Collection"; "Microsoft.WindowsAlarms";
```

```
"Microsoft.WindowsFeedbackHub"; "Microsoft.WindowsMaps"; "Microsoft.ZuneMusic"; "Microsoft.BingNews";
"Microsoft.DesktopAppInstaller"; "Microsoft.WindowsCamera"; "Microsoft.Getstarted"; "Microsoft.Cortana";
"Microsoft.BingWeather"; "Microsoft.GetHelp"; "Microsoft.MicrosoftOfficeHub"; "Microsoft.People";
"Microsoft.StorePurchaseApp"; "Microsoft.Todos"; "Microsoft.WebMediaExtensions"; "Microsoft.Windows.Photos";
"Microsoft.WindowsCalculator"; "Microsoft.Windows.CommunicationsApps"; "Microsoft.WindowsSoundRecorder";
"Microsoft.Xbox.TCUI"; "Microsoft.XboxGameOverlay"; "Microsoft.XboxGamingOverlay";
"Microsoft.XboxIdentityProvider"; "Microsoft.XboxSpeechToTextOverlay"; "Microsoft.YourPhone";
"Microsoft.ZuneVideo"; "MicrosoftCorporationII.QuickAssist"; "MicrosoftWindows.Client.WebExperience";
"Microsoft.RawImageExtension";
    )
}

@{
    Name = @(
        "EnterpriseN"; "EnterpriseGN"; "EnterpriseSN"; "ProfessionalN"; "EducationN"; "ProfessionalWorkstationN";
"ProfessionalEducationN"; "CloudN"; "CloudEN"; "CloudEditionN"; "CloudEditionLN"; "StarterN";
    )
    Apps = @(
        "Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.SecHealthUI"; "Microsoft.WindowsStore";
"Microsoft.Sticky.Notes"; "Microsoft.Paint"; "Microsoft.PowerAutomateDesktop"; "Microsoft.ScreenSketch";
"Microsoft.WindowsNotepad"; "Microsoft.WindowsTerminal"; "Clipchamp.Clipchamp";
"Microsoft.Solitaire.Collection"; "Microsoft.WindowsAlarms"; "Microsoft.WindowsFeedbackHub";
"Microsoft.WindowsMaps"; "Microsoft.BingNews"; "Microsoft.DesktopAppInstaller"; "Microsoft.WindowsCamera";
"Microsoft.Getstarted"; "Microsoft.Cortana"; "Microsoft.BingWeather"; "Microsoft.GetHelp";
"Microsoft.MicrosoftOfficeHub"; "Microsoft.People"; "Microsoft.StorePurchaseApp"; "Microsoft.Todos";
"Microsoft.Windows.Photos"; "Microsoft.WindowsCalculator"; "Microsoft.Windows.CommunicationsApps";
"Microsoft.XboxGameOverlay"; "Microsoft.XboxIdentityProvider"; "Microsoft.XboxSpeechToTextOverlay";
"Microsoft.YourPhone"; "MicrosoftCorporationII.QuickAssist"; "MicrosoftWindows.Client.WebExperience";
    )
}
)

$Allow_Install_App = @()
ForEach ($item in $Pre_Config_Rules) {
    if ($item.Name -contains $Current_Edition_Version) {
        Write-host "`n  Match to: "-NoNewline
        Write-host $Current_Edition_Version -ForegroundColor Green

        $Allow_Install_App = $item.Apps
        break
    }
}

Write-host "`n  The app to install ( $($Allow_Install_App.Count) item )" -ForegroundColor Yellow
Write-host "  $('-' * 80)"
ForEach ($item in $Allow_Install_App) {
    Write-host "  $($item)" -ForegroundColor Green
}

$InBoxApps = @(
    @{ Name = "Microsoft.UI.Xaml.2.3"; File = "Microsoft.UI.Xaml.x64.2.3.appx"; License = ""; }
    @{ Name = "Microsoft.UI.Xaml.2.4"; File = "Microsoft.UI.Xaml.x64.2.4.appx"; License = ""; }
    @{ Name = "Microsoft.UI.Xaml.2.7"; File = "Microsoft.UI.Xaml.x64.2.7.appx"; License = ""; }
    @{ Name = "Microsoft.NET.Native.Framework.2.2"; File = "Microsoft.NET.Native.Framework.x64.2.2.appx"; License =
    ""; }
    @{ Name = "Microsoft.NET.Native.Runtime.2.2"; File = "Microsoft.NET.Native.Runtime.x64.2.2.appx"; License = ""; }
    @{ Name = "Microsoft.VCLibs.140.00"; File = "Microsoft.VCLibs.x64.14.00.appx"; License = ""; }
```

```
@{ Name = "Microsoft.VCLibs.140.00.UWPDesktop"; File = "Microsoft.VCLibs.x64.14.00.UWPDesktop.appx";  
License = ""; }  
  
@{ Name = "Microsoft.WindowsStore"; File = "Microsoft.WindowsStore_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.WindowsStore_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.HEIFImageExtension"; File = "Microsoft.HEIFImageExtension_8wekyb3d8bbwe.appxbundle";  
License = "Microsoft.HEIFImageExtension_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.HEVCVideoExtension"; File = "Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.x64.appx";  
License = "Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.x64.xml"; }  
  
@{ Name = "Microsoft.SecHealthUI"; File = "Microsoft.SecHealthUI_8wekyb3d8bbwe.x64.appx"; License =  
"Microsoft.SecHealthUI_8wekyb3d8bbwe.x64.xml"; }  
  
@{ Name = "Microsoft.VP9VideoExtensions"; File = "Microsoft.VP9VideoExtensions_8wekyb3d8bbwe.x64.appx";  
License = "Microsoft.VP9VideoExtensions_8wekyb3d8bbwe.x64.xml"; }  
  
@{ Name = "Microsoft.WebplImageExtension"; File = "Microsoft.WebplImageExtension_8wekyb3d8bbwe.x64.appx";  
License = "Microsoft.WebplImageExtension_8wekyb3d8bbwe.x64.xml"; }  
  
@{ Name = "Microsoft.GamingApp"; File = "Microsoft.GamingApp_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.GamingApp_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.Sticky.Notes"; File = "Microsoft.MicrosoftStickyNotes_8wekyb3d8bbwe.msixbundle"; License  
= "Microsoft.MicrosoftStickyNotes_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.Paint"; File = "Microsoft.Paint_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.Paint_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.PowerAutomateDesktop"; File =  
"Microsoft.PowerAutomateDesktop_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.PowerAutomateDesktop_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.ScreenSketch"; File = "Microsoft.ScreenSketch_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.ScreenSketch_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.WindowsNotepad"; File = "Microsoft.WindowsNotepad_8wekyb3d8bbwe.msixbundle";  
License = "Microsoft.WindowsNotepad_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.WindowsTerminal"; File = "Microsoft.WindowsTerminal_8wekyb3d8bbwe.msixbundle";  
License = "Microsoft.WindowsTerminal_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Clipchamp.Clipchamp"; File = "Clipchamp.Clipchamp_yxz26nhyzhsrt.msixbundle"; License =  
"Clipchamp.Clipchamp_yxz26nhyzhsrt.xml"; }  
  
@{ Name = "Microsoft.Solitaire.Collection"; File =  
"Microsoft.MicrosoftSolitaireCollection_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.MicrosoftSolitaireCollection_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.WindowsAlarms"; File = "Microsoft.WindowsAlarms_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.WindowsAlarms_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.WindowsFeedbackHub"; File =  
"Microsoft.WindowsFeedbackHub_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.WindowsFeedbackHub_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.WindowsMaps"; File = "Microsoft.WindowsMaps_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.WindowsMaps_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.ZuneMusic"; File = "Microsoft.ZuneMusic_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.ZuneMusic_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "MicrosoftCorporationII.MicrosoftFamily"; File =  
"MicrosoftCorporationII.MicrosoftFamily_8wekyb3d8bbwe.msixbundle"; License =  
"MicrosoftCorporationII.MicrosoftFamily_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.BingNews"; File = "Microsoft.BingNews_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.BingNews_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.DesktopAppInstaller"; File = "Microsoft.DesktopAppInstaller_8wekyb3d8bbwe.msixbundle";  
License = "Microsoft.DesktopAppInstaller_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.WindowsCamera"; File = "Microsoft.WindowsCamera_8wekyb3d8bbwe.msixbundle"; License  
= "Microsoft.WindowsCamera_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.Getstarted"; File = "Microsoft.Getstarted_8wekyb3d8bbwe.msixbundle"; License =  
"Microsoft.Getstarted_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.Cortana"; File = "Microsoft.CortanaApp_8wekyb3d8bbwe.appxbundle"; License =  
"Microsoft.CortanaApp_8wekyb3d8bbwe.xml"; }  
  
@{ Name = "Microsoft.BingWeather"; File = "Microsoft.BingWeather_8wekyb3d8bbwe.appxbundle"; License =  
"Microsoft.BingWeather_8wekyb3d8bbwe.xml"; }
```



```
@{ Name = "Microsoft.GetHelp"; File = "Microsoft.GetHelp_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.GetHelp_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.MicrosoftOfficeHub"; File = "Microsoft.MicrosoftOfficeHub_8wekyb3d8bbwe.appxbundle";
License = "Microsoft.MicrosoftOfficeHub_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.People"; File = "Microsoft.People_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.People_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.StorePurchaseApp"; File = "Microsoft.StorePurchaseApp_8wekyb3d8bbwe.appxbundle";
License = "Microsoft.StorePurchaseApp_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.Todos"; File = "Microsoft.Todos_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.Todos_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.WebMediaExtensions"; File =
"Microsoft.WebMediaExtensions_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.WebMediaExtensions_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.Windows.Photos"; File = "Microsoft.Windows.Photos_8wekyb3d8bbwe.appxbundle"; License
= "Microsoft.Windows.Photos_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.WindowsCalculator"; File = "Microsoft.WindowsCalculator_8wekyb3d8bbwe.appxbundle";
License = "Microsoft.WindowsCalculator_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.Windows.CommunicationsApps"; File =
"Microsoft.WindowsCommunicationsApps_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.WindowsCommunicationsApps_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.WindowsSoundRecorder"; File =
"Microsoft.WindowsSoundRecorder_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.WindowsSoundRecorder_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.Xbox.TCUI"; File = "Microsoft.Xbox.TCUI_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.Xbox.TCUI_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.XboxGameOverlay"; File = "Microsoft.XboxGameOverlay_8wekyb3d8bbwe.appxbundle";
License = "Microsoft.XboxGameOverlay_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.XboxGamingOverlay"; File = "Microsoft.XboxGamingOverlay_8wekyb3d8bbwe.appxbundle";
License = "Microsoft.XboxGamingOverlay_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.XboxIdentityProvider"; File = "Microsoft.XboxIdentityProvider_8wekyb3d8bbwe.appxbundle";
License = "Microsoft.XboxIdentityProvider_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.XboxSpeechToTextOverlay"; File =
"Microsoft.XboxSpeechToTextOverlay_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.XboxSpeechToTextOverlay_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.YourPhone"; File = "Microsoft.YourPhone_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.YourPhone_8wekyb3d8bbwe.xml"; }

@{ Name = "Microsoft.ZuneVideo"; File = "Microsoft.ZuneVideo_8wekyb3d8bbwe.appxbundle"; License =
"Microsoft.ZuneVideo_8wekyb3d8bbwe.xml"; }

@{ Name = "MicrosoftCorporationII.QuickAssist"; File =
"MicrosoftCorporationII.QuickAssist_8wekyb3d8bbwe.appxbundle"; License =
"MicrosoftCorporationII.QuickAssist_8wekyb3d8bbwe.xml"; }

@{ Name = "MicrosoftWindows.Client.WebExperience"; File =
"MicrosoftWindows.Client.WebExperience_cw5n1h2txyewy.appxbundle"; License =
"MicrosoftWindows.Client.WebExperience_cw5n1h2txyewy.xml"; }

@{ Name = "Microsoft.RawImageExtension"; File = "Microsoft.RawImageExtension_8wekyb3d8bbwe.appxbundle";
License = "Microsoft.RawImageExtension_8wekyb3d8bbwe.xml"; }

)
```

```
Function Install_Appx
{
    param ( $File, $License )

    Write-host "  $('-' * 80)"
    Write-host "  Installing: " -NoNewline
    Write-host $File -ForegroundColor Yellow

    if (Test-Path -Path $File -PathType Leaf) {
        if (Test-Path -Path $License -PathType Leaf) {
```

```

Write-host "  License: " -NoNewline; Write-host $License -ForegroundColor Yellow

Write-host "  With License".PadRight(22) -NoNewline -ForegroundColor Green
Write-host "  Installing".PadRight(22) -NoNewline

try {
    Add-AppxProvisionedPackage -Path $Mount -PackagePath $File -LicensePath $License -ErrorAction
SilentlyContinue | Out-Null
    Write-Host "Done" -ForegroundColor Green
} catch {
    Write-Host "Failed" -ForegroundColor Red
    Write-Host "  $($_) " -ForegroundColor Yellow
}
} else {
    Write-host "  No License".PadRight(22) -NoNewline -ForegroundColor Red
    Write-host "  Installing".PadRight(22) -NoNewline

try {
    Add-AppxProvisionedPackage -Path $Mount -PackagePath $File -SkipLicense -ErrorAction SilentlyContinue |
Out-Null
    Write-Host "Done" -ForegroundColor Green
} catch {
    Write-Host "Failed" -ForegroundColor Red
    Write-Host "  $($_) " -ForegroundColor Yellow
}
}
} else {
    Write-host "  The installation package does not exist" -ForegroundColor Red
}
}

ForEach ($Rule in $InBoxApps) {
    Write-host "`n  Name: " -NoNewline
    Write-host $Rule.Name -ForegroundColor Yellow
    Write-host "  $('-' * 80)"

if($Allow_Install_App -contains $Rule.Name) {
    Write-host "  Search for apps: " -NoNewline
    Write-host $Rule.File -ForegroundColor Yellow
    Write-host "  Search for License: " -NoNewline
    Write-host $Rule.File -ForegroundColor Yellow

if ($ISO -eq "Auto") {
    Get-PSDrive -PSProvider FileSystem -ErrorAction SilentlyContinue | ForEach-Object {
        $AppPath = Join-Path -Path $_.Root -ChildPath "packages\$($Rule.File)" -ErrorAction SilentlyContinue
        $LicensePath = Join-Path -Path $_.Root -ChildPath "packages\$($Rule.License)" -ErrorAction SilentlyContinue
        if (Test-Path $AppPath -PathType Leaf) {
            Write-host "  $('-' * 80)"

            Write-host "  Discover apps: " -NoNewLine; Write-host $AppPath -ForegroundColor Green
            if (Test-Path $LicensePath -PathType Leaf) {
                Write-host "  Discover License: " -NoNewLine; Write-host $LicensePath -ForegroundColor Green
            } else {
                Write-host "  License: " -NoNewLine; Write-host "Not found" -ForegroundColor Red
            }
        }
        Install_Appx -File $AppPath -License $LicensePath
        return
    }
}
}
}

```



```

    } else {
        Install_Appx -File "$($ISO)\$($Rule.File)" -License "$($ISO)\$($Rule.License)"
    }
} else {
    Write-host " Skip the installation" -ForegroundColor Red
}
}
}

```

5.7. Region tag: delete

After completing the installation of the InBox Apps application, the Region tag is no longer important and can be deleted or not deleted. Delete "Local Language Experience Package (LXPs), Simplified Chinese - China" and uniquely identify the Region tag: **zh-CN**, can be changed to other Region tag.

Copy the code or view the source file: [Install.Clear.Flag.ps1](#) ([Local](#), [Github](#))

```

$Lang = "zh-CN"
Get-AppXProvisionedPackage -Path "D:\OS11_Custom\Install\Install\Mount" | Foreach-object {
    if ($_.DisplayName -Like "*LanguageExperiencePack*$($Lang)*") {
        Write-host " $_.DisplayName"; Write-Host " Deleting ".PadRight(22) -NoNewline
        try {
            Remove-AppxProvisionedPackage -Path "D:\OS11_Custom\Install\Install\Mount" -PackageName $_.PackageName -
ErrorAction SilentlyContinue | Out-Null
            Write-host "Finish" -ForegroundColor Green
        } catch {
            Write-host "Failed" -ForegroundColor Red
        }
    }
}
}

```

5.8. InBox Apps: optimization

After the app is installed, provisioning the Appx package should be optimized to reduce the app's disk usage by replacing identical files with hard links, only for offline images.

```
Dism /Image:"D:\OS11_Custom\Install\Install\Mount" /Optimize-ProvisionedAppxPackages
```

6. Cumulative updates

It is recommended that you download the latest version, which provides cumulative updates of the initial version to solve the problem of refreshing the "Component: All packages installed in the image" status after reinstalling the same version number.

6.1. Initial version

6.1.1. How to download

Cumulative update [KB5016632](#) can no longer be searched from

<https://www.catalog.update.microsoft.com/Search.aspx?q=KB5016632>. For other download methods, select any website and open it:

- <https://uupdump.net>
- <https://uup.ee>

6.1.1.1. After opening, search for keywords: [22621.382](#), select from the search results: [Windows 11, version 22H2 \(22621.382\) amd64](#)

6.1.1.2. After opening, select "[All files](#)";

6.1.1.3. Search for: [KB5016632](#) in the "All Files" page, download:

- [Windows11.0-KB5016632-x64.cab](#)
- [Windows11.0-KB5016632-x64.psf](#)

6.1.1.4. **Merging cumulative updates**

6.1.1.4.1. Go to <https://github.com/abbodi1406/WHd/tree/master/scripts> After downloading [PSFX_Repack_6.zip](#)

6.1.1.4.2. After downloading, unzip it to: [D:\PSFX_Repack_6](#)

6.1.1.4.3. Copy [Windows11.0-KB5016632-x64.cab](#), [Windows11.0-KB5016632-x64.psf](#) to: [D:\PSFX_Repack_6](#)

6.1.1.4.4. After running: [psfx2cab_GUI.cmd](#), you will get a new file:

[Windows11.0-KB5016632-x64-full_psf.cab](#)

6.1.1.4.5. Save [Windows11.0-KB5016632-x64-full_psf.cab](#) to:

[D:\OS11_Custom\Install\Install\Update\Windows11.0-KB5016632-x64-full_psf.cab](#)

6.1.2. **Add**

```
$KBPath = "D:\OS11_Custom\Install\Install\Update\Windows11.0-KB5016632-x64-full_psf.cab"
Add-WindowsPackage -Path "D:\OS11_Custom\Install\Install\Mount" -PackagePath $KBPath
```

6.2. **Other Version**

6.2.1. **How to download**

Check out "[Windows 11 version information](#)", for example, to download the cumulative update: [KB5030219](#), go to the download page: <https://www.catalog.update.microsoft.com/Search.aspx?q=KB5030219> or "[Direct download](#)", Save to:

[D:\OS11_Custom\Install\Install\Update\windoOS11.0-kb5030219-x64_659d407821da654d564a3108bf493594bd143ab1.msu](#)

6.2.2. **Add**

```
$KBPath = "D:\OS11_Custom\Install\Install\Update\windoOS11.0-kb5030219-x64_659d407821da654d564a3108bf493594bd143ab1.msu"
Add-WindowsPackage -Path "D:\OS11_Custom\Install\Install\Mount" -PackagePath $KBPath
```

6.3. **Solidify Updated, optional**

It cannot be uninstalled after curing, which cleans the recovery image and resets the basis of any superseded components.

```
Dism /Image:"D:\OS11_Custom\Install\Install\Mount" /cleanup-image /StartComponentCleanup /ResetBase
```

6.3.1. **Clean components after curing and updating, optional**

```
$Mount = "D:\OS11_Custom\Install\Install\Mount"
Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {
    if ($_.PackageState -eq "Superseded") {
```

```

Write-Host " $($_.PackageName)" -ForegroundColor Green
Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null
}
}

```

7. Driver, optional

8. Add deployment engine, optional

- Learn "Deployment Engine", if added to ISO installation media, can skip adding to mounted.
- After adding the deployment engine, continue at the current location.

9. Health

Before saving, check whether it is damaged. If the health status is abnormal, stop saving.

```
Repair-WindowsImage -Path "D:\OS11_Custom\Install\Install\Mount" -ScanHealth
```

10. Replace WinRE.wim

WinRE.wim in all index numbers in Install.wim has been replaced in batches. Please skip this step.

```

$WinRE = "D:\OS11_Custom\Install\Install\Update\Winlib\WinRE.wim"
$CopyTo = "D:\OS11_Custom\Install\Install\Mount\Windows\System32\Recovery"
Copy-Item -Path $WinRE -Destination $CopyTo -Force

```

11. Save image

```
Save-WindowsImage -Path "D:\OS11_Custom\Install\Install\Mount"
```

12. Unmount image

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowsImage -Path "D:\OS11_Custom\Install\Install\Mount" -Discard
```

LOOP OPERATING AREA, END.

13. How to batch replace WinRE.wim in all index numbers in Install.wim

13.1. Obtain WimLib

After going to the official website of <https://wimlib.net>, select a different version: [arm64](#), [x64](#), [x86](#), and extract it to: [D:Wimlib](#) after downloading

13.2. How to extract and update WinRE.wim in Install.wim

13.2.1. Extract the WinRE.wim file Install.wim from Install.wim

Copy the code or view the source file: Install.WinRE.Extract ([Local](#), [Github](#))

```

$Arguments = @(
    "extract",

```

```

"D:\OS11\sources\install.wim", "1",
"\Windows\System32\Recovery\Winre.wim",
"--dest-dir=""D:\OS11_Custom\Install\Install\Update\Winlib""""
)

New-Item -Path "D:\OS11_Custom\Install\Install\Update\Winlib" -ItemType Directory -ea SilentlyContinue
Start-Process -FilePath "d:\wimlib\wimlib-imagex.exe" -ArgumentList $Arguments -wait -nonewwindow

```

13.2.2. **Get all index numbers of Install.wim and replace the old WinRE.wim**

Copy the code or view the source file: [Install.WinRE.Replace.wim.ps1](#) ([Local](#), [Github](#))

```

Get-WindowsImage -ImagePath "D:\OS11\sources\install.wim" -ErrorAction SilentlyContinue | ForEach-Object {
    Write-Host "  Image name: " -NoNewline
    Write-Host $_.ImageName -ForegroundColor Yellow
    Write-Host "  The index number: " -NoNewline
    Write-Host $_.ImageIndex -ForegroundColor Yellow
    Write-Host "`n  Replacement "
    $Arguments = @(
        "update",
        "D:\OS11\sources\install.wim", $_.ImageIndex,
        "--command=""add 'D:\OS11_Custom\Install\Install\Update\Winlib\WinRE.wim'
'\Windows\System32\Recovery\WinRe.wim'""""
    )
    Start-Process -FilePath "d:\wimlib\wimlib-imagex.exe" -ArgumentList $Arguments -wait -nonewwindow
    Write-Host "  Finish`n" -ForegroundColor Green
}

```

14. **Rebuilding Install.wim reduces file size**

Copy the code or view the source file: [Install.Rebuild.wim.ps1](#) ([Local](#), [Github](#))

```

$InstallWim = "D:\OS11\sources\install.wim"
Get-WindowsImage -ImagePath $InstallWim -ErrorAction SilentlyContinue | ForEach-Object {
    Write-Host "  Image name: " -NoNewline
    Write-Host $_.ImageName -ForegroundColor Yellow
    Write-Host "  The index number: " -NoNewline
    Write-Host $_.ImageIndex -ForegroundColor Yellow
    Write-Host "`n  Under reconstruction".PadRight(28) -NoNewline
    Export-WindowsImage -SourceImagePath $InstallWim -SourceIndex $_.ImageIndex -DestinationImagePath "$($InstallWim).New" -
CompressionType max | Out-Null
    Write-Host "Finish`n" -ForegroundColor Green
}

if (Test-Path "$($InstallWim).New" -PathType Leaf) {
    Remove-Item -Path $InstallWim
    Move-Item -Path "$($InstallWim).New" -Destination $InstallWim
    Write-Host "Finish" -ForegroundColor Green
} else {
    Write-host "Failed" -ForegroundColor Red
}

```

III **Custom deployment image: boot.wim**

1. **View Boot.wim details**

Image name, image description, image size, architecture, version, index number, etc.

```
$ViewFile = "D:\OS11\Sources\Boot.wim"
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object {
    Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex
}
```

2. Specify the path to mount Boot.wim

```
New-Item -Path "D:\OS11_Custom\Boot\Boot\Mount" -ItemType directory -ea SilentlyContinue
```

3. Start mounting Boot.wim

Default index number: 2

```
Mount-WindowsImage -ImagePath "D:\OS11\sources\boot.wim" -Index "2" -Path "D:\OS11_Custom\Boot\Boot\Mount"
```

4. Language pack

Automatically install language packs: Get "Component: All installed packages in the image" and match them. After matching the corresponding names, install the local corresponding language pack files.

4.1. Language pack: add

Copy the code or view the source file: [Boot.Instl.lang.ps1](#) ([Local](#), [Github](#))

```
$Mount = "D:\OS11_Custom\Boot\Boot\Mount"
$Sources = "D:\OS11_Custom\Boot\Boot\Language\Add\zh-CN"

$Initl_install_Language_Component = @()
Get-WindowsPackage -Path $Mount | ForEach-Object {
    $Initl_install_Language_Component += $_.PackageName
}
Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\WinPE-FontSupport-zh-CN.cab"

$Language_List = @(
    @{ Match = "*WinPE*Setup*Client*Package*"; File = "WINPE-SETUP-CLIENT_zh-CN.CAB"; }
    @{ Match = "*WinPE*Setup*Package*"; File = "WinPE-Setup_zh-CN.cab"; }
    @{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }
    @{ Match = "*SecureStartup*"; File = "winpe-securestartup_zh-CN.cab"; }
    @{ Match = "*ATBroker*"; File = "winpe-atbroker_zh-CN.cab"; }
    @{ Match = "*AudioCore*"; File = "winpe-audiocore_zh-CN.cab"; }
    @{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_zh-CN.cab"; }
    @{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_zh-CN.cab"; }
    @{ Match = "*Narrator*"; File = "winpe-narrator_zh-CN.cab"; }
    @{ Match = "*scripting*"; File = "winpe-scripting_zh-CN.cab"; }
    @{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_zh-CN.cab"; }
    @{ Match = "*srh*"; File = "winpe-srh_zh-CN.cab"; }
    @{ Match = "*srt*"; File = "winpe-srt_zh-CN.cab"; }
    @{ Match = "*wds-tools*"; File = "winpe-wds-tools_zh-CN.cab"; }
    @{ Match = "*-WMI-Package*"; File = "winpe-wmi_zh-CN.cab"; }
)

ForEach ($Rule in $Language_List) {
    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host " $('-' * 80)"
    ForEach ($Component in $Initl_install_Language_Component) {
        if ($Component -like "$($Rule.Match)*") {
            Write-host " Component name: " -NoNewline
```

```

Write-host $Component -ForegroundColor Green
Write-host "  Language pack file: " -NoNewline
Write-host "$($Sources)\ $($Rule.File)" -ForegroundColor Green
Write-Host "  Installing ".PadRight(22) -NoNewline
try {
    Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\ $($Rule.File)" | Out-Null
    Write-host "Finish" -ForegroundColor Green
} catch {
    Write-host "Failed" -ForegroundColor Red
}
break
}
}
}

```

4.2. Offline image language: change

4.2.1. Change default language, regional settings, and other international settings

```

Region: zh-CN

Dism /Image:"D:\OS11_Custom\Boot\Boot\Mount" /Set-AllIntl:"zh-CN"

```

4.2.2. View available language settings

```

Dism /Image:"D:\OS11_Custom\Boot\Boot\Mount" /Get-Intl

```

4.3. Language packs: Removed, optional

- After you add languages, if you want to deploy to a non-English locale, you can save space by removing the English language component. When you remove a language, uninstall the language components in the reverse order in which you added them.
- After adding the Chinese, delete "English - United States" in reverse, the Region tag: en-US, you need to extract the language pack in advance

Copy the code or view the source files: [Boot.Del.Specified.lang.Tag.ps1](#) ([Local](#), [Github](#))

```

$Lang = "en-US"
$Mount = "D:\OS11_Custom\Boot\Boot\Mount"
$Sources = "D:\OS11_Custom\Boot\Boot\Language\Del\en-US"
$Initl_install_Language_Component = @()
Get-WindowsPackage -Path $Mount | ForEach-Object {
    $Initl_install_Language_Component += $_.PackageName
}
$Language = @(
    @{ Match = "*WordPad*wow64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~wow64~ $($Lang)~.cab"; }
    @{ Match = "*WordPad*amd64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~amd64~ $($Lang)~.cab"; }
    @{ Match = "*WMIC*FoD*Package*wow64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~wow64~ $($Lang)~.cab"; }
    @{ Match = "*WMIC*FoD*Package*amd64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~AMD64~ $($Lang)~.cab"; }
    @{ Match = "*StepsRecorder*wow64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~wow64~ $($Lang)~.cab"; }
    @{ Match = "*StepsRecorder*amd64*"; File = "Microsoft-Windows-StepsRecorder-

```

```
Package~31bf3856ad364e35~amd64~$(Lang)~.cab"; }

    @{ Match = "**Printing*PMCPPC*amd64*"; File = "Microsoft-Windows-Printing-PMCPPC-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

    @{ Match = "**PowerShell*wow64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

    @{ Match = "**PowerShell*amd64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~amd64~$(Lang)~.cab"; }

    @{ Match = "**MediaPlayer*wow64*"; File = "Microsoft-Windows-MediaPlayer-Package-wow64-$(Lang).cab"; }

    @{ Match = "**MediaPlayer*amd64*"; File = "Microsoft-Windows-MediaPlayer-Package-AMD64-$(Lang).cab"; }

    @{ Match = "**Notepad*wow64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

    @{ Match = "**Notepad*amd64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

    @{ Match = "**InternetExplorer*"; File = "Microsoft-Windows-InternetExplorer-Optional-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

    @{ Match = "**TextToSpeech*"; File = "Microsoft-Windows-LanguageFeatures-TextToSpeech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "**LanguageFeatures-Speech*"; File = "Microsoft-Windows-LanguageFeatures-Speech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "**OCR*"; File = "Microsoft-Windows-LanguageFeatures-OCR-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "**Handwriting*"; File = "Microsoft-Windows-LanguageFeatures-Handwriting-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "**LanguageFeatures-Basic*"; File = "Microsoft-Windows-LanguageFeatures-Basic-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "**Client-LanguagePack-Package*"; File = "Microsoft-Windows-Client-Language-Pack_x64_$(Lang).cab"; }
)

ForEach ($Rule in $Language) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "*$($Rule.Match)*$(Lang)*") {

            Write-host "  Component name: " -NoNewline

            Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline

            Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

            Write-Host "  Deleting ".PadRight(22) -NoNewline

            try{

                Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" -ErrorAction SilentlyContinue | Out-Null

                Write-host "Finish" -ForegroundColor Green

            } catch {

                Write-host "Failed" -ForegroundColor Red

                Write-host "  $('_)*" -ForegroundColor Red

            }

            break

        }

    }

}

$InitlClearLanguagePackage = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    if ($_.PackageName -like "*$(Lang)*") {

        $InitlClearLanguagePackage += $_.PackageName

    }

}

if ($InitlClearLanguagePackage.count -gt 0) {

    ForEach ($item in $InitlClearLanguagePackage) {

        Write-Host "`n  $($item)" -ForegroundColor Green

        Write-Host "  Deleting ".PadRight(22) -NoNewline

    }

}
```

```

try{
    Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction SilentlyContinue | Out-Null
    Write-host "Finish" -ForegroundColor Green
} catch {
    Write-host "Failed" -ForegroundColor Red
    Write-host " $($*)" -ForegroundColor Red
}
}
}
}

```

4.4. Components: All packages installed in the image

4.4.1. View

```
Get-WindowsPackage -Path "D:\OS11_Custom\Boot\Boot\Mount" | Out-GridView
```

4.4.2. Export to csv

```

$SaveTo = "D:\OS11_Custom\Boot\Boot\Report.$(Get-Date -Format "yyyyMMddHHmmss").csv"
Get-WindowsPackage -Path "D:\OS11_Custom\Boot\Boot\Mount" | Export-CSV -NoType -Path $SaveTo
Write-host $SaveTo -ForegroundColor Green

```

4.5. Language: Repair

4.5.1. Extract

Open: [D:\OS11_Custom\Install\Install\Language\Add\zh-CN\Microsoft-Windows-Client-Language-Pack_x64_zh-CN.cab](#), enter the directory: [Setup\sources\zh-cn\cli](#), and copy the following files to the deskto:

- 4.5.1.1. [arunres.dll.mui](#)
- 4.5.1.2. [spwizres.dll.mui](#)
- 4.5.1.3. [w32uires.dll.mui](#)

4.5.2. Copy

Copy the extracted files to: [D:\OS11_Custom\Boot\Boot\Mount\sources\zh-CN](#)

4.6. Language packs: sync to ISO installer

```
Copy-Item -Path "D:\OS11_Custom\Boot\Boot\Mount\sources\zh-CN" -Destination "D:\OS11\sources\zh-CN" -Recurse -Force
```

4.7. Regenerate Lang.ini

After regeneration, you can adjust the "Installation Interface", the order when selecting "Language", open lang.ini, the default preferred value = 3, non-default value = 2.

4.7.1. Regenerate the mounted directory lang.ini

Regenerated Lang.ini file location: D:\en-us_windows_server_2022_x64_dvd_620d7eac_Custom\Boot\Boot\Mount\Sources\lang.ini

```
Dism /image:"D:\OS11_Custom\Boot\Boot\Mount" /gen-langini /distribution:"D:\OS11_Custom\Boot\Boot\Mount"
```


4.7.2. After regenerating lang.ini, sync to the installer

Regenerated Lang.ini file location: D:\en-us_windows_server_2022_x64_dvd_620d7eac\Sources\lang.ini

```
Dism /image:"D:\OS11_Custom\Boot\Boot\Mount" /gen-langini /distribution:"D:\OS11"
```

5. Cumulative updates, optional

To prepare the cumulative updates file available, change the example file name: **KB_Boot.cab**

5.1. Add

```
$KBPath = "D:\OS11_Custom\Boot\Boot\Update\KB_Boot.cab"
Add-WindowsPackage -Path "D:\OS11_Custom\Boot\Boot\Mount" -PackagePath $KBPath
```

5.2. Delete

```
$KBPath = "D:\OS11_Custom\Boot\Boot\Update\KB_Boot.cab"
Remove-WindowsPackage -Path "D:\OS11_Custom\Boot\Boot\Mount" -PackagePath $KBPath
```

5.3. Solid update, optional

It cannot be uninstalled after curing, which cleans the recovery image and resets the basis of any superseded components.

```
Dism /image:"D:\OS11_Custom\Boot\Boot\Mount" /cleanup-image /StartComponentCleanup /ResetBase
```

5.3.1. Clean components after curing and updating, optional

```
$Mount = "D:\OS11_Custom\Boot\Boot\Mount"
Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {
    if ($_.PackageState -eq "Superseded") {
        Write-Host " ${_.PackageName}" -ForegroundColor Green
        Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null
    }
}
```

6. Drive, optional

7. Other

7.1. Bypass TPM

Copy the code or view the source file: [Boot.Bypass.TPM.ps1](#) ([Local](#), [Github](#))

```
$RegSystem = "D:\OS11_Custom\Boot\Boot\Mount\Windows\System32\Config\SYSTEM"
$RandomGuid = [guid]::NewGuid()
Write-Host " HKLM:\${$RandomGuid}"
New-PSDrive -PSProvider Registry -Name OtherTasksTPM -Root HKLM -ErrorAction SilentlyContinue | Out-Null
Start-Process reg -ArgumentList "Load ""HKLM\${$RandomGuid}"" ""${$RegSystem}"""" -Wait -WindowStyle Hidden -ErrorAction SilentlyContinue
New-Item "HKLM:\${$RandomGuid}\Setup\LabConfig" -force -ea SilentlyContinue | Out-Null
New-ItemProperty -LiteralPath "HKLM:\${$RandomGuid}\Setup\LabConfig" -Name "BypassCPUCheck" -Value 1 -PropertyType DWord -Force -ea SilentlyContinue | Out-Null
```

```
New-ItemProperty -LiteralPath "HKLM:\$(($RandomGuid)\Setup\LabConfig" -Name "BypassStorageCheck" -Value 1 -PropertyType
DWord -Force -ea SilentlyContinue | Out-Null
New-ItemProperty -LiteralPath "HKLM:\$(($RandomGuid)\Setup\LabConfig" -Name "BypassRAMCheck" -Value 1 -PropertyType
DWord -Force -ea SilentlyContinue | Out-Null
New-ItemProperty -LiteralPath "HKLM:\$(($RandomGuid)\Setup\LabConfig" -Name "BypassTPMCheck" -Value 1 -PropertyType
DWord -Force -ea SilentlyContinue | Out-Null
New-ItemProperty -LiteralPath "HKLM:\$(($RandomGuid)\Setup\LabConfig" -Name "BypassSecureBootCheck" -Value 1 -
PropertyType DWord -Force -ea SilentlyContinue | Out-Null
[gc]::collect()
Start-Process reg -ArgumentList "unload ""HKLM\$(($RandomGuid)"" -Wait -WindowStyle Hidden -ErrorAction SilentlyContinue
Remove-PSDrive -Name OtherTasksTPM
```

8. **Save image**

```
Save-WindowsImage -Path "D:\OS11_Custom\Boot\Boot\Mount"
```

9. **Unmount image**

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowsImage -Path "D:\OS11_Custom\Boot\Boot\Mount" -Discard
```

IV **Deployment engine**

- Learn about "Automatically Adding Languages Installed in Windows Systems", learn: <https://github.com/ilikeyi/Multilingual>, how to download:
 - After entering the website, click "Code", "Download Compressed Package", and after the download is completed, you will get the [main.zip](#) compressed package file.
 - Go to the <https://github.com/ilikeyi/Multilingual/releases> download page, select the available version: [1.1.0.4](#), select the download source code format: zip, and get the [Multilingual-1.1.0.4.zip](#) compressed package file after the download is completed;
- Unzip the downloaded [main.zip](#) or [Multilingual-1.1.0.4.zip](#) to: [D:\Multilingual-1.1.0.4](#), and rename: [D:\Multilingual](#)
- Learn "[Unattended Windows Setup Reference](#)", Intervene in the installation process by leaving it unattended.

1. **Add method**

1.1. **Add to ISO installation media**

1.1.1. **Unattended**

1.1.1.1. **Add to: [\[ISO\]:\Autounattend.xml](#)**

Autounattend.xml interferes with the WinPE installer when booting an ISO installation.

Copy [D:\Multilingual\Unattend\Mul.Unattend.xml](#) to [D:\OS11\Autounattend.xml](#)

```
Copy-Item "D:\Multilingual\Unattend\Mul.Unattend.xml" -Destination "D:\OS11\Autounattend.xml" -
Force
```

1.1.1.2. **Add to: [\[ISO\]:\Sources\Unattend.xml](#)**

When mounting or unpacking an ISO, after running the [\[ISO\]:\Setup.exe](#) installer, [\[ISO\]:\Sources\Unattend.xml](#) will intervene in the installation process.

Copy [D:\Multilingual\Unattend\Mul.Unattend.xml](#) to [D:\OS11\Sources\Unattend.xml](#)

```
Copy-Item "D:\Multilingual\Unattend\Mul.Unattend.xml" -Destination "D:\OS11\Sources\Unattend.xml" -
Force
```

1.1.1.3. **Add to: [ISO]:\sources\\$OEM\$\\$\$\Panther\unattend.xml**

Copy it to the system disk during the installation process, copy to: {system
disk}\Windows\Panther\unattend.xml

1.1.1.3.1. **Create \$OEM\$ path**

```
New-Item -Path "D:\OS11\sources\`$OEM$\`$$\Panther" -ItemType Directory
```

1.1.1.3.2. **Copy**

Copy D:\Multilingual\Unattend\Mul.Unattend.xml to
D:\OS11\Sources\\$OEM\$\Panther\Unattend.xml

```
Copy-Item "D:\Multilingual\Unattend\Mul.Unattend.xml" -Destination
"D:\OS11\sources\`$OEM$\`$$\Panther\Unattend.xml" -Force
```

1.1.2. **Deployment engine: add**

Add "Automatically add installed languages for Windows systems" to D:\OS11\sources\\$OEM\$\\$1\Yi\Engine in the
directory.

1.1.2.1. **Deployment Engine: Copy**

Copy D:\Multilingual\Engine to D:\OS11\Sources\\$OEM\$\\$1\Yi\Engine

```
Copy-Item "D:\Multilingual\Engine" -Destination "D:\OS11\sources\`$OEM$\`$1\Yi\Engine" -Recurse -
Force
```

1.1.2.2. **Deployment engine: custom deployment tags**

```
$Flag = @(
    "Is_Mark_Sync" # Allow global search and synchronization of deployment tags
    # Prerequisite deployment
# "Auto_Update" # Allow automatic updates
# "Use_UTF8" # Beta: Global language support using Unicode UTF-8
    "Disable_Network_Location_Wizard" # Network Location Wizard
    "Disable_Cleanup_Appx_Tasks" # Appx Cleanup and maintenance tasks
    "Disable_Cleanup_On_Demand_Language" # Prevent cleanup of unused on-demand feature language
packs
    "Disable_Cleanup_Unsed_Language" # Prevent cleaning of unused language packs
    "Prerequisites_Reboot" # Restart your computer

    # Complete first deployment
# "Popup_Engine" # Allow the deployment engine main interface to pop up for the first time
# "Allow_First_Pre_Experience" # Allow first preview, as planned
    "Reset_Execution_Policy" # Restore PowerShell execution policy: Restricted
    "Clear_Solutions" # Delete the entire solution
    "Clear_Engine" # Delete the deployment engine and keep the others
# "First_Experience_Reboot" # Restart your computer
)
```

```

ForEach ($item in $Flag) {
    Write-host "  $($item)" -ForegroundColor Green

    New-Item -Path "D:\OS11\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow" -ItemType Directory -
    ErrorAction SilentlyContinue | Out-Null

    Out-File -FilePath "D:\OS11\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow\$( $item)" -Encoding utf8 -
    ErrorAction SilentlyContinue
}

```

1.2. Add to mounted

Through "[Customized deployment image: Install.wim](#)", execute "[Start mounting Install.wim](#)" and mount to:
[D:\OS11_Custom\Install\Install\Mount](#)

1.2.1. Unattended

Copy [D:\Multilingual\Unattend\Mul.Unattend.xml](#) to [D:\OS11_Custom\Install\Install\Mount\Panther\Unattend.xml](#)

```

Copy-Item "D:\Multilingual\Unattend\Mul.Unattend.xml" -Destination
"D:\OS11_Custom\Install\Install\Mount\Panther" -Force

```

1.2.2. Deployment engine: add

Add "[Automatically add languages installed on Windows systems](#)" to the
[D:\OS11_Custom\Install\Install\Mount\Yi\Engine](#) directory.

1.2.2.1. Deployment Engine: Copy

Copy [D:\Multilingual\Engine](#) to [D:\OS11_Custom\Install\Install\Mount\Yi\Engine](#)

```

Copy-Item "D:\Multilingual\Engine" -Destination "D:\OS11_Custom\Install\Install\Mount\Yi\Engine" -
Recurse -Force

```

1.2.2.2. Deployment engine: custom deployment tags

```

$Flag = @(
    "Is_Mark_Sync" # Allow global search and synchronization of deployment tags

    # Prerequisite deployment
    # "Auto_Update" # Allow automatic updates
    # "Use_UTF8" # Beta: Global language support using Unicode UTF-8
    "Disable_Network_Location_Wizard" # Network Location Wizard
    "Disable_Cleanup_Appx_Tasks" # Appx Cleanup and maintenance tasks
    "Disable_Cleanup_On_Demand_Language" # Prevent cleanup of unused on-demand feature language
    packs
    "Disable_Cleanup_Unsed_Language" # Prevent cleaning of unused language packs
    "Prerequisites_Reboot" # Restart your computer

    # Complete first deployment
    # "Popup_Engine" # Allow the deployment engine main interface to pop up for the first time
    # "Allow_First_Pre_Experience" # Allow first preview, as planned
    "Reset_Execution_Policy" # Restore PowerShell execution policy: Restricted
    "Clear_Solutions" # Delete the entire solution

```

```

        "Clear_Engine" # Delete the deployment engine and keep the others
#   "First_Experience_Reboot" # Restart your computer
)
ForEach ($item in $Flag) {
    Write-host "  $($item)" -ForegroundColor Green

    New-Item -Path "D:\OS11\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow" -ItemType Directory -
ErrorAction SilentlyContinue | Out-Null

    Out-File -FilePath "D:\OS11\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow\$( $item)" -Encoding utf8 -
ErrorAction SilentlyContinue
}

```

2. Deployment Engine: Advanced

2.1. Deployment engine: adding process

After copying the deployment engine, you can add deployment tags to intervene in the installation process.

2.2. Unattended solution

When the customization is unattended, please modify it simultaneously if the following files exist:

- [D:\OS11\Autounattend.xml](#)
- [D:\OS11\Sources\Unattend.xml](#)
- [D:\OS11\sources\`\\$OEM\\$\`\\$1\Yi\Engine\Deploy\Allow\\\$\(\\$item\)](#)
- [D:\OS11_Custom\Install\Install\Mount\Panther\Unattend.xml](#)

2.2.1. Multilingual or monolingual

In multi-language and monolingual, you can switch between each other. When replacing, please replace all the same ones in the file.

2.2.1.1. Multi-language

```

<UILanguage>%OSDUILanguage%</UILanguage>
<InputLocale>%OSDInputLocale%</InputLocale>
<SystemLocale>%OSDSystemLocale%</SystemLocale>
<UILanguage>%OSDUILanguage%</UILanguage>
<UILanguageFallback>%OSDUILanguageFallback%</UILanguageFallback>
<UserLocale>%OSDUserLocale%</UserLocale>

```

2.2.1.2. Monolingual

A single language needs to specify a Region tag, for example, specify a Region tag: [zh-CN](#)

```

<UILanguage>zh-CN</UILanguage>
<InputLocale>zh-CN</InputLocale>
<SystemLocale>zh-CN</SystemLocale>
<UILanguage>zh-CN</UILanguage>
<UILanguageFallback>zh-CN</UILanguageFallback>
<UserLocale>zh-CN</UserLocale>

```

2.2.2. User plan

By default, the self-created user [Administrator](#) is used and logged in automatically. It can be switched by modifying the

following configuration: self-created or customized user.

2.2.2.1. Self-created user Administrator

By default, the self-created user: Administrator is used and logged in automatically, inserted between <OOBE> and </OOBE>.

```
<UserAccounts>
  <LocalAccounts>
    <LocalAccount wcm:action="add">
      <Password>
        <Value></Value>
        <PlainText>true</PlainText>
      </Password>
      <Description>Administrator</Description>
      <DisplayName>Administrator</DisplayName>
      <Group>Administrators</Group>
      <Name>Administrator</Name>
    </LocalAccount>
  </LocalAccounts>
</UserAccounts>
<AutoLogon>
  <Password>
    <Value></Value>
    <PlainText>true</PlainText>
  </Password>
  <Enabled>true</Enabled>
  <Username>Administrator</Username>
</AutoLogon>
```

2.2.2.2. Custom user

After setting up a custom user and installing the system, in OOBE, you can choose settings such as local and online users.

2.2.2.2.1. Delete

Username: Removed from start <UserAccounts> to </UserAccounts>

Autologin: Remove from start <AutoLogon> to </AutoLogon>

2.2.2.2.2. Replace

From the beginning <OOBE> to </OOBE>

```
<OOBE>
  <ProtectYourPC>3</ProtectYourPC>
  <HideEULAPage>true</HideEULAPage>
  <HideWirelessSetupInOOBE>true</HideWirelessSetupInOOBE>
</OOBE>
```

D. ISO

II Generate ISO

1. After downloading oscdimg, save it to: C:\Windows\System32 directory, save it in another path, or please enter the absolute location of OScdimg.exe;
2. Use the oscdimg command line to generate an ISO file and save it to: D:\OS11.iso

Copy the code or view the source file: [ISO.ps1](#) ([Local](#), [Github](#))

```
$ISO = "D:\OS11"
$Volume = "OS11"
$SaveTo = "D:\OS11.iso"
$Arguments = @("-m", "-o", "-u2", "-udfver102", "-l" "$($Volume)", "-bootdata:2#p0,e,b" "$($ISO)\boot\etfsboot.com" "#pEF,e,b" "$($ISO)\efi\microsoft\boot\efisys.bin", $ISO, $SaveTo)
Start-Process -FilePath "OScdimg.exe" -ArgumentList $Arguments -wait -nonewwindow
```

III Bypass TPM installation check

1. Learn about: <https://github.com/AveYo/MediaCreationTool.bat/tree/main/bypass11> and download: [Quick_11_iso_esd_wim_TPM_toggle.bat](#)
2. Drag the [D:\OS11.iso](#) file to [Quick_11_iso_esd_wim_TPM_toggle.bat](#), and "add" or "delete" the TPM installation check function in reverse order.

TWO. COMMON PROBLEM

II Clean all mounts to

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowsImage -Path "D:\OS11_Custom\Install\Install\Mount" -Discard
```

```
Dismount-WindowsImage -Path "D:\OS11_Custom\Install\WinRE\Mount" -Discard
```

```
Dismount-WindowsImage -Path "D:\OS11_Custom\Boot\Boot\Mount" -Discard
```

III Fix the problem of abnormal mounting

1. View mounted

```
Get-WindowsImage -Mounted
```

2. Delete the DISM mount record saved in the registry

```
Remove-Item -Path "HKLM:\SOFTWARE\Microsoft\WIMMount\Mounted Images\*" -Force -Recurse -ErrorAction SilentlyContinue | Out-Null
```

3. Delete all resources associated with the corrupted mounted image

```
Clear-WindowsCorruptMountPoint
```

```
Dism /cleanup-wim
```

IV Clean directories

```
Remove-Item "D:\OS11_Custom" -Force -Recurse
```

Remove-Item "D:\OS11\Sources\` \$OEM\$" -Force -Recurse

Remove-Item -Path "D:\OS11\Autounattend.xml" -Force

Remove-Item -Path "D:\OS11\Sources\Unattend.xml" -Force

THREE. KNOWN ISSUES

None yet

FOUR. COMPONENTS: ALL PACKAGES INSTALLED IN THE IMAGE, COMPARISON

Changes after installing new language pack, component list:

| SN | TYPE | COMPONENT: ORIGINAL | COMPONENT: CHANGES AFTER INSTALLING "SIMPLIFIED CHINESE - CHINA" LANGUAGE PACK |
|----|--------------|------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| 1 | OnDemandPack | Microsoft-OneCore-ApplicationModel-Sync-Desktop-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.317 | Microsoft-OneCore-ApplicationModel-Sync-Desktop-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.317 |
| 2 | OnDemandPack | Microsoft-OneCore-DirectX-Database-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-OneCore-DirectX-Database-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 3 | LanguagePack | Microsoft-Windows-Client-LanguagePack-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.382 | Microsoft-Windows-Client-LanguagePack-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.382 |
| 4 | LanguagePack | | Microsoft-Windows-Client-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.382 |
| 5 | OnDemandPack | Microsoft-Windows-Ethernet-Client-Intel-E1i68x64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Ethernet-Client-Intel-E1i68x64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 6 | OnDemandPack | Microsoft-Windows-Ethernet-Client-Intel-E2f68-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Ethernet-Client-Intel-E2f68-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 7 | OnDemandPack | Microsoft-Windows-Ethernet-Client-Realtek-Rtcx21x64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Ethernet-Client-Realtek-Rtcx21x64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 8 | OnDemandPack | Microsoft-Windows-Ethernet-Client-Vmware-Vmxnet3-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Ethernet-Client-Vmware-Vmxnet3-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 9 | FeaturePack | Microsoft-Windows-FodMetadata-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-FodMetadata-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 10 | Foundation | Microsoft-Windows-Foundation-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Foundation-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 11 | OnDemandPack | Microsoft-Windows-Hello-Face-Package~31bf3856ad364e35~amd64~~10.0.22621.317 | Microsoft-Windows-Hello-Face-Package~31bf3856ad364e35~amd64~~10.0.22621.317 |
| 12 | OnDemandPack | Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~en-US~11.0.22621.1 | Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~en-US~11.0.22621.1 |
| 13 | OnDemandPack | | Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~zh-CN~11.0.22621.1 |
| 14 | OnDemandPack | Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~~11.0.22621.1 | Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~~11.0.22621.1 |
| 15 | OnDemandPack | Microsoft-Windows-Kernel-LA57-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.382 | Microsoft-Windows-Kernel-LA57-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.382 |
| 16 | OnDemandPack | Microsoft-Windows-LanguageFeatures-Basic-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-LanguageFeatures-Basic-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 17 | OnDemandPack | | Microsoft-Windows-LanguageFeatures-Basic-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 18 | OnDemandPack | | Microsoft-Windows-LanguageFeatures-Fonts-Hans-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 19 | OnDemandPack | Microsoft-Windows-LanguageFeatures-Handwriting-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-LanguageFeatures-Handwriting-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 20 | OnDemandPack | | Microsoft-Windows-LanguageFeatures-Handwriting-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.22621.317 |
| 21 | OnDemandPack | Microsoft-Windows-LanguageFeatures-OCR-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-LanguageFeatures-OCR-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 22 | OnDemandPack | | Microsoft-Windows-LanguageFeatures-OCR-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 23 | OnDemandPack | Microsoft-Windows-LanguageFeatures-Speech-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-LanguageFeatures-Speech-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 24 | OnDemandPack | | Microsoft-Windows-LanguageFeatures-Speech-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 25 | OnDemandPack | Microsoft-Windows-LanguageFeatures-TextToSpeech-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-LanguageFeatures-TextToSpeech-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 26 | OnDemandPack | | Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 27 | OnDemandPack | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.317 | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.317 |

| SN | TYPE | COMPONENT: ORIGINAL | COMPONENT: CHANGES AFTER INSTALLING "SIMPLIFIED CHINESE - CHINA" LANGUAGE PACK |
|----|--------------|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|
| 28 | OnDemandPack | | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.317 |
| 29 | OnDemandPack | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~amd64~~10.0.22621.382 | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~amd64~~10.0.22621.382 |
| 30 | OnDemandPack | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 |
| 31 | OnDemandPack | | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1 |
| 32 | OnDemandPack | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~wow64~~10.0.22621.1 | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~wow64~~10.0.22621.1 |
| 33 | OnDemandPack | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 |
| 34 | OnDemandPack | | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1 |
| 35 | OnDemandPack | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 36 | OnDemandPack | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 |
| 37 | OnDemandPack | | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1 |
| 38 | OnDemandPack | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~wow64~~10.0.22621.1 | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~wow64~~10.0.22621.1 |
| 39 | OnDemandPack | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 |
| 40 | OnDemandPack | | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1 |
| 41 | OnDemandPack | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 42 | OnDemandPack | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 |
| 43 | OnDemandPack | | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1 |
| 44 | OnDemandPack | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~~10.0.22621.1 | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~~10.0.22621.1 |
| 45 | OnDemandPack | Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 | Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 |
| 46 | OnDemandPack | | Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1 |
| 47 | OnDemandPack | Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 48 | OnDemandPack | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 |
| 49 | OnDemandPack | | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1 |
| 50 | OnDemandPack | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 51 | OnDemandPack | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 |
| 52 | OnDemandPack | | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1 |
| 53 | OnDemandPack | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~~10.0.22621.1 | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~~10.0.22621.1 |
| 54 | OnDemandPack | Microsoft-Windows-TabletPCMath-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-TabletPCMath-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 55 | OnDemandPack | Microsoft-Windows-Wallpaper-Content-Extended-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wallpaper-Content-Extended-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 56 | OnDemandPack | Microsoft-Windows-Wifi-Client-Broadcom-Bcmppciedhd63-FOD- | Microsoft-Windows-Wifi-Client-Broadcom-Bcmppciedhd63-FOD- |

| SN | TYPE | COMPONENT: ORIGINAL | COMPONENT: CHANGES AFTER INSTALLING "SIMPLIFIED CHINESE - CHINA" LANGUAGE PACK |
|----|--------------|------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| | | Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 57 | OnDemandPack | Microsoft-Windows-Wifi-Client-Broadcom-Bcmwl63a-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Broadcom-Bcmwl63a-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 58 | OnDemandPack | Microsoft-Windows-Wifi-Client-Broadcom-Bcmwl63al-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Broadcom-Bcmwl63al-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 59 | OnDemandPack | Microsoft-Windows-Wifi-Client-Intel-Netwbw02-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Intel-Netwbw02-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 60 | OnDemandPack | Microsoft-Windows-Wifi-Client-Intel-Netwew00-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Intel-Netwew00-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 61 | OnDemandPack | Microsoft-Windows-Wifi-Client-Intel-Netwew01-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Intel-Netwew01-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 62 | OnDemandPack | Microsoft-Windows-Wifi-Client-Intel-Netwlv64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Intel-Netwlv64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 63 | OnDemandPack | Microsoft-Windows-Wifi-Client-Intel-Netwns64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Intel-Netwns64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 64 | OnDemandPack | Microsoft-Windows-Wifi-Client-Intel-Netwsw00-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Intel-Netwsw00-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 65 | OnDemandPack | Microsoft-Windows-Wifi-Client-Intel-Netwtw02-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Intel-Netwtw02-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 66 | OnDemandPack | Microsoft-Windows-Wifi-Client-Intel-Netwtw04-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Intel-Netwtw04-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 67 | OnDemandPack | Microsoft-Windows-Wifi-Client-Intel-Netwtw06-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Intel-Netwtw06-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 68 | OnDemandPack | Microsoft-Windows-Wifi-Client-Intel-Netwtw08-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Intel-Netwtw08-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 69 | OnDemandPack | Microsoft-Windows-Wifi-Client-Intel-Netwtw10-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Intel-Netwtw10-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 70 | OnDemandPack | Microsoft-Windows-Wifi-Client-Marvel-Mrvlpcie8897-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Marvel-Mrvlpcie8897-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 71 | OnDemandPack | Microsoft-Windows-Wifi-Client-Qualcomm-Athw8x-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Qualcomm-Athw8x-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 72 | OnDemandPack | Microsoft-Windows-Wifi-Client-Qualcomm-Athwnx-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Qualcomm-Athwnx-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 73 | OnDemandPack | Microsoft-Windows-Wifi-Client-Qualcomm-Qcamain10x64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Qualcomm-Qcamain10x64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 74 | OnDemandPack | Microsoft-Windows-Wifi-Client-Ralink-Netr28x-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Ralink-Netr28x-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 75 | OnDemandPack | Microsoft-Windows-Wifi-Client-Realtek-Rtl8187se-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Realtek-Rtl8187se-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 76 | OnDemandPack | Microsoft-Windows-Wifi-Client-Realtek-Rtl8192se-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Realtek-Rtl8192se-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 77 | OnDemandPack | Microsoft-Windows-Wifi-Client-Realtek-Rtl819xp-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Realtek-Rtl819xp-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 78 | OnDemandPack | Microsoft-Windows-Wifi-Client-Realtek-Rtl85n64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Realtek-Rtl85n64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 79 | OnDemandPack | Microsoft-Windows-Wifi-Client-Realtek-Rtlwlan-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Realtek-Rtlwlan-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 80 | OnDemandPack | Microsoft-Windows-Wifi-Client-Realtek-Rtlwlan01-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Realtek-Rtlwlan01-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 81 | OnDemandPack | Microsoft-Windows-Wifi-Client-Realtek-Rtlwlan13-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | Microsoft-Windows-Wifi-Client-Realtek-Rtlwlan13-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 82 | OnDemandPack | Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 | Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 |
| 83 | OnDemandPack | | Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1 |
| 84 | OnDemandPack | Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.382 | Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.382 |

| SN | TYPE | COMPONENT: ORIGINAL | COMPONENT: CHANGES AFTER INSTALLING "SIMPLIFIED CHINESE - CHINA" LANGUAGE PACK |
|----|----------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 85 | OnDemandPack | Microsoft-Windows-WMIC-FoD- Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 | Microsoft-Windows-WMIC-FoD- Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 |
| 86 | OnDemandPack | | Microsoft-Windows-WMIC-FoD- Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1 |
| 87 | OnDemandPack | Microsoft-Windows-WMIC-FoD- Package~31bf3856ad364e35~wow64~~10.0.22621.1 | Microsoft-Windows-WMIC-FoD- Package~31bf3856ad364e35~wow64~~10.0.22621.1 |
| 88 | OnDemandPack | Microsoft-Windows-WordPad-FoD- Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 | Microsoft-Windows-WordPad-FoD- Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 |
| 89 | OnDemandPack | | Microsoft-Windows-WordPad-FoD- Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1 |
| 90 | OnDemandPack | Microsoft-Windows-WordPad-FoD- Package~31bf3856ad364e35~amd64~~10.0.22621.317 | Microsoft-Windows-WordPad-FoD- Package~31bf3856ad364e35~amd64~~10.0.22621.317 |
| 91 | OnDemandPack | Microsoft-Windows-WordPad-FoD- Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 | Microsoft-Windows-WordPad-FoD- Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 |
| 92 | OnDemandPack | | Microsoft-Windows-WordPad-FoD- Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1 |
| 93 | OnDemandPack | Microsoft-Windows-WordPad-FoD- Package~31bf3856ad364e35~wow64~~10.0.22621.1 | Microsoft-Windows-WordPad-FoD- Package~31bf3856ad364e35~wow64~~10.0.22621.1 |
| 94 | OnDemandPack | OpenSSH-Client- Package~31bf3856ad364e35~amd64~~10.0.22621.1 | OpenSSH-Client- Package~31bf3856ad364e35~amd64~~10.0.22621.1 |
| 95 | Update | Package_for_DotNetRollup_481~31bf3856ad364e35~amd64~~10.0.9065.6 | Package_for_DotNetRollup_481~31bf3856ad364e35~amd64~~10.0.9065.6 |
| 96 | SecurityUpdate | Package_for_RollupFix~31bf3856ad364e35~amd64~~22621.382.1.13 | Package_for_RollupFix~31bf3856ad364e35~amd64~~22621.382.1.13 |
| 97 | SecurityUpdate | Package_for_ServicingStack_378~31bf3856ad364e35~amd64~~22621.378.1.0 | Package_for_ServicingStack_378~31bf3856ad364e35~amd64~~22621.378.1.0 |