

PACKAGING TUTORIAL: MICROSOFT WINDOWS SERVER 2022

Different system versions have different packaging methods. The packaging process includes: "Language pack: add, associate, delete", "Drive: add, delete", "Cumulative update: add, delete", "InBox Apps: add, Update, mark" etc.

There are many hidden stories hidden behind this. If you want to unlock these, are you ready to start trying to encapsulate them?



WHAT'S INCLUDED:

- Chapter 1 DEPLOYMENT IMAGE
- Chapter 2 COMMON PROBLEM
- Chapter 3 KNOWN ISSUES
- Chapter 4 Report

TABLE OF CONTENTS

Chapter 1	Deployment image	Page 6
A.	Prerequisites	Page 6
II	ISO tools	Page 6
III	Requirements	Page 6
1.	System installation package	Page 6
2.	Language pack	Page 6
2.1.	Learn	Page 6
2.2.	Language pack: Download	Page 7
IV	Command Line	Page 7
B.	Language Pack: Extraction	Page 7
II	Language pack: Ready	Page 7
III	Language pack: Extract scheme	Page 7
IV	Execute the extract command	Page 7
C.	Customize the deployment image	Page 12
II	Custom deployment image: Install.wim	Page 12
1.	View Install.wim details	Page 12
2.	Specify the path to mount Install.wim	Page 12
3.	Start mounting Install.wim	Page 12
3.1.	Custom deployment image: WinRE.wim	Page 13
3.1.1.	View WinRE.wim details	Page 13
3.1.2.	Specify the path to mount WinRE.wim	Page 13
3.1.3.	Start mounting WinRE.wim	Page 13
3.1.4.	Language pack	Page 13
3.1.4.1.	Language pack: add	Page 13
3.1.4.2.	Offline image language: change	Page 15
3.1.4.2.1.	Change default language, regional settings, and other international settings	Page 15

3.1.4.2.2.	View available language settings	Page 15
3.1.4.3.	Language packs: Removed	Page 15
3.1.4.4.	Components: All packages installed in the image	Page 17
3.1.5.	Cumulative updates	Page 17
3.1.5.1.	Add	Page 17
3.1.5.2.	Delete	Page 17
3.1.5.3.	Solid update	Page 18
3.1.5.3.1.	Clean components after curing and updating	Page 18
3.1.6.	Drive	Page 18
3.1.7.	Save image	Page 18
3.1.8.	Unmount image	Page 18
3.1.9.	After rebuilding WinRE.wim, the file size can be reduced	Page 18
3.1.10.	Backup WinRE.wim	Page 19
3.1.11.	Replace WinRE.wim within the Install.wim image	Page 19
4.	Language pack	Page 19
4.1.	Language pack: add	Page 20
4.2.	Offline image language: change	Page 24
4.2.1.	Change the default language, locale, and other international settings	Page 25
4.2.2.	View the available language settings	Page 25
4.3.	Language packs: Removed	Page 25
4.4.	Components: All packages installed in the image	Page 27
5.	Cumulative updates	Page 27
5.1.	Download	Page 27
5.2.	Add	Page 28
5.3.	Solidify Updated	Page 28
5.3.1.	Clean components after curing and updating	Page 28
6.	Drive	Page 28
7.	Add deployment engine	Page 28
8.	Health	Page 28

9.	Replace WinRE.wim	Page 29
10.	Save image	Page 29
11.	Unmount image	Page 29
12.	Rebuilding Install.wim reduces file size	Page 29
13.	How to batch replace WinRE.wim in all index numbers in Install.wim	Page 30
13.1.	Obtain WimLib	Page 30
13.2.	How to extract and update WinRE.wim in Install.wim	Page 30
III	Custom deployment image: boot.wim	Page 31
1.	View Boot.wim details	Page 31
2.	Specify the path to mount Boot.wim	Page 31
3.	Start mounting Boot.wim	Page 31
4.	Language pack	Page 31
4.1.	Language pack: Add	Page 31
4.2.	Offline image language: change	Page 33
4.2.1.	Change default language, regional settings, and other international settings	Page 33
4.2.2.	View available language settings	Page 33
4.3.	Language pack: Removed	Page 33
4.4.	Components: All packages installed in the image	Page 35
4.5.	Language packs: sync to ISO installer	Page 35
4.6.	Regenerate Lang.ini	Page 36
4.6.1.	Regenerate the mounted directory lang.ini	Page 36
4.6.2.	After regenerating lang.ini, sync to the installer	Page 36
5.	Cumulative updates	Page 36
5.1.	Add	Page 36
5.2.	Delete	Page 36
5.3.	Solid update	Page 36
5.3.1.	Clean components after curing and updating	Page 36
6.	Drive	Page 37

7.	Save image	Page 37
8.	Unmount image	Page 37
IV	Deployment engine	Page 37
1.	Add method	Page 37
2.	Deployment Engine: Advanced	Page 40
D.	Generate ISO	Page 42
Chapter 2	Common problem	Page 43
II	Clean all mounts to	Page 43
III	Fix the problem of abnormal mounting	Page 43
IV	Clean directories	Page 43
Chapter 3	Known issues	Page 43
Chapter 4	Report	Page 4444
II	Reports: Different versions	Page 44
III	Report: Language installation packages apply to Install.wim	Page 46
IV	Report: Language installation packages apply to WinRE.wim	Page 47
V	Report: Language installation packages apply to Boot.wim	Page 48

Chapter 1 DEPLOYMENT IMAGE

A. PREREQUISITES

II ISO tools

Use a software that can edit ISO files, such as: [PowerISO](#), [DAEMON Tools](#), [ISO Workshop](#);

III Requirements

Learn "[Attachment: OS](#)" and view the "[Windows Server 2022](#)",

1. System installation package

1.1. Prepare: [en-us_windows_server_2022_x64_dvd_620d7eac.iso](#)

1.2. Unzip to: [D:\en-us_windows_server_2022_x64_dvd_620d7eac](#)

1.3. After decompression is complete, change the directory [en-us_windows_server_2022_x64_dvd_620d7eac](#) to [D:\OS_2022](#)

1.4. All scripts and all paths have been set to [D:\OS_2022](#) by default as the image source.

2. Language Pack

2.1. Learn

2.1.1. [Add languages to a Windows 11 image](#)

2.1.2. [Language and region Features on Demand \(FOD\)](#)

2.1.2.1. Fonts

- When adding a language pack, when the corresponding region is triggered, the required font functions need to be added, download "[List of all available language FODs](#)" learn more.
- In "[Language Pack: Extraction](#)", the automatic recognition function has been added, and you can understand the functions: [Function Match_Required_Fonts](#)

2.1.2.2. Regional association

What are regional connections?

- When the image language is only in English, after adding the [zh-HK](#) language pack, the image language will not be added. You should install [zh-TW](#) first, and then install [zh-HK](#) to obtain the corresponding association.
- Please refer to Microsoft's official original version: Windows 10, Windows 11 Traditional Chinese version.

Known regional associations:

2.1.2.2.1. Region: zh-TW, Optional associated areas: zh-HK

2.2. Language pack: Download

[20348.1.210507-1500.fe_release_amd64fre_SERVER_LOF_PACKAGES_OEM.iso](#)

IV Command line

1. Optional "Terminal" or "PowerShell ISE", if "Terminal" is not installed, please go to: <https://github.com/microsoft/terminal/releases>
After downloading;
2. Open "Terminal" or "PowerShell ISE" as administrator, it is recommended to set the PowerShell execution policy: bypass, PS
command line:

`Set-ExecutionPolicy -ExecutionPolicy Bypass -Force`
3. In this article, PS command line, green part, please copy it, paste it into the "Terminal" dialog box, press Enter and start running;
4. When there is .ps1, right-click the file and select Run with PowerShell, or copy the path and paste it into Terminal to run.

B. LANGUAGE PACKAGE: EXTRACT

II Language pack: Ready

Mounted [20348.1.210507-1500.fe_release_amd64fre_SERVER_LOF_PACKAGES_OEM.iso](#) or unzip it to any location;

III Language pack: Extract scheme

1. Add

1.1. Language name: [Simplified Chinese - China](#), language tag: [zh-CN](#), Scope of application: [Install.Wim](#), [Boot.Wim](#),
[WinRE.Wim](#)
2. Delete

2.1. Language name: [English - United States](#), language tag: [en-US](#), Scope of application: [Install.Wim](#), [Boot.Wim](#), [WinRE.Wim](#)

IV Execute the extract command

- [Auto](#) = automatically search all local disks, default;
- Customize the path, for example, specify the E drive: `$ISO = "E:\"`
- Extract.ps1
 - [\Expand\Extract.ps1](#)

- https://github.com/ilikeyi/solutions/blob/main/_Documents/Attachment/OS.2022/Expand/Extract.ps1

- Copy the code

```
$ISO = "Auto"

$SaveTo = "D:\OS_2022_Custom"

$Extract_language_Pack = @(

    @{ Tag = "zh-CN"; Act = "Add"; Scope = @( "Install\Install"; "Install\WinRE"; "Boot\Boot" ) }

    @{ Tag = "en-US"; Act = "Del"; Scope = @( "Install\Install"; "Install\WinRE"; "Boot\Boot" ) }

)

Function Extract_Language

{

    param( $Act, $NewLang, $Expand )

    Function Match_Required_Fonts

    {

        param( $Lang )

        $Fonts = @(

            @{ Match = @( "as", "ar-SA", "ar", "ar-AE", "ar-BH", "ar-DJ", "ar-DZ", "ar-EG", "ar-ER", "ar-IL", "ar-IQ", "ar-JO", "ar-KM", "ar-KW", "ar-LB", "ar-LY", "ar-MA", "ar-MR", "ar-OM", "ar-PS", "ar-QA", "ar-SD", "ar-SO", "ar-SS", "ar-SY", "ar-TD", "ar-TN", "ar-YE", "arz-Arab", "ckb-Arab", "fa", "fa-AF", "fa-IR", "glk-Arab", "ha-Arab", "ks-Arab", "ks-Arab-IN", "ku-Arab", "ku-Arab-IQ", "mzn-Arab", "pa-Arab", "pa-Arab-PK", "pnb-Arab", "prs", "prs-AF", "prs-Arab", "ps", "ps-AF", "sd-Arab", "sd-Arab-PK", "tk-Arab", "ug", "ug-Arab", "ug-CN", "ur", "ur-IN", "ur-PK", "uz-Arab", "uz-Arab-AF"); Name = "Arab"; }

            @{ Match = @( "bn-IN", "as-IN", "bn", "bn-BD", "bpy-Beng"); Name = "Beng"; }

            @{ Match = @( "da-dk", "iu-Cans", "iu-Cans-CA"); Name = "Cans"; }

            @{ Match = @( "chr-Cher-US", "chr-Cher"); Name = "Cher"; }

            @{ Match = @( "hi-IN", "bh-Deva", "brx", "brx-Deva", "brx-IN", "hi", "ks-Deva", "mai", "mr", "mr-IN", "ne", "ne-IN", "ne-NP", "new-Deva", "pi-Deva", "sa", "sa-Deva", "sa-IN"); Name = "Deva"; }

            @{ Match = @( "am", "am-ET", "byn", "byn-ER", "byn-Ethi", "ti", "ti-ER", "ti-ET", "tig", "tig-ER", "tig-Ethi", "ve-Ethi", "wal", "wal-ET", "wal-Ethi"); Name = "Ethi"; }

            @{ Match = @( "gu", "gu-IN"); Name = "Gujr"; }

            @{ Match = @( "pa", "pa-IN", "pa-Guru"); Name = "Guru"; }

            @{ Match = @( "zh-CN", "cmn-Hans", "gan-Hans", "hak-Hans", "wuu-Hans", "yue-Hans", "zh-gan-Hans", "zh-hak-Hans", "zh-Hans", "zh-SG", "zh-wuu-Hans", "zh-yue-Hans"); Name = "Hans"; }

            @{ Match = @( "zh-TW", "cmn-Hant", "hak-Hant", "lzh-Hant", "zh-hak-Hant", "zh-Hant", "zh-HK", "zh-lzh-Hant", "zh-MO", "zh-yue-Hant"); Name = "Hant"; }

            @{ Match = @( "he", "he-IL", "yi"); Name = "Hebr"; }

            @{ Match = @( "ja", "ja-JP"); Name = "Jpan"; }

            @{ Match = @( "km", "km-KH"); Name = "Khmr"; }

            @{ Match = @( "kn", "kn-IN"); Name = "Knda"; }

            @{ Match = @( "ko", "ko-KR"); Name = "Kore"; }

            @{ Match = @( "de-de", "lo", "lo-LA"); Name = "Lao"; }

            @{ Match = @( "ml", "ml-IN"); Name = "Mlym"; }

            @{ Match = @( "or", "or-IN"); Name = "Orya"; }

            @{ Match = @( "si", "si-LK"); Name = "Sinh"; }

            @{ Match = @( "tr-tr", "arc-Syrc", "syr", "syr-SY", "syr-Syrc"); Name = "Syrc"; }

            @{ Match = @( "ta", "ta-IN", "ta-LK", "ta-MY", "ta-SG"); Name = "Taml"; }
```



```

        @{ Match = @"(\"te\", \"te-IN\"); Name = \"Telu\"; }

        @{ Match = @"(\"th\", \"th-TH\"); Name = \"Thai\"; }

    )

    ForEach ($item in $Fonts) {

        if (($item.Match) -Contains $Lang) {

            return $item.Name

        }

    }

    return \"Not_matched\"

}

Function Match_Other_Region_Specific_Requirements

{

    param( $Lang )

    $RegionSpecific = @(

        @{ Match = @"(\"zh-TW\"); Name = \"Taiwan\"; }

    )

    ForEach ($item in $RegionSpecific) {

        if (($item.Match) -Contains $Lang) {

            return $item.Name

        }

    }

    return \"Skip_specific_packages\"

}

Function Extract_Process

{

    param( $Package, $Name, $NewSaveTo )

    $NewSaveTo = \"$(($SaveTo)\\$( $NewSaveTo)\\Language\\$( $Act)\\$( $NewLang)\"

    New-Item -Path $NewSaveTo -ItemType Directory -ErrorAction SilentlyContinue | Out-Null

    if ($ISO -eq \"Auto\") {

        Get-PSDrive -PSProvider FileSystem -ErrorAction SilentlyContinue | ForEach-Object {

            ForEach ($item in $Package) {

                $TempFilePath = Join-Path -Path $_.Root -ChildPath $item -ErrorAction SilentlyContinue

                if (Test-Path $TempFilePath -PathType Leaf) {

                    Write-host "`n Find: \" -NoNewLine; Write-host $TempFilePath -ForegroundColor Green

                    Write-host \" Copy to: \" -NoNewLine; Write-host $NewSaveTo

                    Copy-Item -Path $TempFilePath -Destination $NewSaveTo -Force

                }

            }

        }

    } else {

        ForEach ($item in $Package) {

            $TempFilePath = Join-Path -Path $ISO -ChildPath $item -ErrorAction SilentlyContinue

            Write-host "`n Find: \" -NoNewline; Write-host $TempFilePath -ForegroundColor Green

```

```

if (Test-Path $TempFilePath -PathType Leaf) {

    Write-host "  Copy to: " -NoNewLine; Write-host $NewSaveTo

    Copy-Item -Path $TempFilePath -Destination $NewSaveTo -Force

} else {

    Write-host "  Not found"

}

}

}

Write-host "`n Verify the language pack file"

ForEach ($item in $Package) {

    $Path = "$($NewSaveTo)\${[IO.Path]::GetFileName($item)}"

    if (Test-Path $Path -PathType Leaf) {

        Write-host "  Discover: " -NoNewLine; Write-host $Path -ForegroundColor Green

    } else {

        Write-host "  Not found: " -NoNewLine; Write-host $Path -ForegroundColor Red

    }

}

}

$AdvLanguage = @(

    @{

        Path = "Install\Install"

        Rule = @(

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Fonts-{DiyLang}-
Package~31bf3856ad364e35~amd64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-Server-Language-Pack_x64_{Lang}.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Basic-{Lang}-
Package~31bf3856ad364e35~amd64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Handwriting-{Lang}-
Package~31bf3856ad364e35~amd64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-OCR-{Lang}-
Package~31bf3856ad364e35~amd64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Speech-{Lang}-
Package~31bf3856ad364e35~amd64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-TextToSpeech-{Lang}-
Package~31bf3856ad364e35~amd64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~amd64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~amd64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~{Lang}~.cab"

```

```

    "LanguagesAndOptionalFeatures\Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"
)
}
@{
    Path = "Install\WinRE"

    Rule = @(
        "Windows Preinstallation Environment\x64\WinPE_OCs\WinPE-FontSupport-{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\lp.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-securestartup_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-atbroker_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-audiocore_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-audiodrivers_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-enhancedstorage_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-narrator_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-scripting_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-speech-tts_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-srh_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-srt_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-wds-tools_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-wmi_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-appxpackaging_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-storagewmi_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-wifi_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-rejuv_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-opcservices_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-hta_{Lang}.cab"
    )
}
@{
    Path = "Boot\Boot"

    Rule = @(
        "Windows Preinstallation Environment\x64\WinPE_OCs\WinPE-FontSupport-{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\lp.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\WinPE-Setup_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\WINPE-SETUP-Server_{Lang}.CAB"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-securestartup_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-atbroker_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-audiocore_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-audiodrivers_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-enhancedstorage_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-narrator_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-scripting_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-speech-tts_{Lang}.cab"
    )
}

```

```

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-srh_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-srt_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-wds-tools_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-wmi_{Lang}.cab"

    )

}

)

$NewFonts = Match_Required_Fonts -Lang $NewLang

$SpecificPackage = Match_Other_Region_Specific_Requirements -Lang $NewLang

Foreach ($item in $Expand) {

    $Language = @()

    Foreach ($itemList in $AdvLanguage) {

        if ($itemList.Path -eq $item) {

            Foreach ($PrintLang in $itemList.Rule) {

                $Language += "$($PrintLang)".Replace("{Lang}", $NewLang).Replace("{DiyLang}", $NewFonts).Replace("{Specific}",
$SpecificPackage)

            }

            Extract_Process -NewSaveTo $itemList.Path -Package $Language -Name $item

        }

    }

}

}

}

Foreach ($item in $Extract_language_Pack) { Extract_Language -Act $item.Act -NewLang $item.Tag -Expand $item.Scope }

```

C. Customize the deployment image

II Custom deployment image: Install.wim

1. View Install.wim details

Image name, image description, image size, architecture, version, index number, etc.;

```
$ViewFile = "D:\OS_2022\Sources\Install.wim"
```

```
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex }
```

CYCLIC OPERATION AREA, START,

2. Specify the path to mount install.wim

```
New-Item -Path "D:\OS_2022_Custom\Install\Install\Mount" -ItemType directory -ea SilentlyContinue
```

3. Start mounting Install.wim

Default index number: 1

```
Mount-WindowsImage -ImagePath "D:\OS_2022\sources\install.wim" -Index "1" -Path "D:\OS_2022_Custom\Install\Install\Mount"
```

PROCESS FILES INSIDE THE INSTALL.WIM IMAGE, OPTIONALLY, START

3.1. Custom deployment image: WinRE.wim

WARNING:

- WinRE.wim is a file within the Install.wim image;
- When Install.wim has multiple index numbers, only process any WinRE.wim;
- Synchronizing to all index numbers reduces the Install.wim volume, Learn "[How to bulk replace WinRE.wim in all index numbers in Install.wim](#)".

3.1.1. View WinRE.wim details

Image name, image description, image size, architecture, version, index number, etc.;

```
$ViewFile = "D:\OS_2022_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"
```

```
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index  
$_ .ImageIndex }
```

3.1.2. Specify the path to mount WinRE.wim

```
New-Item -Path "D:\OS_2022_Custom\Install\WinRE\Mount" -ItemType directory -ea SilentlyContinue
```

3.1.3. Start mounting WinRE.wim

Default index number: 1

```
$FileName = "D:\OS_2022_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"
```

```
Mount-WindowsImage -ImagePath $FileName -Index "1" -Path "D:\OS_2022_Custom\Install\WinRE\Mount"
```

3.1.4. Language pack

Automatically install language packs: Get "Component: All installed packages in the image" and match them.

After matching the corresponding names, install the local corresponding language pack files, View the report

"[Language installation package for WinRE.wim](#)".

3.1.4.1. Language pack: add

- WinRE.Instl.lang.ps1
 - [\Expand\Install\WinRE\WinRE.Instl.lang.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Documents/Attachment/OS.2022/Expanded/Install/WinRE/WinRE.Instl.lang.ps1

- Copy the code

```
$Mount = "D:\OS_2022_Custom\Install\WinRE\Mount"

$Sources = "D:\OS_2022_Custom\Install\WinRE\Language\Add\zh-CN"

$InitL_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    $InitL_install_Language_Component += $_.PackageName

}

Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\WinPE-FontSupport-zh-CN.cab"

$Language_List = @(

    @{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }

    @{ Match = "*SecureStartup*"; File = "winpe-securestartup_zh-CN.cab"; }

    @{ Match = "*ATBroker*"; File = "winpe-atbroker_zh-CN.cab"; }

    @{ Match = "*AudioCore*"; File = "winpe-audiocore_zh-CN.cab"; }

    @{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_zh-CN.cab"; }

    @{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_zh-CN.cab"; }

    @{ Match = "*Narrator*"; File = "winpe-narrator_zh-CN.cab"; }

    @{ Match = "*scripting*"; File = "winpe-scripting_zh-CN.cab"; }

    @{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_zh-CN.cab"; }

    @{ Match = "*srh*"; File = "winpe-srh_zh-CN.cab"; }

    @{ Match = "*srt*"; File = "winpe-srt_zh-CN.cab"; }

    @{ Match = "*wds-tools*"; File = "winpe-wds-tools_zh-CN.cab"; }

    @{ Match = "*-WMI-Package*"; File = "winpe-wmi_zh-CN.cab"; }

    @{ Match = "*WinPE-AppxPackaging*"; File = "winpe-appxpackaging_zh-CN.cab"; }

    @{ Match = "*StorageWMI*"; File = "winpe-storagewmi_zh-CN.cab"; }

    @{ Match = "*WiFi*"; File = "winpe-wifi_zh-CN.cab"; }

    @{ Match = "*rejuv*"; File = "winpe-rejuv_zh-CN.cab"; }

    @{ Match = "*opcservices*"; File = "winpe-opcservices_zh-CN.cab"; }

    @{ Match = "*hta*"; File = "winpe-hta_zh-CN.cab"; }

)

ForEach ($Rule in $Language_List) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $InitL_install_Language_Component) {

        if ($Component -like "$($Rule.Match)*") {

            Write-host "  Component name: " -NoNewline

            Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline

            Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

            Write-Host "  Installing ".PadRight(22) -NoNewline

            try {

                Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" | Out-Null

                Write-host "Finish" -ForegroundColor Green

            } catch {
```

```

        Write-host "Failed" -ForegroundColor Red
    }

    break
}

}

}

```

3.1.4.2. Offline image language: change

3.1.4.2.1. Change default language, regional settings, and other international settings

Language Tag: **zh-CN**

```
Dism /Image:"D:\OS_2022_Custom\Install\WinRE\Mount" /Set-AllIntl:zh-CN
```

3.1.4.2.2. View available language settings

```
Dism /Image:"D:\OS_2022_Custom\Install\WinRE\Mount" /Get-Intl
```

3.1.4.3. Language packs: Removed, optional

- After you add languages, if you want to deploy to a non-English locale, you can save space by removing the English language component. When you remove a language, uninstall the language components in the reverse order in which you added them.
- After adding the Chinese, delete "**English - United States**" in reverse, the language tag: **en-US**, you need to extract the language pack in advance
- WinRE.Del.Specified.lang.Tag.ps1
 - [\Expand\Install\WinRE\WinRE.Del.Specified.lang.Tag.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Documents/Attachment/OS.2022/Expand\Install\WinRE\WinRE.Del.Specified.lang.Tag.ps1

- Copy the code

```

$Lang = "en-US"

$Mount = "D:\OS_2022_Custom\Install\WinRE\Mount"

$Sources = "D:\OS_2022_Custom\Install\WinRE\Language\Del\en-US"

$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    $Initl_install_Language_Component += $_.PackageName

}

$Language = @(

    @{ Match = "*windowsupdate*"; File = "winpe-windowsupdate_{$Lang}.cab"; }

    @{ Match = "*appxdeployment*"; File = "winpe-appxdeployment_{$Lang}.cab"; }

```

```

@{ Match = "*hta*"; File = "winpe-hta_$(Lang).cab"; }

@{ Match = "*opcservices*"; File = "winpe-opcservices_$(Lang).cab"; }

@{ Match = "*rejuv*"; File = "winpe-rejuv_$(Lang).cab"; }

@{ Match = "*WiFi*"; File = "winpe-wifi_$(Lang).cab"; }

@{ Match = "*StorageWMI*"; File = "winpe-storagewmi_$(Lang).cab"; }

@{ Match = "*WinPE-AppxPackaging*"; File = "winpe-appxpackaging_$(Lang).cab"; }

@{ Match = "*-WMI-Package*"; File = "winpe-wmi_$(Lang).cab"; }

@{ Match = "*wds-tools*"; File = "winpe-wds-tools_$(Lang).cab"; }

@{ Match = "*srt*"; File = "winpe-srt_$(Lang).cab"; }

@{ Match = "*srh*"; File = "winpe-srh_$(Lang).cab"; }

@{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_$(Lang).cab"; }

@{ Match = "*scripting*"; File = "winpe-scripting_$(Lang).cab"; }

@{ Match = "*Narrator*"; File = "winpe-narrator_$(Lang).cab"; }

@{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_$(Lang).cab"; }

@{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_$(Lang).cab"; }

@{ Match = "*AudioCore*"; File = "winpe-audiocore_$(Lang).cab"; }

@{ Match = "*ATBroker*"; File = "winpe-atbroker_$(Lang).cab"; }

@{ Match = "*SecureStartup*"; File = "winpe-securestartup_$(Lang).cab"; }

@{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }

)

ForEach ($Rule in $Language) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "*$($Rule.Match)*$(Lang)*") {

            Write-host "  Component name: " -NoNewline

            Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline

            Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

            Write-Host "  Deleting ".PadRight(22) -NoNewline

            try{

                Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" -
ErrorAction SilentlyContinue | Out-Null

                Write-host "Finish" -ForegroundColor Green

            } catch {

                Write-host "Failed" -ForegroundColor Red

                Write-host "  $($_) " -ForegroundColor Red

            }

            break

        }

    }

}

$InitlClearLanguagePackage = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

```



```

        if ($_.PackageName -like "*${$Lang}*") { InitlClearLanguagePackage += $_.PackageName }
    }

    if ($InitlClearLanguagePackage.count -gt 0) {

        ForEach ($item in $InitlClearLanguagePackage) {

            Write-Host "`n  ${$item}" -ForegroundColor Green

            Write-Host "    Deleting ".PadRight(22) -NoNewline

            try {

                Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction
                SilentlyContinue | Out-Null

                Write-host "Finish" -ForegroundColor Green

            } catch {

                Write-host "Failed" -ForegroundColor Red

                Write-host "  ${$_}" -ForegroundColor Red

            }

        }

    }
}

```

3.1.4.4. Components: All packages installed in the image

3.1.4.4.1. View

```

Get-WindowsPackage -Path "D:\OS_2022_Custom\Install\WinRE\Mount" | Out-
GridView

```

3.1.4.4.2. Export to Csv

```

$SaveTo = "D:\OS_2022_Custom\Install\WinRE\Report.${(Get-Date -Format
"yyyyMMddHHmmss")}.csv"

Get-WindowsPackage -Path "D:\OS_2022_Custom\Install\WinRE\Mount" | Export-
CSV -NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green

```

3.1.5. Cumulative updates, optional

To prepare the cumulative updates file available, change the example file name: **KB_WinRE.cab**

3.1.5.1. Add

```

$KBPath = "D:\OS_2022_Custom\Install\WinRE\Update\KB_WinRE.cab"

Add-WindowsPackage -Path "D:\OS_2022_Custom\Install\WinRE\Mount" -PackagePath $KBPath

```

3.1.5.2. Delete

```

$KBPath = "D:\OS_2022_Custom\Install\WinRE\Update\KB_WinRE.cab"

```

```
Remove-WindowsPackage -Path "D:\OS_2022_Custom\Install\WinRE\Mount" -PackagePath  
$KBPath
```

3.1.5.3. Solid update, optional

It cannot be uninstalled after curing, which cleans the recovery image and resets the basis of any superseded components.

```
Dism /image:"D:\OS_2022_Custom\Install\WinRE\Mount" /cleanup-image  
/StartComponentCleanup /ResetBase
```

3.1.5.3.1. Clean components after curing and updating, optional

```
$Mount = "D:\OS_2022_Custom\Install\WinRE\Mount"  
Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {  
    if ($_.PackageState -eq "Superseded") {  
        Write-Host " $($_.PackageName)" -ForegroundColor Green  
        Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-  
Null  
    }  
}
```

3.1.6. Drive, optional

3.1.7. Save image

```
Save-WindowsImage -Path "D:\OS_2022_Custom\Install\WinRE\Mount"
```

3.1.8. Unmount image

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowsImage -Path "D:\OS_2022_Custom\Install\WinRE\Mount" -Discard
```

3.1.9. After rebuilding WinRE.wim, the file size can be reduced

- WinRE.Rebuild.ps1
 - [\Expand\Install\WinRE\WinRE.Rebuild.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Documents/Attachment/OS.2022/Expand/Install/WinRE/WinRE.Rebuild.ps1
- Copy the code

```
$FileName = "D:\OS_2022_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"  
Get-WindowsImage -ImagePath $Filename -ErrorAction SilentlyContinue | ForEach-Object {
```

```

Write-Host " Image name: " -NoNewline

Write-Host $_.ImageName -ForegroundColor Yellow

Write-Host " The index number: " -NoNewline

Write-Host $_.ImageIndex -ForegroundColor Yellow

Write-Host "`n Rebuilding ".PadRight(28) -NoNewline

Export-WindowsImage -SourceImagePath $Filename -SourceIndex $_.ImageIndex -DestinationImagePath
"($FileName).New" -CompressionType max

Write-Host "Finish`n" -ForegroundColor Green
}

if (Test-Path "($FileName).New" -PathType Leaf) {

    Remove-Item -Path $Filename

    Move-Item -Path "($FileName).New" -Destination $Filename

    Write-Host "Finish" -ForegroundColor Green

} else {

    Write-host "Failed" -ForegroundColor Red

}

```

3.1.10. Backup WinRE.wim

- WinRE.Backup.ps1
 - [\Expand\Install\WinRE\WinRE.Backup.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Documents/Attachment/OS.2022/Expand/Install/WinRE/WinRE.Backup.ps1
- Copy the code

```

$WimLibPath = "D:\OS_2022_Custom\Install\Install\Update\Winlib"

$FileName = "D:\OS_2022_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"

New-Item -Path $WimLibPath -ItemType Directory -ea SilentlyContinue

Copy-Item -Path $FileName -Destination $WimLibPath -Force

```

3.1.11. Replace WinRE.wim within the Install.wim image

- After each installation of Install.wim, use item "[Replace the WinRE.wim](#)";
- Learning "[After obtaining all the index numbers of Install.wim and replace the old WinRE.wim](#)".

PROCESS FILES INSIDE THE INSTALL.WIM IMAGE, END

4. Language pack

Automatically install language packs: Get "Component: All installed packages in the image" and match them. After matching the corresponding names, install the local corresponding language pack files, View the report "[Language installation package for Install.wim](#)".

4.1. Language pack: add

- Install.Instl.lang.ps1
 - [\Expand\Install\Install.Instl.lang.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Documents/Attachment/OS.2022/Expand/Install/Install.Instl.lang.ps1

- Copy the code

```
Function Language_Install
{
    param($Mount, $Sources, $Lang)

    $Initl_install_Language_Component = @()

    if (Test-Path $Mount -PathType Container) {

        Get-WindowsPackage -Path $Mount | ForEach-Object { $Initl_install_Language_Component += $_.PackageName }

    } else {

        Write-Host "Not mounted: $($Mount)"

        return

    }

    $Script:Init_Folder_All_File = @()

    if (Test-Path "$($Sources)\($Lang)" -PathType Container) {

        Get-ChildItem -Path $Sources -Recurse -Include "*.cab" -ErrorAction SilentlyContinue | ForEach-Object {

            $Script:Init_Folder_All_File += $_.FullName

        }

        Write-host "`n Available language pack installation files"

        if ($Script:Init_Folder_All_File.Count -gt 0 ) {

            ForEach ($item in $Script:Init_Folder_All_File) {

                Write-host "  $($item)"

            }

        } else {

            Write-host "There are no language pack files locally"

            return

        }

    } else {

        Write-Host "Path does not exist: $($Sources)\($Lang)"

        return

    }

    $Script:Init_Folder_All_File_Match_Done = @()

    $Script:Init_Folder_All_File_Exclude = @()

    $Global:Search_File_Order = @(

        @{

            Name = "Fonts"

            Description = "Fonts"
```

```

Rule = @(
    @{ Match_Name = "*Fonts*"; IsMatch = "No"; Capability = ""; }
)
}

@{
    Name = "Basic"

    Description = "Basic"

    Rule = @(
        @{ Match_Name = "*LanguageFeatures-Basic*"; IsMatch = "Yes"; Capability = "Language.Basic~~~lb-
LU~0.0.1.0"; }

        @{ Match_Name = "*Server-LanguagePack-Package*"; IsMatch = "Yes"; Capability = "Language.Basic~~~lb-
LU~0.0.1.0"; }

    )
}

@{
    Name = "OCR"

    Description = "Optical character recognition"

    Rule = @(
        @{ Match_Name = "*LanguageFeatures-OCR*"; IsMatch = "Yes"; Capability = "Language.OCR~~~fr-FR~0.0.1.0"; }

    )
}

@{
    Name = "Handwriting"

    Description = "Handwriting recognition"

    Rule = @(
        @{ Match_Name = "*LanguageFeatures-Handwriting*"; IsMatch = "Yes"; Capability =
"Language.Handwriting~~~fr-FR~0.0.1.0"; }

    )
}

@{
    Name = "TextToSpeech"

    Description = "Text-to-speech"

    Rule = @(
        @{ Match_Name = "*LanguageFeatures-TextToSpeech*"; IsMatch = "Yes"; Capability =
"Language.TextToSpeech~~~fr-FR~0.0.1.0"; }

    )
}

@{
    Name = "Speech"

    Description = "Speech recognition"

    Rule = @(
        @{ Match_Name = "*LanguageFeatures-Speech*"; IsMatch = "Yes"; Capability = "Language.Speech~~~fr-
FR~0.0.1.0"; }

    )
}

```

```

}

@{
    Name = "RegionSpecific"

    Description = "Other region-specific requirements"

    Rule = @(
        @{ Match_Name = "*InternationalFeatures*zh-TW*"; IsMatch = "Yes"; Capability = ""; }
    )
}

@{
    Name = "Retail"

    Description = "Retail demo experience"

    Rule = @(
        @{ Match_Name = "*RetailDemo*"; IsMatch = "Yes"; Capability = ""; }
    )
}

@{
    Name = "Features_On_Demand"

    Description = "Features on demand"

    Rule = @(
        @{ Match_Name = "*MSPaint*amd64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.MSPaint~~~~0.0.1.0"; }

        @{ Match_Name = "*MSPaint*wow64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.MSPaint~~~~0.0.1.0"; }

        @{ Match_Name = "*Notepad*amd64*"; IsMatch = "Yes"; Capability =
"Microsoft.Windows.Notepad~~~~0.0.1.0"; }

        @{ Match_Name = "*Notepad*wow64*"; IsMatch = "Yes"; Capability =
"Microsoft.Windows.Notepad~~~~0.0.1.0"; }

        @{ Match_Name = "*PowerShell-ISE-FOD-Package*amd64*"; IsMatch = "Yes"; Capability =
"Microsoft.Windows.PowerShell.ISE~~~~0.0.1.0"; }

        @{ Match_Name = "*PowerShell-ISE-FOD-Package*wow64*"; IsMatch = "Yes"; Capability =
"Microsoft.Windows.PowerShell.ISE~~~~0.0.1.0"; }

        @{ Match_Name = "*StepsRecorder*amd64*"; IsMatch = "Yes"; Capability = "App.StepsRecorder~~~~0.0.1.0"; }

        @{ Match_Name = "*StepsRecorder*wow64*"; IsMatch = "Yes"; Capability = "App.StepsRecorder~~~~0.0.1.0"; }

        @{ Match_Name = "*WordPad*amd64*"; IsMatch = "Yes"; Capability =
"Microsoft.Windows.WordPad~~~~0.0.1.0"; }

        @{ Match_Name = "*WordPad*wow64*"; IsMatch = "Yes"; Capability =
"Microsoft.Windows.WordPad~~~~0.0.1.0"; }
    )
}

)

ForEach ($item in $Global:Search_File_Order) {

    New-Variable -Scope global -Name "Init_File_Type_$( $item.Name )" -Value @() -Force

}

ForEach ($Wildcard in $Script:Init_Folder_All_File) {

    ForEach ($item in $Global:Search_File_Order) {

        ForEach ($TTT in $item.Rule) {

```

```

        if ($Wildcard -like "*$(TTT.Match_Name)*") {

            Write-host "`n  Fuzzy matching: " -NoNewline; Write-host $TTT.Match_Name -ForegroundColor Green

            Write-host "    Language pack file: " -NoNewline; Write-host $Wildcard -ForegroundColor Green

            $OSDefaultUser = (Get-Variable -Scope global -Name "Init_File_Type_$(Item.Name)" -ErrorAction
SilentlyContinue).Value

            $TempSave = @{ Match_Name = $TTT.Match_Name; Capability = $TTT.Capability; FileName = $Wildcard }

            $new = $OSDefaultUser + $TempSave

            if ($TTT.IsMatch -eq "Yes") {

                ForEach ($Component in $InitL_install_Language_Component) {

                    if ($Component -like "*$(TTT.Match_Name)*") {

                        Write-host "    Component name: " -NoNewline; Write-host $Component -ForegroundColor Green

                        New-Variable -Scope global -Name "Init_File_Type_$(Item.Name)" -Value $new -Force

                        $Script:Init_Folder_All_File_Match_Done += $Wildcard

                        break

                    }

                }

            } else {

                Write-host "    Do not match, install directly" -ForegroundColor Yellow

                New-Variable -Scope global -Name "Init_File_Type_$(Item.Name)" -Value $new -Force

                $Script:Init_Folder_All_File_Match_Done += $Wildcard

            }

        }

    }

    Write-host "`n  Grouping is complete, pending installation" -ForegroundColor Yellow

    Write-host "    $('-' * 80)"

    ForEach ($Wildcard in $Global:Search_File_Order) {

        $OSDefaultUser = (Get-Variable -Scope global -Name "Init_File_Type_$(Wildcard.Name)" -ErrorAction
SilentlyContinue).Value

        Write-host "`n  $($Wildcard.Description) ( $($OSDefaultUser.Count) item )"

        if ($OSDefaultUser.Count -gt 0) {

            ForEach ($item in $OSDefaultUser) {

                Write-host "    $($item.FileName)" -ForegroundColor Green

            }

        } else {

            Write-host "    Not available" -ForegroundColor Red

        }

    }

    Write-host "`n  Not matched, no longer installed" -ForegroundColor Yellow

    Write-host "    $('-' * 80)"

    ForEach ($item in $Script:Init_Folder_All_File) {

```

```

if ($Script:Init_Folder_All_File_Match_Done -notcontains $item) {

    $Script:Init_Folder_All_File_Exclude += $item

    Write-host "  $($item)" -ForegroundColor Red

}

}

Write-host "`n  Install" -ForegroundColor Yellow

Write-host "  $('-' * 80)"

ForEach ($WildCard in $Global:Search_File_Order) {

    $OSDefaultUser = (Get-Variable -Scope global -Name "Init_File_Type_$( $WildCard.Name)" -ErrorAction
SilentlyContinue).Value

    Write-host "`n  $($WildCard.Description) ( $($OSDefaultUser.Count) item )"; Write-host "  $('-' * 80)"

    if ($OSDefaultUser.Count -gt 0) {

        ForEach ($item in $OSDefaultUser) {

            Write-host "    Language pack file: " -NoNewline; Write-host $item.FileName -ForegroundColor Green

            Write-Host "    Installing ".PadRight(22) -NoNewline

            if (Test-Path $item.FileName -PathType Leaf) {

                try {

                    Add-WindowsPackage -Path $Mount -PackagePath $item.FileName | Out-Null

                    Write-host "Finish`n" -ForegroundColor Green

                } catch {

                    Write-host "Failed" -ForegroundColor Red

                    Write-host "  $($_) " -ForegroundColor Red

                }

            } else {

                Write-host "Does not exist`n"

            }

        }

    } else {

        Write-host "    Not available`n" -ForegroundColor Red

    }

}

}

Language_Install -Mount "D:\OS_2022_Custom\Install\Install\Mount" -Sources
"D:\OS_2022_Custom\Install\Install\Language\Add" -Lang "zh-CN"

```

4.2. Offline image language: change

- Starting Windows 11, the [default System UI Language](#) set by DISM is left unaltered on all editions except for Home edition. For all [commercial editions](#) the language chosen during the Out-of-Box Experience (OOBE) is set as the [System Preferred UI language](#) and Windows will be displayed in this language and for Home edition the language chosen at OOBE will continue to be the default System UI Language.

- As of Windows 10, version 2004, if an .appx-based Language Experience Pack (LXP) backed language is passed as an argument then the language will be set as the System Preferred UI language and its parent language will be set as the Default System UI language. In prior versions only .cab based language packs were supported.

4.2.1. Change default language, regional settings, and other international settings

Language Tag: zh-CN

```
Dism /Image:"D:\OS_2022_Custom\Install\Install\Mount" /Set-AllIntl:zh-CN
```

4.2.2. View available language settings

```
Dism /Image:"D:\OS_2022_Custom\Install\Install\Mount" /Get-Intl
```

4.3. Language packs: Removed, optional

- After you add languages, if you want to deploy to a non-English locale, you can save space by removing the English language component. When you remove a language, uninstall the language components in the reverse order in which you added them.
- After adding the Chinese, delete "English - United States" in reverse, the language tag: en-US, you need to extract the language pack in advance

- Install.Del.Specified.lang.Tag.ps1

- \Expand\Install\Install.Del.Specified.lang.Tag.ps1
- https://github.com/ilikeyi/solutions/blob/main/_Documents/Attachment/OS.2022/Expand/Install/Install/WinRE.Del.Specified.lang.Tag.ps1

- Copy the code

```
$Lang = "en-US"

$Mount = "D:\OS_2022_Custom\Install\Install\Mount"

$Sources = "D:\OS_2022_Custom\Install\Install\Language\Del\en-US"

$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    $Initl_install_Language_Component += $_.PackageName

}

$Language = @(

    @{ Match = "*WordPad*wow64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }

    @{ Match = "*WordPad*amd64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~amd64~$( $Lang)~.cab"; }

    @{ Match = "*WMIC*FoD*Package*wow64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }

    @{ Match = "*WMIC*FoD*Package*amd64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~AMD64~$( $Lang)~.cab"; }
```

```

        @{ Match = "*StepsRecorder*wow64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

        @{ Match = "*StepsRecorder*amd64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~amd64~$(Lang)~.cab"; }

        @{ Match = "*Printing*PMCPPC*amd64*"; File = "Microsoft-Windows-Printing-PMCPPC-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*PowerShell*wow64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

        @{ Match = "*PowerShell*amd64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~amd64~$(Lang)~.cab"; }

        @{ Match = "*MediaPlayer*wow64*"; File = "Microsoft-Windows-MediaPlayer-Package-wow64-$(Lang).cab"; }

        @{ Match = "*MediaPlayer*amd64*"; File = "Microsoft-Windows-MediaPlayer-Package-AMD64-$(Lang).cab"; }

        @{ Match = "*Notepad*wow64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

        @{ Match = "*Notepad*amd64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*InternetExplorer*"; File = "Microsoft-Windows-InternetExplorer-Optional-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*TextToSpeech*"; File = "Microsoft-Windows-LanguageFeatures-TextToSpeech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*LanguageFeatures-Speech*"; File = "Microsoft-Windows-LanguageFeatures-Speech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*OCR*"; File = "Microsoft-Windows-LanguageFeatures-OCR-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*Handwriting*"; File = "Microsoft-Windows-LanguageFeatures-Handwriting-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*LanguageFeatures-Basic*"; File = "Microsoft-Windows-LanguageFeatures-Basic-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*Client-LanguagePack-Package*"; File = "Microsoft-Windows-Client-Language-Pack_x64_$(Lang).cab"; }
    )

ForEach ($Rule in $Language) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "*$($Rule.Match)*$(Lang)*") {

            Write-host "  Component name: " -NoNewline

            Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline

            Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

            Write-Host "  Deleting ".PadRight(22) -NoNewline

            try {

                Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" -ErrorAction SilentlyContinue
            } Out-Null

            Write-host "Finish" -ForegroundColor Green

        } catch {

            Write-host "Failed" -ForegroundColor Red

            Write-host "  $_" -ForegroundColor Red
        }
    }
}

```

```

    }
    break
}
}
}
}

$InitlClearLanguagePackage = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    if ($_.PackageName -like "*$($Lang)*") {

        $InitlClearLanguagePackage += $_.PackageName

    }

}

if ($InitlClearLanguagePackage.count -gt 0) {

    ForEach ($item in $InitlClearLanguagePackage) {

        Write-Host "`n $($item)" -ForegroundColor Green

        Write-Host "  Deleting ".PadRight(22) -NoNewline

        try {

            Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction SilentlyContinue | Out-Null

            Write-host "Finish" -ForegroundColor Green

        } catch {

            Write-host "Failed" -ForegroundColor Red

            Write-host "  $($_) " -ForegroundColor Red

        }

    }

}
}

```

4.4. Components: All packages installed in the image

4.4.1. View

```
Get-WindowsPackage -Path "D:\OS_2022_Custom\Install\Install\Mount" | Out-GridView
```

4.4.2. Export to Csv

```

$SaveTo = "D:\OS_2022_Custom\Install\Install\Report.$(Get-Date -Format "yyyyMMddHHmmss").csv"

Get-WindowsPackage -Path "D:\OS_2022_Custom\Install\Install\Mount" | Export-CSV -NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green

```

5. Cumulative updates, optional

5.1. Download

Check the "[Windows Server 2022 Update History](#)", for example, install the cumulative update: KB5030216

Go to the download page: <https://www.catalog.update.microsoft.com/Search.aspx?q=Kb5030216> Or "[Direct download](#)" (If you cannot download, please go to the download page), save to

```
D:\OS_2022_Custom\Install\Install\Update\windows10.0-kb5030216-  
x64_cbe587155f9818548b75f65d5cd41d341ed2fc61.msu
```

5.2. Add

```
$KBPath = "D:\OS_2022_Custom\Install\Install\Update\windows10.0-kb5030216-  
x64_cbe587155f9818548b75f65d5cd41d341ed2fc61.msu"  
  
Add-WindowsPackage -Path "D:\OS_2022_Custom\Install\Install\Mount" -PackagePath $KBPath
```

5.3. Solid update, optional

It cannot be uninstalled after curing, which cleans the recovery image and resets the basis of any superseded components.

```
Dism /Image:"D:\OS_2022_Custom\Install\Install\Mount" /cleanup-image /StartComponentCleanup /ResetBase
```

5.3.1. Clean up components after curing updates

- Install.Update.Curing.ps1
 - [\Expand\Install\Install.Update.Curing.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Documents/Attachment/OS.2022/Expand/Install/Install.Update.Curing.ps1
- Copy the code

```
$Mount = "D:\OS_2022_Custom\Install\Install\Mount"  
  
Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {  
  
    if ($_.PackageState -eq "Superseded") {  
  
        Write-Host " $($_.PackageName)" -ForegroundColor Green  
  
        Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null  
  
    }  
  
}
```

6. Drive, optional

7. Add deployment engine, optional

- Learn "Deployment Engine", if added to ISO installation media, can skip adding to mounted.
- After adding the deployment engine, continue at the current location.

8. Health

Check whether there is any damage before saving. When the health status is abnormal, abort saving

```
Repair-WindowsImage -Path "D:\OS_2022_Custom\Install\Install\Mount" -ScanHealth
```

9. Replace the WinRE.wim

WinRE.wim in all index numbers in Install.wim has been replaced in batches. Please skip this step.

```
$WinRE = "D:\OS_2022_Custom\Install\Install\Update\Winlib\WinRE.wim"
$CopyTo = "D:\OS_2022_Custom\Install\Install\Mount\Windows\System32\Recovery"
Copy-Item -Path $WinRE -Destination $CopyTo -Force
```

10. Save image

```
Save-WindowsImage -Path "D:\OS_2022_Custom\Install\Install\Mount"
```

11. Unmount image

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowsImage -Path "D:\OS_2022_Custom\Install\Install\Mount" -Discard
```

CYCLIC OPERATION AREA, END.

12. Rebuilding Install.wim reduces file size

- Install.Rebuild.wim.ps1
 - [\Expand\Install\Install.Rebuild.wim.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Documents/Attachment/OS.2022/Expand/Install/Install.Rebuild.wim.ps1

- Copy the code

```
$InstallWim = "D:\OS_2022\sources\install.wim"
Get-WindowsImage -ImagePath $InstallWim -ErrorAction SilentlyContinue | ForEach-Object {
    Write-Host " Image name: " -NoNewline
    Write-Host $_.ImageName -ForegroundColor Yellow
    Write-Host " The index number: " -NoNewline
    Write-Host $_.ImageIndex -ForegroundColor Yellow
    Write-Host "`n Rebuilding".PadRight(28) -NoNewline
    Export-WindowsImage -SourceImagePath $InstallWim -SourceIndex $_.ImageIndex -DestinationImagePath "$($InstallWim).New"
    -CompressionType max | Out-Null
    Write-Host "Finish`n" -ForegroundColor Green
}

if (Test-Path "$($InstallWim).New" -PathType Leaf) {
    Remove-Item -Path $InstallWim
    Move-Item -Path "$($InstallWim).New" -Destination $InstallWim
    Write-Host "Finish" -ForegroundColor Green
}
```

```

} else {

    Write-host "Failed" -ForegroundColor Red

}

```

13. How to batch replace WinRE.wim in all index numbers in Install.wim

13.1. Get WimLib

After going to the official website of <https://wimlib.net>, select a different version: [arm64](#), [x64](#), [x86](#), and extract it to: [D:Wimlib](#) after downloading.

13.2. How to extract and update WinRE.wim in Install.wim

13.2.1. Extract the WinRE.wim file from Install.wim

- Install.WinRE.Extract.ps1
 - [\Expand\Install\Install.WinRE.Extract.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Documents/Attachment/OS.2022/Expand/Install/Install.WinRE.Extract.ps1

- Copy the code

```

$Arguments = @(
    "extract",
    "D:\OS_2022\sources\install.wim", "1",
    "\Windows\System32\Recovery\Winre.wim",
    "--dest-dir=""D:\OS_2022_Custom\Install\Install\Update\Winlib""
)

New-Item -Path "D:\OS_2022_Custom\Install\Install\Update\Winlib" -ItemType Directory -ea SilentlyContinue

Start-Process -FilePath "d:\wimlib\wimlib-imageex.exe" -ArgumentList $Arguments -wait -nonewwindow

```

13.2.2. Get all index numbers of Install.wim and replace the old WinRE.wim

- Install.WinRE.Replace.wim.ps1
 - [\Expand\Install\Install.WinRE.Replace.wim.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Documents/Attachment/OS.2022/Expand/Install/Install.WinRE.Replace.wim.ps1

- Copy the code

```

Get-WindowsImage -ImagePath "D:\OS_2022\sources\install.wim" -ErrorAction SilentlyContinue | ForEach-Object {

    Write-Host "  Image name: " -NoNewline

    Write-Host $_.ImageName -ForegroundColor Yellow

```

```

Write-Host " The index number: " -NoNewLine

Write-Host $_.ImageIndex -ForegroundColor Yellow

Write-Host "`n Replacement "

$Arguments = @(
    "update",
    "D:\OS_2022\sources\install.wim",
    $_.ImageIndex,
    "--command=""add 'D:\OS_2022_Custom\Install\Install\Update\Winlib\WinRE.wim'
'\Windows\System32\Recovery\WinRe.wim'""""
)

Start-Process -FilePath "d:\wimlib\wimlib-imagex.exe" -ArgumentList $Arguments -wait -nonewwindow

Write-Host " Finish`n" -ForegroundColor Green
}

```

III Custom deployment image: boot.wim

1. View Boot.wim details

Image name, image description, image size, architecture, version, index number, etc.;

```
$ViewFile = "D:\OS_2022\Sources\Boot.wim"
```

```
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex }
```

2. Specify the path to mount Boot.wim

```
New-Item -Path "D:\OS_2022_Custom\Boot\Boot\Mount" -ItemType directory -ea SilentlyContinue
```

3. Start mounting Boot.wim

Default index number: 2

```
Mount-WindowsImage -ImagePath "D:\OS_2022\sources\boot.wim" -Index "2" -Path "D:\OS_2022_Custom\Boot\Boot\Mount"
```

4. Language pack

Automatically install language packs: Get "Component: All installed packages in the image" and match them. After matching the corresponding names, install the local corresponding language pack files, View the report "[Language installation package for Boot.wim](#)".

4.1. Language pack: add

- Boot.Instl.lang.ps1
 - [\Expand\Boot\Boot.Instl.lang.ps1](#)

- https://github.com/ilikeyi/solutions/blob/main/_Documents/Attachment/OS.2022/Expand/Boot/Boot.Instl.lang.

ps1

- Copy the code

```
$Mount = "D:\OS_2022_Custom\Boot\Boot\Mount"

$Sources = "D:\OS_2022_Custom\Boot\Boot\Language\Add\zh-CN"

$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    $Initl_install_Language_Component += $_.PackageName

}

Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\WinPE-FontSupport-zh-CN.cab"

$Language = @(

    @{ Match = "*WinPE*Setup*Server*Package*"; File = "WINPE-SETUP-Server_zh-CN.CAB"; }

    @{ Match = "*WinPE*Setup*Package*"; File = "WinPE-Setup_zh-CN.cab"; }

    @{ Match = "*WinPE-LanguagePack*Package*"; File = "lp.cab"; }

    @{ Match = "*SecureStartup*"; File = "winpe-securestartup_zh-CN.cab"; }

    @{ Match = "*ATBroker*"; File = "winpe-atbroker_zh-CN.cab"; }

    @{ Match = "*AudioCore*"; File = "winpe-audiocore_zh-CN.cab"; }

    @{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_zh-CN.cab"; }

    @{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_zh-CN.cab"; }

    @{ Match = "*Narrator*"; File = "winpe-narrator_zh-CN.cab"; }

    @{ Match = "*scripting*"; File = "winpe-scripting_zh-CN.cab"; }

    @{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_zh-CN.cab"; }

    @{ Match = "*srh*"; File = "winpe-srh_zh-CN.cab"; }

    @{ Match = "*srt*"; File = "winpe-srt_zh-CN.cab"; }

    @{ Match = "*wds-tools*"; File = "winpe-wds-tools_zh-CN.cab"; }

    @{ Match = "*-WMI-Package*"; File = "winpe-wmi_zh-CN.cab"; }

)

ForEach ($Rule in $Language) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "$($Rule.Match)*") {

            Write-host "  Component name: " -NoNewline

            Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline

            Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

            Write-Host "  Installing ".PadRight(22) -NoNewline

            try {

                Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" | Out-Null

                Write-host "Finish" -ForegroundColor Green

            } catch {

                Write-host "Failed" -ForegroundColor Red

            }

        }

    }

}
```



```

        break
    }
}
}

```

4.2. Offline image language: change

4.2.1. Change default language, regional settings, and other international settings

Language Tag: zh-CN

```
Dism /Image:"D:\OS_2022_Custom\Boot\Boot\Mount" /Set-AllIntl:zh-CN
```

4.2.2. View available language settings

```
Dism /Image:"D:\OS_2022_Custom\Boot\Boot\Mount" /Get-Intl
```

4.3. Language packs: Removed, optional

- After you add languages, if you want to deploy to a non-English locale, you can save space by removing the English language component. When you remove a language, uninstall the language components in the reverse order in which you added them.
- After adding the Chinese, delete "English - United States" in reverse, the language tag: en-US, you need to extract the language pack in advance
- Boot.Del.Specified.lang.Tag.ps1

- [\Expand\Boot\Boot.Del.Specified.lang.Tag.ps1](#)

- https://github.com/ilikeyi/solutions/blob/main/_Documents/Attachment/OS.2022/Expand/Boot/Boot/Boot.Del.Specified.lang.Tag.ps1

- Copy the code

```

$Lang = "en-US"

$Mount = "D:\OS_2022_Custom\Boot\Boot\Mount"

$Sources = "D:\OS_2022_Custom\Boot\Boot\Language\Del\en-US"

$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    $Initl_install_Language_Component += $_.PackageName

}

$Language = @(

    @{ Match = "*WordPad*wow64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }

    @{ Match = "*WordPad*amd64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~amd64~$( $Lang)~.cab"; }

```

```

        @{ Match = "*WMIC*FoD*Package*wow64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

        @{ Match = "*WMIC*FoD*Package*amd64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*StepsRecorder*wow64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

        @{ Match = "*StepsRecorder*amd64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~amd64~$(Lang)~.cab"; }

        @{ Match = "*Printing*PMCPPC*amd64*"; File = "Microsoft-Windows-Printing-PMCPPC-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*PowerShell*wow64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

        @{ Match = "*PowerShell*amd64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~amd64~$(Lang)~.cab"; }

        @{ Match = "*MediaPlayer*wow64*"; File = "Microsoft-Windows-MediaPlayer-Package-wow64-$(Lang).cab"; }

        @{ Match = "*MediaPlayer*amd64*"; File = "Microsoft-Windows-MediaPlayer-Package-AMD64-$(Lang).cab"; }

        @{ Match = "*Notepad*wow64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

        @{ Match = "*Notepad*amd64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*InternetExplorer*"; File = "Microsoft-Windows-InternetExplorer-Optional-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*TextToSpeech*"; File = "Microsoft-Windows-LanguageFeatures-TextToSpeech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*LanguageFeatures-Speech*"; File = "Microsoft-Windows-LanguageFeatures-Speech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*OCR*"; File = "Microsoft-Windows-LanguageFeatures-OCR-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*Handwriting*"; File = "Microsoft-Windows-LanguageFeatures-Handwriting-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*LanguageFeatures-Basic*"; File = "Microsoft-Windows-LanguageFeatures-Basic-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*Client-LanguagePack-Package*"; File = "Microsoft-Windows-Client-Language-Pack_x64_$(Lang).cab"; }

        @{ Match = "*Fonts-Hans*"; File = "Microsoft-Windows-LanguageFeatures-Fonts-Hans-
Package~31bf3856ad364e35~amd64~~.cab"; }

    )

    ForEach ($Rule in $Language) {

        Write-host "`n  Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

        ForEach ($Component in $Initl_install_Language_Component) {

            if ($Component -like "*$($Rule.Match)*$(Lang)*") {

                Write-host "  Component name: " -NoNewline

                Write-host $Component -ForegroundColor Green

                Write-host "  Language pack file: " -NoNewline

                Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

                Write-Host "  Deleting ".PadRight(22) -NoNewline

                try {

```

```

        Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\${$Rule.File}" -ErrorAction SilentlyContinue |
Out-Null

        Write-host "Finish" -ForegroundColor Green

    } catch {

        Write-host "Failed" -ForegroundColor Red

        Write-host "  ${$_}" -ForegroundColor Red

    }

    break

}

}

}

$InitlClearLanguagePackage = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    if ($_.PackageName -like "*${$Lang}*") {

        $InitlClearLanguagePackage += $_.PackageName

    }

}

if ($InitlClearLanguagePackage.count -gt 0) {

    ForEach ($item in $InitlClearLanguagePackage) {

        Write-Host "`n  ${$item}" -ForegroundColor Green

        Write-Host "    Deleting ".PadRight(22) -NoNewline

        try {

            Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction SilentlyContinue | Out-Null

            Write-host "Finish" -ForegroundColor Green

        } catch {

            Write-host "Failed" -ForegroundColor Red

            Write-host "  ${$_}" -ForegroundColor Red

        }

    }

}

}

```

4.4. Components: All packages installed in the image

4.4.1. View

```
Get-WindowsPackage -Path "D:\OS_2022_Custom\Boot\Boot\Mount" | Out-GridView
```

4.4.2. Export to Csv

```

$SaveTo = "D:\OS_2022_Custom\Boot\Boot\Report.${(Get-Date -Format "yyyyMMddHHmmss")}.csv"

Get-WindowsPackage -Path "D:\OS_2022_Custom\Boot\Boot\Mount" | Export-CSV -NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green

```

4.5. Language packs: sync to ISO installer

```
Copy-Item -Path "D:\OS_2022_Custom\Boot\Boot\Mount\sources\zh-CN" -Destination "D:\OS_2022\sources\zh-CN" -
Recurse -Force
```

4.6. Regenerate Lang.ini

After regeneration, you can adjust the "Installation Interface", the order when selecting "Language", open lang.ini, the default preferred value = 3, non-default value = 2.

4.6.1. Regenerate the mounted directory lang.ini

Re-generated Lang.ini file location: [D:\OS_2022_Custom\Boot\Boot\Mount\Sources\lang.ini](#)

```
Dism /image:"D:\OS_2022_Custom\Boot\Boot\Mount" /gen-langini
/distribution:"D:\OS_2022_Custom\Boot\Boot\Mount"
```

4.6.2. After regenerating lang.ini, synchronize to the installer

Re-generated Lang.ini file location: [D:\OS_2022\Sources\lang.ini](#)

```
Dism /image:"D:\OS_2022_Custom\Boot\Boot\Mount" /gen-langini /distribution:"D:\OS_2022"
```

5. Cumulative updates, optional

To prepare the cumulative updates file available, change the example file name: [KB_Boot.cab](#)

5.1. Add

```
$KBPath = "D:\OS_2022_Custom\Boot\Boot\Update\KB_Boot.cab"

Add-WindowsPackage -Path "D:\OS_2022_Custom\Boot\Boot\Mount" -PackagePath $KBPath
```

5.2. Delete

```
$KBPath = "D:\OS_2022_Custom\Boot\Boot\Update\KB_Boot.cab"

Remove-WindowsPackage -Path "D:\OS_2022_Custom\Boot\Boot\Mount" -PackagePath $KBPath
```

5.3. Solid update, optional

It cannot be uninstalled after curing, which cleans the recovery image and resets the basis of any superseded components.

```
Dism /image:"D:\OS_2022_Custom\Boot\Boot\Mount" /cleanup-image /StartComponentCleanup /ResetBase
```

5.3.1. Clean components after curing and updating, optional

```
$Mount = "D:\OS_2022_Custom\Boot\Boot\Mount"

Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {
    if ($_.PackageState -eq "Superseded") {
```

```

        Write-Host " $($_.PackageName)" -ForegroundColor Green

        Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null
    }
}

```

6. Drive, optional

7. Save image

```
Save-WindowsImage -Path "D:\OS_2022_Custom\Boot\Boot\Mount"
```

8. Unmount image

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowsImage -Path "D:\OS_2022_Custom\Boot\Boot\Mount" -Discard
```

IV Deployment engine

- Learn about "Automatically Adding Languages Installed in Windows Systems", learn: <https://github.com/ilikeyi/Multilingual>, how to download:
 - After entering the website, click "Code", "Download Compressed Package", and after the download is completed, you will get the [main.zip](#) compressed package file.
 - Go to the <https://github.com/ilikeyi/Multilingual/releases> download page, select the available version: [1.1.0.4](#), select the download source code format: zip, and get the [Multilingual-1.1.0.4.zip](#) compressed package file after the download is completed;
- Unzip the downloaded [main.zip](#) or [Multilingual-1.1.0.4.zip](#) to: [D:\Multilingual-1.1.0.4](#), and rename: [D:\Multilingual](#)
- Learn "[Unattended Windows Setup Reference](#)", Intervene in the installation process by leaving it unattended.

1. Add method

1.1. Add to ISO installation media

1.1.1. Unattended

1.1.1.1. Add to: [\[ISO\]:\Autounattend.xml](#)

Autounattend.xml interferes with the WinPE installer when booting an ISO installation.

Copy [D:\Multilingual\Unattend\Mul.Unattend.xml](#) to [D:\OS_2022\Autounattend.xml](#)

```
Copy-Item "D:\Multilingual\Unattend\Mul.Unattend.xml" -Destination
```

```
"D:\OS_2022\Autounattend.xml" -Force
```

1.1.1.2. Add to: [\[ISO\]:\Sources\Unattend.xml](#)

When mounting or unpacking an ISO, after running the [ISO]:\Setup.exe installer, [ISO]:\Sources\Unattend.xml will intervene in the installation process.

Copy D:\Multilingual\Unattend\Mul.Unattend.xml to D:\OS_2022\Sources\Unattend.xml

```
Copy-Item "D:\Multilingual\Unattend\Mul.Unattend.xml" -Destination
"D:\OS_2022\Sources\Unattend.xml" -Force
```

1.1.1.3. Add to: [ISO]:\sources\\$\OEM\$\\$\Panther\unattend.xml

Copy it to the system disk during the installation process, copy to: {system disk}\Windows\Panther\unattend.xml

1.1.1.3.1. Create \$OEM\$ path

```
New-Item -Path "D:\OS_2022\sources\`$OEM$\`$$\Panther" -ItemType Directory
```

1.1.1.3.2. Copy

Copy D:\Multilingual\Unattend\Mul.Unattend.xml to D:\OS_2022\Sources\\$\OEM\$\Panther\Unattend.xml

```
Copy-Item "D:\Multilingual\Unattend\Mul.Unattend.xml" -Destination
"D:\OS_2022\sources\`$OEM$\`$$\Panther\Unattend.xml" -Force
```

1.1.2. Deployment engine: add

Add "Automatically add installed languages for Windows systems" to D:\OS_2022\sources\\$\OEM\$\\$1\Yi\Engine in the directory.

1.1.2.1. Deployment Engine: Copy

Copy D:\Multilingual\Engine to D:\OS_2022\Sources\\$\OEM\$\\$1\Yi\Engine

```
Copy-Item "D:\Multilingual\Engine" -Destination "D:\OS_2022\sources\`$OEM$\`$1\Yi\Engine" -
Recurse -Force
```

1.1.2.2. Deployment engine: custom deployment tags

```
$Flag = @(
    "Is_Mark_Sync" # Allow global search and synchronization of deployment tags
    # Prerequisite deployment
    # "Auto_Update" # Allow automatic updates
    # "Use_UTF8" # Beta: Global language support using Unicode UTF-8
    "Disable_Network_Location_Wizard" # Network Location Wizard
    "Disable_Cleanup_Appx_Tasks" # Appx Cleanup and maintenance tasks
```

```

        "Disable_Cleanup_On_Demand_Language" # Prevent cleanup of unused on-demand feature
        language packs

        "Disable_Cleanup_Unsed_Language"    # Prevent cleaning of unused language packs

        "Prerequisites_Reboot" # Restart your computer

        # Complete first deployment

#   "Popup_Engine" # Allow the deployment engine main interface to pop up for the first time

#   "Allow_First_Pre_Experience" # Allow first preview, as planned

        "Reset_Execution_Policy" # Restore PowerShell execution policy: Restricted

        "Clear_Solutions" # Delete the entire solution

        "Clear_Engine" # Delete the deployment engine and keep the others

#   "First_Experience_Reboot" # Restart your computer
    )

ForEach ($item in $Flag) {

    Write-host "  $($item)" -ForegroundColor Green

    New-Item -Path "D:\OS_2022\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow" -ItemType Directory
    -ErrorAction SilentlyContinue | Out-Null

    Out-File -FilePath "D:\OS_2022\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow\$( $item )" -
    Encoding utf8 -ErrorAction SilentlyContinue

}

```

1.2. Add to mounted

Through "Customized deployment image: Install.wim", execute "Start mounting Install.wim" and mount to:

[D:\OS_2022_Custom\Install\Install\Mount](#)

1.2.1. Unattended

Copy [D:\Multilingual\Unattend\Mul.Unattend.xml](#) to

[D:\OS_2022_Custom\Install\Install\Mount\Panther\Unattend.xml](#)

```
Copy-Item "D:\Multilingual\Unattend\Mul.Unattend.xml" -Destination
```

```
"D:\OS_2022_Custom\Install\Install\Mount\Panther" -Force
```

1.2.2. Deployment engine: add

Add "[Automatically add languages installed on Windows systems](#)" to the

[D:\OS_2022_Custom\Install\Install\Mount\Yi\Engine](#) directory.

1.2.2.1. Deployment Engine: Copy

Copy [D:\Multilingual\Engine](#) to [D:\OS_2022_Custom\Install\Install\Mount\Yi\Engine](#)

```
Copy-Item "D:\Multilingual\Engine" -Destination
```

```
"D:\OS_2022_Custom\Install\Install\Mount\Yi\Engine" -Recurse -Force
```

1.2.2.2. Deployment engine: custom deployment tags

```
$Flag = @(
    "Is_Mark_Sync" # Allow global search and synchronization of deployment tags
    # Prerequisite deployment

#   "Auto_Update" # Allow automatic updates

#   "Use_UTF8" # Beta: Global language support using Unicode UTF-8

"Disable_Network_Location_Wizard" # Network Location Wizard

"Disable_Cleanup_Appx_Tasks" # Appx Cleanup and maintenance tasks

"Disable_Cleanup_On_Demand_Language" # Prevent cleanup of unused on-demand feature
language packs

"Disable_Cleanup_Unsed_Language" # Prevent cleaning of unused language packs

"Prerequisites_Reboot" # Restart your computer

# Complete first deployment

#   "Popup_Engine" # Allow the deployment engine main interface to pop up for the first time

#   "Allow_First_Pre_Experience" # Allow first preview, as planned

"Reset_Execution_Policy" # Restore PowerShell execution policy: Restricted

"Clear_Solutions" # Delete the entire solution

"Clear_Engine" # Delete the deployment engine and keep the others

#   "First_Experience_Reboot" # Restart your computer
)

ForEach ($item in $Flag) {

    Write-host "  $($item)" -ForegroundColor Green

    New-Item -Path "D:\OS_2022\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow" -ItemType Directory
    -ErrorAction SilentlyContinue | Out-Null

    Out-File -FilePath "D:\OS_2022\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow\$($item)" -
    Encoding utf8 -ErrorAction SilentlyContinue

}
```

2. Deployment Engine: Advanced

2.1. Deployment engine: adding process

After copying the deployment engine, you can add deployment tags to intervene in the installation process.

2.2. Unattended solution

When the customization is unattended, please modify it simultaneously if the following files exist:

- D:\OS_2022\Autounattend.xml
- D:\OS_2022\Sources\Unattend.xml
- D:\OS_2022\sources\\$\OEM\\$\$\Panther\unattend.xml
- D:\OS_2022_Custom\Install\Install\Mount\Panther\Unattend.xml

2.2.1. Multilingual or monolingual

In multi-language and monolingual, you can switch between each other. When replacing, please replace all the same ones in the file.

2.2.1.1. Multi-language

```
<UILanguage>%OSDUILanguage%</UILanguage>

<InputLocale>%OSDInputLocale%</InputLocale>

<SystemLocale>%OSDSystemLocale%</SystemLocale>

<UILanguage>%OSDUILanguage%</UILanguage>

<UILanguageFallback>%OSDUILanguageFallback%</UILanguageFallback>

<UserLocale>%OSDUserLocale%</UserLocale>
```

2.2.1.2. Monolingual

A single language needs to specify a language tag, for example, specify a language tag: **zh-CN**

```
<UILanguage>zh-CN</UILanguage>

<InputLocale>zh-CN</InputLocale>

<SystemLocale>zh-CN</SystemLocale>

<UILanguage>zh-CN</UILanguage>

<UILanguageFallback>zh-CN</UILanguageFallback>

<UserLocale>zh-CN</UserLocale>
```

2.2.2. User plan

By default, the self-created user **Administrator** is used and logged in automatically. It can be switched by modifying the following configuration: self-created or customized user.

2.2.2.1. Self-created user Administrator

By default, the self-created user: **Administrator** is used and logged in automatically, inserted between **<OOBE>** and **</OOBE>**.

```
<UserAccounts>

  <LocalAccounts>

    <LocalAccount wcm:action="add">

      <Password>

        <Value></Value>

        <PlainText>true</PlainText>

      </Password>

      <Description>Administrator</Description>

      <DisplayName>Administrator</DisplayName>

      <Group>Administrators</Group>

      <Name>Administrator</Name>

    </LocalAccount>

  </LocalAccounts>

</UserAccounts>

<AutoLogon>

  <Password>

    <Value></Value>
```

```

        <PlainText>true</PlainText>

    </Password>

    <Enabled>true</Enabled>

    <Username>Administrator</Username>

</AutoLogon>

```

2.2.2.2. Custom user

After setting up a custom user and installing the system, in OOBE, you can choose settings such as local and online users.

2.2.2.3. Delete

Username: Removed from start `<UserAccounts>` to `</UserAccounts>`

Autologin: Remove from start `<AutoLogon>` to `</AutoLogon>`

2.2.2.4. Replace

From the beginning `<OOBE>` to `</OOBE>`

```

<OOBE>

    <ProtectYourPC>3</ProtectYourPC>

    <HideEULAPage>true</HideEULAPage>

    <HideWirelessSetupInOOBE>true</HideWirelessSetupInOOBE>

</OOBE>

```

D. Generate ISO

II After downloading oscdimg, save it to: C:\Windows\System32 directory, save it in another path, or please enter the absolute location of OScdimg.exe;

III Use the oscdimg command line to generate an ISO file and save it to: `D:\WS2022.iso`

- ISO.ps1
 - `\Expand\ISO.ps1`
 - https://github.com/likeyi/solutions/blob/main/_Documents/Attachment/OS.2022/Expand/ISO.ps1

- Copy the code

```

$ISO = "D:\Win2022"

$Volume = "Win2022"

$SaveTo = "D:\Win2022.iso"

$Arguments = @"(-m", "-o", "-u2", "-udfver102", "-l" $($Volume)""", "-
bootdata:2#p0,e,b" $($ISO)\boot\etfsboot.com""#pEF,e,b" $($ISO)\efi\microsoft\boot\efisys.bin""", $ISO, $SaveTo)

Start-Process -FilePath "OScdimg.exe" -ArgumentList $Arguments -wait -nonewwindow

```

Chapter 2 COMMON PROBLEM

II Clean all mounts to

Close any applications that may be accessing files in the image, including File Explorer.

`Dismount-WindowsImage -Path "D:\OS_2022_Custom\Install\Install\Mount" -Discard`

`Dismount-WindowsImage -Path "D:\OS_2022_Custom\Install\WinRE\Mount" -Discard`

`Dismount-WindowsImage -Path "D:\OS_2022_Custom\Boot\Boot\Mount" -Discard`

III Fix the problem of abnormal mounting

1. View mounted

`Get-WindowsImage -Mounted`

2. Delete the DISM mount record saved in the registry

`Remove-Item -Path "HKLM:\SOFTWARE\Microsoft\WIMMount\Mounted Images*" -Force -Recurse -ErrorAction SilentlyContinue`

3. Delete all resources associated with the corrupted mounted image

`Clear-WindowsCorruptMountPoint`

`Dism /cleanup-wim`

IV Clean directories

`Remove-Item "D:\OS_2022_Custom" -Force -Recurse`

`Remove-Item "D:\OS_2022\Sources\`OEM" -Force -Recurse`

`Remove-Item -Path "D:\OS_2022\Autounattend.xml" -Force`

`Remove-Item -Path "D:\OS_2022\Sources\Unattend.xml" -Force`

Chapter 3 KNOWN ISSUES

1. Add Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~zh-CN~.cab to Windows Server 2022 Standard Core, Windows Server 2022 Datacenter Core will add Microsoft-Windows-PowerShell-ISE-FOD -Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1, an error will be reported when deleting it, and the operation is not recommended for the time being.

- Group abbreviations:
 - Group A: WINDOWS SERVER 2022 STANDARD (DESKTOP EXPERIENCE), WINDOWS SERVER 2022 DATACENTER (DESKTOP EXPERIENCE)
 - Group B: WINDOWS SERVER 2022 STANDARD CORE, WINDOWS SERVER 2022 DATACENTER CORE
- Marked green, installed; Not marked green: Not installed.

II Reports: Different versions

SN	NAME	A	B
1	Downlevel-NLS-Sorting-Versions-Server-FoD-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
2	Downlevel-NLS-Sorting-Versions-Server-FoD-Package~31bf3856ad364e35~wow64~~10.0.20348.1		
3	Microsoft-OneCore-DirectX-Database-FOD-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
4	Microsoft-OneCore-RasSstp-Api-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
5	Microsoft-Windows-FodMetadata-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
6	Microsoft-Windows-Foundation-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
7	Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~~11.0.20348.1		
8	Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~~11.0.20348.75		
9	Microsoft-Windows-LanguageFeatures-Basic-en-us-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
10	Microsoft-Windows-LanguageFeatures-Handwriting-en-us-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
11	Microsoft-Windows-LanguageFeatures-OCR-en-us-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
12	Microsoft-Windows-LanguageFeatures-Speech-en-us-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
13	Microsoft-Windows-LanguageFeatures-TextToSpeech-en-us-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
14	Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
15	Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~amd64~~10.0.20348.169		
16	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~amd64~~10.0.20348.1 Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.20348.1		
17	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~~10.0.20348.1 Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.20348.1		
18	Microsoft-Windows-Networking-RemoteAccess-PowerShell-Base-Package~31bf3856ad364e35~amd64~~10.0.20348.1 Microsoft-Windows-Networking-RemoteAccess-PowerShell-Base-Package~31bf3856ad364e35~amd64~~10.0.20348.143 Microsoft-Windows-Networking-RemoteAccess-PowerShell-Base-Package~31bf3856ad364e35~amd64~en-US~10.0.20348.1		

SN	NAME	A	B
19	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~amd64~~10.0.20348.1 Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.20348.1		
20	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~~10.0.20348.1 Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.20348.1		
21	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~~10.0.20348.1 Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~en-US~10.0.20348.1		
22	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~~10.0.20348.1 Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~en-US~10.0.20348.1		
23	Microsoft-Windows-Server-LanguagePack-Package~31bf3856ad364e35~amd64~en-US~10.0.20348.1		
24	Microsoft-Windows-Server-LanguagePack-Package~31bf3856ad364e35~amd64~en-US~10.0.20348.169		
25	Microsoft-Windows-ServerCore-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
26	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~~10.0.20348.1 Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~en-US~10.0.20348.1		
27	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~~10.0.20348.1 Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~en-US~10.0.20348.1		
28	Microsoft-Windows-TabletPCMath-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
29	Microsoft-Windows-TabletPCMath-Package~31bf3856ad364e35~amd64~~10.0.20348.143		
30	Microsoft-Windows-UserExperience-Desktop-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
31	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~~10.0.20348.1 Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.20348.1		
32	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~~10.0.20348.1 Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.20348.1		
33	Microsoft-Windows-Xps-Xps-Viewer-Opt-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
34	OpenSSH-Client-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
35	Package_for_DotNetRollup~31bf3856ad364e35~amd64~~10.0.4400.		
36	Package_for_RollupFix~31bf3856ad364e35~amd64~~20348.169.1.7		
37	Package_for_ServicingStack~31bf3856ad364e35~amd64~~20348.169.1.1		

III Report: Language installation packages apply to Install.wim

SN	LANGUAGE PACK INSTALLATION FILE, CORRESPONDING PACKAGE NAME	A	B
1	Microsoft-Windows-LanguageFeatures-Fonts-Hans-Package~31bf3856ad364e35~AMD64~~.cab Microsoft-Windows-LanguageFeatures-Fonts-Hans-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
2	Microsoft-Windows-Server-Language-Pack_x64_zh-CN.cab Microsoft-Windows-Server-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1		
3	Microsoft-Windows-LanguageFeatures-Basic-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab Microsoft-Windows-LanguageFeatures-Basic-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
4	Microsoft-Windows-LanguageFeatures-Handwriting-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab Microsoft-Windows-LanguageFeatures-Handwriting-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
5	Microsoft-Windows-LanguageFeatures-OCR-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab Microsoft-Windows-LanguageFeatures-OCR-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
6	Microsoft-Windows-LanguageFeatures-Speech-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab Microsoft-Windows-LanguageFeatures-Speech-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
7	Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.20348.1		
8	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~amd64~zh-CN~.cab Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1		
9	Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.20348.1		
10	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~amd64~zh-CN~.cab Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1		
11	Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.20348.1		
12	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~zh-CN~.cab Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1		
13	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~zh-CN~.cab Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.20348.1		
14	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~zh-CN~.cab Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1		
15	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~zh-CN~.cab Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~zh-CN~10.0.20348.1		
16	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~zh-CN~.cab Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1		

SN	LANGUAGE PACK INSTALLATION FILE, CORRESPONDING PACKAGE NAME	A	B
17	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.20348.1		

IV Report: Language installation packages apply to WinRE.wim

SN	TYPE	LANGUAGE PACK INSTALLATION FILE, CORRESPONDING PACKAGE NAME
1	Fonts	WinPE-FontSupport-zh-CN.cab Microsoft-Windows-WinPE-FontSupport-ZH-CN-Package~31bf3856ad364e35~amd64~~10.0.20348.1
2	Language pack	lp.cab Microsoft-Windows-WinPE-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
3	Feature Pack	winpe-appxpackaging_zh-CN.cab Microsoft-Windows-WinPE-AppxPackaging-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
4	Feature Pack	winpe-atbroker_zh-CN.cab WinPE-ATBroker-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
5	Feature Pack	winpe-audiocore_zh-CN.cab WinPE-AudioCore-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
6	Feature Pack	winpe-audiodrivers_zh-CN.cab WinPE-AudioDrivers-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
7	Feature Pack	winpe-enhancedstorage_zh-CN.cab WinPE-EnhancedStorage-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
8	Feature Pack	winpe-hta_zh-CN.cab WinPE-HTA-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
9	Feature Pack	winpe-narrator_zh-CN.cab WinPE-Narrator-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
10	Feature Pack	winpe-opcservices_zh-CN.cab WinPE-OpcServices-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
11	Feature Pack	winpe-rejuv_zh-CN.cab WinPE-Rejuv-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
12	Feature Pack	winpe-scripting_zh-CN.cab WinPE-Scripting-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
13	Feature Pack	winpe-securestartup_zh-CN.cab WinPE-SecureStartup-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
14	Feature Pack	winpe-speech-tts_zh-CN.cab WinPE-Speech-TTS-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1

SN	TYPE	LANGUAGE PACK INSTALLATION FILE, CORRESPONDING PACKAGE NAME
15	Feature Pack	winpe-srh_zh-CN.cab WinPE-SRH-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
16	Feature Pack	winpe-srt_zh-CN.cab WinPE-SRT-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
17	Feature Pack	winpe-storagewmi_zh-CN.cab WinPE-StorageWMI-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
18	Feature Pack	winpe-wds-tools_zh-CN.cab WinPE-WDS-Tools-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
19	Feature Pack	winpe-wifi_zh-CN.cab WinPE-WiFi-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
20	Feature Pack	winpe-wmi_zh-CN.cab WinPE-WMI-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1

V Report: Language installation packages apply to Boot.wim

SN	TYPE	LANGUAGE PACK INSTALLATION FILE, CORRESPONDING PACKAGE NAME
1	Fonts	WinPE-FontSupport-zh-CN.cab Microsoft-Windows-WinPE-FontSupport-ZH-CN-Package~31bf3856ad364e35~amd64~~10.0.20348.1
2	Language pack	lp.cab Microsoft-Windows-WinPE-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
3	Feature Pack	winpe-atbroker_zh-CN.cab WinPE-ATBroker-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
4	Feature Pack	winpe-audiocore_zh-CN.cab WinPE-AudioCore-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
5	Feature Pack	winpe-audiodrivers_zh-CN.cab WinPE-AudioDrivers-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
6	Feature Pack	winpe-enhancedstorage_zh-CN.cab WinPE-EnhancedStorage-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
7	Feature Pack	winpe-narrator_zh-CN.cab WinPE-Narrator-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
8	Feature Pack	winpe-scripting_zh-CN.cab WinPE-Scripting-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
9	Feature Pack	winpe-securestartup_zh-CN.cab WinPE-SecureStartup-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1

SN	TYPE	LANGUAGE PACK INSTALLATION FILE, CORRESPONDING PACKAGE NAME
10	Feature Pack	WINPE-SETUP-Server_zh-CN.CAB WinPE-Setup-Server-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
11	Feature Pack	WinPE-Setup_zh-CN.cab WinPE-Setup-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
12	Feature Pack	winpe-speech-tts_zh-CN.cab WinPE-Speech-TTS-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
13	Feature Pack	winpe-srh_zh-CN.cab WinPE-SRH-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
14	Feature Pack	winpe-srt_zh-CN.cab WinPE-SRT-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
15	Feature Pack	winpe-wds-tools_zh-CN.cab WinPE-WDS-Tools-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1
16	Feature Pack	winpe-wmi_zh-CN.cab WinPE-WMI-Package~31bf3856ad364e35~amd64~zh-CN~10.0.20348.1

Author: [Feng Yi](#)

Website: <https://fengyi.tel>

EMail: 775159955@qq.com, fengyitel@gmail.com, ilikeyi@icloud.com

Document version: [1.0](#)

Updated: [2024-1](#)

Suggestions or feedback: <https://github.com/ilikeyi/solutions/issues>



© Yi. All rights reserved.