



MICROSOFT WINDOWS 11 22H2

PACKAGING TUTORIAL: Different system versions have different packaging methods. The packaging process includes: "Language pack: add, associate, delete", "Drive: add, delete", "Cumulative update: add, delete", "InBox Apps: add, Update, mark" etc.

There are many hidden stories hidden behind this. If you want to unlock these, are you ready to start trying to encapsulate them?

Summary

Chapter 1	Deployment image
Chapter 2	Report
Chapter 3	Common problem
Chapter 4	Known issues

Table of contents

Chapter 1	Deployment image	Page 5
A.	Prerequisites	Page 5
II	ISO tools	Page 5
III	Requirements	Page 5
1.	System installation package	Page 5
2.	Language pack	Page 6
2.1.	Learn	Page 6
2.2.	Language pack: Download	Page 9
2.3.	Language pack: Fixed	Page 9
3.	InBox Apps	Page 9
IV	Windows Security	Page 10
V	Command Line	Page 10
B.	Language Pack: Extract	Page 10
II	Language pack: Ready	Page 10
III	Language pack: Scheme	Page 11
IV	Execute the extract command	Page 11
C.	Customize the deployment image	Page 17
II	Custom deployment image Install.wim	Page 17
1.	View Install.wim details	Page 17
2.	Specify the path to mount Install.wim	Page 17
3.	Start mounting Install.wim	Page 17
3.1.	Custom deployment image WinRE.wim	Page 17
3.1.1.	View WinRE.wim details	Page 17
3.1.2.	Specify the path to mount WinRE.wim	Page 17
3.1.3.	Start mounting WinRE.wim	Page 17
3.1.4.	Language pack	Page 18
3.1.4.1.	Language pack: add	Page 18
3.1.4.2.	Offline image language: change	Page 19
3.1.4.2.1.	Change default language, regional settings, and other international settings	Page 19
3.1.4.2.2.	View available language settings	Page 19

3.1.4.3.	Language packs: Removed	Page 20
3.1.4.4.	Components: All packages installed in the image	Page 22
3.1.5.	Cumulative updates	Page 22
3.1.5.1.	Add	Page 22
3.1.5.2.	Delete	Page 22
3.1.5.3.	Solid update	Page 22
3.1.5.3.1.	Clean components after curing and updating	Page 23
3.1.6.	Drive	Page 23
3.1.7.	Save image	Page 23
3.1.8.	Unmount image	Page 23
3.1.9.	After rebuilding WinRE.wim, the file size can be reduced	Page 23
3.1.10.	Backup WinRE.wim	Page 24
3.1.11.	Replace WinRE.wim within the Install.wim image	Page 24
4.	Language pack	Page 24
4.1.	Language pack: add	Page 24
4.2.	Offline image language: change	Page 30
4.2.1.	Change default language, regional settings, and other international settings	Page 30
4.2.2.	View available language settings	Page 30
4.3.	Language packs: Removed	Page 30
4.4.	Components: All packages installed in the image	Page 33
5.	InBox Apps	Page 33
5.1.	Learn	Page 33
5.2.	InBox Apps: Pre-install the application	Page 33
5.3.	InBox Apps: Installed	Page 35
5.4.	Remove all installed pre-applications	Page 35
5.5.	Region tag: Understanding	Page 36
5.6.	Region tag: adding method	Page 36
5.7.	InBox Apps: Install	Page 39
5.8.	Region tag: delete	Page 49
5.9.	InBox Apps: optimization	Page 49

6.	Cumulative updates	Page 49
6.1.	Initial version	Page 50
6.2.	Other Version	Page 50
6.3.	Solidify Updated	Page 51
7.	Drive	Page 51
8.	Add deployment engine	Page 51
9.	Health	Page 52
10.	Replace WinRE.wim	Page 52
11.	Save image	Page 52
12.	Unmount image	Page 52
13.	Rebuilding Install.wim reduces file size	Page 52
14.	How to batch replace WinRE.wim in all index numbers in Install.wim	Page 52
14.1.	Obtain WimLib	Page 53
14.2.	How to extract and update WinRE.wim in Install.wim	Page 53
III	Custom deployment image boot.wim	Page 54
1.	View Boot.wim details	Page 54
2.	Specify the path to mount Boot.wim	Page 54
3.	Start mounting Boot.wim	Page 54
4.	Language pack	Page 54
4.1.	Language pack: Add	Page 54
4.2.	Offline image language: change	Page 56
4.2.1.	Change default language, regional settings, and other international settings	Page 56
4.2.2.	View available language settings	Page 56
4.3.	Language pack: Removed	Page 56
4.4.	Components: All packages installed in the image	Page 59
4.5.	Language: Repair	Page 59
4.6.	Language packs: sync to ISO installer	Page 59
4.7.	Regenerate Lang.ini	Page 59
4.7.1.	Regenerate the mounted directory lang.ini	Page 59
4.7.2.	After regenerating lang.ini, sync to the installer	Page 59
5.	Cumulative updates	Page 59

5.1.	Add	Page 60
5.2.	Delete	Page 60
5.3.	Solid update	Page 60
5.3.1.	Clean components after curing and updating	Page 60
6.	Drive	Page 60
7.	Other	Page 60
7.1.	Bypass TPM check during installation	Page 60
8.	Save image	Page 61
9.	Unmount image	Page 61
IV	Deployment engine	Page 61
1.	Add method	Page 61
2.	Deployment Engine: Advanced	Page 64
D.	ISO	Page 66
II	Generate ISO	Page 66
III	Bypass TPM installation check	Page 67
Chapter 2	Report	Page 67
II	Reports: Different versions	Page 68
III	Report: Language installation packages apply to Install.wim	Page 70
IV	Report: Language installation packages apply to WinRE.wim	Page 71
V	Report: Language installation packages apply to Boot.wim	Page 72
Chapter 3	Common problem	Page 67
II	Clean all mounts to	Page 73
III	Fix the problem of abnormal mounting	Page 74
IV	Clean directories	Page 74
Chapter 4	Known issues	Page 74

Chapter 1 Deployment image

A. Prerequisites

II ISO tools

Use a software that can edit ISO files, such as: [PowerISO](#), [DAEMON Tools](#), [ISO Workshop](#);

III Requirements

1. System installation package

Keywords: [iteration](#), [cross-version](#), [major version](#), [cumulative update](#), [initial release](#)

1.1. illustrate

- 1.1.1. Please remake the image when each version is updated, for example, when crossing from 21H1 to 22H2, avoid other compatibility problems, and do not make the image based on the old image;
- 1.1.2. The regulation has been clearly communicated to packagers in various forms by some OEMs, and direct upgrades from iterative versions are not allowed;
- 1.1.3. Please use "Initial Version" and "Developer Edition" for production. There was a brief appearance in the official Microsoft documentation that the initial version must be used in production, but this sentence was later deleted in the official documentation;
- 1.1.4. After installing the language pack, you must re-add the cumulative update (the same version number), and if you do not add the cumulative update, problems such as "garbled characters" and "interface flashback" will occur.
- 1.1.5. Evolutionary process: Windows 11 22H2, Build 22621.382 + KB5027303 = OS Build 22621.1928

1.2. Prepare to download the initial or developer version

- 1.2.1. [en-us_windows_11_business_editions_version_22h2_x64_dvd_17a08ce3.iso](#)
- 1.2.2. [en-us_windows_11_consumer_editions_version_22h2_x64_dvd_e630fafd.iso](#)
- 1.2.3. [en-us_windows_11_iot_enterprise_version_22h2_arm64_dvd_f09f5d29.iso](#)
- 1.2.4. [en-us_windows_11_iot_enterprise_version_22h2_x64_dvd_eb39bf70.iso](#)

1.3. After the sample download [en-us_windows_11_business_editions_version_22h2_x64_dvd_17a08ce3.iso](#), Unzip to: [D:\en-us_windows_11_business_editions_version_22h2_x64_dvd_17a08c](#)

1.4. After decompression is complete, change the directory [en-us_windows_11_business_editions_version_22h2_x64_dvd_17a08c](#) change to [D:\OS_11](#)

1.5. All scripts and all paths are set to [D:\OS_11](#) as the image source.

1.6. Installation configuration

1.6.1. Learn: [Windows Setup Edition Configuration and Product ID Files \(Ei.cfg and PID.txt \)](#)

1.6.2. Known issues

- 1.6.2.1. When there is no Ei.cfg, ISO boot installation will report an error when selecting certain versions, prompting:
[Windows cannot find the Microsoft Software License terms. Make sure the installation sources are valid and restart the installation.](#)
- 1.6.2.2. How to solve it? Add ei.cfg to D:\OS_11\Sources and create ei.cfg:

```
@"  
  
[Channel]  
  
volume  
  
  
  
[VL]  
  
1  
  
"@ | Out-File -FilePath "D:\OS_11\sources\EI.CFG" -Encoding Ascii
```

1.7. Report

Check the installed image package: language packs, associated language pack components, pre-installed InBox Apps applications and other detailed information. After downloading the report, use Excel software to open the .xlsx.

1.7.1. Report: Overview

Contains: ISO system installation package, image version, region, region association, associated language pack components, etc.

[Report.Overview.xlsx](#)

1.7.2. Report: Complete

Inclusion: ISO system installation package, image version, region, region association, associated language pack components, installed InBox Apps pre-installed applications, etc.

[en-us, ar-sa, bg-bg, cs-cz, da-dk, de-de, el-gr, en-gb, es-es, es-mx, et-ee, fi-fi, fr-ca, fr-fr, he-il, hr-hr, hu-hu, it-it, ja-jp, ko-kr, lt-lt, lv-lv, nb-no, nl-nl, pl-pl, pt-br, pt-pt, ro-ro, ru-ru, sk-sk, sl-si, sr-latn-rs, sv-se, th-th, tr-tr, uk-ua, zh-cn, zh-tw](#)

2. Language pack

2.1. Learn

As you read, please understand the important highlights of "Blue".

2.1.1. [Languages overview](#)

2.1.2. [Add languages to a Windows 11 image](#)

2.1.3. [Language and region Features on Demand \(FOD\)](#)

2.1.3.1. Fonts

- When adding a language pack, when the corresponding region is triggered, the required font functions need to be added, download "[List of all available language FODs](#)" learn more.
- In "Language Pack: Extract", the automatic recognition function has been added, and you can understand the functions: [Function Match_Required_Fonts](#)

2.1.3.2. Regional association

What are regional connections?

- When the image language is only in English, after adding the [zh-HK](#) language pack, the image language

will not be added. You should install [zh-TW](#) first, and then install [zh-HK](#) to obtain the corresponding association.

Known regional associations:

2.1.3.2.1. Region: [ar-sa](#), Optional associated areas: [en-US](#), associated installation package:

2.1.3.2.1.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.1.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.2. Region: [bg-bg](#), Optional associated areas: [en-US](#), associated installation package:

2.1.3.2.2.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.2.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.3. Region: [da-dk](#), Optional associated areas: [en-US](#), associated installation package:

2.1.3.2.3.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.3.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.4. Region: [el-gr](#), Optional associated areas: [en-US](#), associated installation package:

2.1.3.2.4.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.4.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.5. Region: [fr-ca](#), Optional associated areas: [en-US](#), [fr-fr](#), associated installation package:

2.1.3.2.5.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.5.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.5.3. Microsoft-Windows-LanguageFeatures-Basic-fr-fr-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.5.4. Microsoft-Windows-LanguageFeatures-Handwriting-fi-fi-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.6. Region: [he-il](#), Optional associated areas: [en-US](#), associated installation package:

2.1.3.2.6.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.6.2.	Microsoft-Windows-LanguageFeatures-OCR-en-us- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.7.	Region: ru-ru , Optional associated areas: en-US , associated installation package:
2.1.3.2.7.1.	Microsoft-Windows-LanguageFeatures-Basic-es-us- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.7.2.	Microsoft-Windows-LanguageFeatures-OCR-en-us- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.8.	Region: th-th , Optional associated areas: en-US , associated installation package:
2.1.3.2.8.1.	Microsoft-Windows-LanguageFeatures-Basic-es-us- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.8.2.	Microsoft-Windows-LanguageFeatures-OCR-en-us- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.9.	Region: uk-ua , Optional associated areas: en-US , associated installation package:
2.1.3.2.9.1.	Microsoft-Windows-LanguageFeatures-Basic-es-us- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.9.2.	Microsoft-Windows-LanguageFeatures-OCR-en-us- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.10.	Region: zh-TW , Optional associated areas: zh-HK , associated installation package:
2.1.3.2.10.1.	Microsoft-Windows-LanguageFeatures-Basic-zh-hk- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.10.2.	Microsoft-Windows-LanguageFeatures-Speech-zh-hk- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.2.10.3.	Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-hk- Package~31bf3856ad364e35~amd64~~.cab
2.1.3.3.	Other region-specific requirements
	When triggering a known area, a specific "package" needs to be added.
2.1.3.3.1.	Region: zh-TW
	Package: Microsoft-Windows-InternationalFeatures-Taiwan- Package~31bf3856ad364e35~amd64~~.cab
	Description: Supplemental support for Taiwan date formatting requirements. Package will be provided to customers located in Taiwan.
	Recommendation: Preinstall only on devices shipping to the Taiwan market. Not installing this capability on devices causes any API calls to that use the Taiwan calendar to fail.

THERE IS CONTROVERSY:

- During the test, it was found that this package was not installed in the original image of Microsoft's official original Windows 11. However, there are known issues in the recommended items. In the end, it is consistent with the official Microsoft original version, and the packager can freely choose to install it or not.

2.2. Language pack: Download

https://software-static.download.prss.microsoft.com/dbazure/988969d5-f34g-4e03-ac9d-1f9786c66749/22621.1.220506-1250.ni_release_amd64fre_CLIENT_LOF_PACKAGES_OEM.iso

2.3. Language pack: Fixed

2.3.1. Select any website and open:

2.3.1.1. <https://uupdump.net>

2.3.1.2. <https://uup.ee>

2.3.1.3. <https://osdump.com>

2.3.2. After opening, search for keywords: **22621.382**, select from the search results: **Windows 11, version 22H2 (22621.382) amd64**

2.3.3. After opening, select "**All files**";

2.3.4. Search the green part in the "**All Files**" page and download

2.3.4.1. Applies to: Install.wim:

2.3.4.1.1. **MediaPlayer**

2.3.4.2. Applies to: WinRE.wim, none yet

2.3.4.3. Applies to: Boot.wim, none yet

2.3.5. After downloading all the files, scroll to the bottom of the page, download and run "**Generate Rename Script (Windows)**"

2.3.6. Use ISO editing software, edit **22621.1.220506-1250.ni_release_amd64fre_CLIENT_LOF_PACKAGES_OEM.iso**, and add the downloaded file to the **[ISO]\LanguagesAndOptionalFeatures** directory;

3. InBox Apps

3.1. Download: https://software-static.download.prss.microsoft.com/dbazure/888969d5-f34g-4e03-ac9d-1f9786c66749/22621.1778.230511-2102.ni_release_svc_prod3_amd64fre_InboxApps.iso

3.2. Download: https://software-static.download.prss.microsoft.com/dbazure/988969d5-f34g-4e03-ac9d-1f9786c66749/22621.1.220506-1250.ni_release_amd64fre_InboxApps.iso finally, Extract:

3.2.1. Microsoft.HEVCVideoExtension

3.2.1.1. **Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.arm64.appx**

3.2.1.2. **Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.arm64.xml**

3.2.1.3. [Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.x64.appx](#)

3.2.1.4. [Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.x64.xml](#)

- 3.3. Use the ISO editing tool to edit [22621.1778.230511-2102.ni_release_svc_prod3_amd64fre_InboxApps.iso](#) and add the extracted files to the [\[ISO\]:\packages](#) directory;

IV Windows Security

- When processing the encapsulation task, a large number of temporary files will be generated, and a large number of installation files will be released when installing the application in InBox Apps;
- Turning on Windows Security scans files and takes up a lot of CPU.
- In test: 1 hour and 22 minutes before shutdown, 20 minutes after shutdown.

How to close:

With the command line in green, hold down the Windows key and press R to launch Run.

1. Open Windows Security or run: [windowsdefender:](#)
2. Select "Virus & Threat Protection" or Run: [windowsdefender://threat](#)
3. Find "Virus & Threat Protection Settings", click "Manage Settings" or Run: [windowsdefender://threatsettings](#), we recommend that you turn off some features:
 - 3.1. Real-time protection
 - 3.2. Cloud=delivered protection
 - 3.3. Automatic sample submission
 - 3.4. Tamper Protection
4. When you're not encapsulated, we recommend that you turn on Windows Security.

V Command line

1. Optional "Terminal" or "PowerShell ISE", if "Terminal" is not installed, please go to: <https://github.com/microsoft/terminal/releases> After downloading;
2. Open "Terminal" or "PowerShell ISE" as administrator, it is recommended to set the PowerShell execution policy: bypass, PS command line:
[Set-ExecutionPolicy -ExecutionPolicy Bypass -Force](#)
3. In this article, PS command line, green part, please copy it, paste it into the "Terminal" dialog box, press Enter and start running;
4. When there is [.ps1](#), right-click the file and select Run with PowerShell, or copy the path and paste it into Terminal to run, the path with a colon, add the & character in the command line, example: [& "D:\Yi.Solutions_Encapsulation_SIP.ps1"](#)

B. Language Pack: Extract

II Language pack: Ready

Mount [22621.1.220506-1250.ni_release_amd64fre_CLIENT_LOF_PACKAGES_OEM.iso](#) or unzipped to any location;

III Language pack: Scheme

1. Add

- 1.1. Language name: **Simplified Chinese - China**, Region: **zh-CN**, Scope of application: **Install.Wim** , **Boot.Wim** , **WinRE.Wim**

2. Delete

- 2.1. Language name: **English - United States**, Region: **en-US**, Scope of application: **Install.Wim** , **Boot.Wim** , **WinRE.Wim**

IV Execute the extract command

- **Auto** = automatically search all local disks, default;
- Customize the path, for example, specify the E drive: **\$ISO = "E:\"**
- **Extract.ps1**
 - **\Expand\Extract.ps1**
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Extract.ps1

- Copy the code

```
$ISO = "Auto"
```

```
$SaveTo = "D:\OS_11_Custom"
```

```
$Extract_language_Pack = @(
```

```
    @{ Tag = "zh-CN"; Act = "Add"; Scope = @( "Install\Install"; "Install\WinRE"; "Boot\Boot" ) }
```

```
    @{ Tag = "en-US"; Act = "Del"; Scope = @( "Install\Install"; "Install\WinRE"; "Boot\Boot" ) }
```

```
)
```

```
Function Extract_Language
```

```
{
```

```
    param( $Act, $NewLang, $Expand )
```

```
    Function Match_Required_Fonts
```

```
{
```

```
    param( $Lang )
```

```
    $Fonts = @(
```

```
        @{ Match = @( "as", "ar-SA", "ar", "ar-AE", "ar-BH", "ar-DJ", "ar-DZ", "ar-EG", "ar-ER", "ar-IL", "ar-IQ", "ar-JO", "ar-KM", "ar-KW", "ar-LB", "ar-LY",  
"ar-MA", "ar-MR", "ar-OM", "ar-PS", "ar-QA", "ar-SD", "ar-SO", "ar-SS", "ar-SY", "ar-TD", "ar-TN", "ar-YE", "arz-Arab", "ckb-Arab", "fa", "fa-AF", "fa-IR",  
"glk-Arab", "ha-Arab", "ks-Arab", "ks-Arab-IN", "ku-Arab", "ku-Arab-IQ", "mzn-Arab", "pa-Arab", "pa-Arab-PK", "pnb-Arab", "prs", "prs-AF", "prs-Arab",  
"ps", "ps-AF", "sd-Arab", "sd-Arab-PK", "tk-Arab", "ug", "ug-Arab", "ug-CN", "ur", "ur-IN", "ur-PK", "uz-Arab", "uz-Arab-AF"); Name = "Arab"; }
```

```
        @{ Match = @( "bn-IN", "as-IN", "bn", "bn-BD", "bpy-Beng"); Name = "Beng"; }
```

```
        @{ Match = @( "da-dk", "iu-Cans", "iu-Cans-CA"); Name = "Cans"; }
```

```
        @{ Match = @( "chr-Cher-US", "chr-Cher"); Name = "Cher"; }
```

```
        @{ Match = @( "hi-IN", "bh-Deva", "brx", "brx-Deva", "brx-IN", "hi", "ks-Deva", "mai", "mr", "mr-IN", "ne", "ne-IN", "ne-NP", "new-Deva", "pi-Deva",
```

```
"sa", "sa-Deva", "sa-IN"); Name = "Deva"; }

    @{ Match = @("am", "am-ET", "byn", "byn-ER", "byn-Ethi", "ti", "ti-ER", "ti-ET", "tig", "tig-ER", "tig-Ethi", "ve-Ethi", "wal", "wal-ET", "wal-Ethi");
    Name = "Ethi"; }

    @{ Match = @("gu", "gu-IN"); Name = "Gujr"; }

    @{ Match = @("pa", "pa-IN", "pa-Guru"); Name = "Guru"; }

    @{ Match = @("zh-CN", "cmn-Hans", "gan-Hans", "hak-Hans", "wuu-Hans", "yue-Hans", "zh-gan-Hans", "zh-hak-Hans", "zh-Hans", "zh-SG", "zh-
wuu-Hans", "zh-yue-Hans"); Name = "Hans"; }

    @{ Match = @("zh-TW", "cmn-Hant", "hak-Hant", "lzh-Hant", "zh-hak-Hant", "zh-Hant", "zh-HK", "zh-lzh-Hant", "zh-MO", "zh-yue-Hant"); Name =
"Hant"; }

    @{ Match = @("he", "he-IL", "yi"); Name = "Hebr"; }

    @{ Match = @("ja", "ja-JP"); Name = "Jpan"; }

    @{ Match = @("km", "km-KH"); Name = "Khmr"; }

    @{ Match = @("kn", "kn-IN"); Name = "Knda"; }

    @{ Match = @("ko", "ko-KR"); Name = "Kore"; }

    @{ Match = @("de-de", "lo", "lo-LA"); Name = "Lao"; }

    @{ Match = @("ml", "ml-IN"); Name = "Mlym"; }

    @{ Match = @("or", "or-IN"); Name = "Orya"; }

    @{ Match = @("si", "si-LK"); Name = "Sinh"; }

    @{ Match = @("tr-tr", "arc-Syrc", "syr", "syr-SY", "syr-Syrc"); Name = "Syrc"; }

    @{ Match = @("ta", "ta-IN", "ta-LK", "ta-MY", "ta-SG"); Name = "Taml"; }

    @{ Match = @("te", "te-IN"); Name = "Telu"; }

    @{ Match = @("th", "th-TH"); Name = "Thai"; }

)

ForEach ($item in $Fonts) {

    if (($item.Match) -Contains $Lang) {

        return $item.Name

    }

}

return "Not_matched"

}

Function Match_Other_Region_Specific_Requirements

{

    param( $Lang )

    $RegionSpecific = @(

        @{ Match = @("zh-TW"); Name = "Taiwan"; }

    )

}
```

```

ForEach ($item in $RegionSpecific){

    if (($item.Match) -Contains $Lang){

        return $item.Name

    }

}

return "Skip_specific_packages"

}

Function Extract_Process

{

    param( $Package, $Name, $NewSaveTo )

    $NewSaveTo = "$($SaveTo)\$($NewSaveTo)\Language\$($Act)\$($NewLang)"

    New-Item -Path $NewSaveTo -ItemType Directory -ErrorAction SilentlyContinue | Out-Null

    if ($ISO -eq "Auto"){

        Get-PSDrive -PSProvider FileSystem -ErrorAction SilentlyContinue | ForEach-Object {

            ForEach ($item in $Package){

                $TempFilePath = Join-Path -Path $_.Root -ChildPath $item -ErrorAction SilentlyContinue

                if (Test-Path $TempFilePath -PathType Leaf){

                    Write-host "`n  Find: " -NoNewLine; Write-host $TempFilePath -ForegroundColor Green

                    Write-host "  Copy to: " -NoNewLine; Write-host $NewSaveTo

                    Copy-Item -Path $TempFilePath -Destination $NewSaveTo -Force

                }

            }

        }

    }else{

        ForEach ($item in $Package){

            $TempFilePath = Join-Path -Path $ISO -ChildPath $item -ErrorAction SilentlyContinue

            Write-host "`n  Find: " -NoNewline; Write-host $TempFilePath -ForegroundColor Green

            if (Test-Path $TempFilePath -PathType Leaf){

                Write-host "  Copy to: " -NoNewLine; Write-host $NewSaveTo

                Copy-Item -Path $TempFilePath -Destination $NewSaveTo -Force

            }else{

                Write-host "  Not found"

            }

        }

    }

}

```

```

}

Write-host "`n  Verify the language pack file"

ForEach ($item in $Package) {

    $Path = "$($NewSaveTo)\${[IO.Path]::GetFileName($item)}"

    if (Test-Path $Path -PathType Leaf) {

        Write-host "  Discover: " -NoNewLine; Write-host $Path -ForegroundColor Green

    } else {

        Write-host "  Not found: " -NoNewLine; Write-host $Path -ForegroundColor Red

    }

}

}

$AdvLanguage = @(

    @(

        Path = "Install\Install"

        Rule = @(

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Fonts-{DiyLang}-Package~31bf3856ad364e35~AMD64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-Client-Language-Pack_x64_{Lang}.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Basic-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Handwriting-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-OCR-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Speech-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-TextToSpeech-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-MediaPlayer-Package-AMD64-{Lang}.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-MediaPlayer-Package-wow64-{Lang}.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

```

```

"LanguagesAndOptionalFeatures\Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-InternationalFeatures-{Specific}-Package~31bf3856ad364e35~amd64~~.cab"

)

}

@{

    Path = "Install\WinRE"

    Rule = @(

        "Windows Preinstallation Environment\x64\WinPE_OC\WinPE-FontSupport-{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\lp.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-securestartup_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-atbroker_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiocore_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiodrivers_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-enhancedstorage_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-narrator_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-scripting_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-speech-tts_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srh_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srt_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wds-tools_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wmi_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-appxdeployment_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-appxpackaging_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-storagewmi_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wifi_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-windowsupdate_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-rejuv_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-opcservices_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-hta_{Lang}.cab"

    )

}

@{

    Path = "Boot\Boot"

```



```

Rule = @(

    "Windows Preinstallation Environment\x64\WinPE_OC\WinPE-FontSupport-{Lang}.cab"

    "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\lp.cab"

    "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\WinPE-Setup_{Lang}.cab"

    "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\WINPE-SETUP-CLIENT_{Lang}.CAB"

    "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-securestartup_{Lang}.cab"

    "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-atbroker_{Lang}.cab"

    "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiocore_{Lang}.cab"

    "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiodrivers_{Lang}.cab"

    "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-enhancedstorage_{Lang}.cab"

    "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-narrator_{Lang}.cab"

    "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-scripting_{Lang}.cab"

    "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-speech-tts_{Lang}.cab"

    "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srh_{Lang}.cab"

    "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srt_{Lang}.cab"

    "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wds-tools_{Lang}.cab"

    "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wmi_{Lang}.cab"

)

}

)

$NewFonts = Match_Required_Fonts -Lang $NewLang

$SpecificPackage = Match_Other_Region_Specific_Requirements -Lang $NewLang

Foreach ($item in $Expand) {

    $Language = @()

    Foreach ($itemList in $AdvLanguage) {

        if ($itemList.Path -eq $item) {

            Foreach ($PrintLang in $itemList.Rule) {

                $Language += "$($PrintLang)".Replace("{Lang}", $NewLang).Replace("{DiyLang}", $NewFonts).Replace("{Specific}", $SpecificPackage)

            }

            Extract_Process -NewSaveTo $itemList.Path -Package $Language -Name $item

        }

    }

}

}

```

```
ForEach ($item in $Extract_language_Pack) { Extract_Language -Act $item.Act -NewLang $item.Tag -Expand $item.Scope }
```

C. Customize the deployment image

II Custom deployment image Install.wim

1. View Install.wim details

Image name, image description, image size, architecture, version, index number, etc.

```
$ViewFile = "D:\OS_11\Sources\Install.wim"
```

```
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex }
```

LOOP OPERATING AREA, START,

2. Specify the path to mount Install.wim

```
New-Item -Path "D:\OS_11_Custom\Install\Install\Mount" -ItemType directory -ea SilentlyContinue
```

3. Start mounting Install.wim

Default index number: 1

```
Mount-WindowsImage -ImagePath "D:\OS_11\sources\install.wim" -Index "1" -Path "D:\OS_11_Custom\Install\Install\Mount"
```

PROCESS FILES WITHIN THE INSTALL.WIM IMAGE, OPTIONALLY, START,

3.1. Custom deployment image WinRE.wim

WARNING:

- WinRE.wim is a file within the Install.wim image;
- When Install.wim has multiple index numbers, only process any WinRE.wim;
- Synchronize to all index numbers to reduce the size of Install.wim, learn "[How to batch replace WinRE.wim in all index numbers in Install.wim](#)".

3.1.1. View WinRE.wim details

Image name, image description, image size, architecture, version, index number, etc.

```
$ViewFile = "D:\OS_11_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"
```

```
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex }
```

3.1.2. Specify the path to mount WinRE.wim

```
New-Item -Path "D:\OS_11_Custom\Install\WinRE\Mount" -ItemType directory -ea SilentlyContinue
```

3.1.3. Start mounting WinRE.wim

Default index number: 1

```
Mount-WindowsImage -ImagePath "D:\OS_11_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim" -
```

Index "1" -Path "D:\OS_11_Custom\Install\WinRE\Mount"

3.1.4. Language pack: WinRE

- Automatically install language packs: Get "Component: All installed packages in the image" and match them. After matching the corresponding names, install the local corresponding language pack files, View the report "[Language installation package for WinRE.wim](#)".
- When adding languages, different schema versions must be corresponded, and if not, errors are reported during the addition process.

3.1.4.1. Language pack: add

- WinRE.Instl.lang.ps1
 - [\Expand\Install\WinRE\WinRE.Instl.lang.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Install/WinRE/WinRE.Instl.lang.ps1

- Copy the code

```
$Mount = "D:\OS_11_Custom\Install\WinRE\Mount"
```

```
$Sources = "D:\OS_11_Custom\Install\WinRE\Language\Add\zh-CN"
```

```
$Initl_install_Language_Component = @()
```

```
Get-WindowsPackage -Path $Mount | ForEach-Object { $Initl_install_Language_Component +=  
$_.PackageName }
```

```
Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\WinPE-FontSupport-zh-CN.cab"
```

```
$Language_List = @(
```

```
@{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }
```

```
@{ Match = "*SecureStartup*"; File = "winpe-securestartup_zh-CN.cab"; }
```

```
@{ Match = "*ATBroker*"; File = "winpe-atbroker_zh-CN.cab"; }
```

```
@{ Match = "*AudioCore*"; File = "winpe-audiocore_zh-CN.cab"; }
```

```
@{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_zh-CN.cab"; }
```

```
@{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_zh-CN.cab"; }
```

```
@{ Match = "*Narrator*"; File = "winpe-narrator_zh-CN.cab"; }
```

```
@{ Match = "*scripting*"; File = "winpe-scripting_zh-CN.cab"; }
```

```
@{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_zh-CN.cab"; }
```

```
@{ Match = "*srh*"; File = "winpe-srh_zh-CN.cab"; }
```

```
@{ Match = "*srt*"; File = "winpe-srt_zh-CN.cab"; }
```

```
@{ Match = "*wds-tools*"; File = "winpe-wds-tools_zh-CN.cab"; }
```

```
@{ Match = "*-WMI-Package*"; File = "winpe-wmi_zh-CN.cab"; }
```

```
@{ Match = "*WinPE-AppxPackaging*"; File = "winpe-appxpackaging_zh-CN.cab"; }
```

```

@{ Match = "*StorageWMI*"; File = "winpe-storagewmi_zh-CN.cab"; }

@{ Match = "*WiFi*"; File = "winpe-wifi_zh-CN.cab"; }

@{ Match = "*rejuv*"; File = "winpe-rejuv_zh-CN.cab"; }

@{ Match = "*opcservices*"; File = "winpe-opcservices_zh-CN.cab"; }

@{ Match = "*hta*"; File = "winpe-hta_zh-CN.cab"; }

@{ Match = "*windowsupdate*"; File = "winpe-windowsupdate_zh-CN.cab"; }

@{ Match = "*appxdeployment*"; File = "winpe-appxdeployment_zh-CN.cab"; }

)

ForEach ($Rule in $Language_List) {

    Write-host "`n  Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "*$($Rule.Match)*") {

            Write-host "  Component name: " -NoNewline; Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline; Write-host "$($Sources)\$($Rule.File)" -
ForegroundColor Green

            Write-Host "  Installing ".PadRight(22) -NoNewline

            try {

                Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" | Out-Null

                Write-host "Finish" -ForegroundColor Green

            } catch {

                Write-host "Failed" -ForegroundColor Red

            }

            break

        }

    }

}

```

3.1.4.2. Offline image language: change

3.1.4.2.1. Change default language, regional settings, and other international settings

Region: **zh-CN**

```
Dism /Image:"D:\OS_11_Custom\Install\WinRE\Mount" /Set-AllIntl:"zh-CN"
```

3.1.4.2.2. View available language settings

```
Dism /Image:"D:\OS_11_Custom\Install\WinRE\Mount" /Get-Intl
```

3.1.4.3. Language packs: Removed, optional

- After you add languages, if you want to deploy to a non-English locale, you can save space by removing the English language component. When you remove a language, uninstall the language components in the reverse order in which you added them.
- After adding the Chinese, delete "English - United States" in reverse, the Region tag: **en-US**, you need to extract the language pack in advance
- WinRE.Del.Specified.lang.Tag.ps1
 - [\Expand\Install\WinRE\WinRE.Del.Specified.lang.Tag.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Install/WinRE/WinRE.Del.Specified.lang.Tag.ps1

- Copy the code

```
$Lang = "en-US"

$Mount = "D:\OS_11_Custom\Install\WinRE\Mount"

$Sources = "D:\OS_11_Custom\Install\WinRE\Language\Del\en-US"

$Initl_install_Language_Component = @(

Get-WindowsPackage -Path $Mount | ForEach-Object { $Initl_install_Language_Component +=
$_.PackageName }

$Language = @(

    @{ Match = "*windowsupdate*"; File = "winpe-windowsupdate_$( $Lang ).cab"; }

    @{ Match = "*appxdeployment*"; File = "winpe-appxdeployment_$( $Lang ).cab"; }

    @{ Match = "*hta*"; File = "winpe-hta_$( $Lang ).cab"; }

    @{ Match = "*opcservices*"; File = "winpe-opcservices_$( $Lang ).cab"; }

    @{ Match = "*rejuv*"; File = "winpe-rejuv_$( $Lang ).cab"; }

    @{ Match = "*WiFi*"; File = "winpe-wifi_$( $Lang ).cab"; }

    @{ Match = "*StorageWMI*"; File = "winpe-storagewmi_$( $Lang ).cab"; }

    @{ Match = "*WinPE-AppxPackaging*"; File = "winpe-appxpackaging_$( $Lang ).cab"; }

    @{ Match = "*-WMI-Package*"; File = "winpe-wmi_$( $Lang ).cab"; }

    @{ Match = "*wds-tools*"; File = "winpe-wds-tools_$( $Lang ).cab"; }

    @{ Match = "*srt*"; File = "winpe-srt_$( $Lang ).cab"; }

    @{ Match = "*srh*"; File = "winpe-srh_$( $Lang ).cab"; }

    @{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_$( $Lang ).cab"; }

    @{ Match = "*scripting*"; File = "winpe-scripting_$( $Lang ).cab"; }

    @{ Match = "*Narrator*"; File = "winpe-narrator_$( $Lang ).cab"; }

    @{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_$( $Lang ).cab"; }

    @{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_$( $Lang ).cab"; }
```

```

@{ Match = "*AudioCore*"; File = "winpe-audiocore_$(Lang).cab"; }

@{ Match = "*ATBroker*"; File = "winpe-atbroker_$(Lang).cab"; }

@{ Match = "*SecureStartup*"; File = "winpe-securestartup_$(Lang).cab"; }

@{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }

)

ForEach ($Rule in $Language) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "*$(Rule.Match)*$(Lang)*") {

            Write-host "  Component name: " -NoNewline; Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline; Write-host "$($Sources)\$(Rule.File)" -
ForegroundColor Green

            Write-Host "  Deleting ".PadRight(22) -NoNewline

            try {

                Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$(Rule.File)" -ErrorAction
SilentlyContinue | Out-Null

                Write-host "Finish" -ForegroundColor Green

            } catch {

                Write-host "Failed" -ForegroundColor Red

                Write-host "  $($_) " -ForegroundColor Red

            }

            break

        }

    }

}

$InitlClearLanguagePackage = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    if ($_.PackageName -like "*$(Lang)*") {

        $InitlClearLanguagePackage += $_.PackageName

    }

}

if ($InitlClearLanguagePackage.count -gt 0) {

    ForEach ($item in $InitlClearLanguagePackage) {

        Write-Host "`n  $($item)" -ForegroundColor Green

        Write-Host "  Deleting ".PadRight(22) -NoNewline

```

```

try{

    Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction SilentlyContinue |
Out-Null

    Write-host "Finish" -ForegroundColor Green

} catch {

    Write-host "Failed" -ForegroundColor Red

    Write-host " $($_) " -ForegroundColor Red

}

}

}

```

3.1.4.4. Components: All packages installed in the image

3.1.4.4.1. View

```
Get-WindowsPackage -Path "D:\OS_11_Custom\Install\WinRE\Mount" | Out-GridView
```

3.1.4.4.2. Export to csv

```
$SaveTo = "D:\OS_11_Custom\Install\WinRE\Report.$(Get-Date -Format
"yyyyMMddHHmmss").csv"
```

```
Get-WindowsPackage -Path "D:\OS_11_Custom\Install\WinRE\Mount" | Export-CSV -
NoType -Path $SaveTo
```

```
Write-host $SaveTo -ForegroundColor Green
```

3.1.5. Cumulative updates, optional

To prepare the cumulative updates file available, change the example file name: **KB_WinRE.cab**

3.1.5.1. Add

```
$KBPath = "D:\OS_11_Custom\Install\WinRE\Update\KB_WinRE.cab"
```

```
Add-WindowsPackage -Path "D:\OS_11_Custom\Install\WinRE\Mount" -PackagePath $KBPath
```

3.1.5.2. Delete

```
$KBPath = "D:\OS_11_Custom\Install\WinRE\Update\KB_WinRE.cab"
```

```
Remove-WindowsPackage -Path "D:\OS_11_Custom\Install\WinRE\Mount" -PackagePath $KBPath
```

3.1.5.3. Solid update, optional

It cannot be uninstalled after curing, which cleans the recovery image and resets the basis of any superseded components.

```
Dism /image:"D:\OS_11_Custom\Install\WinRE\Mount" /cleanup-image /StartComponentCleanup
/ResetBase
```

3.1.5.3.1. Clean components after curing and updating, optional

```
$Mount = "D:\OS_11_Custom\Install\WinRE\Mount"

Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {

    if ($_.PackageState -eq "Superseded") {

        Write-Host "  ${_.PackageName}" -ForegroundColor Green

        Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null

    }

}
```

3.1.6. Drive, optional

3.1.7. Save image

```
Save-WindowsImage -Path "D:\OS_11_Custom\Install\WinRE\Mount"
```

3.1.8. Unmount image

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowsImage -Path "D:\OS_11_Custom\Install\WinRE\Mount" -Discard
```

3.1.9. After rebuilding WinRE.wim, the file size can be reduced

- WinRE.Rebuild.ps1
 - [\Install\WinRE\WinRE.Rebuild.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Install/WinRE/WinRE.Rebuild.ps1

- Copy the code

```
$FileName = "D:\OS_11_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"

Get-WindowsImage -ImagePath $Filename -ErrorAction SilentlyContinue | ForEach-Object {

    Write-Host "  Image name: " -NoNewline

    Write-Host $_.ImageName -ForegroundColor Yellow

    Write-Host "  The index number: " -NoNewline

    Write-Host $_.ImageIndex -ForegroundColor Yellow

    Write-Host "`n  Rebuild".PadRight(28) -NoNewline

    Export-WindowsImage -SourceImagePath $Filename -SourceIndex $_.ImageIndex -DestinationImagePath
"$($FileName).New" -CompressionType max

    Write-Host "Finish`n" -ForegroundColor Green

}

if (Test-Path "$($FileName).New" -PathType Leaf) {
```



```

Remove-Item -Path $Filename

Move-Item -Path "$($FileName).New" -Destination $Filename

Write-Host "Finish" -ForegroundColor Green

} else {

Write-host "Failed" -ForegroundColor Red

}

```

3.1.10. Backup WinRE.wim

- WinRE.Backup.ps1
 - [\Expand\Install\WinRE\WinRE.Backup.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Install/WinRE/WinRE.Backup.ps1

- Copy the code

```

$WimLibPath = "D:\OS_11_Custom\Install\Install\Update\Winlib"

$FileName = "D:\OS_11_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"

New-Item -Path $WimLibPath -ItemType Directory -ea SilentlyContinue

Copy-Item -Path $FileName -Destination $WimLibPath -Force

```

3.1.11. Replace WinRE.wim within the Install.wim image

- After each mount Install.wim "[Replace WinRE.wim](#)";
- Learn "[Get all index numbers of Install.wim and replace the old WinRE.wim](#)".

[Process the files in the Install.wim image and end.](#)

4. Language pack

- Automatically install language packs: Get "Component: All installed packages in the image" and match them. After matching the corresponding names, install the local corresponding language pack files, View the report "[Language installation package for Install.wim](#)".
- When adding languages, different schema versions must be corresponded, and if not, errors are reported during the addition process.

4.1. Language pack: add

- Install.Instl.lang.ps1
 - [\Expand\Install\Install.Instl.lang.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Install/Install.Instl.lang.ps1
- Copy the code

```

Function Language_Install

{

    param($Mount, $Sources, $Lang)

    $Initl_install_Language_Component = @()

    if (Test-Path $Mount -PathType Container) {

        Get-WindowsPackage -Path $Mount | ForEach-Object { $Initl_install_Language_Component += $_.PackageName }

    } else {

        Write-Host "Not mounted: $($Mount)"

        return

    }

    $Script:Init_Folder_All_File = @()

    if (Test-Path "$($Sources)\($Lang)" -PathType Container) {

        Get-ChildItem -Path $Sources -Recurse -Include "*.cab" -ErrorAction SilentlyContinue | ForEach-Object {

            $Script:Init_Folder_All_File += $_.FullName

        }

        Write-host "`n  Available language pack installation files"

        if ($Script:Init_Folder_All_File.Count -gt 0) {

            ForEach ($item in $Script:Init_Folder_All_File) {

                Write-host "  $($item)"

            }

        } else {

            Write-host "There are no language pack files locally"

            return

        }

    } else {

        Write-Host "Path does not exist: $($Sources)\($Lang)"

        return

    }

    $Script:Init_Folder_All_File_Match_Done = @()

    $Script:Init_Folder_All_File_Exclude = @()

    $Script:Search_File_Order = @(

        @{

            Name = "Fonts"

            Description = "Fonts"

        }
    )

```

```

Rule = @(

    @{ Match_Name = "*Fonts*"; IsMatch = "No"; Capability = ""; }

)

}

@{

    Name = "Basic"

    Description = "Basic"

    Rule = @(

        @{ Match_Name = "*LanguageFeatures-Basic*"; IsMatch = "Yes"; Capability = "Language.Basic~~~lb-LU~0.0.1.0"; }

        @{ Match_Name = "*Client*Language*Pack*"; IsMatch = "Yes"; Capability = "Language.Basic~~~lb-LU~0.0.1.0"; }

    )

}

@{

    Name = "OCR"

    Description = "Optical character recognition"

    Rule = @(

        @{ Match_Name = "*LanguageFeatures-OCR*"; IsMatch = "Yes"; Capability = "Language.OCR~~~fr-FR~0.0.1.0"; }

    )

}

@{

    Name = "Handwriting"

    Description = "Handwriting recognition"

    Rule = @(

        @{ Match_Name = "*LanguageFeatures-Handwriting*"; IsMatch = "Yes"; Capability = "Language.Handwriting~~~fr-FR~0.0.1.0"; }

    )

}

@{

    Name = "TextToSpeech"

    Description = "Text-to-speech"

    Rule = @(

        @{ Match_Name = "*LanguageFeatures-TextToSpeech*"; IsMatch = "Yes"; Capability = "Language.TextToSpeech~~~fr-FR~0.0.1.0"; }

    )

}

```

```

@{

    Name = "Speech"

    Description = "Speech recognition"

    Rule = @(

        @{ Match_Name = "*LanguageFeatures-Speech*"; IsMatch = "Yes"; Capability = "Language.Speech~~~fr-FR~0.0.1.0"; }

    )

}

@{

    Name = "RegionSpecific"

    Description = "Other region-specific requirements"

    Rule = @(

        @{ Match_Name = "*InternationalFeatures*"; IsMatch = "No"; Capability = ""; }

    )

}

@{

    Name = "Retail"

    Description = "Retail demo experience"

    Rule = @(

        @{ Match_Name = "*RetailDemo*"; IsMatch = "Yes"; Capability = ""; }

    )

}

@{

    Name = "Features_On_Demand"

    Description = "Features on demand"

    Rule = @(

        @{ Match_Name = "*InternetExplorer*"; IsMatch = "Yes"; Capability = ""; }

        @{ Match_Name = "*MSPaint*amd64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.MSPaint~~~~0.0.1.0"; }

        @{ Match_Name = "*MSPaint*wow64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.MSPaint~~~~0.0.1.0"; }

        @{ Match_Name = "*Notepad*amd64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.Notepad~~~~0.0.1.0"; }

        @{ Match_Name = "*Notepad*wow64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.Notepad~~~~0.0.1.0"; }

        @{ Match_Name = "*MediaPlayer*amd64*"; IsMatch = "Yes"; Capability = "Media.WindowsMediaPlayer~~~~0.0.12.0"; }

        @{ Match_Name = "*MediaPlayer*wow64*"; IsMatch = "Yes"; Capability = "Media.WindowsMediaPlayer~~~~0.0.12.0"; }

        @{ Match_Name = "*PowerShell-ISE-FOD-Package*amd64*"; IsMatch = "Yes"; Capability =
"Microsoft.Windows.PowerShell.ISE~~~~0.0.1.0"; }

        @{ Match_Name = "*PowerShell-ISE-FOD-Package*wow64*"; IsMatch = "Yes"; Capability =

```

```

"Microsoft.Windows.PowerShell.ISE~~~~0.0.1.0"; }

    @{ Match_Name = "*Printing*PMCPPC*amd64*"; IsMatch = "Yes"; Capability = "Print.Management.Console~~~~0.0.1.0"; }

    @{ Match_Name = "*StepsRecorder*amd64*"; IsMatch = "Yes"; Capability = "App.StepsRecorder~~~~0.0.1.0"; }

    @{ Match_Name = "*StepsRecorder*wow64*"; IsMatch = "Yes"; Capability = "App.StepsRecorder~~~~0.0.1.0"; }

    @{ Match_Name = "*WordPad*amd64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.WordPad~~~~0.0.1.0"; }

    @{ Match_Name = "*WordPad*wow64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.WordPad~~~~0.0.1.0"; }

    @{ Match_Name = "*WMIC*FoD*Package*amd64*"; IsMatch = "Yes"; Capability = "WMIC~~~~"; }

    @{ Match_Name = "*WMIC*FoD*Package*wow64*"; IsMatch = "Yes"; Capability = "WMIC~~~~"; }

)

}

)

ForEach ($item in $Script:Search_File_Order) { New-Variable -Name "Init_File_Type_$( $item.Name )" -Value @() -Force }

ForEach ($Wildcard in $Script:Init_Folder_All_File) {

    ForEach ($item in $Script:Search_File_Order) {

        ForEach ($NewRule in $item.Rule) {

            if ($Wildcard -like "*$( $NewRule.Match_Name )*") {

                Write-host "`n  Fuzzy matching: " -NoNewline; Write-host $NewRule.Match_Name -ForegroundColor Green

                Write-host "  Language pack file: " -NoNewline; Write-host $Wildcard -ForegroundColor Green

                $OSDefaultUser = (Get-Variable -Name "Init_File_Type_$( $item.Name )" -ErrorAction SilentlyContinue).Value

                $TempSave = @{ Match_Name = $NewRule.Match_Name; Capability = $NewRule.Capability; FileName = $Wildcard }

                $new = $OSDefaultUser + $TempSave

                if ($NewRule.IsMatch -eq "Yes") {

                    ForEach ($Component in $Initl_install_Language_Component) {

                        if ($Component -like "*$( $NewRule.Match_Name )*") {

                            Write-host "  Component name: " -NoNewline; Write-host $Component -ForegroundColor Green

                            New-Variable -Name "Init_File_Type_$( $item.Name )" -Value $new -Force

                            $Script:Init_Folder_All_File_Match_Done += $Wildcard

                            break

                        }

                    }

                } else {

                    Write-host "  Do not match, install directly" -ForegroundColor Yellow

                    New-Variable -Name "Init_File_Type_$( $item.Name )" -Value $new -Force

                    $Script:Init_Folder_All_File_Match_Done += $Wildcard

```

```

    }

}

}

}

}

}

Write-host "`n  Grouping is complete, pending installation" -ForegroundColor Yellow

Write-host "  $('-' * 80)"

ForEach ($WildCard in $Script:Search_File_Order) {

    $OSDefaultUser = (Get-Variable -Name "Init_File_Type_{$WildCard.Name}" -ErrorAction SilentlyContinue).Value

    Write-host "`n  $($WildCard.Description) ( $($OSDefaultUser.Count) item )"

    if ($OSDefaultUser.Count -gt 0) {

        ForEach ($item in $OSDefaultUser) {

            Write-host "    $($item.FileName)" -ForegroundColor Green

        }

    } else {

        Write-host "    Not available" -ForegroundColor Red

    }

}

Write-host "`n  Not matched, no longer installed" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

ForEach ($item in $Script:Init_Folder_All_File) {

    if ($Script:Init_Folder_All_File_Match_Done -notcontains $item) {

        $Script:Init_Folder_All_File_Exclude += $item

        Write-host "    $($item)" -ForegroundColor Red

    }

}

Write-host "`n  Install" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

ForEach ($WildCard in $Script:Search_File_Order) {

    $OSDefaultUser = (Get-Variable -Name "Init_File_Type_{$WildCard.Name}" -ErrorAction SilentlyContinue).Value

    Write-host "`n  $($WildCard.Description) ( $($OSDefaultUser.Count) item )"; Write-host "  $('-' * 80)"

    if ($OSDefaultUser.Count -gt 0) {

        ForEach ($item in $OSDefaultUser) {

            Write-host "    Language pack file: " -NoNewline; Write-host $item.FileName -ForegroundColor Green

            Write-Host "    Installing ".PadRight(22) -NoNewline

            if (Test-Path $item.FileName -PathType Leaf) {

```

```

    try{

        Add-WindowsPackage -Path $Mount -PackagePath $item.FileName | Out-Null

        Write-host "Finish`n" -ForegroundColor Green

    } catch {

        Write-host "Failed" -ForegroundColor Red

        Write-host " $($_) " -ForegroundColor Red

    }

} else {

    Write-host "Does not exist`n"

}

}

} else {

    Write-host " Not available`n" -ForegroundColor Red

}

}

}

}

Language_Install -Mount "D:\OS_11_Custom\Install\Install\Mount" -Sources "D:\OS_11_Custom\Install\Install\Language\Add" -
Lang "zh-CN"

```

4.2. Offline image language: change

- Starting Windows 11, the [default System UI Language](#) set by DISM is left unaltered on all editions except for Home edition. For [all commercial editions](#) the language chosen during the Out-of-Box Experience (OOBE) is set as the [System Preferred UI language](#) and Windows will be displayed in this language and for Home edition the language chosen at OOBE will continue to be the default System UI Language.
- As of Windows 10, version 2004, if an .appx-based Language Experience Pack (LXP) backed language is passed as an argument then the language will be set as the System Preferred UI language and its parent language will be set as the Default System UI language. In prior versions only .cab based language packs were supported.

4.2.1. Change default language, regional settings, and other international settings

Region: [zh-CN](#)

```
Dism /Image:"D:\OS_11_Custom\Install\Install\Mount" /Set-AllIntl:zh-CN
```

4.2.2. View available language settings

```
Dism /Image:"D:\OS_11_Custom\Install\Install\Mount" /Get-Intl
```

4.3. Language packs: Removed, optional

- After you add languages, if you want to deploy to a non-English locale, you can save space by removing the English language component. When you remove a language, uninstall the language components in the reverse order in which you added them.

- After adding the Chinese, delete "English - United States" in reverse, the Region tag: en-US, you need to extract the language pack in advance
- Install.Del.Specified.lang.Tag.ps1
 - \Expand\Install\Install.Del.Specified.lang.Tag.ps1
 - https://github.com/likeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Install/Install/Install.Del.Specified.lang.Tag.ps1

- Copy the code

```
$Lang = "en-US"

$Mount = "D:\OS_11_Custom\Install\Install\Mount"

$Sources = "D:\OS_11_Custom\Install\Install\Language\Del\en-US"

$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    $Initl_install_Language_Component += $_.PackageName

}

$Language = @(

    @{ Match = "*WordPad*wow64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }

    @{ Match = "*WordPad*amd64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~amd64~$( $Lang)~.cab"; }

    @{ Match = "*WMIC*FoD*Package*wow64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }

    @{ Match = "*WMIC*FoD*Package*amd64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~AMD64~$( $Lang)~.cab"; }

    @{ Match = "*StepsRecorder*wow64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }

    @{ Match = "*StepsRecorder*amd64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~amd64~$( $Lang)~.cab"; }

    @{ Match = "*Printing*PMCPPC*amd64*"; File = "Microsoft-Windows-Printing-PMCPPC-FoD-
Package~31bf3856ad364e35~AMD64~$( $Lang)~.cab"; }

    @{ Match = "*PowerShell*wow64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }

    @{ Match = "*PowerShell*amd64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~amd64~$( $Lang)~.cab"; }

    @{ Match = "*MediaPlayer*wow64*"; File = "Microsoft-Windows-MediaPlayer-Package-wow64-$( $Lang).cab"; }

    @{ Match = "*MediaPlayer*amd64*"; File = "Microsoft-Windows-MediaPlayer-Package-AMD64-$( $Lang).cab"; }

    @{ Match = "*Notepad*wow64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }

    @{ Match = "*Notepad*amd64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~AMD64~$( $Lang)~.cab"; }
```



```

        @{ Match = "*InternetExplorer*"; File = "Microsoft-Windows-InternetExplorer-Optional-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*TextToSpeech*"; File = "Microsoft-Windows-LanguageFeatures-TextToSpeech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*LanguageFeatures-Speech*"; File = "Microsoft-Windows-LanguageFeatures-Speech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*OCR*"; File = "Microsoft-Windows-LanguageFeatures-OCR-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*Handwriting*"; File = "Microsoft-Windows-LanguageFeatures-Handwriting-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*LanguageFeatures-Basic*"; File = "Microsoft-Windows-LanguageFeatures-Basic-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*Client-LanguagePack-Package*"; File = "Microsoft-Windows-Client-Language-Pack_x64_$(Lang).cab"; }
    )

ForEach ($Rule in $Language) {

    Write-host "`n  Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "*$($Rule.Match)*$(Lang)*") {

            Write-host "  Component name: " -NoNewline

            Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline

            Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

            Write-Host "  Deleting ".PadRight(22) -NoNewline

            try {

                Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" -ErrorAction SilentlyContinue | Out-Null

                Write-host "Finish" -ForegroundColor Green

            } catch {

                Write-host "Failed" -ForegroundColor Red

                Write-host "  $($_) " -ForegroundColor Red

            }

            break

        }

    }

}

$InitlClearLanguagePackage = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    if ($_.PackageName -like "*$(Lang)*") {

```

```

        $InitlClearLanguagePackage += $_.PackageName
    }
}

if ($InitlClearLanguagePackage.count -gt 0) {

    ForEach ($item in $InitlClearLanguagePackage) {

        Write-Host "`n $($item)" -ForegroundColor Green

        Write-Host "  Deleting ".PadRight(22) -NoNewline

        try {

            Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction SilentlyContinue | Out-Null

            Write-host "Finish" -ForegroundColor Green

        } catch {

            Write-host "Failed" -ForegroundColor Red

            Write-host "  $($_) " -ForegroundColor Red

        }

    }

}

```

4.4. Components: All packages installed in the image

4.4.1. View

```
Get-WindowsPackage -Path "D:\OS_11_Custom\Install\Install\Mount" | Out-GridView
```

4.4.2. Export to csv

```

$SaveTo = "D:\OS_11_Custom\Install\Install\Report.$(Get-Date -Format "yyyyMMddHHmmss").csv"

Get-WindowsPackage -Path "D:\OS_11_Custom\Install\Install\Mount" | Export-CSV -NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green

```

5. InBox Apps

5.1. Learn

5.1.1. DISM App Package (.appx or .appxbundle) Servicing Command-Line Options

5.2. InBox Apps: Pre-install the application

- Group abbreviations
 - Group A: [Education](#), [Professional](#), [ProfessionalEducation](#), [ProfessionalWorkstation](#), [Enterprise](#), [IoTEnterprise](#), [ServerRdsh](#)
 - Group B: [EnterpriseN](#), [EnterpriseGN](#), [EnterpriseSN](#), [ProfessionalN](#), [EducationN](#), [ProfessionalWorkstationN](#), [ProfessionalEducationN](#)

- Group C: Core, CoreN, CoreSingleLanguage

	Name	Products ID	Grouping
1.	Microsoft.HEIFImageExtension	9PMMSR1CGPWG	A, C
2.	Microsoft.HEVCVideoExtension	9NMZLZ57R3T7	A, C
3.	Microsoft.VP9VideoExtensions	9N4D0MSMP0PT	A, C
4.	Microsoft.WebpImageExtension	9PG2DK419DRG	A, C
5.	Microsoft.GamingApp	9MV0B5HZVK9Z	A, C
6.	Microsoft.ZuneMusic	9WZDNCRFJ3PT	A, C
7.	MicrosoftCorporationII.MicrosoftFamily	9PDJDS743XF	C
8.	Microsoft.WebMediaExtensions	9N5TDP8VCMHS	A, C
9.	Microsoft.WindowsSoundRecorder	9WZDNCRFHWKN	A, C
10.	Microsoft.Xbox.TCUI	9NKNC0LD5NN6	A, C
11.	Microsoft.XboxGamingOverlay	9NZKPSTSNW4P	A, C
12.	Microsoft.ZuneVideo	9WZDNCRFJ3P2	A, C
13.	Microsoft.RawImageExtension	9NCTDW2W1BH8	A, C
14.	Microsoft.UI.Xaml.2.3		A, B, C
15.	Microsoft.UI.Xaml.2.4		A, B, C
16.	Microsoft.UI.Xaml.2.7		A, B, C
17.	Microsoft.NET.Native.Framework.2.2		A, B, C
18.	Microsoft.NET.Native.Runtime.2.2		A, B, C
19.	Microsoft.VCLibs.140.00		A, B, C
20.	Microsoft.VCLibs.140.00.UWPDesktop		A, B, C
21.	Microsoft.SecHealthUI	9NK0JLZT7JD0	A, B, C
22.	Microsoft.WindowsStore	9WZDNCRFJBMP	A, B, C
23.	Microsoft.Sticky.Notes	9NBLGGH4QGHW	A, B, C
24.	Microsoft.Paint	9PCFS5B6T72H	A, B, C
25.	Microsoft.PowerAutomateDesktop	9NFTCH6J7FHV	A, B, C
26.	Microsoft.ScreenSketch	9MZ95KL8MR0L	A, B, C
27.	Microsoft.WindowsNotepad	9MSMLRH6LZF3	A, B, C
28.	Microsoft.WindowsTerminal	9N0DX20HK701	A, B, C
29.	Clipchamp.Clipchamp	9P1J8S7CCWWT	A, B, C
30.	Microsoft.Solitaire.Collection	9WZDNCRFHWD2	A, B, C
31.	Microsoft.WindowsAlarms	9WZDNCRFJ3PR	A, B, C
32.	Microsoft.WindowsFeedbackHub	9NBLGGH4R32N	A, B, C

33.	Microsoft.WindowsMaps	9WZDNCRDTBVB	A, B, C
34.	Microsoft.BingNews	9WZDNCRFHVFW	A, B, C
35.	Microsoft.DesktopAppInstaller	9NBLGGH4NNS1	A, B, C
36.	Microsoft.WindowsCamera	9WZDNCRFJBBG	A, B, C
37.	Microsoft.Getstarted	9WZDNCRDTBJJ	A, B, C
38.	Microsoft.Cortana	9NFFX4SZZ23L	A, B, C
39.	Microsoft.BingWeather	9WZDNCRFJ3Q2	A, B, C
40.	Microsoft.GetHelp	9PKDZBMV1H3T	A, B, C
41.	Microsoft.MicrosoftOfficeHub	9WZDNCRD29V9	A, B, C
42.	Microsoft.People	9NBLGGH10PG8	A, B, C
43.	Microsoft.StorePurchaseApp	9NBLGGH4LS1F	A, B, C
44.	Microsoft.Todos	9NBLGGH5R558	A, B, C
45.	Microsoft.Windows.Photos	9WZDNCRFJBH4	A, B, C
46.	Microsoft.WindowsCalculator	9WZDNCRFHVN5	A, B, C
47.	Microsoft.Windows.CommunicationsApps	9WZDNCRFHVQM	A, B, C
48.	Microsoft.XboxGameOverlay	9NBLGGH537C2	A, B, C
49.	Microsoft.XboxIdentityProvider	9WZDNCRD1HKW	A, B, C
50.	Microsoft.XboxSpeechToTextOverlay	9P086NHDNB9W	A, B, C
51.	Microsoft.YourPhone	9NMPJ99VJBWV	A, B, C
52.	MicrosoftCorporationII.QuickAssist	9P7BP5VNWKX5	A, B, C
53.	MicrosoftWindows.Client.WebExperience	9MSSGKG348SP	A, B, C

5.3. InBox Apps: Installed

5.3.1. View

```
Get-AppXProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" | Out-GridView
```

5.3.2. Export to Csv

```
$SaveTo = "D:\OS_11_Custom\Install\Install\Report.$(Get-Date -Format "yyyyMMddHHmmss").csv"
```

```
Get-AppXProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" | Export-CSV -NoType -Path $SaveTo
```

```
Write-host $SaveTo -ForegroundColor Green
```

5.4. Remove all installed pre-applications

- Install.InBox.Appx.Clear.all.ps1
 - [\Expand\Install\Install.InBox.Appx.Clear.all.ps1](#)
 - https://github.com/likeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Install/Install.InBox.Appx.Clear

[.all.ps1](#)

- Copy the code

```
Get-AppXProvisionedPackage -path "D:\OS_11_Custom\Install\Install\Mount" -ErrorAction SilentlyContinue | ForEach-Object {  
  
    Write-host "`n $($_.DisplayName)"; Write-Host "  Deleting ".PadRight(22) -NoNewline  
  
    try {  
  
        Remove-AppxProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" -PackageName $_.PackageName -  
ErrorAction SilentlyContinue | Out-Null  
  
        Write-host "Finish" -ForegroundColor Green  
  
    } catch {  
  
        Write-host "Failed" -ForegroundColor Red  
  
    }  
  
}
```

5.5. Region tag: Understanding

Before understanding zone tags, first understand the list of languages available in the ZuneMusic app: [en-us](#), en-gb, as-in, az-latn-az, bs-latn-ba, bn-in, cs-cz, cy-gb, ar-sa, de-de, af-za, am-et, da-dk, el-gr, es-es, es-mx, ca-es, ca-es-valencia, eu-es, fi-fi, bg-bg, ga-ie, et-ee, gl-es, gu-in, gd-gb, fil-ph, fr-ca, fr-fr, hy-am, fa-ir, hu-hu, id-id, it-it, ja-jp, hr-hr, ka-ge, is-is, he-il, hi-in, kk-kz, lo-la, km-kh, lt-lt, kn-in, kok-in, ko-kr, mk-mk, lv-lv, ms-my, mi-nz, mr-in, mt-mt, ne-np, nl-nl, nb-no, ml-in, nn-no, lb-lu, or-in, ro-ro, sk-sk, ru-ru, pl-pl, quz-pe, pt-br, pt-pt, sq-al, ta-in, th-th, sv-se, pa-in, sr-cyrl-ba, sr-cyrl-rs, sr-latn-rs, ur-pk, ug-cn, tr-tr, uk-ua, tt-ru, [zh-cn](#), vi-vn, uz-latn-uz, sl-si, zh-tw, te-in

View installed languages for offline images

```
Dism /Image:"D:\OS_11_Custom\Install\Install\Mount" /Get-Intl
```

View results for installed languages: [en-US](#), [zh-CN](#), When installing the ZuneMusic app, the installer will match "Installed Languages" and automatically filter the list of uninstalled languages, This is the area tag.

5.6. Region tag: adding method

5.6.1. Execute "Language Pack: Add"

5.6.2. Install “Local Language Experience Packages (LXPs)”

Microsoft officially provides the Local Language Experience Package (LXPS) installation file for Windows 10. It will no longer be provided for Windows 11. Want to get:

5.6.2.1. Download using the Windows Local Language Experience Packs (LXPs) Downloader

learn: <https://github.com/ilikeyi/LXPs>

After downloading, save to: [D:\OS_11_Custom\Install\Install\InBox.Appx](#)

File format: [LanguageExperiencePack.zh-CN.Neutral.Appx](#)

5.6.2.2. Manual download

5.6.2.2.1. Region

Region	Products ID	Region	Products ID
en-US	C9PDSCC711RVF	af-za	9PDW16B5HMXR
am-et	9NGL4R61W3PL	ar-sa	9N4S78P86PKX
as-in	9NTJLXMX35J	az-latn-az	9P5TFKZH5K8
be-by	9MXPBGNNNDW3L	bg-bg	9MX54588434F
bn-bd	9PH7TKVXGGM8	bn-in	9P1M44L7W84T
bs-latn-ba	9MVFKLJ10MFL	ca-es	9P6JMKJQZ9S7
ca-es-valencia	9P9K3WMFSW90	chr-cher-us	9MX15485N3RK
cs-cz	9P3WXZ1KTM7C	cy-gb	9NKJ9TBM4HB
da-dk	9NDMT2VKS1L	de-de	9P6CT0SLW589
el-gr	9N586B13PBLD	en-gb	9NT52VQ39BVN
es-es	9NWVGWLHPB1Z	es-mx	9N8MCM1X3928
et-ee	9NFBHFMCR30L	eu-es	9NMCHQHZ37HZ
fa-ir	9NGS7DD4QS21	fi-fi	9MW3PQ7SD3QK
fil-ph	9NWM2KGTDSSS	fr-ca	9MTP2VP0VL92
fr-fr	9NHMG4BJKMDG	ga-ie	9P0L5Q848KXT
gd-gb	9P1DBPF36BF3	gl-es	9NXRNB1JN9B
gu-in	9P2HMSWDJDQ1	ha-latn-ng	9N1L95DBG3G3
he-il	9NB6ZFND5HCQ	hi-in	9NZC3GRX8LD3
hr-hr	9NW01VND4LTW	hu-hu	9MWN3C58HL87
hy-am	9NKM28TM6P67	id-id	9P4X3N4SDK8P
ig-ng	9PG4ZFJ48JSX	is-is	9NTHJR7TQXX1
it-it	9P8PQWNS6VJX	ja-jp	9N1W692FV4S1
ka-ge	9P60JZL05WGH	kk-kz	9PHV179R97LV
km-kh	9PGKTS4JS531	kn-in	9NC6DB7N95F9
kok-in	9MV3P55CMZ6P	ko-kr	9N4TXPCVRNGF
ku-arab-iq	9P1C18QL3D7H	ky-kg	9P7D3JJGZM48
lb-lu	9N0ST1WBZ9D9	lo-la	9N8X352G5NZV
lt-lt	9NWWD891H6HN	lv-lv	9N5CQDPH6SQT
mi-nz	9P2GDFB3JPSX	mk-mk	9P1X6XB1K3RN
ml-in	9NWDTV8FFV7L	mn-mn	9PG1DHC4VTZW
mr-in	9MWXCKHJVR1J	ms-my	9NPXL8ZSDDQ7

mt-mt	9PDG96SQ6BN8	nb-no	9N6J0M5DHCK0
ne-np	9P7CHPLWDQVN	nl-nl	9PF1C9NB5PRV
nn-no	9PK7KM3Z06KH	nso-za	9NS49QLX5CDV
or-in	9NTHCXCXSJDH	pa-arab-pk	9NJRL03WH6FM
pa-in	9NSNC0ZJX69B	pl-pl	9NC5HW94R0LD
prs-af	9P3NGC6X5ZQC	pt-br	9P8LBDM4FW35
pt-pt	9P7X8QJ7FL0X	quc-latn-gt	9P2V6MNNQZ0B
quz-pe	9NHTX8NVQ04K	ro-ro	9MWXGPJ5PJ3H
ru-ru	9NMJCX77QKPX	rw-rw	9NFW0M20H9WG
sd-arab-pk	9NB9JSCXW9X5	si-lk	9NVF9QSLGTL0
sk-sk	9N7LSNN099WB	sl-si	9NV27L34J4ST
sq-al	9MWLRGNMDGK7	sr-cyrl-ba	9MXGN7V65C7B
sr-cyrl-rs	9PPD6CCK9K5H	sr-latn-rs	9NBZ0SJDPPVT
sv-se	9P0HSNX08177	sw-ke	9NFF2M19DQ55
ta-in	9PDZB1WT1B34	te-in	9PMQJJGF63FW
tg-cyrl-tj	9MZHLBPPT2HC	th-th	9MSTWFRL0LR4
ti-et	9NC8C9RDNK2S	tk-tm	9NKHQ4GL6VLT
tn-za	9NFSXM123DHT	tr-tr	9NL1D3T5HG9R
tt-ru	9NV90Q1X1ZR2	ug-cn	9P52C5D7VL5S
uk-ua	9PPPMZRSGHR8	ur-pk	9NDWFTFW12BQ
uz-latn-uz	9P5P2T5P5L9S	vi-vn	9P0W68X0XZPT
wo-sn	9NH3SW1CR90F	xh-za	9NW3QWSLQD17
yo-ng	9NGM3VPPZS5V	zh-cn	9NRMNT6GMZ7
zh-tw	9PCJ4DHCQ1JQ	zu-za	9NNRM7KT5NB0

Download Region: zh-CN, application ID: 9NRMNT6GMZ70, Store link:
<https://www.microsoft.com/store/productId/9NRMNT6GMZ70>

5.6.2.2.2. Open the website: <https://store.rg-adguard.net>

5.6.2.2.2.1. Search keywords:

<https://www.microsoft.com/store/productId/9NRMNT6GMZ70>

5.6.2.2.2.2. Search 22621 content in the web page, search results:
[Microsoft.LanguageExperiencePackzh-CN_22621.*.neutral__8wekyb3d8bbwe.appx](#)

5.6.2.2.2.3. After downloading, save it to the

[D:\OS_11_Custom\Install\Install\InBox.Appx](#) directory and rename it:

5.6.2.3. Execute the installation command to install the local language experience package (LXPs)

After understanding how to add zone tags, obtain [LanguageExperiencePack.zh-cn.Neutral](#), execute the installation command:

```
Add-AppxProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" -PackagePath
"D:\OS_11_Custom\Install\Install\InBox.appx\LanguageExperiencePack.zh-cn.Neutral.appx" -SkipLicense
```

5.6.2.4. InBox Apps: An installed application package

5.6.2.4.1. View

```
Get-AppXProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" | Out-
GridView
```

5.6.2.4.2. Export to Csv

```
$SaveTo = "D:\OS_11_Custom\Install\Install\Report.$(Get-Date -Format
"yyyyMMddHHmmss").csv"

Get-AppXProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" | Export-
CSV -NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green
```

5.7. InBox Apps: Install

5.7.1. Mount or decompress the InBox Apps installation file

Mount [22621.1.220506-1250.ni_release_amd64fre_InboxApps.iso](#) or extract to any location;

5.7.2. After executing the installation command, install InBox Apps to: Install.wim

- [Auto](#) = Automatically search all local disks, default;
- Custom path, e.g. specify F drive: [\\$ISO = "F:\packages"](#)
- Architecture: [x64](#)
- Install.Inst.InBox.Appx.ps1
 - [\Expand\Install\Install.Inst.InBox.Appx.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Install/Install.Inst.InBox.Appx.ps1
- Copy the code

```
$ISO = "Auto"

$Mount = "D:\OS_11_Custom\Install\Install\Mount"

$Arch = "x64"

try{
```



```

Write-host "`n  Offline image version: " -NoNewline

$Current_Edition_Version = (Get-WindowsEdition -Path $Mount).Edition

Write-Host $Current_Edition_Version -ForegroundColor Green

} catch {

Write-Host "Error" -ForegroundColor Red

Write-Host "  $($_) " -ForegroundColor Yellow

return

}

$Pre_Config_Rules = @{

Edition = @(

@{

Name = @( "CloudEdition"; )

Apps = @(

"Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.Services.Store.Engagement"; "Microsoft.VP9VideoExtensions";
"Clipchamp.Clipchamp"; "Microsoft.BingNews"; "Microsoft.BingWeather"; "Microsoft.DesktopAppInstaller";
"Microsoft.GetHelp"; "Microsoft.Getstarted"; "Microsoft.HEIFImageExtension"; "Microsoft.HEVCVideoExtension";
"Microsoft.MicrosoftOfficeHub"; "Microsoft.MicrosoftStickyNotes"; "Microsoft.MinecraftEducationEdition";
"Microsoft.Paint"; "Microsoft.RawImageExtension"; "Microsoft.ScreenSketch"; "Microsoft.SecHealthUI";
"Microsoft.StorePurchaseApp"; "Microsoft.Todos"; "Microsoft.WebMediaExtensions";
"Microsoft.WebpImageExtension"; "Microsoft.Whiteboard"; "Microsoft.Windows.Photos"; "Microsoft.WindowsAlarms";
"Microsoft.WindowsCalculator"; "Microsoft.WindowsCamera"; "Microsoft.WindowsFeedbackHub";
"Microsoft.WindowsMaps"; "Microsoft.WindowsNotepad"; "Microsoft.WindowsSoundRecorder";
"Microsoft.Xbox.TCUI"; "Microsoft.XboxIdentityProvider"; "Microsoft.XboxSpeechToTextOverlay";
"Microsoft.ZuneMusic"; "Microsoft.ZuneVideo"; "MicrosoftCorporationII.QuickAssist";

)

}

@{

Name = @( "CloudEditionN"; )

Apps = @(

"Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.Services.Store.Engagement";
"Microsoft.XboxSpeechToTextOverlay"; "Clipchamp.Clipchamp"; "Microsoft.BingNews"; "Microsoft.BingWeather";
"Microsoft.DesktopAppInstaller"; "Microsoft.GetHelp"; "Microsoft.Getstarted"; "Microsoft.MicrosoftOfficeHub";
"Microsoft.MicrosoftStickyNotes"; "Microsoft.MinecraftEducationEdition"; "Microsoft.Paint"; "Microsoft.ScreenSketch";
"Microsoft.SecHealthUI"; "Microsoft.StorePurchaseApp"; "Microsoft.Whiteboard"; "Microsoft.Windows.Photos";
"Microsoft.WindowsAlarms"; "Microsoft.WindowsCalculator"; "Microsoft.WindowsCamera";
"Microsoft.WindowsFeedbackHub"; "Microsoft.WindowsMaps"; "Microsoft.WindowsNotepad";
"Microsoft.XboxIdentityProvider"; "MicrosoftCorporationII.QuickAssist";

)

}

```

```

@{

    Name = @(

        "Core"; "CoreN"; "CoreSingleLanguage";

    )

    Apps = @(

        "Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.HEIFImageExtension"; "Microsoft.HEVCVideoExtension";
"Microsoft.SecHealthUI"; "Microsoft.VP9VideoExtensions"; "Microsoft.WebpImageExtension";
"Microsoft.WindowsStore"; "Microsoft.GamingApp"; "Microsoft.MicrosoftStickyNotes"; "Microsoft.Paint";
"Microsoft.PowerAutomateDesktop"; "Microsoft.ScreenSketch"; "Microsoft.WindowsNotepad";
"Microsoft.WindowsTerminal"; "Clipchamp.Clipchamp"; "Microsoft.MicrosoftSolitaireCollection";
"Microsoft.WindowsAlarms"; "Microsoft.WindowsFeedbackHub"; "Microsoft.WindowsMaps"; "Microsoft.ZuneMusic";
"Microsoft.BingNews"; "Microsoft.BingWeather"; "Microsoft.DesktopAppInstaller"; "Microsoft.WindowsCamera";
"Microsoft.Getstarted"; "Microsoft.Cortana"; "Microsoft.GetHelp"; "Microsoft.MicrosoftOfficeHub"; "Microsoft.People";
"Microsoft.StorePurchaseApp"; "Microsoft.Todos"; "Microsoft.WebMediaExtensions"; "Microsoft.Windows.Photos";
"Microsoft.WindowsCalculator"; "Microsoft.windowscommunicationsapps"; "Microsoft.WindowsSoundRecorder";
"Microsoft.Xbox.TCUI"; "Microsoft.XboxGameOverlay"; "Microsoft.XboxGamingOverlay";
"Microsoft.XboxIdentityProvider"; "Microsoft.XboxSpeechToTextOverlay"; "Microsoft.YourPhone";
"Microsoft.ZuneVideo"; "MicrosoftCorporationII.QuickAssist"; "MicrosoftWindows.Client.WebExperience";
"Microsoft.RawImageExtension"; "MicrosoftCorporationII.MicrosoftFamily";

    )

}

@{

    Name = @(

        "Education"; "Professional"; "ProfessionalEducation"; "ProfessionalWorkstation"; "Enterprise"; "IoTEnterprise";
"ServerRdsh";

    )

    Apps = @(

        "Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.HEIFImageExtension"; "Microsoft.HEVCVideoExtension";
"Microsoft.SecHealthUI"; "Microsoft.VP9VideoExtensions"; "Microsoft.WebpImageExtension";
"Microsoft.WindowsStore"; "Microsoft.GamingApp"; "Microsoft.MicrosoftStickyNotes"; "Microsoft.Paint";
"Microsoft.PowerAutomateDesktop"; "Microsoft.ScreenSketch"; "Microsoft.WindowsNotepad";
"Microsoft.WindowsTerminal"; "Clipchamp.Clipchamp"; "Microsoft.MicrosoftSolitaireCollection";
"Microsoft.WindowsAlarms"; "Microsoft.WindowsFeedbackHub"; "Microsoft.WindowsMaps"; "Microsoft.ZuneMusic";
"Microsoft.BingNews"; "Microsoft.BingWeather"; "Microsoft.DesktopAppInstaller"; "Microsoft.WindowsCamera";
"Microsoft.Getstarted"; "Microsoft.Cortana"; "Microsoft.GetHelp"; "Microsoft.MicrosoftOfficeHub"; "Microsoft.People";
"Microsoft.StorePurchaseApp"; "Microsoft.Todos"; "Microsoft.WebMediaExtensions"; "Microsoft.Windows.Photos";
"Microsoft.WindowsCalculator"; "Microsoft.windowscommunicationsapps"; "Microsoft.WindowsSoundRecorder";
"Microsoft.Xbox.TCUI"; "Microsoft.XboxGameOverlay"; "Microsoft.XboxGamingOverlay";
"Microsoft.XboxIdentityProvider"; "Microsoft.XboxSpeechToTextOverlay"; "Microsoft.YourPhone";
"Microsoft.ZuneVideo"; "MicrosoftCorporationII.QuickAssist"; "MicrosoftWindows.Client.WebExperience";
"Microsoft.RawImageExtension";

    )

}

```

```

@{
    Name = @(
        "EnterpriseN"; "EnterpriseGN"; "EnterpriseSN"; "ProfessionalN"; "EducationN"; "ProfessionalWorkstationN";
        "ProfessionalEducationN"; "CloudN"; "CloudEN"; "CloudEditionLN"; "StarterN";

    )

    Apps = @(
        "Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
        "Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
        "Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.SecHealthUI"; "Microsoft.WindowsStore";
        "Microsoft.MicrosoftStickyNotes"; "Microsoft.Paint"; "Microsoft.PowerAutomateDesktop"; "Microsoft.ScreenSketch";
        "Microsoft.WindowsNotepad"; "Microsoft.WindowsTerminal"; "Clipchamp.Clipchamp";
        "Microsoft.MicrosoftSolitaireCollection"; "Microsoft.WindowsAlarms"; "Microsoft.WindowsFeedbackHub";
        "Microsoft.WindowsMaps"; "Microsoft.BingNews"; "Microsoft.BingWeather"; "Microsoft.DesktopAppInstaller";
        "Microsoft.WindowsCamera"; "Microsoft.Getstarted"; "Microsoft.Cortana"; "Microsoft.GetHelp";
        "Microsoft.MicrosoftOfficeHub"; "Microsoft.People"; "Microsoft.StorePurchaseApp"; "Microsoft.Todos";
        "Microsoft.Windows.Photos"; "Microsoft.WindowsCalculator"; "Microsoft.windowscommunicationsapps";
        "Microsoft.XboxGameOverlay"; "Microsoft.XboxIdentityProvider"; "Microsoft.XboxSpeechToTextOverlay";
        "Microsoft.YourPhone"; "MicrosoftCorporationII.QuickAssist"; "MicrosoftWindows.Client.WebExperience";

    )

}

)

Rule = @(

    @{ Name="Microsoft.UI.Xaml.2.3"; Match="UI.Xaml*{ARCHTag}*2.3";License="UI.Xaml*{ARCHTag}*2.3";
    Dependencies=@(); }

    @{ Name="Microsoft.UI.Xaml.2.4"; Match="UI.Xaml*{ARCHTag}*2.4";License="UI.Xaml*{ARCHTag}*2.4";
    Dependencies=@(); }

    @{ Name="Microsoft.UI.Xaml.2.7"; Match="UI.Xaml*{ARCHTag}*2.7";License="UI.Xaml*{ARCHTag}*2.7";
    Dependencies=@(); }

    @{ Name="Microsoft.NET.Native.Framework.2.2";
    Match="Native.Framework*{ARCHTag}*2.2";License="Native.Framework*{ARCHTag}*2.2"; Dependencies=@(); }

    @{ Name="Microsoft.NET.Native.Runtime.2.2";
    Match="Native.Runtime*{ARCHTag}*2.2";License="Native.Runtime*{ARCHTag}*2.2"; Dependencies=@(); }

    @{ Name="Microsoft.VCLibs.140.00"; Match="VCLibs*{ARCHTag}";License="VCLibs*{ARCHTag}";
    Dependencies=@(); }

    @{ Name="Microsoft.VCLibs.140.00.UWPDesktop";
    Match="VCLibs*{ARCHTag}*Desktop";License="VCLibs*{ARCHTag}*Desktop"; Dependencies=@(); }

    @{ Name="Microsoft.HEIFImageExtension"; Match="HEIFImageExtension";License="HEIFImageExtension*";
    Dependencies=@("Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.HEVCVideoExtension";
    Match="HEVCVideoExtension*{ARCHC}";License="HEVCVideoExtension*{ARCHC}*xml";
    Dependencies=@("Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.SecHealthUI"; Match="SecHealthUI*{ARCHC}";License="SecHealthUI*{ARCHC}";
    Dependencies=@("Microsoft.UI.Xaml.2.4","Microsoft.VCLibs.140.00"); }

```

```

    @{ Name="Microsoft.VP9VideoExtensions";
Match="VP9VideoExtensions*{ARCHC}";License="VP9VideoExtensions*{ARCHC}";
Dependencies=@("Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.WebpImageExtension";
Match="WebpImageExtension*{ARCHC}";License="WebpImageExtension*{ARCHC}";
Dependencies=@("Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.WindowsStore"; Match="WindowsStore";License="WindowsStore";
Dependencies=@("Microsoft.UI.Xaml.2.3","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2"
,"Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.GamingApp"; Match="GamingApp";License="GamingApp";
Dependencies=@("Microsoft.UI.Xaml.2.3","Microsoft.VCLibs.140.00","Microsoft.VCLibs.140.00.UWPDesktop"); }

    @{ Name="Microsoft.MicrosoftStickyNotes"; Match="Microsoft.Sticky.Notes";License="MicrosoftStickyNotes";
Dependencies=@("Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2","Microsoft.VCLibs.140.
00"); }

    @{ Name="Microsoft.Paint"; Match="Paint";License="Paint";
Dependencies=@("Microsoft.VCLibs.140.00","Microsoft.VCLibs.140.00.UWPDesktop","Microsoft.UI.Xaml.2.7"); }

    @{ Name="Microsoft.PowerAutomateDesktop";
Match="PowerAutomateDesktop";License="PowerAutomateDesktop";
Dependencies=@("Microsoft.VCLibs.140.00.UWPDesktop"); }

    @{ Name="Microsoft.ScreenSketch"; Match="ScreenSketch";License="ScreenSketch";
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.WindowsNotepad"; Match="WindowsNotepad";License="WindowsNotepad";
Dependencies=@("Microsoft.VCLibs.140.00","Microsoft.VCLibs.140.00.UWPDesktop","Microsoft.UI.Xaml.2.7"); }

    @{ Name="Microsoft.WindowsTerminal"; Match="WindowsTerminal";License="WindowsTerminal";
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.VCLibs.140.00.UWPDesktop"); }

    @{ Name="Clipchamp.Clipchamp"; Match="Clipchamp.Clipchamp";License="Clipchamp.Clipchamp";
Dependencies=@(); }

    @{ Name="Microsoft.MicrosoftSolitaireCollection";
Match="MicrosoftSolitaireCollection";License="MicrosoftSolitaireCollection";
Dependencies=@("Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2","Microsoft.VCLibs.140.
00"); }

    @{ Name="Microsoft.WindowsAlarms"; Match="WindowsAlarms";License="WindowsAlarms";
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2"
,"Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.WindowsFeedbackHub"; Match="WindowsFeedbackHub";License="WindowsFeedbackHub";
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2"
,"Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.WindowsMaps"; Match="WindowsMaps";License="WindowsMaps";
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2"
,"Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.ZuneMusic"; Match="ZuneMusic";License="ZuneMusic";
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.VCLibs.140.00"); }

    @{ Name="MicrosoftCorporationII.MicrosoftFamily"; Match="MicrosoftFamily";License="MicrosoftFamily";
Dependencies=@(); }

    @{ Name="Microsoft.BingNews"; Match="BingNews";License="BingNews";

```

```
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2",  
,"Microsoft.VCLibs.140.00"); }
```

```
@{ Name="Microsoft.BingWeather"; Match="BingWeather";License="BingWeather";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2",  
,"Microsoft.VCLibs.140.00"); }
```

```
@{ Name="Microsoft.DesktopAppInstaller"; Match="DesktopAppInstaller";License="DesktopAppInstaller";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.VCLibs.140.00.UWPDesktop"); }
```

```
@{ Name="Microsoft.WindowsCamera"; Match="WindowsCamera";License="WindowsCamera";  
Dependencies=@("Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2","Microsoft.VCLibs.140.  
00"); }
```

```
@{ Name="Microsoft.Getstarted"; Match="Getstarted";License="Getstarted";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2",  
,"Microsoft.VCLibs.140.00"); }
```

```
@{ Name="Microsoft.Cortana"; Match="Cortana";License="Cortana";  
Dependencies=@("Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2","Microsoft.VCLibs.140.  
00","Microsoft.VCLibs.140.00.UWPDesktop"); }
```

```
@{ Name="Microsoft.GetHelp"; Match="GetHelp";License="GetHelp";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2",  
,"Microsoft.VCLibs.140.00"); }
```

```
@{ Name="Microsoft.MicrosoftOfficeHub"; Match="MicrosoftOfficeHub";License="MicrosoftOfficeHub";  
Dependencies=@("Microsoft.VCLibs.140.00","Microsoft.VCLibs.140.00.UWPDesktop"); }
```

```
@{ Name="Microsoft.People"; Match="People";License="People";  
Dependencies=@("Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2","Microsoft.VCLibs.140.  
00"); }
```

```
@{ Name="Microsoft.StorePurchaseApp"; Match="StorePurchaseApp";License="StorePurchaseApp";  
Dependencies=@("Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2","Microsoft.VCLibs.140.  
00"); }
```

```
@{ Name="Microsoft.Todos"; Match="Todos";License="Todos";  
Dependencies=@("Microsoft.UI.Xaml.2.4","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2",  
,"Microsoft.VCLibs.140.00"); }
```

```
@{ Name="Microsoft.WebMediaExtensions"; Match="WebMediaExtensions";License="WebMediaExtensions";  
Dependencies=@("Microsoft.VCLibs.140.00"); }
```

```
@{ Name="Microsoft.Windows.Photos"; Match="Windows.Photos";License="Windows.Photos";  
Dependencies=@("Microsoft.UI.Xaml.2.4","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2",  
,"Microsoft.VCLibs.140.00"); }
```

```
@{ Name="Microsoft.WindowsCalculator"; Match="WindowsCalculator";License="WindowsCalculator";  
Dependencies=@("Microsoft.UI.Xaml.2.4","Microsoft.VCLibs.140.00"); }
```

```
@{ Name="Microsoft.windowscommunicationsapps";  
Match="WindowsCommunicationsApps";License="WindowsCommunicationsApps";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.VCLibs.140.00"); }
```

```
@{ Name="Microsoft.WindowsSoundRecorder";  
Match="WindowsSoundRecorder";License="WindowsSoundRecorder";  
Dependencies=@("Microsoft.UI.Xaml.2.3","Microsoft.VCLibs.140.00"); }
```

```
@{ Name="Microsoft.Xbox.TCUI"; Match="Xbox.TCUI";License="Xbox.TCUI";  
Dependencies=@("Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2","Microsoft.VCLibs.140.  
00"); }
```

```

        @{ Name="Microsoft.XboxGameOverlay"; Match="XboxGameOverlay";License="XboxGameOverlay";
Dependencies=@("Microsoft.VCLibs.140.00"); }

        @{ Name="Microsoft.XboxGamingOverlay"; Match="XboxGamingOverlay";License="XboxGamingOverlay";
Dependencies=@("Microsoft.VCLibs.140.00"); }

        @{ Name="Microsoft.XboxIdentityProvider"; Match="XboxIdentityProvider";License="XboxIdentityProvider";
Dependencies=@("Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2","Microsoft.VCLibs.140.
00"); }

        @{ Name="Microsoft.XboxSpeechToTextOverlay";
Match="XboxSpeechToTextOverlay";License="XboxSpeechToTextOverlay";
Dependencies=@("Microsoft.VCLibs.140.00"); }

        @{ Name="Microsoft.YourPhone"; Match="YourPhone";License="YourPhone";
Dependencies=@("Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2","Microsoft.VCLibs.140.
00","Microsoft.VCLibs.140.00.UWPDesktop"); }

        @{ Name="Microsoft.ZuneVideo"; Match="ZuneVideo";License="ZuneVideo";
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.VCLibs.140.00"); }

        @{ Name="MicrosoftCorporationII.QuickAssist"; Match="QuickAssist";License="QuickAssist";
Dependencies=@(); }

        @{ Name="MicrosoftWindows.Client.WebExperience"; Match="WebExperience";License="WebExperience";
Dependencies=@("Microsoft.VCLibs.140.00"); }

        @{ Name="Microsoft.MinecraftEducationEdition";
Match="MinecraftEducationEdition";License="MinecraftEducationEdition";
Dependencies=@("Microsoft.VCLibs.140.00.UWPDesktop"); }

        @{ Name="Microsoft.Whiteboard"; Match="Whiteboard";License="Whiteboard";
Dependencies=@("Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2","Microsoft.VCLibs.140.
00"); }

        @{ Name="Microsoft.RawImageExtension"; Match="RawImageExtension"; License="RawImageExtension";
Dependencies=@(); }

    )

}

$Allow_Install_App = @()

ForEach ($item in $Pre_Config_Rules.Edition) {

    if ($item.Name -contains $Current_Edition_Version) {

        Write-host "`n  Match to: "-NoNewline; Write-host $Current_Edition_Version -ForegroundColor Green

        $Allow_Install_App = $item.Apps

        break

    }

}

Write-host "`n  The app to install ( $($Allow_Install_App.Count) item )" -ForegroundColor Yellow

Write-host "  $('-' * 80)"

ForEach ($item in $Allow_Install_App) {

    Write-host "  $($item)" -ForegroundColor Green

```

```

}

Function Match_InBox_Apps_Install_Pack

{

    param ( $NewPath )

    $NewArch = $Arch

    $NewArchC = $Arch.Replace("AMD64", "x64")

    $NewArchCTag = $Arch.Replace("AMD64", "x64")

    if ($Arch -eq "arm64") { $NewArchCTag = "arm" }

    if ($Pre_Config_Rules.Rule.Count -gt 0) {

        ForEach ($itemInBoxApps in $Pre_Config_Rules.Rule){

            $InstallPacker = ""

            $InstallPackerCert = ""

            $SearchNewStructure = $itemInBoxApps.Match.Replace("{ARCH}", $NewArch).Replace("{ARCHC}",
$NewArchC).Replace("{ARCHTag}", $NewArchCTag)

            $SearchNewLicense = $itemInBoxApps.License.Replace("{ARCH}", $NewArch).Replace("{ARCHC}",
$NewArchC).Replace("{ARCHTag}", $NewArchCTag)

            Get-ChildItem -Path $NewPath -Filter "*${$SearchNewStructure}*" -Include "*.appx", "*.appxbundle",
"*.msixbundle" -Recurse -Force -ErrorAction SilentlyContinue | ForEach-Object {

                if (Test-Path -Path $_.FullName -PathType Leaf) {

                    $InstallPacker = $_.FullName

                    Get-ChildItem -Path $NewPath -Filter "*${$SearchNewLicense}*" -Include *.xml -Recurse -Force -ErrorAction
SilentlyContinue | ForEach-Object {

                        $InstallPackerCert = $_.FullName

                    }

                }

                $Script:InBoxAppx += @{

                    Name      = $itemInBoxApps.Name;

                    Depend    = $itemInBoxApps.Dependencies;

                    Search    = $SearchNewStructure;

                    InstallPacker = $InstallPacker;

                    Certificate = $InstallPackerCert

                    CertificateRule = $SearchNewLicense

                }

                return

            }

        }

    }

}

```

```

    }

}

Write-host "`n  Inbox Apps: Installation packages, automatic search for full disk or specified paths" -ForegroundColor
Yellow

Write-host "  $('-' * 80)"

$Script:InBoxAppx = @()

if ($ISO -eq "Auto"){

    Get-PSDrive -PSProvider FileSystem -ErrorAction SilentlyContinue | ForEach-Object {

        $AppPath = Join-Path -Path $_.Root -ChildPath "packages" -ErrorAction SilentlyContinue

        Match_InBox_Apps_Install_Pack -NewPath $AppPath

    }

} else {

    Match_InBox_Apps_Install_Pack -NewPath $ISO

}

Write-host "  Search Complete" -ForegroundColor Green

Write-host "`n  Inbox Apps: Installer Match Results" -ForegroundColor Yellow

Write-host "  $('-' * 80)"

if ($Script:InBoxAppx.Count -gt 0) {

    Write-host "  Match successful" -ForegroundColor Green

} else {

    Write-host "  Failed match" -ForegroundColor Red

    return

}

Write-host "`n  Inbox Apps: Details of the application to be installed ( $($Script:InBoxAppx.Count) item )" -
ForegroundColor Yellow

Write-host "  $('-' * 80)"

ForEach ($Rule in $Script:InBoxAppx) {

    Write-host "  Apps name: " -NoNewline; Write-host $Rule.Name -ForegroundColor Yellow

    Write-host "  Apps installer: " -NoNewline; Write-host $Rule.InstallPacker -ForegroundColor Yellow

    Write-host "  License: " -NoNewline; Write-host $Rule.Certificate -ForegroundColor Yellow

    Write-host ""

}

Write-host "`n  Inbox Apps: Installation" -ForegroundColor Yellow

Write-host "  $('-' * 80)"

ForEach ($Rule in $Script:InBoxAppx) {

```



```

Write-host "  Name: " -NoNewline; Write-host $Rule.Name -ForegroundColor Yellow

Write-host "  $('-' * 80)"

if($Allow_Install_App -contains $Rule.Name) {

    Write-host "  Search for apps: " -NoNewline; Write-host $Rule.InstallPacker -ForegroundColor Yellow

    Write-host "  Search for License: " -NoNewline; Write-host $Rule.Certificate -ForegroundColor Yellow

    if (Test-Path -Path $Rule.InstallPacker -PathType Leaf) {

        if (Test-Path -Path $Rule.Certificate -PathType Leaf) {

            Write-host "    License: " -NoNewline

            Write-host $Rule.Certificate -ForegroundColor Yellow

            Write-host "    With License".PadRight(22) -NoNewline -ForegroundColor Green

            Write-host "    Installing".PadRight(22) -NoNewline

            try {

                Add-AppxProvisionedPackage -Path $Mount -PackagePath $Rule.InstallPacker -LicensePath $Rule.Certificate
-ErrorAction SilentlyContinue | Out-Null

                Write-Host "Done`n" -ForegroundColor Green

            } catch {

                Write-Host "Failed" -ForegroundColor Red

                Write-Host "  $($_)`n" -ForegroundColor Red

            }

        } else {

            Write-host "    No License".PadRight(22) -NoNewline -ForegroundColor Red

            Write-host "    Installing".PadRight(22) -NoNewline

            try {

                Add-AppxProvisionedPackage -Path $Mount -PackagePath $Rule.InstallPacker -SkipLicense -ErrorAction
SilentlyContinue | Out-Null

                Write-Host "Done`n" -ForegroundColor Green

            } catch {

                Write-Host "Failed" -ForegroundColor Red

                Write-Host "  $($_)`n" -ForegroundColor Red

            }

        }

    } else {

        Write-host "    The installation package does not exist" -ForegroundColor Red

    }

} else {

```

```

        Write-host " Skip the installation`n" -ForegroundColor Red
    }
}

```

5.8. Region tag: delete

- After completing the installation of the InBox Apps application, the Region tag is no longer important and can be deleted or not deleted. Delete "Local Language Experience Package (LXPs), Simplified Chinese - China)" and uniquely identify the Region tag: **zh-CN**, can be changed to other Region tag.

- Install.Clear.Flag.ps1

- [\Expand\Install\Install.Clear.Flag.ps1](#)

- https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Install/Install.Clear.Flag.ps1

- Copy the code

```

$Lang = "zh-CN"

Get-AppXProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" | Foreach-object {

    if ($_.DisplayName -Like "*LanguageExperiencePack*${$Lang}*") {

        Write-host " ${$_DisplayName}"; Write-Host " Deleting ".PadRight(22) -NoNewline

        try{

            Remove-AppxProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" -PackageName $_.PackageName -
            ErrorAction SilentlyContinue | Out-Null

            Write-host "Finish" -ForegroundColor Green

        } catch {

            Write-host "Failed" -ForegroundColor Red

        }

    }

}

```

5.9. InBox Apps: optimization

After the app is installed, provisioning the Appx package should be optimized to reduce the app's disk usage by replacing identical files with hard links, only for offline images.

```

Dism /Image:"D:\OS_11_Custom\Install\Install\Mount" /Optimize-ProvisionedAppxPackages

```

6. Cumulative updates

- When upgrading different versions or old versions to the latest version, you need to add the "Function Enablement Package" first before adding the latest cumulative update;
- After adding a language pack, you can install the same cumulative update as the initial version to resolve a known issue where the "Components: All packages installed in the image" status is not refreshed after installation;

- To stay up to date, it is recommended that you download the latest version.

6.1. Initial version

6.1.1. How to download

Cumulative update [KB5016632](#) is no longer searchable from <https://www.catalog.update.microsoft.com/Search.aspx?q=KB5016632>.

6.1.1.1. Select any website and open:

6.1.1.1.1. <https://uupdump.net>

6.1.1.1.2. <https://uup.ee>

6.1.1.1.3. <https://osdump.com>

6.1.1.2. After opening, search for keywords: [22621.382](#), select from the search results: [Windows 11, version 22H2 \(22621.382\) amd64](#) and [Windows 11, version 22H2 \(22621.382\) arm64](#)

6.1.1.3. After opening, select "[All files](#)";

6.1.1.4. Search for: [KB5016632](#) in the "All Files" page, download:

- [Windows11.0-KB5016632-x64.cab](#)
- [Windows11.0-KB5016632-x64.psf](#)

6.1.1.5. Cumulative updates: Merging

6.1.1.5.1. Go to <https://github.com/abbodi1406/WHd/tree/master/scripts> After downloading [PSFX_Repack_6.zip](#)

6.1.1.5.2. After downloading, unzip it to: [D:\PSFX_Repack_6](#)

6.1.1.5.3. Copy [Windows11.0-KB5016632-x64.cab](#), [Windows11.0-KB5016632-x64.psf](#) to: [D:\PSFX_Repack_6](#)

6.1.1.5.4. After running: [psfx2cab_GUI.cmd](#), you will get a new file:

[Windows11.0-KB5016632-x64-full_psf.cab](#)

6.1.1.5.5. Save [Windows11.0-KB5016632-x64-full_psf.cab](#) to:

[D:\OS_11_Custom\Install\Install\Update\Windows11.0-KB5016632-x64-full_psf.cab](#)

6.1.2. Add

```
$KBPath = "D:\OS_11_Custom\Install\Install\Update\Windows11.0-KB5016632-x64-full_psf.cab"
```

```
Add-WindowsPackage -Path "D:\OS_11_Custom\Install\Install\Mount" -PackagePath $KBPath
```

6.2. Other Version

Check "[Windows 11 version information](#)", for example, download cumulative update: [KB5032288](#), version number: 22631.2792, go to the download page: <https://www.catalog.update.microsoft.com/Search.aspx?q=KB5032288>, download and save to:

[D:\OS_11_Custom\Install\Install\Update](#), or download through direct connection, select download according to the architecture:

6.2.1. x64, default

- Direct download

https://catalog.sf.dl.delivery.mp.microsoft.com/filestreamingservice/files/d44c2ec3-2179-4305-9f27-fe303f81a9b6/public/windows11.0-kb5032288-x64_04212175664d85ed0f439f8f1f883e9f383b84cf.msu

- Add to

```
$KBPath = "D:\OS_11_Custom\Install\Install\Update\windows11.0-kb5032288-x64_04212175664d85ed0f439f8f1f883e9f383b84cf.msu"
```

```
Add-WindowsPackage -Path "D:\OS_11_Custom\Install\Install\Mount" -PackagePath $KBPath
```

6.2.2. Arm64

- Direct download

https://catalog.sf.dl.delivery.mp.microsoft.com/filestreamingservice/files/896c22e8-0e75-46b9-88aa-e2964a650705/public/windows11.0-kb5032288-arm64_384c85d652f32362fbee964d349fa220288d7140.msu

- Add to

```
$KBPath = "D:\OS_11_Custom\Install\Install\Update\windows11.0-kb5032288-arm64_384c85d652f32362fbee964d349fa220288d7140.msu"
```

```
Add-WindowsPackage -Path "D:\OS_11_Custom\Install\Install\Mount" -PackagePath $KBPath
```

6.3. Solidify Updated, optional

It cannot be uninstalled after curing, which cleans the recovery image and resets the basis of any superseded components.

```
Dism /Image:"D:\OS_11_Custom\Install\Install\Mount" /cleanup-image /StartComponentCleanup /ResetBase
```

6.3.1. Clean components after curing and updating, optional

```
$Mount = "D:\OS_11_Custom\Install\Install\Mount"
```

```
Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {
```

```
    if ($_.PackageState -eq "Superseded") {
```

```
        Write-Host "  $($_.PackageName)" -ForegroundColor Green
```

```
        Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null
```

```
    }
```

```
}
```

7. Drive, optional

8. Add deployment engine, optional

- Learn "Deployment Engine", if added to ISO installation media, can skip adding to mounted.
- After adding the deployment engine, continue at the current location.

9. Health

Before saving, check whether it is damaged. If the health status is abnormal, stop saving.

```
Repair-WindowsImage -Path "D:\OS_11_Custom\Install\Install\Mount" -ScanHealth
```

10. Replace WinRE.wim

WinRE.wim in all index numbers in Install.wim has been replaced in batches. Please skip this step.

```
$WinRE = "D:\OS_11_Custom\Install\Install\Update\Winlib\WinRE.wim"
```

```
$CopyTo = "D:\OS_11_Custom\Install\Install\Mount\Windows\System32\Recovery"
```

```
Copy-Item -Path $WinRE -Destination $CopyTo -Force
```

11. Save image: Install.wim

```
Save-WindowsImage -Path "D:\OS_11_Custom\Install\Install\Mount"
```

12. Unmount image: Install.wim

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowsImage -Path "D:\OS_11_Custom\Install\Install\Mount" -Discard
```

LOOP OPERATING AREA, END.

13. Rebuilding Install.wim reduces file size

- Install.Rebuild.wim.ps1
 - [\Expand\Install\Install.Rebuild.wim.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Install/Install.Rebuild.wim.ps1

- Copy the code

```
$InstallWim = "D:\OS_11\sources\install.wim"
```

```
Get-WindowsImage -ImagePath $InstallWim -ErrorAction SilentlyContinue | ForEach-Object {
```

```
    Write-Host "  Image name: " -NoNewline; Write-Host $_.ImageName -ForegroundColor Yellow
```

```
    Write-Host "  The index number: " -NoNewline; Write-Host $_.ImageIndex -ForegroundColor Yellow
```

```
    Write-Host "`n    Under reconstruction".PadRight(28) -NoNewline
```

```
    Export-WindowsImage -SourceImagePath $InstallWim -SourceIndex $_.ImageIndex -DestinationImagePath "$($InstallWim).New" -  
    CompressionType max | Out-Null
```

```
    Write-Host "Finish`n" -ForegroundColor Green
```

```
}
```

```
if (Test-Path "$($InstallWim).New" -PathType Leaf) {
```

```
    Remove-Item -Path $InstallWim
```

```

Move-Item -Path "$($InstallWim).New" -Destination $InstallWim

Write-Host "Finish" -ForegroundColor Green

} else {

    Write-host "Failed" -ForegroundColor Red

}

```

14. How to batch replace WinRE.wim in all index numbers in Install.wim

14.1. Obtain WimLib

After going to the official website of <https://wimlib.net>, select a different version: [arm64](#), [x64](#), [x86](#), and extract it to: [D:Wimlib](#) after downloading

14.2. How to extract and update WinRE.wim in Install.wim

14.2.1. Extract the WinRE.wim file Install.wim from Install.wim

- Install.WinRE.Extract.ps1
 - [\Expand\Install\Install.WinRE.Extract.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Install/Install.WinRE.Extract.ps1

- Copy the code

```

$Arguments = @(

    "extract",

    "D:\OS_11\sources\install.wim", "1",

    "\Windows\System32\Recovery\Winre.wim",

    "--dest-dir=""D:\OS_11_Custom\Install\Install\Update\Winlib""

)

New-Item -Path "D:\OS_11_Custom\Install\Install\Update\Winlib" -ItemType Directory -ea SilentlyContinue

Start-Process -FilePath "d:\wimlib\wimlib-imagex.exe" -ArgumentList $Arguments -wait -nonewwindow

```

14.2.2. Get all index numbers of Install.wim and replace the old WinRE.wim

- Install.WinRE.Replace.wim.ps1
 - [\Expand\Install\Install.WinRE.Replace.wim.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Install/Install.WinRE.Replace.wim.ps1

- Copy the code

```

Get-WindowsImage -ImagePath "D:\OS_11\sources\install.wim" -ErrorAction SilentlyContinue | ForEach-Object {

    Write-Host "  Image name: " -NoNewline; Write-Host $_.ImageName -ForegroundColor Yellow
}

```

```

Write-Host " The index number: " -NoNewLine; Write-Host $_.ImageIndex -ForegroundColor Yellow

Write-Host "`n Replacement "

$Arguments = @(

    "update",

    "D:\OS_11\sources\install.wim", $_.ImageIndex,

    "--command=""add 'D:\OS_11_Custom\Install\Install\Update\Winlib\WinRE.wim'
'Windows\System32\Recovery\WinRe.wim'""""

)

Start-Process -FilePath "d:\wimlib\wimlib-imagex.exe" -ArgumentList $Arguments -wait -nonewwindow

Write-Host " Finish`n" -ForegroundColor Green

}

```

III Custom deployment image boot.wim

1. View Boot.wim details

Image name, image description, image size, architecture, version, index number, etc.

```
$ViewFile = "D:\OS_11\Sources\Boot.wim"
```

```
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex }
```

2. Specify the path to mount Boot.wim

```
New-Item -Path "D:\OS_11_Custom\Boot\Boot\Mount" -ItemType directory -ea SilentlyContinue
```

3. Start mounting Boot.wim

Default index number: 2

```
Mount-WindowsImage -ImagePath "D:\OS_11\sources\boot.wim" -Index "2" -Path "D:\OS_11_Custom\Boot\Boot\Mount"
```

4. Language pack: Boot

- Automatically install language packs: Get "Component: All installed packages in the image" and match them. After matching the corresponding names, install the local corresponding language pack files, View the report "[Language installation package for Boot.wim](#)".
- When adding languages, different schema versions must be corresponded, and if not, errors are reported during the addition process.

4.1. Language pack: Add

- Boot.Instl.lang.ps1
 - [\Expand\Boot\Boot.Instl.lang.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Boot/Boot.Instl.lang.ps1
- Copy the code

```

$Mount = "D:\OS_11_Custom\Boot\Boot\Mount"

$Sources = "D:\OS_11_Custom\Boot\Boot\Language\Add\zh-CN"

$InitL_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    $InitL_install_Language_Component += $_.PackageName

}

Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\WinPE-FontSupport-zh-CN.cab"

$Language_List = @(

    @{ Match = "*WinPE*Setup*Client*Package*"; File = "WINPE-SETUP-CLIENT_zh-CN.CAB"; }

    @{ Match = "*WinPE*Setup*Package*"; File = "WinPE-Setup_zh-CN.cab"; }

    @{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }

    @{ Match = "*SecureStartup*"; File = "winpe-securestartup_zh-CN.cab"; }

    @{ Match = "*ATBroker*"; File = "winpe-atbroker_zh-CN.cab"; }

    @{ Match = "*AudioCore*"; File = "winpe-audiocore_zh-CN.cab"; }

    @{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_zh-CN.cab"; }

    @{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_zh-CN.cab"; }

    @{ Match = "*Narrator*"; File = "winpe-narrator_zh-CN.cab"; }

    @{ Match = "*scripting*"; File = "winpe-scripting_zh-CN.cab"; }

    @{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_zh-CN.cab"; }

    @{ Match = "*srh*"; File = "winpe-srh_zh-CN.cab"; }

    @{ Match = "*srt*"; File = "winpe-srt_zh-CN.cab"; }

    @{ Match = "*wds-tools*"; File = "winpe-wds-tools_zh-CN.cab"; }

    @{ Match = "*-WMI-Package*"; File = "winpe-wmi_zh-CN.cab"; }

)

ForEach ($Rule in $Language_List) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $InitL_install_Language_Component) {

        if ($Component -like "*$($Rule.Match)*") {

            Write-host "  Component name: " -NoNewline

            Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline

            Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

            Write-Host "  Installing ".PadRight(22) -NoNewline

            try {

```



```

        Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\ $($Rule.File)" | Out-Null

        Write-host "Finish" -ForegroundColor Green

    } catch {

        Write-host "Failed" -ForegroundColor Red

    }

    break

}

}

}

```

4.2. Offline image language: change

4.2.1. Change default language, regional settings, and other international settings

Region: **zh-CN**

```
Dism /Image:"D:\OS_11_Custom\Boot\Boot\Mount" /Set-AllIntl:"zh-CN"
```

4.2.2. View available language settings

```
Dism /Image:"D:\OS_11_Custom\Boot\Boot\Mount" /Get-Intl
```

4.3. Language pack: Removed, optional

- After you add languages, if you want to deploy to a non-English locale, you can save space by removing the English language component. When you remove a language, uninstall the language components in the reverse order in which you added them.
- After adding the Chinese, delete "**English - United States**" in reverse, the Region tag: **en-US**, you need to extract the language pack in advance
- Boot.Del.Specified.lang.Tag.ps1
 - [\Expand\Boot\Boot.Del.Specified.lang.Tag.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Boot/Boot/Boot.Del.Specified.lang.Tag.ps1

- Copy the code

```

$Lang = "en-US"

$Mount = "D:\OS_11_Custom\Boot\Boot\Mount"

$Sources = "D:\OS_11_Custom\Boot\Boot\Language\Del\en-US"

$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object { $Initl_install_Language_Component += $_.PackageName }

$Language = @(

    @{ Match = "*WordPad*wow64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~wow64~ $($Lang)~.cab"; }

```

```

        @{ Match = "*WordPad*amd64*"; File = "Microsoft-Windows-WordPad-FoD-
Package~31bf3856ad364e35~amd64~$(Lang)~.cab"; }

        @{ Match = "*WMIC*FoD*Package*wow64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

        @{ Match = "*WMIC*FoD*Package*amd64*"; File = "Microsoft-Windows-WMIC-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*StepsRecorder*wow64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

        @{ Match = "*StepsRecorder*amd64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~amd64~$(Lang)~.cab"; }

        @{ Match = "*Printing*PMCPPC*amd64*"; File = "Microsoft-Windows-Printing-PMCPPC-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*PowerShell*wow64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

        @{ Match = "*PowerShell*amd64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~amd64~$(Lang)~.cab"; }

        @{ Match = "*MediaPlayer*wow64*"; File = "Microsoft-Windows-MediaPlayer-Package-wow64-$(Lang).cab"; }

        @{ Match = "*MediaPlayer*amd64*"; File = "Microsoft-Windows-MediaPlayer-Package-AMD64-$(Lang).cab"; }

        @{ Match = "*Notepad*wow64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

        @{ Match = "*Notepad*amd64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*InternetExplorer*"; File = "Microsoft-Windows-InternetExplorer-Optional-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*TextToSpeech*"; File = "Microsoft-Windows-LanguageFeatures-TextToSpeech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*LanguageFeatures-Speech*"; File = "Microsoft-Windows-LanguageFeatures-Speech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*OCR*"; File = "Microsoft-Windows-LanguageFeatures-OCR-$(Lang)-Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*Handwriting*"; File = "Microsoft-Windows-LanguageFeatures-Handwriting-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*LanguageFeatures-Basic*"; File = "Microsoft-Windows-LanguageFeatures-Basic-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*Client-LanguagePack-Package*"; File = "Microsoft-Windows-Client-Language-Pack_x64_$(Lang).cab"; }

    )

    ForEach ($Rule in $Language) {

        Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

        ForEach ($Component in $InitL_install_Language_Component) {

            if ($Component -like "*$($Rule.Match)*$(Lang)*") {

                Write-host "  Component name: " -NoNewline
            }
        }
    }
}

```

```

Write-host $Component -ForegroundColor Green

Write-host "  Language pack file: " -NoNewline

Write-host "$($Sources)\${$Rule.File}" -ForegroundColor Green

Write-Host "  Deleting".PadRight(22) -NoNewline

try{

    Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\${$Rule.File}" -ErrorAction SilentlyContinue | Out-Null

    Write-host "Finish" -ForegroundColor Green

} catch {

    Write-host "Failed" -ForegroundColor Red

    Write-host "  ${$_}" -ForegroundColor Red

}

break

}

}

}

$InitlClearLanguagePackage = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    if ($_.PackageName -like "*${$Lang}*") {

        $InitlClearLanguagePackage += $_.PackageName

    }

}

if ($InitlClearLanguagePackage.count -gt 0) {

    ForEach ($item in $InitlClearLanguagePackage) {

        Write-Host "`n  ${$item}" -ForegroundColor Green

        Write-Host "  Deleting".PadRight(22) -NoNewline

        try{

            Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction SilentlyContinue | Out-Null

            Write-host "Finish" -ForegroundColor Green

        } catch {

            Write-host "Failed" -ForegroundColor Red

            Write-host "  ${$_}" -ForegroundColor Red

        }

    }

}

}

```

4.4. Components: All packages installed in the image

4.4.1. View

```
Get-WindowsPackage -Path "D:\OS_11_Custom\Boot\Boot\Mount" | Out-GridView
```

4.4.2. Export to csv

```
$SaveTo = "D:\OS_11_Custom\Boot\Boot\Report.$(Get-Date -Format "yyyyMMddHHmmss").csv"
```

```
Get-WindowsPackage -Path "D:\OS_11_Custom\Boot\Boot\Mount" | Export-CSV -NoType -Path $SaveTo
```

```
Write-host $SaveTo -ForegroundColor Green
```

4.5. Language: Repair

4.5.1. Extract

Open: [D:\OS_11_Custom\Install\Install\Language\Add\zh-CN\Microsoft-Windows-Client-Language-Pack_x64_zh-CN.cab](#), enter the directory: [Setup\sources\zh-cn\cli](#), and copy the following files to the deskto:

4.5.1.1. [arunres.dll.mui](#)

4.5.1.2. [spwizres.dll.mui](#)

4.5.1.3. [w32uires.dll.mui](#)

4.5.2. Copy

Copy the extracted files to: [D:\OS_11_Custom\Boot\Boot\Mount\sources\zh-CN](#)

4.6. Language packs: sync to ISO installer

```
Copy-Item -Path "D:\OS_11_Custom\Boot\Boot\Mount\sources\zh-CN" -Destination "D:\OS_11\sources\zh-CN" -Recurse -Force
```

4.7. Regenerate Lang.ini

After regeneration, you can adjust the "Installation Interface", the order when selecting "Language", open lang.ini, the default preferred value = 3, non-default value = 2.

4.7.1. Regenerate the mounted directory lang.ini

Regenerated Lang.ini file location: D:\en-us_windows_server_2022_x64_dvd_620d7eac_Custom\Boot\Boot\Mount\Sources\lang.ini

```
Dism /image:"D:\OS_11_Custom\Boot\Boot\Mount" /gen-langini /distribution:"D:\OS_11_Custom\Boot\Boot\Mount"
```

4.7.2. After regenerating lang.ini, sync to the installer

Regenerated Lang.ini file location: D:\en-us_windows_server_2022_x64_dvd_620d7eac\Sources\lang.ini

```
Dism /image:"D:\OS_11_Custom\Boot\Boot\Mount" /gen-langini /distribution:"D:\OS_11"
```

5. Cumulative updates, optional

To prepare the cumulative updates file available, change the example file name: **KB_Boot.cab**

5.1. Add

```
$KBPath = "D:\OS_11_Custom\Boot\Boot\Update\KB_Boot.cab"

Add-WindowsPackage -Path "D:\OS_11_Custom\Boot\Boot\Mount" -PackagePath $KBPath
```

5.2. Delete

```
$KBPath = "D:\OS_11_Custom\Boot\Boot\Update\KB_Boot.cab"

Remove-WindowsPackage -Path "D:\OS_11_Custom\Boot\Boot\Mount" -PackagePath $KBPath
```

5.3. Solid update, optional

It cannot be uninstalled after curing, which cleans the recovery image and resets the basis of any superseded components.

```
Dism /image:"D:\OS_11_Custom\Boot\Boot\Mount" /cleanup-image /StartComponentCleanup /ResetBase
```

5.3.1. Clean components after curing and updating, optional

```
$Mount = "D:\OS_11_Custom\Boot\Boot\Mount"

Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {

    if ($_.PackageState -eq "Superseded") {

        Write-Host " $($_.PackageName)" -ForegroundColor Green

        Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null

    }

}
```

6. Drive, optional

7. Other

7.1. Bypass TPM check during installation

- Boot.Bypass.TPM.ps1
 - [\Expand\Boot\Boot.Bypass.TPM.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/Boot/Boot.Bypass.TPM.ps1

- Copy the code

```
$RegSystem = "D:\OS_11_Custom\Boot\Boot\Mount\Windows\System32\Config\SYSTEM"

$RandomGuid = [guid]::NewGuid()

Write-Host " HKLM:\$($RandomGuid)"

New-PSDrive -PSProvider Registry -Name OtherTasksTPM -Root HKLM -ErrorAction SilentlyContinue | Out-Null

Start-Process reg -ArgumentList "Load ""HKLM\$($RandomGuid)"" ""$($RegSystem)"" -Wait -WindowStyle Hidden -ErrorAction
```

```
SilentlyContinue
```

```
New-Item "HKLM:\$($RandomGuid)\Setup\LabConfig" -force -ea SilentlyContinue | Out-Null
```

```
New-ItemProperty -LiteralPath "HKLM:\$($RandomGuid)\Setup\LabConfig" -Name "BypassCPUCheck" -Value 1 -PropertyType DWord  
-Force -ea SilentlyContinue | Out-Null
```

```
New-ItemProperty -LiteralPath "HKLM:\$($RandomGuid)\Setup\LabConfig" -Name "BypassStorageCheck" -Value 1 -PropertyType  
DWord -Force -ea SilentlyContinue | Out-Null
```

```
New-ItemProperty -LiteralPath "HKLM:\$($RandomGuid)\Setup\LabConfig" -Name "BypassRAMCheck" -Value 1 -PropertyType DWord  
-Force -ea SilentlyContinue | Out-Null
```

```
New-ItemProperty -LiteralPath "HKLM:\$($RandomGuid)\Setup\LabConfig" -Name "BypassTPMCheck" -Value 1 -PropertyType DWord  
-Force -ea SilentlyContinue | Out-Null
```

```
New-ItemProperty -LiteralPath "HKLM:\$($RandomGuid)\Setup\LabConfig" -Name "BypassSecureBootCheck" -Value 1 -PropertyType  
DWord -Force -ea SilentlyContinue | Out-Null
```

```
[gc]::collect()
```

```
Start-Process reg -ArgumentList "unload ""HKLM\$($RandomGuid)"" -Wait -WindowStyle Hidden -ErrorAction SilentlyContinue
```

```
Remove-PSDrive -Name OtherTasksTPM
```

8. Save image: Boot.wim

```
Save-WindowsImage -Path "D:\OS_11_Custom\Boot\Boot\Mount"
```

9. Unmount image: Boot.wim

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowsImage -Path "D:\OS_11_Custom\Boot\Boot\Mount" -Discard
```

IV Deployment engine

- Learn about "Automatically Adding Languages Installed in Windows Systems", learn: <https://github.com/ilikeyi/Multilingual>, how to download:
 - After entering the website, click "Code", "Download Compressed Package", and after the download is completed, you will get the [main.zip](#) compressed package file.
 - Go to the <https://github.com/ilikeyi/Multilingual/releases> download page, select the available version: [1.1.0.4](#), select the download source code format: zip, and get the [Multilingual-1.1.0.4.zip](#) compressed package file after the download is completed;
- Unzip the downloaded [main.zip](#) or [Multilingual-1.1.0.4.zip](#) to: [D:\Multilingual-1.1.0.4](#), and rename: [D:\Multilingual](#)
- Learn "[Unattended Windows Setup Reference](#)", Intervene in the installation process by leaving it unattended.

1. Add method

1.1. Add to ISO installation media

1.1.1. Unattended

1.1.1.1. Add to: [\[ISO\]:\Autounattend.xml](#)

Autounattend.xml interferes with the WinPE installer when booting an ISO installation.

Copy [D:\Multilingual\Unattend\Mul.Unattend.xml](#) to [D:\OS_11\Autounattend.xml](#)

Copy-Item "D:\Multilingual\Unattend\Mul.Unattend.xml" -Destination "D:\OS_11\Autounattend.xml" -Force

1.1.1.2. Add to: [ISO]:\Sources\Unattend.xml

When mounting or unpacking an ISO, after running the [ISO]:\Setup.exe installer, [ISO]:\Sources\Unattend.xml will intervene in the installation process.

Copy D:\Multilingual\Unattend\Mul.Unattend.xml to D:\OS_11\Sources\Unattend.xml

Copy-Item "D:\Multilingual\Unattend\Mul.Unattend.xml" -Destination "D:\OS_11\Sources\Unattend.xml" -Force

1.1.1.3. Add to: [ISO]:\sources\\$OEM\$\\$\$\Panther\unattend.xml

Copy it to the system disk during the installation process, copy to: {system disk}\Windows\Panther\unattend.xml

1.1.1.3.1. Create \$OEM\$ path

New-Item -Path "D:\OS_11\sources\`\$OEM\$\`\$\$\Panther" -ItemType Directory

1.1.1.3.2. Copy

Copy D:\Multilingual\Unattend\Mul.Unattend.xml to D:\OS_11\Sources\\$OEM\$\Panther\Unattend.xml

Copy-Item "D:\Multilingual\Unattend\Mul.Unattend.xml" -Destination "D:\OS_11\sources\`\$OEM\$\`\$\$\Panther\Unattend.xml" -Force

1.1.2. Deployment engine: add

Add "Automatically add installed languages for Windows systems" to D:\OS_11\sources\\$OEM\$\\$1\Yi\Engine in the directory.

1.1.2.1. Deployment Engine: Copy

Copy D:\Multilingual\Engine to D:\OS_11\Sources\\$OEM\$\\$1\Yi\Engine

Copy-Item "D:\Multilingual\Engine" -Destination "D:\OS_11\sources\`\$OEM\$\`\$1\Yi\Engine" -Recurse -Force

1.1.2.2. Deployment engine: custom deployment tags

\$Flag = @(

"Is_Mark_Sync" # Allow global search and synchronization of deployment tags

Prerequisite deployment

"Auto_Update" # Allow automatic updates

"Use_UTF8" # Beta: Global language support using Unicode UTF-8

"Disable_Network_Location_Wizard" # Network Location Wizard

"Disable_Cleanup_Appx_Tasks" # Appx Cleanup and maintenance tasks

```

        "Disable_Cleanup_On_Demand_Language" # Prevent cleanup of unused on-demand feature language
        packs

        "Disable_Cleanup_Unsed_Language"    # Prevent cleaning of unused language packs

        "Prerequisites_Reboot" # Restart your computer

        # Complete first deployment

#   "Popup_Engine" # Allow the deployment engine main interface to pop up for the first time

#   "Allow_First_Pre_Experience" # Allow first preview, as planned

        "Reset_Execution_Policy" # Restore PowerShell execution policy: Restricted

        "Clear_Solutions" # Delete the entire solution

        "Clear_Engine" # Delete the deployment engine and keep the others

#   "First_Experience_Reboot" # Restart your computer

    )

ForEach ($item in $Flag) {

    Write-host "  $($item)" -ForegroundColor Green

    New-Item -Path "D:\OS_11\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow" -ItemType Directory -
    ErrorAction SilentlyContinue | Out-Null

    Out-File -FilePath "D:\OS_11\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow\${$item}" -Encoding utf8 -
    ErrorAction SilentlyContinue

}

```

1.2. Add to mounted

Through "[Customized deployment image: Install.wim](#)", execute "[Start mounting Install.wim](#)" and mount to:
[D:\OS_11_Custom\Install\Install\Mount](#)

1.2.1. Unattended

Copy [D:\Multilingual\Unattend\Mul.Unattend.xml](#) to [D:\OS_11_Custom\Install\Install\Mount\Panther\Unattend.xml](#)

```
Copy-Item "D:\Multilingual\Unattend\Mul.Unattend.xml" -Destination "D:\OS_11_Custom\Install\Install\Mount\Panther" -
Force
```

1.2.2. Deployment engine: add

Add "[Automatically add languages installed on Windows systems](#)" to the
[D:\OS_11_Custom\Install\Install\Mount\Yi\Engine](#) directory.

1.2.2.1. Deployment Engine: Copy

Copy [D:\Multilingual\Engine](#) to [D:\OS_11_Custom\Install\Install\Mount\Yi\Engine](#)

```
Copy-Item "D:\Multilingual\Engine" -Destination "D:\OS_11_Custom\Install\Install\Mount\Yi\Engine" -
Recurse -Force
```


1.2.2.2. Deployment engine: custom deployment tags

```
$Flag = @(

    "Is_Mark_Sync" # Allow global search and synchronization of deployment tags

    # Prerequisite deployment

    # "Auto_Update" # Allow automatic updates

    # "Use_UTF8" # Beta: Global language support using Unicode UTF-8

    "Disable_Network_Location_Wizard" # Network Location Wizard

    "Disable_Cleanup_Appx_Tasks" # Appx Cleanup and maintenance tasks

    "Disable_Cleanup_On_Demand_Language" # Prevent cleanup of unused on-demand feature language
packs

    "Disable_Cleanup_Unsed_Language"  # Prevent cleaning of unused language packs

    "Prerequisites_Reboot" # Restart your computer

    # Complete first deployment

    # "Popup_Engine" # Allow the deployment engine main interface to pop up for the first time

    # "Allow_First_Pre_Experience" # Allow first preview, as planned

    "Reset_Execution_Policy" # Restore PowerShell execution policy: Restricted

    "Clear_Solutions" # Delete the entire solution

    "Clear_Engine" # Delete the deployment engine and keep the others

    # "First_Experience_Reboot" # Restart your computer

)

ForEach ($item in $Flag) {

    Write-host "  $($item)" -ForegroundColor Green

    New-Item -Path "D:\OS_11\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow" -ItemType Directory -
ErrorAction SilentlyContinue | Out-Null

    Out-File -FilePath "D:\OS_11\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow\$( $item )" -Encoding utf8 -
ErrorAction SilentlyContinue

}
```

2. Deployment Engine: Advanced

2.1. Deployment engine: adding process

After copying the deployment engine, you can add deployment tags to intervene in the installation process.

2.2. Unattended solution

When the customization is unattended, please modify it simultaneously if the following files exist:

- [D:\OS_11\Autounattend.xml](#)
- [D:\OS_11\Sources\Unattend.xml](#)

- D:\OS_11\sources\\$\OEM\$\\$\$\Panther\unattend.xml
- D:\OS_11_Custom\Install\Install\Mount\Panther\Unattend.xml

2.2.1. Multilingual or monolingual

In multi-language and monolingual, you can switch between each other. When replacing, please replace all the same ones in the file.

2.2.1.1. Multi-language

```
<UILanguage>%OSDUILanguage%</UILanguage>

<InputLocale>%OSDInputLocale%</InputLocale>

<SystemLocale>%OSDSysLocale%</SystemLocale>

<UILanguage>%OSDUILanguage%</UILanguage>

<UILanguageFallback>%OSDUILanguageFallback%</UILanguageFallback>

<UserLocale>%OSDUserLocale%</UserLocale>
```

2.2.1.2. Monolingual

A single language needs to specify a Region tag, for example, specify a Region tag: zh-CN

```
<UILanguage>zh-CN</UILanguage>

<InputLocale>zh-CN</InputLocale>

<SystemLocale>zh-CN</SystemLocale>

<UILanguage>zh-CN</UILanguage>

<UILanguageFallback>zh-CN</UILanguageFallback>

<UserLocale>zh-CN</UserLocale>
```

2.2.2. User plan

By default, the self-created user Administrator is used and logged in automatically. It can be switched by modifying the following configuration: self-created or customized user.

2.2.2.1. Self-created user Administrator

By default, the self-created user: Administrator is used and logged in automatically, inserted between <OOBE> and </OOBE>.

```
<UserAccounts>

<LocalAccounts>

<LocalAccount wcm:action="add">

<Password>

<Value></Value>

<PlainText>true</PlainText>
```

```
</Password>

<Description>Administrator</Description>

<DisplayName>Administrator</DisplayName>

<Group>Administrators</Group>

<Name>Administrator</Name>

</LocalAccount>

</LocalAccounts>

</UserAccounts>

<AutoLogon>

  <Password>

    <Value></Value>

    <PlainText>true</PlainText>

  </Password>

  <Enabled>true</Enabled>

  <Username>Administrator</Username>

</AutoLogon>
```

2.2.2.2. Custom user

After setting up a custom user and installing the system, in OOBE, you can choose settings such as local and online users.

2.2.2.2.1. Delete

Username: Removed from start <UserAccounts> to </UserAccounts>

Autologin: Remove from start <AutoLogon> to </AutoLogon>

2.2.2.2.2. Replace

From the beginning <OOBE> to </OOBE>

```
<OOBE>

  <ProtectYourPC>3</ProtectYourPC>

  <HideEULAPage>true</HideEULAPage>

  <HideWirelessSetupInOOBE>true</HideWirelessSetupInOOBE>

</OOBE>
```

D.	ISO
II	Generate ISO
1.	Download OScdimg

Select the Oscdimg version according to the architecture, and save it to: **D:** after downloading. To save in other paths, please enter the absolute path of OScdimg.exe;

1.1. x64

https://github.com/ilikeyi/solutions/raw/main/_Software/Oscdimg/amd64/oscdimg.exe

1.2. x86

https://github.com/ilikeyi/solutions/raw/main/_Software/Oscdimg/x86/oscdimg.exe

1.3. arm64

https://github.com/ilikeyi/solutions/raw/main/_Software/Oscdimg/arm64/oscdimg.exe

2. Use the oscdimg command line to generate an ISO file and save it to: **D:\OS_11.iso**

- ISO.ps1
 - [\Expand\ISO.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Attachment/OS.11/22H2/Expand/ISO.ps1

- Copy the code

```
$Oscdimg = "D:\Oscdimg.exe"
```

```
$ISO = "D:\OS_11"
```

```
$Volume = "OS_11"
```

```
$SaveTo = "D:\OS_11.iso"
```

```
$Arguments = @("-m", "-o", "-u2", "-udfver102", "-l" "$($Volume)", "-bootdata:2#p0,e,b" "$($ISO)\boot\etfsboot.com" "#pEF,e,b" "$($ISO)\efi\microsoft\boot\efisys.bin", $ISO, $SaveTo)
```

```
Start-Process -FilePath $Oscdimg -ArgumentList $Arguments -wait -nonewwindow
```

III Bypass TPM installation check

1. Learn about: <https://github.com/AveYo/MediaCreationTool.bat/tree/main/bypass11> and download: [Quick_11_iso_esd_wim_TPM_toggle.bat](#)
2. Drag the **D:\OS_11.iso** file to [Quick_11_iso_esd_wim_TPM_toggle.bat](#), and "add" or "delete" the TPM installation check function in reverse order.

Chapter 2 Report

- Group abbreviations:
 - Group A: [Windows 11 Education](#), [Windows 11 Enterprise](#), [Windows 11 Pro](#), [Windows 11 Pro Education](#), [Windows 11 Pro for Workstations](#), [Windows 11 IoT Enterprise](#)
 - Group B: [Windows 11 Education N](#), [Windows 11 Enterprise N](#), [Windows 11 Pro N](#), [Windows 11 Pro Education N](#), [Windows 11 Pro N for Workstations](#)
 - Group C: [Windows 11 Home](#), [Windows 11 Home Single Language](#)

- Group D: [Windows 11 Home N](#)

II Reports: Different versions

1.	Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~amd64~~10.0.22621.382	A, C
	Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.317	
2.	Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~wow64~~10.0.22621.1	A, C
	Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1	
3.	Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B
4.	Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1	
5.	Microsoft-OneCore-ApplicationModel-Sync-Desktop-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.317	A, B, C, D
6.	Microsoft-OneCore-DirectX-Database-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
7.	Microsoft-Windows-Client-LanguagePack-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.382	A, B, C, D
8.	Microsoft-Windows-Ethernet-Client-Intel-E1i68x64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
9.	Microsoft-Windows-Ethernet-Client-Intel-E2f68-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
10.	Microsoft-Windows-Ethernet-Client-Realtek-Rtcx21x64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
11.	Microsoft-Windows-Ethernet-Client-Vmware-Vmxnet3-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
12.	Microsoft-Windows-FodMetadata-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
13.	Microsoft-Windows-Foundation-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
14.	Microsoft-Windows-Hello-Face-Package~31bf3856ad364e35~amd64~~10.0.22621.317	A, B, C, D
15.	Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~~11.0.22621.1	A, B, C, D
	Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~en-US~11.0.22621.1	A, B, C, D
16.	Microsoft-Windows-Kernel-LA57-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.382	A, B, C, D
17.	Microsoft-Windows-LanguageFeatures-Basic-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
18.	Microsoft-Windows-LanguageFeatures-Handwriting-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
19.	Microsoft-Windows-LanguageFeatures-OCR-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
20.	Microsoft-Windows-LanguageFeatures-Speech-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
21.	Microsoft-Windows-LanguageFeatures-TextToSpeech-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
22.	Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
	Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1	A, B, C, D
23.	Microsoft-Windows -Notepad-System-FoD-Package~31bf3856ad364e35~wow64~~10.0.22621.1	A, B, C, D
	Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1	A, B, C, D
24.	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1	A, B, C, D
25.	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~~10.0.22621.1	A, B, C, D
	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1	A, B, C, D

26.	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1	A, B, C, D
27.	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~~10.0.22621.1	A, B, C, D
	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1	A, B, C, D
28.	Microsoft-Windows-TabletPCMath-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
29.	Microsoft-Windows-Wallpaper-Content-Extended-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
30.	Microsoft-Windows-Wifi-Client-Broadcom-Bcmpeciedhd63-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
31.	Microsoft-Windows-Wifi-Client-Broadcom-Bcmwl63a-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
32.	Microsoft-Windows-Wifi-Client-Broadcom-Bcmwl63al-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
33.	Microsoft-Windows-Wifi-Client-Intel-Netwbw02-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
34.	Microsoft-Windows-Wifi-Client-Intel-Netwew00-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
35.	Microsoft-Windows-Wifi-Client-Intel-Netwew01-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
36.	Microsoft-Windows-Wifi-Client-Intel-Netwlv64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
37.	Microsoft-Windows-Wifi-Client-Intel-Netwns64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
38.	Microsoft-Windows-Wifi-Client-Intel-Netwsw00-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
39.	Microsoft-Windows-Wifi-Client-Intel-Netwtw02-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
40.	Microsoft-Windows-Wifi-Client-Intel-Netwtw04-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
41.	Microsoft-Windows-Wifi-Client-Intel-Netwtw06-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
42.	Microsoft-Windows-Wifi-Client-Intel-Netwtw08-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
43.	Microsoft-Windows-Wifi-Client-Intel-Netwtw10-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
44.	Microsoft-Windows-Wifi-Client-Marvel-Mrvlpcie8897-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
45.	Microsoft-Windows-Wifi-Client-Qualcomm-Athw8x-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
46.	Microsoft-Windows-Wifi-Client-Qualcomm-Athwnx-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
47.	Microsoft-Windows-Wifi-Client-Qualcomm-Qcamain10x64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
48.	Microsoft-Windows-Wifi-Client-Ralink-Netr28x-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
49.	Microsoft-Windows-Wifi-Client-Realtek-Rtl8187se-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
50.	Microsoft-Windows-Wifi-Client-Realtek-Rtl8192se-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
51.	Microsoft-Windows-Wifi-Client-Realtek-Rtl819xp-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
52.	Microsoft-Windows-Wifi-Client-Realtek-Rtl85n64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
53.	Microsoft-Windows-Wifi-Client-Realtek-Rtlwlan-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
54.	Microsoft-Windows-Wifi-Client-Realtek-Rtlwlan01-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
55.	Microsoft-Windows-Wifi-Client-Realtek-Rtlwlan13-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
56.	Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.382	A, B, C, D
	Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621	A, B, C, D

57.	Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~wow64~~10.0.22621.1	A, B, C, D
	Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1	A, B, C, D
58.	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.317	A, B, C, D
	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1	A, B, C, D
59.	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~~10.0.22621.1	A, B, C, D
	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1	A, B, C, D
60.	OpenSSH-Client-Package~31bf3856ad364e35~amd64~~10.0.22621.1	A, B, C, D
61.	Package_for_DotNetRollup_481~31bf3856ad364e35~amd64~~10.0.9065.6	A, B, C, D
62.	Package_for_RollupFix~31bf3856ad364e35~amd64~~22621.382.1.13	A, B, C, D
63.	Package_for_ServicingStack_378~31bf3856ad364e35~amd64~~22621.378.1.0	A, B, C, D

III Report: Language installation packages apply to Install.wim

1.	Microsoft-Windows-MediaPlayer-Package-AMD64-zh-CN.cab	A, C
	Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1	
2.	Microsoft-Windows-MediaPlayer-Package-wow64-zh-CN.cab	A,C
	Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1	
3.	Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B
	Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1	
4.	Microsoft-Windows-LanguageFeatures-Fonts-Hans-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-Fonts-Hans-Package~31bf3856ad364e35~amd64~~10.0.22621.1	
5.	Microsoft-Windows-Client-Language-Pack_x64_zh-CN.cab	A, B, C, D
	Microsoft-Windows-Client-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1	
6.	Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~zh-CN~11.0.22621.1	
7.	Microsoft-Windows-LanguageFeatures-Basic-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-Basic-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.22621.1	
8.	Microsoft-Windows-LanguageFeatures-Handwriting-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-Handwriting-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.22621.1	
9.	Microsoft-Windows-LanguageFeatures-OCR-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-OCR-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.22621.1	
10.	Microsoft-Windows-LanguageFeatures-Speech-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-Speech-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.22621.1	
11.	Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab	A, B, C, D
	Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.22621.1	
12.	Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1	

13.	Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1	
14.	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1	
15.	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~zh-CN~.cab	
	Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1	
16.	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1	
17.	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1	
18.	Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1	
19.	Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1	
20.	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1	
21.	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab	A, B, C, D
	Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1	

IV Report: Language installation packages apply to WinRE.wim

1.	WinPE-FontSupport-zh-CN.cab
	Microsoft-Windows-WinPE-FontSupport-ZH-CN-Package~31bf3856ad364e35~amd64~~10.0.22621.1
2.	lp.cab
	Microsoft-Windows-WinPE-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
3.	winpe-appxdeployment_zh-CN.cab
	WinPE-AppxDeployment-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
4.	winpe-appxpackaging_zh-CN.cab
	WinPE-AppxPackaging-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
5.	winpe-atbroker_zh-CN.cab
	WinPE-ATBroker-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
6.	winpe-audiocore_zh-CN.cab
	WinPE-AudioCore-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
7.	winpe-audiodrivers_zh-CN.cab
	WinPE-AudioDrivers-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
8.	winpe-enhancedstorage_zh-CN.cab

- WinPE-EnhancedStorage-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
9. winpe-hta_zh-CN.cab
- WinPE-HTA-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
10. winpe-narrator_zh-CN.cab
- WinPE-Narrator-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
11. winpe-opcservices_zh-CN.cab
- WinPE-OpcServices-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
12. winpe-rejuv_zh-CN.cab
- WinPE-Rejuv-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
13. winpe-scripting_zh-CN.cab
- WinPE-Scripting-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
14. winpe-securestartup_zh-CN.cab
- WinPE-SecureStartup-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
15. winpe-speech-tts_zh-CN.cab
- WinPE-Speech-TTS-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
16. winpe-srh_zh-CN.cab
- WinPE-SRH-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
17. winpe-srt_zh-CN.cab
- WinPE-SRT-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
18. winpe-storagewmi_zh-CN.cab
- WinPE-StorageWMI-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
19. winpe-wds-tools_zh-CN.cab
- WinPE-WDS-Tools-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
20. winpe-wifi_zh-CN.cab
- WinPE-WiFi-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
21. winpe-windowsupdate_zh-CN.cab
- WinPE-WindowsUpdate-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
22. winpe-wmi_zh-CN.cab
- WinPE-WMI-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1

V Report: Language installation packages apply to Boot.wim

1. WinPE-FontSupport-zh-CN.cab
- Microsoft-Windows-WinPE-FontSupport-ZH-CN-Package~31bf3856ad364e35~amd64~~10.0.22621.1
2. lp.cab
- Microsoft-Windows-WinPE-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1

3.

winpe-atbroker_zh-CN.cab

WinPE-ATBroker-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
4.

winpe-audiocore_zh-CN.cab

WinPE-AudioCore-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
5.

winpe-audiodrivers_zh-CN.cab

WinPE-AudioDrivers-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
6.

winpe-enhancedstorage_zh-CN.cab

WinPE-EnhancedStorage-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
7.

winpe-narrator_zh-CN.cab

WinPE-Narrator-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
8.

winpe-scripting_zh-CN.cab

WinPE-Scripting-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
9.

winpe-securestartup_zh-CN.cab

WinPE-SecureStartup-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
10.

WINPE-SETUP-CLIENT_zh-CN.CAB

WinPE-Setup-Client-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
11.

WinPE-Setup_zh-CN.cab

WinPE-Setup-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
12.

winpe-speech-tts_zh-CN.cab

WinPE-Speech-TTS-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
13.

winpe-srh_zh-CN.cab

WinPE-SRH-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
14.

winpe-srt_zh-CN.cab

WinPE-SRT-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
15.

winpe-wds-tools_zh-CN.cab

WinPE-WDS-Tools-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
16.

winpe-wmi_zh-CN.cab

WinPE-WMI-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1

Chapter 3	Common problem
II	Clean all mounts to
	Close any applications that may be accessing files in the image, including File Explorer.
	Dismount-WindowsImage -Path "D:\OS_11_Custom\Install\Install\Mount" -Discard
	Dismount-WindowsImage -Path "D:\OS_11_Custom\Install\WinRE\Mount" -Discard
	Dismount-WindowsImage -Path "D:\OS_11_Custom\Boot\Boot\Mount" -Discard

III Fix the problem of abnormal mounting

1. View mounted

`Get-WindowsImage -Mounted`

2. Delete the DISM mount record saved in the registry

`Remove-Item -Path "HKLM:\SOFTWARE\Microsoft\WIMMount\Mounted Images*" -Force -Recurse -ErrorAction SilentlyContinue`

3. Delete all resources associated with the corrupted mounted image

`Clear-WindowsCorruptMountPoint`

`Dism /cleanup-wim`

IV Clean directories

`Remove-Item "D:\OS_11_Custom" -Force -Recurse`

`Remove-Item "D:\OS_11\Sources\`OEM" -Force -Recurse`

`Remove-Item -Path "D:\OS_11\Autounattend.xml" -Force`

`Remove-Item -Path "D:\OS_11\Sources\Unattend.xml" -Force`

Chapter 4 Known issues

None yet



Author: Yi

Website: <https://fengyi.tel>

Email: 775159955@qq.com, ilikeyi@outlook.com

Document version: 1.0

Documentation model: Full version

Translation: Chinese to English version

Updated: 2024 - 4

Suggestions or feedback: <https://github.com/ilikeyi/solutions/issues>