

C Programming

Recitation 6

April 2017

OUTLINE

DYNAMIC ALLOCATION

MALLOC

CALLOC

REALLOC

FREE

STRINGS AND POINTERS

STRINGS

STRING ARRAYS VS

STRING POINTERS

PROCESSING STRINGS

2D ARRAYS

USING 2D ARRAYS

PASSING 2D ARRAYS

TASK

HANDLING MEMORY ON RUN TIME

- ▶ Allows us to use and control memory on run time.
- ▶ Requires standard library (`stdlib.h`).
- ▶ Done by four functions: `malloc`, `calloc`, `realloc`, `free`.

MALLOC

- ▶ Given as `void* malloc (size_t size);`
- ▶ Allocates a block of `size` bytes of memory **without initializing it**.
- ▶ Returns a **void pointer** to the beginning of the block. A void pointer can be casted to any type of pointer.
- ▶ Returns `NULL` on failure.

```
/* Allocate memory large enough to hold 10 integers */  
/* Suggested way */  
int *array1 = (int*) malloc(10 * sizeof(int));  
/* Bad way */  
int *array2 = (int*) malloc(10 * 4);
```

CALLOC

- ▶ Given as `void* calloc (size_t num, size_t size);`
- ▶ Allocates a block of memory for an array of `num` elements, each of them `size` bytes long.
- ▶ **Initializes** all its bits to zero.
- ▶ Returns a **void pointer** to the beginning of the block.
- ▶ Returns `NULL` on failure.

```
/* Allocate memory large enough to hold 10 integers and ↵  
initialize them to 0 */
```

```
int *array = (int*) calloc(10, sizeof(int));
```

REALLOC

- ▶ Given as `void* realloc(void *ptr, size_t size);`
- ▶ Reallocates the area of memory given with pointer `ptr`. It must be previously allocated and not yet freed.
- ▶ **Does not** change the existing data.
- ▶ Either **expands/shrinks** the block or **allocates** new block and **copies** the existing data there.
- ▶ Returns a **void pointer** to the beginning of newly allocated memory.
- ▶ On failure, returns `NULL` but the old memory is not freed.

```
/* Allocate memory large enough to hold 10 integers*/  
int *array = (int*) malloc(10 * sizeof(int));  
  
/* Reallocate the array to hold 100 integers */  
array = (int*) realloc(array, 100 * sizeof(int));
```

FREE

- ▶ Given as `void free (void* ptr);`
- ▶ Deallocates an already allocated memory block pointed by `ptr`.
- ▶ **Does not** do anything if `ptr` is `NULL`.
- ▶ **Does not** change `ptr`.

```
/* Allocate memory large enough to hold 10 integers*/  
int *array = (int*) malloc(10 * sizeof(int));  
  
/* Free the array */  
free(array);  
/* Good practice to reset the pointer */  
array = NULL;
```

STRINGS

- ▶ C does not have a built-in *string* data type, but uses null-terminated arrays of characters.
- ▶ *String constants* are surrounded by double quotes ("), e.g. "Hello world!".
- ▶ To create a *string variable*, you must allocate sufficient space for the number of characters in the string and the null character '\0'.

```
/* Static array initialization */  
char butler[7] = {'A', 'l', 'f', 'r', 'e', 'd', '\0'};  
/* Adds the null character */  
char villain[10] = "Joker";  
char *hero = "Harvey Dent";  
/* Print the string */  
printf("%s\n", villain);  
/* Assign new string to char pointer */  
hero = "Batman";  
/* Gives incompatible types error */  
villain = "Batman";
```


STRING ARRAYS VS STRING POINTERS

```
char lover[] = "Harley Quinn";
char *iterator;
char* first;
int i = 0;
int size;

/* Find the size of the string by iterating with index */
while(lover[i] != '\0') i++;
size = i;

/* Find the size of the string by iterating with pointer */
first = lover;
iterator = lover;
while(*iterator != '\0') iterator++;
size = iterator - first;
```

- ▶ Example: *dynamic_strings.c*.
- ▶ Example: *reverse_string.c*.

PROCESSING STRINGS

- ▶ The functions are provided in the library: `string.h`.
- ▶ Example: *string_functions.c*

Method	Description
<code>size_t strlen(const char *s);</code>	Calculates the length of the string <code>s</code> .
<code>char *strcpy(char *dest, const char *src);</code>	Copies the string <code>src</code> to <code>dest</code> (including <code>'\0'</code>) and returns <code>dest</code> .
<code>char *strncpy(char *dest, const char *src, size_t n);</code>	Copies at most <code>n</code> characters.
<code>char *strcat(char *dest, const char *src);</code>	Concatenates the string <code>src</code> to the end of <code>dest</code> , placing <code>'\0'</code> at the end of <code>dest</code> , returns <code>dest</code> .
<code>int strcmp(const char *s1, const char *s2);</code>	Compares the string <code>s1</code> and <code>s2</code> , returns -1, 0, 1 accordingly.
<code>char *strchr(const char *s, int c);</code>	Returns a pointer to the first occurrence of the character <code>c</code> in the string <code>s</code> .

USING 2D ARRAYS

```
int myMatrix[3][4] = {{1,2,3,4},{5,6,7,8},{9,10,11,12}};
```

- ▶ Physically, all elements are stored in a single block of memory.
- ▶ Array elements are stored in row major order.
- ▶ Indexing;
 - ▶ `myMatrix`: pointer to the first element of the 2D array.
 - ▶ `myMatrix[0]`: pointer to the first row of the 2D array.
 - ▶ `myMatrix[1]`: pointer to the second row of the 2D array.
 - ▶ `*myMatrix[1]`: the element `myMatrix[1][0]`.
 - ▶ `myMatrix[i][j]` is the same as;

```
*(myMatrix[i] + j)  
(*myMatrix + i)[j]  
*((myMatrix + i) + j)  
*(&myMatrix[0][0] + 4*i + j)
```

PASSING 2D ARRAYS

```
int myMatrix[3][4] = {{1,2,3,4},{5,6,7,8},{9,10,11,12}};
```

- ▶ While passing a multi-dimensional array, the first array size does not have to be specified. The second (and any subsequent) dimensions must be given.
- ▶ Example: *matrix_allocate.c*

```
#define ROWS 3
#define COLS 5

int addMatrix(int list[][COLS]);

int main() {
    int a[][COLS] = { {13, 22, 9, 23, 12}, {17, 5, 24, 31, 55}, {4, 19, 29, 41, 61} };
    printf("Sum = %d\n", addMatrix(a));
}

int addMatrix( int t[][COLS] ) {
    int i, j, sum = 0;
    for (i = 0; i < ROWS; i++)
        for (j = 0; j < COLS; j++)
            sum += t[i][j];
    return sum;
}
```

LAB DEMO

- Let's use what we have learned today and complete simple task in Moodle.