

Geometric Design:
Mesh Simplification
Level-of-Detail Rendering

Professor Eric Shaffer

ILLINOIS

Level-of-Detail Rendering

- Construct multiple versions of mesh
  - Varying polygon count
- Multi-resolution hierarchies enable
  - efficient geometry processing
  - level-of-detail (LOD) rendering



Pick which model to use based on approximate screen size…

Approx screen size → need to guess the width and height in pixels of the rendered mesh….

How could the engine make this guess?

ILLINOIS

Unreal Engine 4 Mesh Editor



ILLINOIS

https://docs.unrealengine.com/4.27/en-US/WorkingWithContent/Types/StaticMeshes/HowTo/AutomaticLODGeneration/

Generating LODs for a Static Mesh

Setting Up Automatic LOD Generation

How To use the Automatic LOD Generation system in UE4.

Intermediate



ON THIS PAGE

The Automatic LOD generation system allows you to automatically reduce the polygon count of your Static Meshes to create LODs with the Unreal Engine 4 (UE4) Editor. Automatic LOD generation uses what is called quadratic mesh simplification to help generate the LODs for Static Meshes. Quadratic mesh simplification works by calculating the amount of visual difference that collapsing an edge (by merging two vertices) would generate. It then picks the edge with the least amount of visual impact and collapses it. When this happens, the tool will pick the best place to put the newly merged vertex, removing any triangles that have also collapsed along with the edge. It will continue to collapse edges until it reaches the requested target number of triangles. In the following guide, we'll show you how-to setup and use the automatic LOD generation system in your UE4 projects.

That's wrong - should be quadric mesh simplification

What is a Quadric?



Quadric

In mathematics, a quadric or quadric surface, is a generalization of conic sections. It is a hypersurface in a-dimensional space, and it is defined as the zero set of an irreducible polynomial of degree two in D + 1 variables. Wikipedia





Error ellipsoids at each vertex are a type of measurement…

Shows how far away from the original surface the vertex is…

ILLINOIS

Bunny LOD 5



ILLINOIS

Comparison: LOD0 vs LOD5





LOD5 has about 3% of the number of polys as LOD0

ILLINOIS

Rendering: LOD0 vs LOD5

ILLINOIS

Error Quadrics

- Squared distance to plane

$$p = (x, y, z, 1)^T, \quad q = (a, b, c, d)^T$$

$$dist(q, p)^2 = (q^T p)^2 = p^T (q q^T) p =: p^T Q_q p$$

$$Q_q = \begin{bmatrix} a^2 & ab & ac & ad \\ ab & b^2 & bc & bd \\ ac & bc & b^2 & cd \\ ad & bd & cd & d^2 \end{bmatrix}$$

Using implicit form of a plane equation ax+by+cz+d=0

Error Quadrics

- Sum distances to vertex' planes

$$\sum_i dist(q_i, p)^2 = \sum_i p^T Q_{q_i} p = p^T \left(\sum_i Q_{q_i} \right) p =: p^T Q_p p$$

- Point that minimizes the error

$$\begin{bmatrix} q_{11} & q_{12} & q_{13} & q_{14} \\ q_{21} & q_{22} & q_{23} & q_{24} \\ q_{31} & q_{32} & q_{33} & q_{34} \\ 0 & 0 & 0 & 1 \end{bmatrix} p^* = \begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix}$$

You can compute the sum of squared distances from p to N planes using a single 4x4 matrix

You simply sum up the N matrices Q_{q_i} component-wise and use it as shown here.

ILLINOIS

Vertex Placement

$$\mathbf{Q} = \begin{bmatrix} \mathbf{A} & \mathbf{b} \\ \mathbf{b}^T & c \end{bmatrix}$$

$$Q(\mathbf{v}) = \mathbf{v}^T\mathbf{A}\mathbf{v} + 2\mathbf{b}^T\mathbf{v} + c$$

Point v that minimizes $Q(v)$ occurs when

$$\partial Q/\partial x = \partial Q/\partial y = \partial Q/\partial z = 0$$

The gradient of $Q(v)$ is

$$\nabla Q(\mathbf{v}) = 2\mathbf{A}\mathbf{v} + 2\mathbf{b}$$

Solving for $\nabla Q(\mathbf{v}) = 0$, we find that the optimal position is

$$\bar{\mathbf{v}} = -\mathbf{A}^{-1}\mathbf{b}$$

ILLINOIS

Incremental Simplification: Edge Collapse



- Merge two adjacent triangles
- Define new vertex position

Incremental Simplification Algorithm

1. Compute Quadric for each vertex
2. Create a priority queue of all possible edge collapses $p_1 + p_2$
   1. For each edge collapse compute $Q_3 = Q_1 + Q_2$
   2. Compute new vertex v_3
   3. Compute error $v_3^T Q_3 v_3$
3. Choose collapse with least error…update quadrics and repeat



ILLINOIS

Comparison of Vertex Placements



average



median



error quadric





Continuous LOD using Vertex Hierarchies



Each original vertex in mesh is a leaf in this diagram

An edge contraction makes vertices siblings and creates a parent

A cut through the tree represents a set of contractions applied to the mesh

Could do CLOD (sort of) by using screen space metric to determine cut
…adjust cut each frame…

ILLINOIS

In practice LOD gets more complicated

- Error metric should incorporate color and texture information
  - …don't want to merge discontinuous parts of texture if possible



Geometry & texture: A 3,872 face model (a) reduced to 53 faces without (b) and with (c) updating texture coordinates.

- Features may need to be preserved or removed…requires artist input



ILLINOIS