

Table of Contents

1	uint64
1.1	Constants
1.2	Arithmetic Operations
1.3	Bitwise Operations
1.4	Comparison and Equality
1.5	Byte Conversion
1.6	Default Value and Hashing
1.7	Type Conversions
1.8	Working with Large Numbers
1.9	Working with Hexadecimal Literals

uint64

The moonbitlang/core/uint64 package provides functionality for working with 64-bit unsigned integers. This package includes constants, operators, and conversions for UInt64 values.

Constants

The package defines the minimum and maximum values for UInt64:

```
1
2  test "UInt64 constants" {
3
4      inspect(@uint64.min_value, content="0")
5
6
7      inspect(@uint64.max_value, content="18446744073709551615")
8  }
```

Arithmetic Operations

UInt64 supports standard arithmetic operations:

```
1
2  test "UInt64 arithmetic" {
3      let a : UInt64 = 100UL
4      let b : UInt64 = 50UL
5
6
7      inspect(a + b, content="150")
8
9
10     inspect(a - b, content="50")
11
12
13     inspect(a * b, content="5000")
14
15
16     inspect(a / b, content="2")
17
18
19     inspect(@uint64.max_value + 1UL, content="0")
20     inspect(@uint64.min_value - 1UL, content="18446744073709551615")
21 }
```

Bitwise Operations

UInt64 supports various bitwise operations:

```

1
2  test "UInt64 bitwise operations" {
3      let a : UInt64 = 0b1010UL
4      let b : UInt64 = 0b1100UL
5
6
7      inspect(a & b, content="8")
8
9
10     inspect(a | b, content="14")
11
12
13     inspect(a ^ b, content="6")
14
15
16     inspect(a << 1, content="20")
17     inspect(a << 2, content="40")
18
19
20     inspect(a >> 1, content="5")
21     inspect(b >> 2, content="3")
22 }

```

Comparison and Equality

UInt64 supports comparison and equality operations:

```

1
2  test "UInt64 comparison and equality" {
3      let a : UInt64 = 100UL
4      let b : UInt64 = 50UL
5      let c : UInt64 = 100UL
6
7
8      inspect(a == c, content="true")
9      inspect(a != b, content="true")
10
11
12     inspect(a > b, content="true")
13     inspect(b < a, content="true")
14     inspect(a >= c, content="true")
15     inspect(c <= a, content="true")
16 }

```

Byte Conversion

UInt64 provides methods for converting to bytes in both big-endian and little-endian formats:

```

1
2  test "UInt64 byte conversion" {
3
4      let be_bytes = 0x123456789ABCDEF0UL.to_be_bytes()
5      inspect(
6          be_bytes,
7          content=(
8              #|b"\x12\x34\x56\x78\x9a\xbc\xde\xfo"
9          ),
10     )
11
12
13     let le_bytes = 0x123456789ABCDEF0UL.to_le_bytes()
14     inspect(
15         le_bytes,
16         content=(
17             #|b"\xf0\xde\xbc\x9a\x78\x56\x34\x12"
18         ),
19     )
20 }

```

Default Value and Hashing

UInt64 implements the Default trait:

```

1
2  test "UInt64 default value" {
3
4      let a : UInt64 = 0UL
5      inspect(a, content="0")
6
7
8      let value : UInt64 = 42UL
9      inspect(value.hash(), content="-1962516083")
10 }

```

Type Conversions

UInt64 works with various conversions to and from other types:

```

1
2  test "UInt64 conversions" {
3
4      inspect((42).to_uint64(), content="42")
5
6
7      let value : UInt64 = 100UL
8      inspect(value.to_int(), content="100")
9      let as_double = value.to_double()
10     inspect(as_double, content="100")
11
12
13     inspect((-1).to_uint64(), content="18446744073709551615")
14
15
16     let from_double = 42.0.to_uint64()
17     inspect(from_double, content="42")
18 }

```

Working with Large Numbers

UInt64 is especially useful for applications requiring large unsigned integers:

```

1
2  test "UInt64 for large numbers" {
3
4      let large_number : UInt64 = (1UL << 63) - 1UL
5
6
7      inspect(large_number > (1UL << 32) - 1UL, content="true")
8
9
10     let result = large_number * 2UL
11     inspect(result, content="18446744073709551614")
12 }

```

Working with Hexadecimal Literals

UInt64 works well with hexadecimal literals for clarity when working with bit patterns:

```
1
2 test "UInt64 hexadecimal literals" {
3
4     let value = 0xDEADBEEFUL
5
6
7     let ad = (value >> 16) & 0xFFUL
8     inspect(ad.to_byte(), content="b'\xAD' ")
9
10
11    let bytes = value.to_be_bytes()
12    inspect(
13        bytes,
14        content=(
15            #|b"\x00\x00\x00\x00\xde\xad\xbe\xef"
16        ),
17    )
18 }
```