

Table of Contents

1	unit
1.1	Understanding Unit Type
1.2	Unit Value Creation
1.3	Working with Side-Effect Functions
1.4	String Representation and Debugging
1.5	Generic Programming with Unit
1.6	Built-in Trait Implementations
1.7	Practical Use Cases
1.7.1	Result Accumulation
1.7.2	Builder Pattern Termination

unit

The unit package provides functionality for working with the singleton type Unit, which represents computations that produce side effects but return no meaningful value. This is a fundamental type in functional programming for operations like I/O, logging, and state modifications.

Understanding Unit Type

The Unit type has exactly one value: (). This might seem trivial, but it serves important purposes in type systems:

- **Side Effect Indication:** Functions returning Unit signal they're called for side effects
- **Placeholder Type:** Used when a type parameter is needed but no meaningful value exists
- **Functional Programming:** Represents "no useful return value" without using null or exceptions
- **Interface Consistency:** Maintains uniform function signatures in generic contexts

Unit Value Creation

The unit value can be created in multiple ways:

```
1
2  test "unit construction" {
3
4      let u1 = ()
5
6
7      let u2 = @unit default()
8      fn println(_ : String) {
9
10     }
11
12     inspect(u1 == u2, content="true")
13
14
15     fn log_message(msg : String) -> Unit {
16
17         println(msg)
18         ()
19     }
20
21     let result = log_message("Hello, world!")
22     inspect(result, content="()")
23 }
```

Working with Side-Effect Functions

Functions that return Unit are typically called for their side effects:

```
1
2  test "side effect patterns" {
3      let numbers = [1, 2, 3, 4, 5]
4      fn println(_ : Int) {
5
6      }
7
8      let processing_result = numbers fold(init=(), fn(_acc, n) {
9
10         if n % 2 == 0 {
11             println(n)
12         }
13         ()
14     })
15     inspect(processing_result, content="()")
16
17
18
19     numbers each(fn(n) { if n % 2 == 0 { println(n) } })
20 }
```

String Representation and Debugging

Unit values have a standard string representation for debugging:

```
1
2  test "unit string conversion" {
3      let u = ()
4      inspect(u to_string(), content="()")
5
6
7      fn perform_operation() -> Unit {
8
9      }
10
11
12     let result = perform_operation()
13     let debug_msg = "Operation completed: \{result}"
14     inspect(debug_msg, content="Operation completed: ()")
15 }
```

Generic Programming with Unit

Unit is particularly useful in generic contexts where you need to represent "no meaningful value":

```

1
2  test "generic unit usage" {
3
4      let items = [1, 2, 3, 4, 5]
5
6
7      items each(fn(x) {
8
9          let processed = x * 2
10         assert_true(processed > 0)
11     })
12
13
14     let completion_status = ()
15     inspect(completion_status, content="()")
16
17
18     let operation_result : Result[Unit, String] = Ok(())
19     inspect(operation_result, content="Ok(())")
20 }

```

Built-in Trait Implementations

Unit implements essential traits for seamless integration with MoonBit's type system:

```

1
2  test "unit trait implementations" {
3      let u1 = ()
4      let u2 = ()
5
6
7      inspect(u1 == u2, content="true")
8
9
10     inspect(u1 compare(u2), content="0")
11
12
13     let h1 = u1 hash()
14     let h2 = u2 hash()
15     inspect(h1 == h2, content="true")
16
17
18     let u3 = Unit::default()
19     inspect(u3 == u1, content="true")
20 }

```

Practical Use Cases

Result Accumulation

```

1
2  test "result accumulation" {
3
4      let operations = [
5          fn() { () },
6          fn() { () },
7          fn() { () },
8      ]
9      let final_result = operations fold(init=(), fn(acc, operation) {
10         operation()
11         acc
12     })
13     inspect(final_result, content="()")
14 }

```

Builder Pattern Termination

```

1
2  test "builder pattern" {
3
4      let settings = ["debug=true", "timeout=30"]
5
6
7      fn apply_config(config_list : Array[String]) -> Unit {
8
9          let _has_settings = config_list length() > 0
10         ()
11     }
12
13     let result = apply_config(settings)
14     inspect(result, content="()")
15 }

```

The Unit type provides essential functionality for representing "no meaningful return value" in a type-safe way, enabling clean functional programming patterns and consistent interfaces across MoonBit code.