

ICT600 CORRECTED STUDENT EDITION

February 2025 Corrected Student Scheme

Official question and answer checked against generated corrections

Scope	February 2025 final examination
Evidence	Printed question, supplied scheme where available, current lecture notes, and technical verification
Status	100 marks: Part A 70, Part B 30

Prepared 26 September 2026

How to use this reference

Teaching-use document

Attempt the original question before revealing this scheme. This corrected edition is not an official UiTM replacement; it records known source errors and accepts equivalent technically correct answers.

- Assessment total: 100 marks: Part A 70, Part B 30.
- Model answers show one defensible solution; alternative correct wording or code may receive full credit.
- For code, method marks remain available when the approach is sound and a minor syntax error does not invalidate the solution.
- Security improvements are shown where historical examples trusted or displayed unvalidated input.

Q1

Network definitions and four MCO teaching cloud applications.

[18 marks]

Model answer

- Use the four accurate network definitions from January 2024 (8).
- Any four relevant applications with their teaching use during MCO/PKP, such as UFuture, Classroom, Teams, Meet, Drive, or OneDrive (10).

Marking guide: Definitions: 2 each. Cloud applications: official 2.5 per complete pair.

Q2

Reproduce the student table and styled web page.

[12 marks]

Model answer

- Valid header plus three complete rows and values (6).
- Required powderblue/center/blue/red presentation and content (6).

Marking guide: 6 marks per subpart.

Q3

JavaScript variables/output and displayName('Sharaf').

[18 marks]

Model answer

- Four variables plus matching output (8).
- Reusable function whose call displays Name: Sharaf (10).

Marking guide: Q3(a) 8; Q3(b) 10.

Correction / moderation note

The official answer accidentally repeats Username: Aidan from January 2024. The generated scheme correctly follows the February prompt.

Q4

HTML table and simple JavaScript page.

[12 marks]

Model answer

- Use colspan for the table title and reproduce both village columns/rows (6).
- Match What Can You Do?, Hello You!, and the click interaction (6).

Marking guide: 6 marks per subpart.

Correction / moderation note

The official JavaScript exemplar contains wording copied from another paper; mark against the February figure and behavior.

Q5

PHP city array and string trace.

[10 marks]

Model answer

- Store LN11/London and OX47/Oxford in a nested array and display them (4).
- Trace original, uppercase, lowercase, replacement, substr(2,6), and strpos after replacement (6); the substring begins with roun.

Marking guide: Q5(a) 4; Q5(b) 6.

Part B Q2

Recommend a checkout-payment wireframe.

[15 marks]

Model answer

- Show header, navigation, page name, billing/delivery information, payment method, order summary, confirmation, and footer.

Marking guide: Use a 15-mark functional-section rubric consistent with the January paper.

Part B Q1 - secure all-required registration

Study the complete working exemplar below.

[See printed allocation]

Model answer

- Equivalent correct implementations that satisfy the stated behaviour should receive credit.

```
<?php
$values = ['fullname' => '', 'email' => '', 'birthdate' => '', 'gender' => ''];
$message = '';

function e(string $value): string {
    return htmlspecialchars($value, ENT_QUOTES, 'UTF-8');
}

if ($_SERVER['REQUEST_METHOD'] === 'POST') {
    foreach ($values as $key => $unused) {
        $values[$key] = trim($_POST[$key] ?? '');
    }
    $password = $_POST['password'] ?? '';
    if ($values['fullname'] === '' || $values['email'] === '' || $password === '' ||
        $values['birthdate'] === '' || $values['gender'] === '') {
        $message = 'Unsuccessful: enter all required information.';
    } else {
        $message = 'Successful signup for ' . $values['fullname'] . '.';
    }
}
?>
<!doctype html>
<html lang="en"><head><meta charset="utf-8"><title>User Signup</title></head>
<body>
```

```

<h1>User Signup</h1>
<form method="post">
  <label>Full name* <input name="fullname" value="<?= e($values['fullname']) ?>" required></label><br>
  <label>Email* <input type="email" name="email" value="<?= e($values['email']) ?>" required></label><br>
  <label>Password* <input type="password" name="password" required></label><br>
  <label>Birthdate <input type="date" name="birthdate" value="<?= e($values['birthdate']) ?>"></label><br>
  <label><input type="radio" name="gender" value="M"> Male</label>
  <label><input type="radio" name="gender" value="F"> Female</label><br>
  <button type="submit">Signup</button>
</form>

<?php if ($message != ' '): ?><p><?= e($message) ?></p><?php endif; ?>
</body></html>

```

Marking guide: Apply the original question's subpart allocation and award method marks consistently.

Correction / moderation note

The February question makes birthdate and gender required. The generated scheme correctly validates them, unlike the official code, but still required output encoding; this exemplar adds it.

Consistency rules

- Award equivalent technically correct syntax and wording.
- Do not reproduce a known historical error merely because it appears in a supplied scheme.
- Keep printed subpart totals fixed unless a documented moderation decision says otherwise.
- For scenario questions, connect the explanation or mitigation to the scenario.
- Record additional accepted alternatives for the next controlled revision.

February 2025 - Complete Coding Answers

Exam-schema presentation

Each answer below includes executable model code and an awardable marking schedule that sums to the printed marks. Equivalent working solutions receive the same marks when they satisfy the required behaviour.

Question 2(a) - student table

6 marks

Reproduce Table 1 using valid HTML table elements.

Mark allocation

Awardable element	Marks
Table structure	1
Header row	1
Three complete data rows	3
Valid nesting	1
Total	6

Complete model answer

```
<table border="1">
  <tr><th>Namapelajar</th><th>Namabapa</th><th>Umur</th></tr>
  <tr><td>Ahmad</td><td>Razman</td><td>51</td></tr>
  <tr><td>Mohamad</td><td>Nizar</td><td>55</td></tr>
  <tr><td>Abdul</td><td>Syazali</td><td>47</td></tr>
</table>
```

Question 2(b) - styled HTML page

6 marks

Organise the required powderblue centred page.

Mark allocation

Awardable element	Marks
Valid HTML and text	2
Body styling	2
Blue h1	1
Red paragraph	1
Total	6

Complete model answer

```
<!doctype html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <title>Web Application and Technology</title>
    <style>
      body { background-color: powderblue; text-align: center; }
      h1 { color: blue; }
      p { color: red; }
    </style>
  </head>
  <body>
    <h1>Web Application and Technology</h1>
    <p>Explore web technology and application</p>
  </body>
</html>
```

Question 3(a) - JavaScript variables

8 marks

Assign the printed name, class, year and CGPA, then display them.

Mark allocation

Awardable element	Marks
Four correct variables/values	4
Four matching outputs	4
Total	8

Complete model answer

```
<!doctype html>
<html lang="en"><body>
<p id="name"></p><p id="class"></p><p id="year"></p><p id="cgpa"></p>
<script>
const studentName = "Shamal bin Aidi";
const className = "Al-Khawarizmi";
const year = 8;
const cgpa = 3.55;
document.getElementById("name").textContent = "Name: " + studentName;
document.getElementById("class").textContent = "Class: " + className;
document.getElementById("year").textContent = "Year: " + year;
document.getElementById("cgpa").textContent = "CGPA: " + cgpa;
</script>
</body></html>
```

Question 3(b) - displayUserName

10 marks

Call displayUserName('Sharaf') and display Name: Sharaf.

Mark allocation

Awardable element	Marks
Function	2
Parameter	2
Name prefix	2
DOM output	2
Correct call	2
Total	10

Complete model answer

```
<p id="result"></p>
<script>
function displayUserName(userName) {
  document.getElementById("result").textContent = "Name: " + userName;
}
displayUserName("Sharaf");
</script>
```

Expected output / behaviour

Name: Sharaf

Marker note

The historical official answer copied Aidan from another paper. Sharaf is required here.

Question 4(a) - family table

6 marks

Create the complete Table 2 with the spanning title row.

Mark allocation

Awardable element	Marks
Table structure	1
Spanning title	2
Village headings	1
Complete values	2
Total	6

Complete model answer

```
<table border="1">
  <tr><th colspan="2">Bilangan Kanak-kanak dalam Keluarga Bawah 7 tahun 2023</th></tr>
  <tr><th>Kampung Tin</th><th>Kampung Changkat</th></tr>
  <tr><td>300 orang</td><td>200 orang</td></tr>
  <tr><td>150 keluarga</td><td>100 keluarga</td></tr>
</table>
```

Question 4(b) - HTML and JavaScript page

6 marks

Produce the illustrated page and a working click interaction.

Mark allocation

Awardable element	Marks
Heading, message and button	3
Event	1
DOM update	2
Total	6

Complete model answer

```
<!doctype html>
<html lang="en"><body>
  <h1>What Can You Do?</h1>
  <p id="message">Hello You!</p>
  <button type="button" id="change">click me!</button>
  <script>
    document.getElementById("change").addEventListener("click", () => {
      document.getElementById("message").textContent = "You can use JavaScript!";
    });
  </script>
</body></html>
```

Marker note

The historical official wording was copied from a different paper; mark against this paper's Figure 2.

Question 5(a) - PHP city array

4 marks

Use a multidimensional array to display the two city rows.

Mark allocation

Awardable element	Marks
Nested array	2
Complete output	2
Total	4

Complete model answer

```
<?php
$cities = [
    ['LN11', 'London'],
    ['OX47', 'Oxford'],
];
?>
<table border="1">
<?php foreach ($cities as $city): ?>
    <tr><td><?= $city[0] ?></td><td><?= $city[1] ?></td></tr>
<?php endforeach; ?>
</table>
```

Question 5(b) - exact PHP trace

6 marks

Produce the exact output of the printed PHP string operations.

Mark allocation

Awardable element	Marks
Original	1
Uppercase	1
Lowercase	1
Replacement	1
Substring	1
strpos result	1
Total	6

Complete model answer

```
How can I cook rice in a clean round pot
HOW CAN I COOK RICE IN A CLEAN ROUND POT
how can i cook rice in a clean round pot
How round I cook rice in a clean round pot
w roun
bool(false)
```

Part B Question 1 - all-required PHP registration

15 marks

Provide complete form processing where full name, email, password, birthdate and gender are all required.

Mark allocation

Awardable element	Marks
Complete form	4
POST handling	2
All five fields validated	4
Success/error messages	2
Safe output	2
Valid structure	1
Total	15

Complete model answer

```
<?php
$values = ['fullname' => '', 'email' => '', 'birthdate' => '', 'gender' => ''];
$message = '';

function e(string $value): string {
    return htmlspecialchars($value, ENT_QUOTES, 'UTF-8');
}

if ($_SERVER['REQUEST_METHOD'] === 'POST') {
    foreach ($values as $key => $unused) {
        $values[$key] = trim($_POST[$key] ?? '');
    }
    $password = $_POST['password'] ?? '';
    if ($values['fullname'] === '' || $values['email'] === '' || $password === '' ||
        $values['birthdate'] === '' || $values['gender'] === '') {
        $message = 'Unsuccessful: enter all required information.';
    } else {
        $message = 'Successful signup for ' . $values['fullname'] . ' .';
    }
}

?>
<!doctype html>
<html lang="en"><head><meta charset="utf-8"><title>User Signup</title></head>
<body>
<h1>User Signup</h1>
<form method="post">
    <label>Full name* <input name="fullname" value="<?= e($values['fullname']) ?>" required></label><br>
    <label>Email* <input type="email" name="email" value="<?= e($values['email']) ?>" required></label><br>
    <label>Password* <input type="password" name="password" required></label><br>
    <label>Birthdate <input type="date" name="birthdate" value="<?= e($values['birthdate']) ?>"></label><br>
    <label><input type="radio" name="gender" value="M"> Male</label>
    <label><input type="radio" name="gender" value="F"> Female</label><br>

    <button type="submit">Signup</button>
</form>
<?php if ($message !== ''): ?><p><?= e($message) ?></p><?php endif; ?>
</body></html>
```

Coding-marker consistency

- Award method marks when the core algorithm and required structure are correct.
- Do not double-penalise one syntax error that causes several later lines to fail.
- Accept equivalent DOM methods, loop forms, variable names, SQL aliases, and control structures.
- Require every behaviour named in the question; a prose description alone is not a complete coding answer.
- For unsafe historical code, award course-aligned logic while teaching prepared SQL, password hashing, validation, and output encoding.