

ICT600 CORRECTED STUDENT EDITION

January 2024 Corrected Student Scheme

Official question and answer checked against the generated student scheme

Scope	January 2024 final examination
Evidence	Printed question, supplied scheme where available, current lecture notes, and technical verification
Status	100 marks: Part A 70, Part B 30

Prepared 26 September 2026

How to use this reference

Teaching-use document

Attempt the original question before revealing this scheme. This corrected edition is not an official UiTM replacement; it records known source errors and accepts equivalent technically correct answers.

- Assessment total: 100 marks: Part A 70, Part B 30.
- Model answers show one defensible solution; alternative correct wording or code may receive full credit.
- For code, method marks remain available when the approach is sound and a minor syntax error does not invalidate the solution.
- Security improvements are shown where historical examples trusted or displayed unvalidated input.

Q1(a)

Describe Intranet, Extranet, Internet and LAN.

[8 marks]

Model answer

- Intranet: private organisational network for authorised internal users.
- Extranet: controlled access to selected organisational resources for authorised external parties.
- Internet: global network of interconnected networks using standard protocols.
- LAN: network covering a limited area such as a home, office, or building.

Marking guide: 2 marks per accurate definition.

Q1(b)

Identify four cloud applications for UiTM teaching and learning, with examples.

[10 marks]

Model answer

- Any four of UFuture, Google Classroom, Microsoft Teams, Google Meet, Google Drive, or OneDrive with a correct teaching use.

Marking guide: Official allocation: 2.5 marks per complete application-and-use pair. Accept the generated 4+4+2 structure only if applied consistently.

Q2

Create the required HTML table and styled page.

[12 marks]

Model answer

- Use a valid table with one header row and three data rows (6).
- Use a powderblue body, centered text, blue h1, red paragraph, and correct displayed content (6).

Marking guide: Award functional structure and required styling; equivalent valid HTML/CSS is acceptable.

Q3

Create JavaScript variables/output and displayUserName(userName).

[18 marks]

Model answer

- Four variables and four corresponding outputs (8).
- Reusable function with parameter, output operation, and correct call/output (10).

Marking guide: Do not require document.write if an equivalent DOM output is used.

Q4(a)

Produce the city table using a PHP multidimensional array.

[4 marks]

Model answer

- Store LN11/London and OX47/Oxford as rows in a nested array and display both rows.

Marking guide: Array construction (2) + correct display of both rows (2).

Q4(b)

Trace the supplied PHP string script.

[6 marks]

Model answer

- 43
- How can I cook rice in a clean round pot?
- HOW CAN I COOK RICE IN A CLEAN ROUND POT?
- how can i cook rice in a clean round pot?
- How round I cook rice in a clean round pot?
- w roun
- bool(false)
- bool(false)

Marking guide: Allocate the six marks across the required output operations.

Correction / moderation note

The official scheme's final int(4) is inconsistent after can has been replaced and the script searches for could. The generated bool(false) is correct.

Q5

Create the flood table and the HTML/JavaScript interaction.

[12 marks]

Model answer

- Use colspan=2 for the table title and reproduce both location columns and data rows (6).
- Use a heading, identified paragraph, button/event, DOM lookup, and content update (6).

Marking guide: 6 marks per subpart.

Part B Q1

Construct a checkout-payment wireframe.

[15 marks]

Model answer

- Show header, navigation, breadcrumb/page name, billing address, delivery/payment method, order summary, confirmation action, and footer.

Marking guide: Score visible functional sections and logical grouping, not decorative quality.

Part B Q2 - secure registration exemplar

Study the complete working exemplar below.

[\[See printed allocation\]](#)

Model answer

- Equivalent correct implementations that satisfy the stated behaviour should receive credit.

```
<?php
$values = ['fullname' => '', 'email' => '', 'birthdate' => '', 'gender' => ''];
$message = '';

function e(string $value): string {
    return htmlspecialchars($value, ENT_QUOTES, 'UTF-8');
}

if ($_SERVER['REQUEST_METHOD'] === 'POST') {
    foreach ($values as $key => $unused) {
        $values[$key] = trim($_POST[$key] ?? '');
    }
    $password = $_POST['password'] ?? '';
    if ($values['fullname'] === '' || $values['email'] === '' || $password === '') {
        $message = 'Unsuccessful: enter all required information.';
    } else {
        $message = 'Successful signup for ' . $values['fullname'] . ' .';
    }
}

?>
<!doctype html>
<html lang="en"><head><meta charset="utf-8"><title>User Signup</title></head>
<body>
<h1>User Signup</h1>
<form method="post">
    <label>Full name* <input name="fullname" value="<?= e($values['fullname']) ?>" required></label><br>
    <label>Email* <input type="email" name="email" value="<?= e($values['email']) ?>" required></label><br>
    <label>Password* <input type="password" name="password" required></label><br>
    <label>Birthdate <input type="date" name="birthdate" value="<?= e($values['birthdate']) ?>"></label><br>
    <label><input type="radio" name="gender" value="M"> Male</label>
    <label><input type="radio" name="gender" value="F"> Female</label><br>
    <button type="submit">Signup</button>
</form>
<?php if ($message !== ''): ?><p><?= e($message) ?></p><?php endif; ?>

</body></html>
```

Marking guide: Apply the original question's subpart allocation and award method marks consistently.

Correction / moderation note

The historical official and generated schemes echo untrusted values. This exemplar preserves the task while encoding output. The official scheme also contains a stray 22-mark label even though the printed question is 15 marks.

Consistency rules

- Award equivalent technically correct syntax and wording.
- Do not reproduce a known historical error merely because it appears in a supplied scheme.
- Keep printed subpart totals fixed unless a documented moderation decision says otherwise.
- For scenario questions, connect the explanation or mitigation to the scenario.
- Record additional accepted alternatives for the next controlled revision.

January 2024 - Complete Coding Answers

Exam-schema presentation

Each answer below includes executable model code and an awardable marking schedule that sums to the printed marks. Equivalent working solutions receive the same marks when they satisfy the required behaviour.

Question 2(a) - HTML table

6 marks

Write complete HTML for Table 1: List of Names.

Mark allocation

Awardable element	Marks
Table/caption structure	1
Three headings	1
Three complete data rows	3
Valid nesting and closing tags	1
Total	6

Complete model answer

```
<!doctype html>
<html lang="en">
<head><meta charset="utf-8"><title>List of Names</title></head>
<body>
<table border="1">
  <caption>Table 1: List of Names</caption>
  <tr><th>Firstname</th><th>Lastname</th><th>Age</th></tr>
  <tr><td>Jill</td><td>Smith</td><td>50</td></tr>
  <tr><td>Eve</td><td>Jackson</td><td>94</td></tr>
  <tr><td>John</td><td>Doe</td><td>80</td></tr>
</table>
</body>
</html>
```

Question 2(b) - styled HTML page

6 marks

Write the complete page with the required background, alignment and colours.

Mark allocation

Awardable element	Marks
Valid HTML and required text	2
Powderblue body and centred text	2
Blue h1	1
Red paragraph	1
Total	6

Complete model answer

```
<!doctype html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <title>Web Application and Technology</title>
  <style>
    body { background-color: powderblue; text-align: center; }
    h1 { color: blue; }
    p { color: red; }
  </style>
</head>
<body>
```

```

<h1>Web Application and Technology</h1>
<p>Explore web technology and application</p>
</body>
</html>

```

Question 3(a) - JavaScript variables and output

8 marks

Store the four printed values in separate variables and reproduce the output.

Mark allocation

Awardable element	Marks
Four correct variables/values	4
Four correct browser outputs	4
Total	8

Complete model answer

```

<!doctype html>
<html lang="en"><body>
<p id="name"></p><p id="program"></p><p id="part"></p><p id="cgpa"></p>
<script>
const studentName = "Imran bin Haziq";
const programCode = "CS240";
const part = 5;
const cgpa = 3.55;

document.getElementById("name").textContent = "Name: " + studentName;
document.getElementById("program").textContent = "Program Code: " + programCode;
document.getElementById("part").textContent = "Part: " + part;
document.getElementById("cgpa").textContent = "CGPA: " + cgpa;
</script>
</body></html>

```

Question 3(b) - displayUserName

10 marks

Write and call displayUserName('Aidan') to display Username: Aidan.

Mark allocation

Awardable element	Marks
Function declaration	2
Parameter	2
Username prefix and concatenation	2
Browser output	2
Correct call	2
Total	10

Complete model answer

```

<!doctype html>
<html lang="en"><body>
<p id="result"></p>
<script>
function displayUserName(userName) {
    document.getElementById("result").textContent = "Username: " + userName;
}
displayUserName("Aidan");
</script>
</body></html>

```

Expected output / behaviour

Username: Aidan

Question 4(a) - PHP multidimensional array

4 marks

Use a PHP multidimensional array to display LN11/London and OX47/Oxford.

Mark allocation

Awardable element	Marks
Correct nested array	2
Both rows displayed in a table	2
Total	4

Complete model answer

```
<?php
$scities = [
    ['LN11', 'London'],
    ['OX47', 'Oxford'],
];
?>
<table border="1">
<?php foreach ($scities as $city): ?>
    <tr><td><?= $city[0] ?></td><td><?= $city[1] ?></td></tr>
<?php endforeach; ?>
</table>
```

Question 5(a) - flood table

6 marks

Create Table 3 exactly with the spanning title and all values.

Mark allocation

Awardable element	Marks
Table structure	1
colspan title row	2
Location headings	1
Complete data rows	2
Total	6

Complete model answer

```
<table border="1">
    <caption>Table 3: Mangsa Banjir di Pahang</caption>
    <tr><th colspan="2">Bilangan Mangsa Banjir Pahang 2021</th></tr>
    <tr><th>Temerloh</th><th>Kuantan</th></tr>
    <tr><td>900 orang</td><td>3314 orang</td></tr>
    <tr><td>253 keluarga</td><td>892 keluarga</td></tr>
</table>
```

Question 5(b) - HTML and JavaScript interaction

6 marks

Build the illustrated page and make the button update its message.

Mark allocation

Awardable element	Marks
Heading, paragraph and button	3
Event handler	1
Correct DOM lookup and content update	2
Total	6

Complete model answer

```
<!doctype html>
<html lang="en"><body>
<h1>What Can JavaScript Do?</h1>
<p id="message">Hello JavaScript!</p>
<button type="button" id="changeMessage">Click Me!</button>
<script>
document.getElementById("changeMessage").addEventListener("click", () => {
    document.getElementById("message").textContent = "JavaScript can change HTML content!";
});
</script>
</body></html>
```

Part B Question 2 - PHP user registration

15 marks

Provide the complete form, POST validation, success state and error state.

Mark allocation

Awardable element	Marks
Form and required/optional controls	4
POST request handling	2
Required-field validation	3
Success and failure messages	2
Safe encoded output	2
Valid overall structure	2
Total	15

Complete model answer

```
<?php
$values = ['fullname' => '', 'email' => '', 'birthdate' => '', 'gender' => ''];
$message = '';

function e(string $value): string {
    return htmlspecialchars($value, ENT_QUOTES, 'UTF-8');
}

if ($_SERVER['REQUEST_METHOD'] === 'POST') {
    foreach ($values as $key => $unused) {
        $values[$key] = trim($_POST[$key] ?? '');
    }
    $password = $_POST['password'] ?? '';
    if ($values['fullname'] === '' || $values['email'] === '' || $password === '') {
        $message = 'Unsuccessful: enter all required information.';
    } else {
        $message = 'Successful signup for ' . $values['fullname'] . '.';
    }
}
?>
<!doctype html>
<html lang="en"><head><meta charset="utf-8"><title>User Signup</title></head>
<body>
<h1>User Signup</h1>
```

```

<form method="post">
  <label>Full name* <input name="fullname" value="<?= e($values['fullname']) ?>" required></label><br>
  <label>Email* <input type="email" name="email" value="<?= e($values['email']) ?>" required></label><br>
  <label>Password* <input type="password" name="password" required></label><br>
  <label>Birthdate <input type="date" name="birthdate" value="<?= e($values['birthdate']) ?>"></label><br>
  <label><input type="radio" name="gender" value="M"> Male</label>
  <label><input type="radio" name="gender" value="F"> Female</label><br>
  <button type="submit">Signup</button>

</form>
<?php if ($message != ''): ?><p><?= e($message) ?></p><?php endif; ?>
</body></html>

```

Marker note

The stray 22-mark label in the historical official answer is incorrect; the printed question is 15 marks.

Coding-marker consistency

- Award method marks when the core algorithm and required structure are correct.
- Do not double-penalise one syntax error that causes several later lines to fail.
- Accept equivalent DOM methods, loop forms, variable names, SQL aliases, and control structures.
- Require every behaviour named in the question; a prose description alone is not a complete coding answer.
- For unsafe historical code, award course-aligned logic while teaching prepared SQL, password hashing, validation, and output encoding.