

13 LBC | Machines in a classroom: Towards human-like active learning

^{1,2,3} Ilona Kulikovskikh, ² Tomislav Šmuc

¹ Faculty of Electrical Engineering and Computing, University of Zagreb, Croatia


² Division of Electronics, Ruđer Bošković Institute, Zagreb, Croatia

³ Samara National Research University, Samara, Russia



Introduction

Machines usually employ a guess-and-check strategy to analyze data: they take the data, make a guess, check the answer, adjust it with regard to the correct one if necessary, and, in the end, they try again on a new data set. This “passive” learning technique normally requires an enormous amount of labeled data that has to provide the correct answers. An active learning environment guarantees **better performance while training on less, but carefully chosen, data** which reduces the costs of both annotating and analyzing large data sets. Learning in an active learning environment, a machine requests instances based upon past queries and their responses. This leads to the optimal leveraging of both new and existing data.






Problem statement

The best-known machine **active learning strategies** still need more adaptivity and learner-centricity that would allow them to **work on most scenarios and datasets**.

Active learning in an educational setting integrates a variety of strategies and instructional models to contribute to learners' knowledge. In particular, in multiple-choice testing:

1) depending on their level of ability, learners may develop a rational strategy of ruling out the most unlikely responses;

2) under no penalty or a low penalty for incorrect responses, learners have an incentive to guess, increasing measurement errors.



Designing a pool of sensible incorrect items (distractors) eliminates pure guessing in the responses. This **increases the amount of information** an item provides for adopting an active learning strategy.

Methodology

To address the posed problem, **we suggest:**

1) a new strategy for pool-based sampling correct answers and distractors with regard to 4PL IRT model;

2) a penalty for incorrect responses to simulate more realistic learners' behavior in a classroom.


A new pool-based strategy

The strategy allows for more efficient information retrieval for the item’s parameters such as learning strategies for guessing a_i and forgetting b_i , a discrimination factor α_i that allows us to differentiate between learners with different levels of knowledge (locations) θ_j , and items difficulty β_i with regard to the four-parameter logistic item response theory (4PL IRT) model:

$$p(x_{ij} = 1|\theta_j, \alpha_i, \beta_i, a_i, b_i) = a_i + \frac{b_i - a_i}{1 + \exp(-\alpha_i(\theta_j - \beta_i))},$$

where $p(x_{ij} = 1|\theta_j, \alpha_i, \beta_i, a_i, b_i)$ is the probability of providing the correct response $x_{ij} = 1$ by a learner with j to an item i . The rate of success mainly depends on the relationship between the item's parameters and learners' working knowledge.

The figure below depicts **the proposed pool-based strategy** to increase the items capacity J with regard to the items' difficulty β_i , learners' locations θ_j , strategies a_i and b_i , and penalty announcement p . **The strategy is aimed at “moving” learners along the difficulty axis while keeping high values for the capacity axis.**



A new informativeness measure

The strategy allows for a new informativeness measure for unlabelled instances based on the definition of m items' information J :

$$J(\theta) = -\mathcal{E} \left[\frac{\partial^2}{\partial \theta^2} \ln L \right] = \sum_{i=1}^m \frac{p_i'^2}{p_i(1-p_i)} = \frac{1}{\sigma_e^2(\hat{\theta}|\theta)},$$

$$\ln L(x_{ij}|\theta_j, \alpha_i, \beta_i, a_i, b_i) = \sum_{i=1}^m (x_{ij} \ln(p_i) + (1 - x_{ij}) \ln(1 - p_i)), \quad p_i \equiv p(x_{ij} = 1|\theta_j, \alpha_i, \beta_i, a_i, b_i),$$

where $\sigma_e^2(\hat{\theta}|\theta)$ is the asymptotic variance error of the estimate θ . The items' capacity can be defined as the maximum of the information function $J(\theta)_{\max}$.

The gradient-based definition of the items’ capacity makes it possible **to employ the strategy** based on the new informativeness measure **at a training step**, thereby bringing **more flexibility and adaptivity** to an active learning framework.

Acknowledgment

This research was funded by the European Union through the European Regional Development Fund, under the grant KK.01.1.1.01.0009 (DATACROSS), the Ministry of Science and Higher Education of Russian Federation (Russian Federation President grant No. MK-6218.2018.9), and the Russian Foundation for Basic Research (grant No. 18-37-00219).