On-Device AI 실습
Quantization for CNN

Taehyun An

Overview

1. **Uniform Quantization**
   - Linear Quantization
   - Per-tensor / Per-channel Quantization
   - Quantized inference

2. **Non-uniform Quantization**
   - K-Means Quantization, Quantization-aware Training

3. **Quantization with PyTorch API**
   - Post-Training Quantization, Quantization Aware Training

Linear Quantization

An affine mapping of integers to real numbers $r = S(q - Z)$



Bit Width	q_{min}	q_{max}
2	-2	1
3	-4	3
4	-8	7
N	-2^{N-1}	$2^{N-1}-1$

Linear Quantization

weights (32-bit float)

2.09	-0.98	1.48	0.09
0.05	-0.14	-1.08	2.12
-0.91	1.92	0	-1.03
1.87	0	1.53	1.49

quantized weights (2-bit signed int)

1	-2	0	-1
-1	-1	-2	1
-2	1	-1	-2
1	-1	0	0

zero point (2-bit signed int)

scale (32-bit float)

$$r = (q - Z) \times S$$

$$\Rightarrow (\text{quantized weights} - \text{zero point}) \times \text{scale} =$$

we will learn how to determine these parameters later

reconstructed weights (32-bit float)

2.14	-1.07	1.07	0
0	0	-1.07	2.14
-1.07	2.14	0	-1.07
2.14	0	1.07	1.07

Binary	Decimal
01	1
00	0
11	-1
10	-2

quantization error

-0.05	0.09	0.41	0.09
0.05	-0.14	-0.01	-0.02
0.16	-0.22	0	0.04
-0.27	0	0.46	0.42

[실습1] Linear Quantization 함수 구현

Given the zero point and scale, how is a tensor quantized?

quantized weights (2-bit signed int)					weights (32-bit float)					scale (32-bit float)		zero point (2-bit signed int)
1	-2	0	-1	=	2.09	-0.98	1.48	0.09	÷	**1.07**	+	**-1**
-1	-1	-2	1		0.05	-0.14	-1.08	2.12				
-2	1	-1	-2		-0.91	1.92	0	-1.03				
1	-1	0	0		1.87	0	1.53	1.49				
q				$=$	r				$\div$	S	$+$	Z
Integer					**Floating-point**					**Floating-point**		**Integer**

[실습1] Linear Quantization 함수 구현

$$q = r/s + z$$

quantized weights (2-bit signed int)					weights (32-bit float)					scale (32-bit float)		zero point (2-bit signed int)
1	-2	0	-1	=	2.09	-0.98	1.48	0.09	÷	**1.07**	+	**-1**
-1	-1	-2	1		0.05	-0.14	-1.08	2.12				
-2	1	-1	-2		-0.91	1.92	0	-1.03				
1	-1	0	0		1.87	0	1.53	1.49				
q				=	r				÷	S	+	Z
Integer					**Floating-point**					**Floating-point**		**Integer**

[실습1] Linear Quantization 함수 구현

$$q = int(round(r/s)) + z$$

quantized weights
(2-bit signed int)

1	-2	0	-1
-1	-1	-2	1
-2	1	-1	-2
1	-1	0	0

$=$

weights
(32-bit float)

2.09	-0.98	1.48	0.09
0.05	-0.14	-1.08	2.12
-0.91	1.92	0	-1.03
1.87	0	1.53	1.49

$\div$ **1.07**

scale
(32-bit float)

$+$ **-1**

zero point
(2-bit signed int)

$q = r \div S + Z$

Integer **Floating-point** **Floating-point** **Integer**

Integer

[실습1] Linear Quantization 함수 구현


```
############### YOUR CODE STARTS HERE ###############
# Step 1: fp_tensor를 scale 하세요.
scaled_tensor = fp_tensor/scale
# Step 2: 부동 소수점 값을 정수 값으로 rounding 하세요.
rounded_tensor = torch.round(scaled_tensor)
############### YOUR CODE ENDS HERE #################

rounded_tensor = rounded_tensor.to(dtype)

############### YOUR CODE STARTS HERE ###############
# Step 3: rounded_tensor를 zero_point 만큼 shift하여 영점을 조정합니다.
shifted_tensor = rounded_tensor + zero_point
############### YOUR CODE ENDS HERE #################
```

Linear Quantization – Scale

Linear Quantization is an affine mapping of integers to real numbers $r = S(q - Z)$



$$r_{max} = S\left(q_{max} - Z\right)$$

$$r_{min} = S\left(q_{min} - Z\right)$$

$$\downarrow$$

$$r_{max} - r_{min} = S\left(q_{max} - q_{min}\right)$$

$$S = \frac{r_{max} - r_{min}}{q_{max} - q_{min}}$$

Linear Quantization – Scale

Linear Quantization is an affine mapping of integers to real numbers $r = S(q - Z)$



Binary	Decimal
01	1
00	0
11	-1
10	-2

2.09	-0.98	1.48	0.09
0.05	-0.14	-1.08	2.12
-0.91	1.92	0	-1.03
1.87	0	1.53	1.49

Min & Max value of fp tensor

$$S = \frac{r_{max} - r_{min}}{q_{max} - q_{min}}$$

$$= \frac{2.12 - (-1.08)}{1 - (-2)}$$

$$= 1.07$$

Linear Quantization – Zero Point

Linear Quantization is an affine mapping of integers to real numbers $r = S(q - Z)$



$$r_{min} = S\left(q_{min} - Z\right)$$

$$\downarrow$$

$$Z = q_{min} - \frac{r_{min}}{S}$$

Linear Quantization – Zero Point

Linear Quantization is an affine mapping of integers to real numbers $r = S(q - Z)$



$$r_{min} = S\left(q_{min} - Z\right)$$

$$\downarrow$$

Floating-point

$$\underset{\text{Integer}}{Z} = \boxed{\underset{\text{Integer}}{q_{min}} - \underset{\text{Floating-point}}{\frac{r_{min}}{S}}}$$

$$\downarrow$$

$$Z = \text{round}\left(q_{min} - \frac{r_{min}}{S}\right)$$

[실습2] Scale and Zero Point 계산

Linear Quantization is an affine mapping of integers to real numbers $r = S(q - Z)$



$$S = \frac{r_{max} - r_{min}}{q_{max} - q_{min}}$$

$$Z = \text{round}\left(q_{min} - \frac{r_{min}}{S}\right)$$

[실습2] Scale and Zero Point 계산


```
############### YOUR CODE STARTS HERE ###############
# hint: quantized_max - quantized_min = 2 ** bitwith - 1
scale = (fp_max - fp_min) / (quantized_max - quantized_min)
zero_point = round(quantized_min - fp_min/scale)
############### YOUR CODE ENDS HERE ################
```

Per-Channel Linear Quantization

- Different scaling factors **S** and zero points **Z** for **different output channels** will **perform better**





Quantized Matrix Multiplication

Linear Quantization is an affine mapping of integers to real numbers $r = S(q - Z)$

- Consider the following matrix multiplication, when Zw=0.

$$\mathbf{Y} = \mathbf{W}\mathbf{X}$$

$$\mathbf{q}_\mathbf{Y} = \frac{S_\mathbf{W} S_\mathbf{X}}{S_\mathbf{Y}} \left(\mathbf{q}_\mathbf{W}\mathbf{q}_\mathbf{X} - Z_\mathbf{W}\mathbf{q}_\mathbf{X} - Z_\mathbf{X}\mathbf{q}_\mathbf{W} + Z_\mathbf{W}Z_\mathbf{X} \right) + Z_\mathbf{Y}$$

Precompute

N-bit Integer Multiplication
32-bit Integer Addition/Subtraction

N-bit Integer Addition

$$Z_\mathbf{W} = 0$$

$$\mathbf{q}_\mathbf{Y} = \frac{S_\mathbf{W} S_\mathbf{X}}{S_\mathbf{Y}} \left(\mathbf{q}_\mathbf{W}\mathbf{q}_\mathbf{X} - Z_\mathbf{X}\mathbf{q}_\mathbf{W} \right) + Z_\mathbf{Y}$$



Quantized Inference

$$\mathbf{Y} = \mathbf{W}\mathbf{X} + \mathbf{b}$$

$$S_{\mathbf{Y}}\left(\mathbf{q}_{\mathbf{Y}} - Z_{\mathbf{Y}}\right) = S_{\mathbf{W}}\left(\mathbf{q}_{\mathbf{W}} - Z_{\mathbf{W}}\right) \cdot S_{\mathbf{X}}\left(\mathbf{q}_{\mathbf{X}} - Z_{\mathbf{X}}\right) + S_{\mathbf{b}}\left(\mathbf{q}_{\mathbf{b}} - Z_{\mathbf{b}}\right)$$

$$\downarrow \; Z_{\mathbf{W}} = 0$$

$$S_{\mathbf{Y}}\left(\mathbf{q}_{\mathbf{Y}} - Z_{\mathbf{Y}}\right) = S_{\mathbf{W}}S_{\mathbf{X}}\left(\mathbf{q}_{\mathbf{W}}\mathbf{q}_{\mathbf{X}} - Z_{\mathbf{X}}\mathbf{q}_{\mathbf{W}}\right) + S_{\mathbf{b}}\left(\mathbf{q}_{\mathbf{b}} - Z_{\mathbf{b}}\right)$$

$$\downarrow \; Z_{\mathbf{b}} = 0, \quad S_{\mathbf{b}} = S_{\mathbf{W}}S_{\mathbf{X}}$$

$$S_{\mathbf{Y}}\left(\mathbf{q}_{\mathbf{Y}} - Z_{\mathbf{Y}}\right) = S_{\mathbf{W}}S_{\mathbf{X}}\left(\mathbf{q}_{\mathbf{W}}\mathbf{q}_{\mathbf{X}} - Z_{\mathbf{X}}\mathbf{q}_{\mathbf{W}} + \mathbf{q}_{\mathbf{b}}\right)$$

Quantized Inference

$$\mathbf{Y} = \mathbf{W}\mathbf{X} + \mathbf{b}$$

$$Z_{\mathbf{W}} = 0 \downarrow Z_{\mathbf{b}} = 0, \quad S_{\mathbf{b}} = S_{\mathbf{W}} S_{\mathbf{X}}$$

$$S_{\mathbf{Y}} \left(\mathbf{q}_{\mathbf{Y}} - Z_{\mathbf{Y}} \right) = S_{\mathbf{W}} S_{\mathbf{X}} \left(\mathbf{q}_{\mathbf{W}} \mathbf{q}_{\mathbf{X}} - Z_{\mathbf{X}} \mathbf{q}_{\mathbf{W}} + \mathbf{q}_{\mathbf{b}} \right)$$

$$\downarrow$$

$$\mathbf{q}_{\mathbf{Y}} = \frac{S_{\mathbf{W}} S_{\mathbf{X}}}{S_{\mathbf{Y}}} \left(\mathbf{q}_{\mathbf{W}} \mathbf{q}_{\mathbf{X}} + \boxed{\text{Precompute } \mathbf{q}_{\mathbf{b}} - Z_{\mathbf{X}} \mathbf{q}_{\mathbf{W}}} \right) + Z_{\mathbf{Y}}$$

$$\downarrow \mathbf{q}_{bias} = \mathbf{q}_{\mathbf{b}} - Z_{\mathbf{X}} \mathbf{q}_{\mathbf{W}}$$

$$\mathbf{q}_{\mathbf{Y}} = \frac{S_{\mathbf{W}} S_{\mathbf{X}}}{S_{\mathbf{Y}}} \left(\mathbf{q}_{\mathbf{W}} \mathbf{q}_{\mathbf{X}} + \mathbf{q}_{bias} \right) + Z_{\mathbf{Y}}$$

[실습3] Quantized Fully-Connected Layer

$$\mathbf{Y} = \mathbf{W}\mathbf{X} + \mathbf{b}$$

$$Z_{\mathbf{W}} = 0$$

$$Z_{\mathbf{b}} = 0, \quad S_{\mathbf{b}} = S_{\mathbf{W}} S_{\mathbf{X}}$$

$$\mathbf{q}_{bias} = \mathbf{q}_{\mathbf{b}} - Z_{\mathbf{X}} \mathbf{q}_{\mathbf{W}}$$

$$\mathbf{q}_{\mathbf{Y}} = \boxed{\frac{S_{\mathbf{W}} S_{\mathbf{X}}}{S_{\mathbf{Y}}}} \left(\boxed{\mathbf{q}_{\mathbf{W}} \mathbf{q}_{\mathbf{X}} + \mathbf{q}_{bias}} \right) + \boxed{Z_{\mathbf{Y}}}$$

***N*-bit Int Mult.**
32-bit Int Add.

***N*-bit Int**
Add

Note: both $\mathbf{q}_{\mathbf{b}}$ and $\mathbf{q}_{bias}$ are 32 bits.

[실습3] Quantized Convolution Layer

$$\mathbf{Y} = \text{Conv}(\mathbf{W}, \mathbf{X}) + \mathbf{b}$$

$$Z_{\mathbf{W}} = 0$$

$$Z_{\mathbf{b}} = 0, \quad S_{\mathbf{b}} = S_{\mathbf{W}} S_{\mathbf{X}}$$

$$\mathbf{q}_{bias} = \mathbf{q}_{\mathbf{b}} - \text{Conv}(\mathbf{q}_{\mathbf{W}}, Z_{\mathbf{X}})$$

$$\mathbf{q}_{\mathbf{Y}} = \frac{S_{\mathbf{W}} S_{\mathbf{X}}}{S_{\mathbf{Y}}} \left(\text{Conv}(\mathbf{q}_{\mathbf{W}}, \mathbf{q}_{\mathbf{X}}) + \mathbf{q}_{bias} \right) + Z_{\mathbf{Y}}$$

***N*-bit Int Mult.**
32-bit Int Add.

***N*-bit Int**
Add

Note: both $\mathbf{q}_{\mathbf{b}}$ and $\mathbf{q}_{bias}$ are 32 bits.

[실습3] Quantized Layer


```
############### YOUR CODE STARTS HERE ###############
# Step 2: output 텐서를 scale합니다.
output = output*(input_scale * weight_scale / output_scale)

# Step 3: output을 out_zero_point 만큼 이동하여 영점을 조정합니다.
output = output + output_zero_point
############### YOUR CODE ENDS HERE ################
```

```
############### YOUR CODE STARTS HERE ###############
# hint: 이번 코드 블록은 quantized_linear()와 매우 유사합니다.

# Step 2: output 텐서를 scale합니다.
output = output*(input_scale * weight_scale / output_scale)

# Step 3: output을 out_zero_point 만큼 이동하여 영점을 조정합니다.
output = output + output_zero_point
############### YOUR CODE ENDS HERE ################
```

Model Fusion

- We can **fuse** a **BatchNorm** layer into its previous **convolutional layer**
- Fusing model can reduce the extra multiplication during inference



Input: Values of x over a mini-batch: $\mathcal{B} = \{x_{1\ldots m}\}$;
Parameters to be learned: γ, β

Output: $\{y_i = \mathrm{BN}_{\gamma,\beta}(x_i)\}$

$$\mu_\mathcal{B} \leftarrow \frac{1}{m}\sum_{i=1}^{m} x_i \qquad \text{// mini-batch mean}$$

$$\sigma_\mathcal{B}^2 \leftarrow \frac{1}{m}\sum_{i=1}^{m} (x_i - \mu_\mathcal{B})^2 \qquad \text{// mini-batch variance}$$

$$\widehat{x}_i \leftarrow \frac{x_i - \mu_\mathcal{B}}{\sqrt{\sigma_\mathcal{B}^2 + \epsilon}} \qquad \text{// normalize}$$

$$\boxed{y_i \leftarrow \gamma \widehat{x}_i + \beta \equiv \mathrm{BN}_{\gamma,\beta}(x_i)} \qquad \text{// scale and shift}$$

Algorithm 1: Batch Normalizing Transform, applied to activation x over a mini-batch.

Inference with quantized model

Neural Network	ResNet-50	Inception-V3
Floating-point Accuracy	76.4%	78.4%
8-bit Integer-quantized Acurracy	74.9%	75.4%



Latency-vs-accuracy tradeoff of float vs. integer-only MobileNets on ImageNet using Snapdragon 835 big cores.

K-Means Clustering

- Popular **unsupervised** learning algorithm to group data into K clusters
- Select K initial centroids and assign each data point into nearest centroids
- Update centroids by calculating the mean of the assigned points



K-Means-based Weight Quantization

weights
(32-bit float)

2.09	-0.98	1.48	0.09
0.05	-0.14	-1.08	2.12
-0.91	1.92	0	-1.03
1.87	0	1.53	1.49

~~2.09, 2.12, 1.92, 1.87~~

↓

2.0

Cluster →



weights
(32-bit float)

2.09	-0.98	1.48	0.09
0.05	-0.14	-1.08	2.12
-0.91	1.92	0	-1.03
1.87	0	1.53	1.49

K-Means-based Weight Quantization

weights
(32-bit float)

2.09	-0.98	1.48	0.09
0.05	-0.14	-1.08	2.12
-0.91	1.92	0	-1.03
1.87	0	1.53	1.49

cluster

cluster index
(2-bit int)

3	0	2	1
1	1	0	3
0	3	1	0
3	1	2	2

indexes

centroids

3:	2.00
2:	1.50
1:	0.00
0:	-1.00

codebook

reconstructed weights
(32-bit float)

2.00	-1.00	1.50	0.00
0.00	0.00	-1.00	2.00
-1.00	2.00	0.00	-1.00
2.00	0.00	1.50	1.50

quantization error

0.09	0.02	-0.02	0.09
0.05	-0.14	-0.08	0.12
0.09	-0.08	0	-0.03
-0.13	0	0.03	-0.01

storage

32 bit × 16
= 512 bit = 64 B

2 bit × 16
= 32 bit = 4 B **+**

32 bit × 4
= 128 bit = 16 B **=** 20 B

3.2 × smaller

[실습4] K-Means Quantization 함수 구현

- Get number of clusters (2^n) based on the quantization precision
- **Decode** the codebook into k-means quantized tensor for inference



[실습4] K-Means Quantization 함수 구현


```
    ############### YOUR CODE STARTS HERE ###############
    # bitwidth에 따라 클러스터 수를 설정하세요.
    n_clusters = 2**bitwidth
    ############### YOUR CODE ENDS HERE #################
    # k-means를 사용하여 quantization centroid를 얻습니다.
    kmeans = KMeans(n_clusters=n_clusters, mode='euclidean', verbose=0)
    labels = kmeans.fit_predict(fp32_tensor.view(-1, 1)).to(torch.long)
    centroids = kmeans.centroids.to(torch.float).view(-1)
    codebook = Codebook(centroids, labels)
############### YOUR CODE STARTS HERE ###############
# 추론에서 사용할 quantized tensor를 구하기 위해 코드북을 디코딩하세요.
quantized_tensor = codebook.centroids[codebook.labels]
############### YOUR CODE ENDS HERE #################
```

QAT with K-means quantization

Fine-tuning Quantized Weights



[실습5] Fine-tuning K-means quantization

Fine-tuning Quantized Weights



For simplicity, **directly** update the centroids according to the latest weights

[실습5] Fine-tuning K-means quantization


```
############### YOUR CODE STARTS HERE ###############
# hint : torch.mean() 함수를 이용하여 평균을 구할 수 있습니다.
    codebook.centroids[k] = torch.mean(fp32_tensor[codebook.labels==k])
############### YOUR CODE ENDS HERE #################
```

Quantization with PyTorch API

Machine Learning Libraries

Quantization with PyTorch API

33