

GD-PMS Frontend Design Inventory

Version: 1.0 **For:** UX Designers **Storybook:** <https://ilterisyucel.github.io/monorepo-bun-starter/>

This document shows all pages, layouts, and components in the three GD-PMS frontend apps. It is a reference for the UX design team.

1. Overview

GD-PMS has three separate React apps for site management:



All three apps use the same shared component library `@gd-monorepo/ui`. Common features: dark/light theme, Turkish/English language support.

2. Shared UI Library (`@gd-monorepo/ui`)

All components below are used by all three apps. The UX team should use these as building blocks.

2.1 Device Cards

Component	What it shows
BSCCard	Battery container card: status badge, SoC, voltage, current, power, temperature, cell data
RackCard	Rack card: status badge, SoC, voltage, current, power, temperature
CBCard	Circuit breaker card: open/closed/tripped state, voltage, current, trip/close counters
DCOutputCard	DC output card: on/off, actual and set voltage/current

Component	What it shows
HvacCard	HVAC card: running/standby/fault badge, mode (cooling/heating/idle), temperatures, humidity, alarm count
FirePanelCard	Fire panel card: fire detected yes/no, fault yes/no, relay states
EnergyAnalyzerCard	Energy analyzer card: 3-phase voltage/current/power, power factor, THD, energy counters
ContainerCard	Container summary card: status dot, SoC bar, power, temperature, device count
FieldCard	Field summary card: status, power, SoC, container count

2.2 SCADA Graphics (PixiJS)

Real-time animated industrial visuals. All work with dark theme.

Component	What it shows
BSC	Battery container diagram: racks, bus bars, breakers, DC outputs, cables, flow arrows, labels
TMS	Thermal management diagram: rooms, HVAC units, temperature/humidity panel
BESSDiagram	Full site panorama: BSCs, TMS, fire panel, energy analyzer, transformer — all on one canvas
RackCell	Rack cell: rectangle colored by SoC level, hover shows info popover
CircuitBreaker	Breaker graphic: open/closed/tripped visual
DCOutput	DC output graphic: on/off visual
HvacUnit	HVAC unit: fan animation spins based on status
PanelCard	Temperature/humidity display graphic
FirePanel	Fire panel status graphic
EnergyAnalyzerGraphic	Energy analyzer graphic

2.3 Charts

Component	What it does
TelemetryChart	Time series chart: one or more devices, multiple metrics, time range picker, multi-metric select, data points control, device filter
SingleTelemetryChart	Chart for a single telemetry metric across one or more devices
MultiLineChart	Multi-line chart with event markers
TelemetryGauge	SVG circular gauge (240° arc), threshold colors

Component	What it does
<code>DeviceGauges</code>	Responsive grid of <code>TelemetryGauges</code> for one device

2.4 Control and Status Components

Component	What it does
<code>ManeuverCard</code>	Command card: idle/running/success/failed states, input fields, step list, timer, rollback button
<code>TelemetryInput</code>	Value input: step buttons, range bar, threshold lines, unit label
<code>SummaryCard</code>	KPI card: icon + value + label, colored by status
<code>LogTerminal</code>	Log viewer: type icons (success/error/warning/info), source icons, auto-scroll
<code>DeviceTable</code>	Device list table: ID, name, type, protocol, rack, model, status, detail button
<code>DeviceDetailModal</code>	Device detail modal window
<code>StatusBadge</code>	Status badges: Online, Offline, Charge, Discharge, Idle
<code>ContainerConnectionBadge</code>	Container connection status badge
<code>MetricBar</code>	Horizontal progress bar (0-100%)
<code>MetricDisplay</code>	<code>MetricBar</code> + value + label combined
<code>DeviceTelemetryProvider</code>	Per-device isolated gauge component (contains <code>Gauge</code> and <code>StatusBadge</code>)
<code>FieldMap</code>	Leaflet site map, colored circle markers
<code>PlayCanvasViewer</code>	3D container visualization

2.5 Atom Components

Component	Purpose
<code>Card</code>	Generic card container
<code>CardGrid</code>	4-column responsive grid
<code>CardHeader</code>	Card header: name + badge slot
<code>ChartGrid</code>	2-column chart grid
<code>DataGrid</code>	2-column data grid
<code>DataRow</code>	Icon + label + value row
<code>SectionHeader</code>	Section title divider
<code>Tabs</code>	Tab container

2.6 Icons

46 icons. All from Tabler Icons family.

Category	Icons
Navigation	dashboard, bsc, hvac, analytics, energyAnalyzer, charts, reports, events, control, settings, scadaChart
Status	statusOnline, statusOffline, statusIdle, logSuccess, logError, logWarning, logInfo
Device	battery, batteryCharge, batteryDischarge, container, circuitBreaker, dcOutput, hvacUnit, fireAlarm
Action	refresh, add, trash, stop, continuous, timer, zoomIn, close, collapse, menu
Other	powerPlug, temperature, health, emergency, logo, user, logout, sourceCommand, sourceScheduler, sourceSystem

2.7 Color System

104 tokens. Works in CSS (hex) and PixiJS (0x) formats.

Group	Count	Examples
Status	14	Success (#10b981), Warning (#f59e0b), Error (#ef4444), Info (#3b82f6), Idle
Surface	14	Background, card, popup, header, input, panel, skeleton, hover
Text	10	Primary, white, muted, disabled, purple, gray
Border	5	Default, stroke, light, hover
Gradient	9	Body, mid, low, screen, panel
Chart	16	chart1-chart16 (data series colors)
Temperature	3	Cold, chilly, hot
Special	21	Cable, terminal, shadow, DC active/idle, opacity variants
Accent	2	Light, dark

3. Container-Level App (container-web)

Deep monitoring and control of a single energy container. The most mature app with the most pages.

Total pages: 13 (11 done, 2 placeholder)

Layout

- **Sidebar:** Fixed 80px width. 11 navigation icons (dashboard, scada, bsc, fire, energy-analyzer, hvac, control, events, reports, devices)
- **System Header:** Horizontal status bar. Charge/discharge/idle icon, container ID, PPC connection (green/red), live clock, power usage (color coded: green <100kW, yellow <300kW, red >300kW),

ambient temperature and humidity.

Page List

#	Page	Route	Status
1	Login	/login	Done
2	Main Dashboard	/, /dashboard	Done
3	SCADA Panorama	/scada	Done
4	BSC Detail	/bsc	Done
5	HVAC Detail	/hvac	Done
6	Fire Panel	/fire	Done
7	Energy Analyzer	/energy-analyzer	Done
8	Maneuver Control	/control	Done
9	System Charts	/system-charts	Done
10	Events	/events	Done
11	Reports	/reports	Placeholder
12	Devices	/devices	Done
13	Settings	(sidebar popup)	Done

3.1 Login ([/login](#))

Centered card on dark fullscreen background. Logo + "EMS" title, username input, password input, login button. "or" divider with guest login button below. Demo credentials hint. No role selection — role is auto-detected on login.

3.2 Main Dashboard ([/, /dashboard](#))

Summary view of the container's current state.

Layout:

1. **Device Gauges:** [DeviceGauges](#) per device — SoC, SoH, Power, Voltage, Current circular gauge displays.
2. **LogTerminal:** System events (bottom of page).

Data: Live.

3.3 SCADA Panorama ([/scada](#))

All SCADA visuals on one page.

Layout:

1. **BSC** PixiJS graphic: 8 battery racks, bus bars, breakers, DC outputs, animated flow arrows, summary panel. Right-click a rack cell → info popover (SoC, voltage, current, temperature).
2. **TMS** PixiJS HVAC graphic: rooms, animated HVAC units, temperature/humidity panel.
3. **BESSDiagram** panorama: all BSCs, TMS, fire panel, energy analyzer, transformer (single canvas, 1200px).
4. **LogTerminal** (bottom of page).

Data: Live.

3.4 BSC Detail (/bsc)

Full detail of the battery system. One of the biggest pages.

Layout (top to bottom):

1. **SectionHeader** ("BSC")
2. **Summary Cards (2):** **BSCCard** for BSC-1 and BSC-2 (SoC, SoH, power, voltage)
3. **Racks:** **SectionHeader** ("Racks"), **CardGrid** with **RackCards** (Rack-1 through Rack-8). Each card: status badge, SoC, voltage, current, power, temperature.
4. **BSC Charts:** **SingleTelemetryChart** per device, plus one combined comparison chart.
5. **Breakers:** **SectionHeader** ("Breakers"), **CardGrid** with **CBCards** (open/closed/tripped).
6. **DC Outputs:** **SectionHeader** ("DC Outputs"), **CardGrid** with **DCOutputCards**.
7. **CB and DC Charts.**

Interactions: Click **RackCard** → **RackDetailModal**. Click "Detail" button → **DeviceDetailModal**.

Data: Live.

3.5 HVAC Detail (/hvac)

Detailed view of heating/cooling units.

Layout:

1. **Summary Cards (4-grid):** Average temperature, average humidity, running/total units, system status (normal/warning).
2. **Unit Cards:** **SectionHeader** ("HVAC Units"), **CardGrid** with **HvacCards**. Each card: room name, status badge (running/standby/fault), current temperature, mode (cooling/heating/idle), set temperature, supply/return temperatures, humidity, equipment status, alarm count.
3. **Charts:** **SingleTelemetryChart** per unit, plus one combined comparison chart (with event markers).

Data: Live.

3.6 Fire Panel (/fire)

Fire alarm panel (EP203) monitoring.

Layout:

1. **Status Cards (3-grid):** System status (OK/WARNING), fire detected (yes/no), fault (yes/no). Color coded (green/red).
2. **FirePanelCard:** EP203 relay states — first stage, second stage, discharged, mute, hold, abort, auto mode, local fire, reset.
3. **Chart:** Time series chart.

Data: Live.

3.7 Energy Analyzer (/energy-analyzer)

PM5340 energy analyzer phase-by-phase detail.

Layout:

1. **Summary Cards (3):** Frequency (Hz), total active power (kW), active energy (kWh).
2. **EnergyAnalyzerCard:** Per phase (L1/L2/L3) — phase-neutral and phase-phase voltage, current, active/reactive/apparent power, power factor, THD, neutral current, demand values, energy counters.
3. **Chart:** Time series chart.

Data: Live.

3.8 Maneuver Control (/control)

Send commands and run multi-device maneuvers.

Layout: Full-width masonry grid (cards flow by content size).

Content: 18 **ManeuverCards**:

- Battery: Charge, discharge, stop
- Emergency stop
- HVAC: Turn on, turn off, force cool, force heat
- Breakers: Open, close, reset
- DC outputs: Turn on, turn off

Each ManeuverCard has:

- State machine: idle → "Run" button (split: Now / Schedule), running → disabled "Running...", success → green check, failed → "Retry" + "Rollback" buttons
- Input fields: number inputs (e.g. power kW), with min/max limits
- Timer: "Scheduled" checkbox → date/time picker → countdown
- Step list: preview of which devices will get which commands

Interaction: Run button sends command directly (no modal). Result shown on the card.

Data: Live.

3.9 System Charts (/system-charts)

Time series charts for all BSC and XRack system metrics.

Layout: Full-width `SingleTelemetryChart` (500px).

Metrics: SOC, SOH, Voltage, Current, ChargePower, DischargePower, Temperature, BalanceTime, etc.

Chart controls:

- Time range picker: 1min / 1hr / 1day / 1week / 1month / 3months / 6months / 1year / custom
- Multi-metric select (grouped: basic / detail)
- Data points: 60 / 120 / 240 / 500
- Device filter dropdown
- Event markers on/off

Data: Live.

3.10 Events (`/events`)

Log viewer for system events and user actions.

Layout: Two columns.

- Left: `LogTerminal` — "System Events & Errors" (warning icon, 800px)
- Right: `LogTerminal` — "User Actions" (user icon, 800px)

Interaction: Each terminal is independent: type filter (success/error/warning/info), auto-scroll on/off, clear logs.

Data: Live.

3.11 Reports (`/reports`) — Placeholder

Current state: Centered card, document icon, "This page is under development" message.

Planned: PDF report generation, Excel export.

3.12 Devices (`/devices`)

Inventory table of all devices in the container.

Layout: Full-width `DeviceTable`. Columns: ID, Name, Type, Protocol, Rack, Model, Status, Detail button. Sorted by type (BSC → XRack → HVAC → CB → DC-Output).

Interaction: "Detail" button → `DeviceDetailModal` (telemetry register map).

Data: Live.

3.13 Settings (Sidebar Popup)

Opened by the settings icon in the sidebar. Two tabs:

- **Options:** Language picker (Turkish/English toggle), Theme picker (Light/Dark toggle)
- **Users (admin only):** User list, create new user form (username, full name, password, role picker)

Data: Live.

4. Field-Level App (**field**)

Overview of all containers under a single field site.

Total pages: 9 (7 done, 2 placeholder)

Note: All pages currently use sample data. Backend development for live data is ongoing.

Layout

- **Sidebar:** Collapsible (260px / 70px), with transition animation. "SCS" logo, 7 navigation icons (Dashboard, Containers, Charts, Control, Events, Reports, Devices). Bottom area: user profile (avatar + name + role badge), emergency stop button, logout.
- **System Header:** 4-box grid — Field ID, PPC connection (green/red), online/total container count, live clock.
- **Emergency stop:** Navigates to the Control page, does not send a command directly.

Page List

#	Page	Route	Status
1	Login	/login	Done
2	Field Dashboard	/field/:fieldId	Done (sample data)
3	Containers	/field/:fieldId/containers	Done (sample data)
4	Container Detail	/field/:fieldId/containers/:containerId	Done (sample data)
5	Charts	/field/:fieldId/charts	Done (sample data)
6	Maneuver Control	/field/:fieldId/control	Placeholder
7	Events	/field/:fieldId/events	Done (sample data)
8	Reports	/field/:fieldId/reports	Placeholder
9	Devices	/field/:fieldId/devices	Done (sample data)

4.1 Login (**/login**)

Same layout as container-web login. Centered card, username/password, login button. No guest login.

4.2 Field Dashboard (**/field/:fieldId**)

Summary of all containers under the field.

Layout:

1. **KPI Cards (4-grid):** **SummaryCard** — Total power (MW), average SoC (%), online/total containers, offline/alarm container count (red highlight)
2. **Container Grid:** Responsive auto-fit grid. Each card is a **ContainerCard**: status dot (green/yellow/red), container name, SoC bar, power (kW), connected/disconnected badge.

Interaction: Click a card → container detail page.

Data: Sample (3 containers).

4.3 Containers (/field/:fieldId/containers)

Grid view of all containers on the field.

Layout: Grid of **ContainerCards**. Each card: name, status badge, connection state, SoC, power, temperature, device counts.

Interaction: Click a card → container detail page.

Data: Sample.

4.4 Container Detail (/field/:fieldId/containers/:containerId)

Deep view of devices inside one container.

Layout:

1. **Header:** Back button, container name, **ContainerConnectionBadge**
2. **Summary Mini Cards (3):** SoC (%), Status, Device count
3. **Device Cards (grouped by type):**
 - **BSC:** 3x2 grid of mini metric boxes — SoC, SoH, Voltage, Current, Power, Temperature (each with icon)
 - **CB:** Closed/Open status, Tripped/Normal status
 - **DC Output:** On/Off status, DC Voltage, DC Current
 - **HVAC:** Room count + average temperature

Data: Sample.

4.5 Charts (/field/:fieldId/charts)

Field-level telemetry charts.

Layout: Full-width **TelemetryChart** (480px).

Metrics: SOC, Power, Voltage, Current, MaxCellTemperature.

Chart controls: Time range picker, metric selector, data points control, container filter.

Data: Sample (288-point time series).

4.6 Maneuver Control (/field/:fieldId/control) — Placeholder

Current state: Centered card, "Field-level maneuvers — ManeuverPanel will be added" message.

Planned: Field-level batch commands (charge all, discharge all, emergency stop).

4.7 Events (/field/:fieldId/events)

Event logs for containers under the field.

Layout: Two columns. Left: System Events, Right: User Actions. Each is a **LogTerminal** (800px). Filter by container.

Data: Sample (15 system + 15 user logs).

4.8 Reports (/field/:fieldId/reports) — Placeholder

Current state: Centered card, "Reports page not yet implemented" message.

4.9 Devices (/field/:fieldId/devices)

Device inventory table with container selector.

Layout: Container selector dropdown + **DeviceTable**. 10 device definitions (BSC-1/2, CB-1/2, DC-1/2, HVAC-1/2/3/4).

Data: Sample.

5. Boss-Level App (superadmin)

Multi-site overview for managers. Mobile-first. PWA supported (can be installed on phone home screen).

Total pages: 3 (all use sample data)

Layout

- **Header Bar:** Fixed 48px. Left: "CCC" logo. Right: username + "Logout" button. No sidebar.
- **Navigation:** Two levels — Dashboard ↔ Field Detail.

Page List

#	Page	Route	Status
1	Login	/login	Done
2	Dashboard	/dashboard	Done (sample data)
3	Field Detail	/fields/:id	Done (sample data)

5.1 Login (/login)

Same as the other apps.

5.2 Dashboard (/dashboard)

Map and list view of all sites.

Layout:

- 1. **Field Map (top ~40%):** `FieldMap` (Leaflet). 3 field markers on a map. Colored circles, clickable.
- 2. **Field Cards List (bottom):** `FieldCards` (`size="small"`). Each card: field name, status, power (MW), SoC (%), container count. Clickable.

Interaction: Click a map marker or card → field detail page.

Data: Sample (3 fields).

5.3 Field Detail (/fields/:id)

Summary and container status for a selected field.

Layout:

- 1. **Header:** Back button, field ID, refresh button
- 2. **Summary Grid (2x2):** 4 `SummaryCards` — Total Power, Average SoC, Container Count, Alarms
- 3. **Container List:** Each row shows container name + `ContainerConnectionBadge` (connected/disconnected)

Data: Sample (4 containers).

6. Overall Summary

App	Total Pages	Done	Placeholder	Data Status
container-web	13	11	2	Live
field	9	7	2	Sample
superadmin	3	3	0	Sample
Total	25	21	4	

Placeholder Pages

#	Page	App	Current State
1	Reports	container-web	"Under development"
2	Reports	field	"Not yet implemented"

#	Page	App	Current State
3	Maneuver Control	field	"ManeuverPanel will be added"

Note: superadmin app has no placeholder pages.

This document is a reference for the UX design team. It shows the current state of all GD-PMS frontend apps.