

XRPL Validator — Daily Engineering Report • 2026-04-21

Compiled retrospectively on 2026-09-23 from the git history. Scope: XRPL work only — the git history of [xrpl-validator](#) and the XRPL Rust SDK, the XRP Ledger itself (amendments) and XRPL research.

Summary

- **6 commits** (xrpl-validator 6)
- 1 test / vector commit

Engineering changes

- **fix(ffl_engine): OverlayedDbProvider::succ() must consult overlay, not just snapshot** (69bc726 , xrpl-validator) The previous implementation iterated only the RocksDB snapshot, so when an earlier transaction in the same ledger modified or deleted an SLE in a directory the current transaction walks (Offer-book traversal in particular), libxrpl saw a stale RocksDB neighbor and crossed wrong offers. Cascade: wrong mutations -> wrong sequence -> tefPAST_SEQ on downstream transactions from the same accounts.
- **fix(ffl_engine): tefBAD_LEDGER recovery — fetch missing SLE and retry apply** (6dd8f22 , xrpl-validator) When AccountDelete walks the deleted account's owner directory, libxrpl FFI returns `tefBAD_LEDGER` with a fatal message like: "DeleteAccount: directory node in ledger N has index to object that is missing: <64-hex-key>" meaning state.rocks is missing an SLE referenced by the owner dir (bulk_sync / ws_sync completeness gap). Historically these divergences also cascaded: 100% of observed Payment terPRE_SEQ ...
- **feat(dashboard): /logs page — progress journal + live GitHub changelog** (8176931 , xrpl-validator) Adds a new /logs route with two tabs: - PROGRESS — hand-written narrative sourced from PROGRESS.md at the repo root. Read at request time via fs.readFileSync so edits to the markdown show up without a rebuild. Clearly labeled as manually-curated.
- **fix(ffl_engine): loop tefBAD_LEDGER recovery for multi-missing-SLE owner dirs** (4ab09ec , xrpl-validator) The single-try recovery shipped in 6dd8f22 handles AccountDeletes with exactly one missing SLE in the owner directory. When the dir references multiple missing SLEs (NFTTokenOffers + Offers + RippleStates on an old high-activity account), the first retry injects SLE #1 but libxrpl then trips on SLE #2 and returns `tefBAD_LEDGER` again.

Tests and campaigns

- **test(node): add release-safety guard against shipped seeds, tokens, and non-local IPs** (cbda593 , xrpl-validator)

Docs and operations

- docs(progress): redact file:line for unfixed SEV findings (a59ae04 , xrpl-validator)

Appendix — commits

Time	Repo	Commit	Subject
01:40	xrpl-validator	cbda593	test(node): add release-safety guard against shipped seeds, tokens, and non-local IPs
02:10	xrpl-validator	69bc726	fix(ffi_engine): OverlayedDbProvider::succ() must consult overlay, not just snapshot
12:00	xrpl-validator	6dd8f22	fix(ffi_engine): tefBAD_LEDGER recovery — fetch missing SLE and retry apply
12:29	xrpl-validator	8176931	feat(dashboard): /logs page — progress journal + live GitHub changelog
12:32	xrpl-validator	a59ae04	docs(progress): redact file:line for unfixed SEV findings
12:42	xrpl-validator	4ab09ec	fix(ffi_engine): loop tefBAD_LEDGER recovery for multi-missing-SLE owner dirs