

```
TRUNCATE TABLE player_prize, team_prize, match_team, match, roster_player,  
roster, player, team, tournament  
RESTART IDENTITY CASCADE;
```

```
INSERT INTO tournament (name, start_date, prize)  
VALUES  
('Major Kyiv', '2026-03-10', 500000),  
('Summer Cup', '2026-07-15', 150000),  
('Winter Clash', '2026-12-01', 200000);
```

```
INSERT INTO team (name)  
VALUES  
('NAVI'),  
('G2'),  
('Liquid');
```

```
INSERT INTO player (nick, age)  
VALUES  
('s1mple', 27),  
('b1t', 21),  
('NiKo', 28),  
('m0NESY', 19),  
('YEKINDAR', 23);
```

```
INSERT INTO roster (team_id, start_date)  
VALUES  
(1, '2026-01-01'),  
(2, '2026-01-01'),  
(3, '2026-01-01');
```

```
INSERT INTO roster_player (roster_id, player_id)  
VALUES  
(1, 1), (1, 2),  
(2, 3), (2, 4),  
(3, 5);
```

```
INSERT INTO match (tournament_id, score)  
VALUES  
(1, '2:1'),  
(1, '0:2');
```

```
INSERT INTO match_team (match_id, team_id)  
VALUES  
(1, 1), (1, 2),
```

(2, 2), (2, 3);

```
SELECT
  EXTRACT(YEAR FROM start_date) AS year,
  AVG(prize) AS avg_prize
FROM tournament
GROUP BY year;
```

	year numeric	avg_prize numeric
1	2026	283333.33333333333

```
SELECT
  t.name AS tournament,
  COUNT(m.id) AS matches_count
FROM match m
JOIN tournament t ON m.tournament_id = t.id
GROUP BY t.name;
```

	tournament character varying (100)	matches_count bigint
1	Major Kyiv	2

```
SELECT
  t.name AS tournament,
  COUNT(m.id) AS matches_count
FROM match m
JOIN tournament t ON m.tournament_id = t.id
GROUP BY ROLLUP (t.name);
```

	tournament character varying (100)	matches_count bigint
1	[null]	2
2	Major Kyiv	2

```
SELECT
  t.name AS tournament,
  COUNT(DISTINCT mt.team_id) AS teams_count
FROM match_team mt
JOIN match m ON mt.match_id = m.id
JOIN tournament t ON m.tournament_id = t.id
```

GROUP BY t.name;

	tournament character varying (100)	teams_count bigint
1	Major Kyiv	3

```
SELECT
    tm.name AS team,
    COUNT(rp.player_id) AS players_in_team
FROM roster r
JOIN team tm ON r.team_id = tm.id
JOIN roster_player rp ON rp.roster_id = r.id
GROUP BY tm.name;
```

	team character varying (100)	players_in_team bigint
1	G2	2
2	Liquid	1
3	NAVI	2

```
SELECT
    t.name AS tournament,
    tm.name AS team,
    COUNT(m.id) AS matches_played
FROM match_team mt
JOIN team tm ON mt.team_id = tm.id
JOIN match m ON mt.match_id = m.id
JOIN tournament t ON m.tournament_id = t.id
GROUP BY GROUPING SETS (
    (t.name, tm.name),
    (t.name),
    (tm.name),
    ()
);
```

	tournament character varying (100) 🔒	team character varying (100) 🔒	matches_played bigint 🔒
1	[null]	[null]	4
2	Major Kyiv	NAVI	1
3	Major Kyiv	G2	2
4	Major Kyiv	Liquid	1
5	Major Kyiv	[null]	4
6	[null]	G2	2
7	[null]	Liquid	1
8	[null]	NAVI	1

```

SELECT
    t.name AS tournament,
    tm.name AS team,
    COUNT(m.id) AS matches_played
FROM match_team mt
JOIN match m ON mt.match_id = m.id
JOIN team tm ON mt.team_id = tm.id
JOIN tournament t ON m.tournament_id = t.id
GROUP BY ROLLUP (t.name, tm.name);

```

	tournament character varying (100) 🔒	team character varying (100) 🔒	matches_played bigint 🔒
1	[null]	[null]	4
2	Major Kyiv	NAVI	1
3	Major Kyiv	G2	2
4	Major Kyiv	Liquid	1
5	Major Kyiv	[null]	4

```

SELECT
    tm.name AS team,
    p.nick AS player,
    p.age
FROM roster r
JOIN team tm ON r.team_id = tm.id
JOIN roster_player rp ON rp.roster_id = r.id
JOIN player p ON p.id = rp.player_id
GROUP BY ROLLUP (tm.name, p.nick, p.age);

```

	team character varying (100) 🔒	player character varying (50) 🔒	age integer 🔒
1	[null]	[null]	[null]
2	G2	NiKo	28
3	Liquid	YEKINDAR	23
4	G2	m0NESY	19
5	NAVI	s1mple	27
6	NAVI	b1t	21
7	G2	m0NESY	[null]
8	NAVI	s1mple	[null]
9	NAVI	b1t	[null]
10	Liquid	YEKINDAR	[null]
11	G2	NiKo	[null]
12	G2	[null]	[null]
13	Liquid	[null]	[null]
14	NAVI	[null]	[null]