



KubeCon



CloudNativeCon

Europe 2018

Kubernetes Storage Lingo 101

Saad Ali

Senior Software Engineer, Google

May 4, 2018



Agenda



KubeCon



CloudNativeCon

Europe 2018

- What do these words mean and how do they fit together?

Persistent Volume Claims Driver Persistent Volumes

Remote File Flex Block CSI Stateless

Storage Classes Ephemeral Local Out-of-tree

Dynamic Provisioning In-tree Volume Object

Stateful Plugin



KubeCon



CloudNativeCon

Europe 2018

Kubernetes Principle

Workload portability

Kubernetes: Workload Portability



KubeCon



CloudNativeCon


Europe 2018

Kubernetes Goal

- Abstract away cluster details
- Decouple apps from infrastructure

To enable users to

- Write once, run anywhere (workload portability!)
- Avoid vendor lock-in



Kubernetes



KubeCon



CloudNativeCon

Europe 2018

App 1

App 2

App 3

App 4



Kubernetes Cluster

Node 1

Kernel/OS

Hardware

Node 2

Kernel/OS

Hardware

Node 3

Kernel/OS

Hardware

Kubernetes



KubeCon



CloudNativeCon

Europe 2018

App 1

App 2

App 3

App 4



Kubernetes Cluster

GCE Instance 1

Kernel/OS

Hardware

GCE Instance 2

Kernel/OS

Hardware

GCE Instance 3

Kernel/OS

Hardware

Kubernetes




KubeCon



CloudNativeCon

Europe 2018



Kubernetes



KubeCon



CloudNativeCon

Europe 2018

App 1

App 2


App 3

App 4



Kubernetes Cluster

Bare Metal 1



Kernel/OS

Hardware

Bare Metal 2



Kernel/OS

Hardware

Bare Metal 3



Kernel/OS

Hardware

Kubernetes



KubeCon



CloudNativeCon

Europe 2018

```
apiVersion: apps/v1
```

```
kind: ReplicaSet
```

```
metadata:
```

```
  name: frontend
```

```
spec:
```

```
  replicas: 2
```

```
  template:
```

```
    spec:
```

```
      containers:
```

```
      - name: php-redis
```

```
        image: gcr.io/google_samples/gb-frontend:v3
```

Kernel/OS

Hardware

App 1

App 2

App 3

App 4



Kubernetes Cluster

Node 1

Node 2

Node 3

Kernel/OS

Kernel/OS

Hardware

Hardware

Kubernetes




KubeCon



CloudNativeCon

Europe 2018



Problem with Containers and State



KubeCon




CloudNativeCon

Europe 2018

What about stateful apps?

Pod and ReplicaSet abstract compute and memory.

1. Containers are ephemeral: no way to persist state
 - Container termination/crashes result in loss of data
 - Can't run stateful applications
2. Containers can't share data between each other.



Challenges with Abstracting Storage



KubeCon



CloudNativeCon

Europe 2018

- So many different types of storage
 - Object Stores
 - AWS S3, GCE GCS, etc.
 - SQL Databases
 - MySQL, SQL Server, Postgres, etc.
 - NoSQL Databases
 - MongoDB, ElasticSearch, etc.
 - Pub Sub Systems
 - Apache Kafka, Google Cloud Pub/Sub, AWS SNS, etc.
 - Time series databases
 - InfluxDB, Graphite, etc.
 - File Storage
 - NFS, SMB, etc.
 - Block Storage
 - GCE PD, AWS EBS, iSCSI, Fibre Channel, etc.
 - File on Block Storage
 - And more!
- What do we focus on?



KubeCon



CloudNativeCon

Europe 2018

Kubernetes Principle

Workload portability

What do we focus on?



KubeCon



CloudNativeCon

Europe 2018

In scope:

- File Storage
 - NFS, SMB, etc.
- Block Storage
 - GCE PD, AWS EBS, iSCSI, Fibre Channel, etc.
- File on Block Storage

Out of scope:

- Object Stores
 - AWS S3, GCE GCS, etc.
- SQL Databases
 - MySQL, SQL Server, Postgres, etc.
- NoSQL Databases
 - MongoDB, ElasticSearch, etc.
- Pub Sub Systems
 - Apache Kafka, Google Cloud Pub/Sub, AWS SNS, etc.
- Time series databases
 - InfluxDB, Graphite, etc.
- etc.

What do we focus on?



KubeCon



CloudNativeCon

Europe 2018

In scope:

- File Storage
 - NFS, SMB, etc.
- Block Storage
 - GCE PD, AWS EBS, iSCSI, Fibre Channel, etc.
- File **Data Path** Standardized (Posix, SCSI)

Out of scope:

- Object Stores
 - AWS S3, GCE GCS, etc.
- SQL Databases
 - MySQL, SQL Server, PostgreSQL, etc.
- NoSQL Databases
 - MongoDB, ElasticSearch, etc.
- Pub Sub Systems
 - Apache Kafka, Google Cloud Pub/Sub, AWS SNS, etc.
- Time series databases
 - InfluxDB, Graphite, etc.
- etc.

Kubernetes Volume Plugins




KubeCon



CloudNativeCon

Europe 2018

- A way to reference **block device** or **mounted filesystem** (possibly with some data in it)
- Accessible by all containers in pod
- Volume plugins specify
 - How volume is setup in pod
 - Medium that backs it
- Lifetime of volume is same as the pod or longer



Kubernetes Volume Plugins



KubeCon



CloudNativeCon

Europe 2018

Kubernetes has many volume plugins

Remote Storage

- GCE Persistent Disk
- AWS Elastic Block Store
- Azure File Storage
- Azure Data Disk
- Dell EMC ScaleIO
- iSCSI
- Flocker
- NFS
- vSphere
- GlusterFS
- Ceph File and RBD
- Cinder
- Quobyte Volume
- FibreChannel
- VMware Photon PD

Ephemeral Storage

- EmptyDir
- Expose Kubernetes API
 - Secret
 - ConfigMap
 - DownwardAPI

Local Persistent Volume (Beta)

Out-of-Tree

- Flex (exec a binary)
- CSI (Beta)

Other

- Host path

Ephemeral Storage




KubeCon



CloudNativeCon

Europe 2018

- Temp scratch file space from host machine
- Data exists only for lifecycle of pod.
- Can only be referenced “in-line” in pod definition not via PV/PVC.
- Volume Plugin: EmptyDir



Ephemeral Storage



KubeCon



CloudNativeCon

Europe 2018

- Temp scratch file space from host machine
- Data exists only for lifecycle of pod.
- Can only be referenced “in-line” in pod definition not via PV/PVC.
- Volume Plugin: EmptyDir

```
apiVersion: v1
kind: Pod
metadata:
  name: test-pod
spec:
  containers:
    - image: k8s.gcr.io/container1
      name: container1
      volumeMounts:
        - mountPath: /shared
          name: shared-scratch-space
    - image: k8s.gcr.io/container2
      name: container2
      volumeMounts:
        - mountPath: /shared
          name: shared-scratch-space
  volumes:
    - name: shared-scratch-space
      emptyDir: {}
```



KubeCon



CloudNativeCon

Europe 2018

Kubernetes Principle

Workload portability

Ephemeral Storage



KubeCon



CloudNativeCon

Europe 2018

- Built on top of EmptyDir:
 - Secret Volume
 - ConfigMap Volume
 - DownwardAPI Volume
- Populate Kubernetes API as files in to an EmptyDir



KubeCon



CloudNativeCon

Europe 2018

Kubernetes Principle

Meet the user where they are

Ephemeral Storage



KubeCon



CloudNativeCon

Europe 2018

- Built on top of EmptyDir:
 - Secret Volume
 - ConfigMap Volume
 - DownwardAPI Volume
- Populate Kubernetes API as files in to an EmptyDir

Remote Storage



KubeCon



CloudNativeCon

Europe 2018

- Data persists beyond lifecycle of any pod
- Examples:
 - GCE Persistent Disk
 - AWS Elastic Block Store
 - Azure Data Disk
 - iSCSI
 - NFS
 - GlusterFS
 - Cinder
 - Ceph File and RBD
 - And more!
- Referenced in pod either in-line or via PV/PVC

Remote Storage



KubeCon



CloudNativeCon

Europe 2018

- Kubernetes will automatically:
 - Attach volume to node
 - Mount volume to pod

```
apiVersion: v1
kind: Pod
metadata:
  name: sleepypod
spec:
  volumes:
    - name: data
      gcePersistentDisk:
        pdName: panda-disk
        fsType: ext4
  containers:
    - name: sleepycontainer
      image: gcr.io/google_containers/busybox
      command:
        - sleep
        - "6000"
      volumeMounts:
        - name: data
          mountPath: /data
          readOnly: false
```

Remote Storage




KubeCon



CloudNativeCon

Europe 2018

- Kubernetes automatically:
 - Attach volume
 - Mount volume



```
apiVersion: v1
```

```
kind: Pod
```

```
k:
  disk
```

```
  container:
    image: containers/busybox
```

```
  volumeMounts:
```

```
    - name: data
      mountPath: /data
      readOnly: false
```



KubeCon



CloudNativeCon

Europe 2018

Kubernetes Principle

Workload portability

Remote Storage



KubeCon



CloudNativeCon

Europe 2018

- Pod yaml is no longer portable across clusters!!

```
apiVersion: v1
kind: Pod
metadata:
  name: sleepypod
spec:
  volumes:
    - name: data
      gcePersistentDisk:
        pdName: panda-disk
        fsType: ext4
  containers:
    - name: sleepycontainer
      image: gcr.io/google_containers/busybox
      command:
        - sleep
        - "6000"
      volumeMounts:
        - name: data
          mountPath: /data
          readOnly: false
```

Persistent Volumes & Persistent Volume Claims



- PersistentVolume and PersistentVolumeClaim Abstraction
 - Decouple storage implementation from storage consumption

PersistentVolume



KubeCon



CloudNativeCon

Europe 2018

```
apiVersion: v1
kind: PersistentVolume
metadata:
  name : myPV1
spec:
  accessModes:
    - ReadWriteOnce
  capacity:
    storage: 10Gi
  persistentVolumeReclaimPolicy: Retain
  gcePersistentDisk:
    fsType: ext4
    pdName: panda-disk
```

```
apiVersion: v1
kind: PersistentVolume
metadata:
  name : myPV2
spec:
  accessModes:
    - ReadWriteOnce
  capacity:
    storage: 100Gi
  persistentVolumeReclaimPolicy: Retain
  gcePersistentDisk:
    fsType: ext4
    pdName: panda-disk2
```

PersistentVolumeClaim



KubeCon



CloudNativeCon

Europe 2018

```
apiVersion: v1
kind: PersistentVolumeClaim
metadata:
  name: mypvc
  namespace: testns
spec:
  accessModes:
    - ReadWriteOnce
  resources:
    requests:
      storage: 100Gi
```


PV to PVC Binding



KubeCon



CloudNativeCon

Europe 2018

```
$ kubectl create -f pv.yaml  
persistentvolume "pv1" created  
persistentvolume "pv2" created
```

```
$ kubectl get pv
```

NAME	CAPACITY	ACCESSMODES	STATUS	CLAIM	REASON	AGE
pv1	10Gi	RWO	Available			1m
pv2	100Gi	RWO	Available			1m

```
$ kubectl create -f pvc.yaml  
persistentvolumeclaim "mypvc" created
```

```
$ kubectl get pv
```

NAME	CAPACITY	ACCESSMODES	STATUS	CLAIM	REASON	AGE
pv1	10Gi	RWO	Available			3m
pv2	100Gi	RWO	Bound	testns/mypvc		3m

Remote Storage



KubeCon



CloudNativeCon

Europe 2018

- Volume referenced via PVC
- Pod YAML is portable across clusters again!!

```
apiVersion: v1
kind: Pod
metadata:
  name: sleepypod
spec:
  volumes:
  - name: data
    gcePersistentDisk:
      pdName: panda-disk
      fsType: ext4
  volumes:
    - name: data
      persistentVolumeClaim:
        claimName: mypvc
  containers:
    - name: sleepycontainer
      image: gcr.io/google_containers/busybox
      command:
        - sleep
        - "6000"
      volumeMounts:
        - name: data
          mountPath: /data
          readOnly: false
```

Dynamic Provisioning & Storage Classes

Dynamic Provisioning



KubeCon



CloudNativeCon

Europe 2018

- Cluster admin pre-provisioning PVs is painful and wasteful.
- Dynamic provisioning creates new volumes on-demand (when requested by user).
- Eliminates need for cluster administrators to pre-provision storage.

Dynamic Provisioning



KubeCon



CloudNativeCon

Europe 2018

- Dynamic provisioning “enabled” by creating StorageClass.
- StorageClass defines the parameters used during creation.
- StorageClass parameters opaque to Kubernetes so storage providers can expose any number of custom parameters for the cluster admin to use.

```
kind: StorageClass
apiVersion: storage.k8s.io/v1
metadata:
  name: slow
provisioner: kubernetes.io/gce-pd
parameters:
  type: pd-standard
--
kind: StorageClass
apiVersion: storage.k8s.io/v1
metadata:
  name: fast
provisioner: kubernetes.io/gce-pd
parameters:
  type: pd-ssd
```

Dynamic Provisioning



KubeCon



CloudNativeCon

Europe 2018

- Users consume storage the same way: PVC
- “Selecting” a storage class in PVC triggers dynamic provisioning

```
apiVersion: v1
kind: PersistentVolumeClaim
metadata:
  name: mypvc
  namespace: testns
spec:
  accessModes:
    - ReadWriteOnce
  resources:
    requests:
      storage: 100Gi
  storageClassName: fast
```

Dynamic Provisioning



KubeCon



CloudNativeCon

Europe 2018

```
$ kubectl create -f storage_class.yaml
storageclass "fast" created
```

```
$ kubectl create -f pvc.yaml
persistentvolumeclaim "mypvc" created
```

```
$ kubectl get pvc --all-namespaces
```

NAMESPACE	NAME	STATUS	VOLUME	CAPACITY	ACCESSMODES	AGE
testns	mypvc	Bound	pvc-331d7407-fe18-11e6-b7cd-42010a8000cd	100Gi	RWO	6s

```
$ kubectl get pv pvc-331d7407-fe18-11e6-b7cd-42010a8000cd
```

NAME	CAPACITY	ACCESSMODES	RECLAIMPOLICY	STATUS	CLAIM	REASON	AGE
pvc-331d7407-fe18-11e6-b7cd-42010a8000cd	100Gi	RWO	Delete	Bound	testns/mypvc		13m

Dynamic Provisioning



KubeCon



CloudNativeCon

Europe 2018

Volume referenced via PVC

```
apiVersion: v1
kind: Pod
metadata:
  name: sleepypod
spec:
  volumes:
    - name: data
      persistentVolumeClaim:
        claimName: mypvc
  containers:
    - name: sleepycontainer
      image: gcr.io/google_containers/busybox
      command:
        - sleep
        - "6000"
      volumeMounts:
        - name: data
          mountPath: /data
          readOnly: false
```


Dynamic Provisioning



KubeCon



CloudNativeCon

Europe 2018

- Default Storage Classes
 - Enable dynamic provisioning even when StorageClass not specified.
- Pre-installed Default Storage Classes
 - Amazon AWS - EBS volume
 - Google Cloud (GCE/GKE) - GCE PD
 - Openstack - Cinder Volume

```
kind: StorageClass
apiVersion: storage.k8s.io/v1
metadata:
  name: slow
  annotations:
    storageclass.beta.kubernetes.io/is-default-class:
      "true"
provisioner: kubernetes.io/gce-pd
parameters:
  type: pd-standard
```

--

```
kind: StorageClass
apiVersion: storage.k8s.io/v1
metadata:
  name: fast
provisioner: kubernetes.io/gce-pd
parameters:
  type: pd-ssd
```

Hostpath Volumes



KubeCon



CloudNativeCon

Europe 2018

- Expose a directory on the host machine to pod
- What happens if your pod is moved to a different node?
- Don't use hostpath (unless you know what you are doing)!!

Local Persistent Volumes



KubeCon



CloudNativeCon

Europe 2018

- Expose a local block or file as a PersistentVolume
- Reduced durability
- Useful for building distributed storage systems
- Useful for high performance caching
- Kubernetes takes care of data gravity
- Referenced via PV/"PVC so workload portability is maintained
- Kubecon EU Talk: Using Kubernetes Local Storage for Scale-Out Storage Services in Production"by Michelle Au

In-Tree Volume Plugins



KubeCon



CloudNativeCon

Europe 2018

- Kubernetes “In-tree” Volume Plugins are awesome =)
 - Powerful abstraction for file and block storage
 - Automate provisioning, attaching, mounting, and more!
 - Storage portability via PV/PVC/StorageClass objects

In-Tree Volume Plugins



KubeCon



CloudNativeCon

Europe 2018

- Kubernetes “In-tree” Volume Plugins are painful =(
 - Painful for Kubernetes Developers
 - Testing and maintaining external code
 - Bugs in volume plugins affect critical Kubernetes components
 - Volume plugins get full privileges of kubernetes components (kubelet and kube-controller-manager)
 - Painful for Storage Vendors
 - Dependent on Kubernetes releases
 - Source code forced to be open source

Out-of-Tree Volume Plugins



KubeCon



CloudNativeCon

Europe 2018



- Container Storage Interface (CSI) - Beta in v1.10
 - Follows in the steps of CRI and CNI
 - Collaboration with other cluster orchestration systems
 - CSI makes Kubernetes volume layer truly extensible
 - Plugins may be containerized
 - Kubecon EU Talk “Container Storage Interface: Present and Future” by Jie Yu
- Flex Volumes
 - Legacy attempt at out-of-tree
 - Exec based
 - Deployment difficult
 - Doesn't support clusters with no master access

Questions?



KubeCon



CloudNativeCon

Europe 2018

- Get Involved!
 - Kubernetes Storage Special-Interest-Group (SIG)
 - github.com/kubernetes/community/tree/master/sig-storage
 - Meeting every 2 weeks, Thursdays at 9 AM (PST)
 - Mailing list:
 - kubernetes-sig-storage@googlegroups.com
- Contact me:
 - Saad Ali, Google
 - github.com/saad-ali
 - twitter.com/the_saad_ali

What are stateful apps?




KubeCon



CloudNativeCon

Europe 2018

Good for **stateless** apps (apps dependent only on input parameters and app code).



What about **stateful** apps (apps that depend on reading or writing some external state in addition to input parameters and app code)?

