

Cheatsheets / Learn  
SQL

# Manipulation

# Column Constraints

Column constraints are the rules applied to the values of individual columns:

- **PRIMARY KEY** constraint can be used to uniquely identify the row.
- **UNIQUE** columns have a different value for every row.
- **NOT NULL** columns must have a value.
- **DEFAULT** assigns a default value for the column when no value is specified.

There can be only one **PRIMARY KEY** column per table and multiple **UNIQUE** columns.

```
CREATE TABLE student (  
  id INTEGER PRIMARY KEY,  
  name TEXT UNIQUE,  
  grade INTEGER NOT NULL,  
  age INTEGER DEFAULT 10  
);
```

## CREATE TABLE

The **CREATE TABLE** statement creates a new table in a database. It allows one to specify the name of the table and the name of each column in the table.

```
CREATE TABLE table_name (  
  column1 datatype,  
  column2 datatype,  
  column3 datatype  
);
```

## INSERT

The **INSERT INTO** statement is used to add a new record (row) to a table.

It has two forms as shown:

- Insert into columns in order.
- Insert into columns by name.

```
-- Insert into columns in order:  
INSERT INTO table_name  
VALUES (value1, value2);  
  
-- Insert into columns by name:  
INSERT INTO table_name (column1, column2)  
VALUES (value1, value2);
```

## ALTER TABLE

The `ALTER TABLE` statement is used to modify the columns of an existing table. When combined with the `ADD COLUMN` clause, it is used to add a new column.

```
ALTER TABLE table_name  
ADD column_name datatype;
```

## DELETE

The `DELETE` statement is used to delete records (rows) in a table. The `WHERE` clause specifies which record or records that should be deleted. If the `WHERE` clause is omitted, all records will be deleted.

```
DELETE FROM table_name  
WHERE some_column = some_value;
```

## UPDATE

The `UPDATE` statement is used to edit records (rows) in a table. It includes a `SET`

The **UPDATE** statement is used to edit records (rows) in a table. It includes a **SET** clause that indicates the column to edit and a **WHERE** clause for specifying the record(s).

```
UPDATE table_name  
SET column1 = value1, column2 = value2  
WHERE some_column = some_value;
```

**Next** →

## Related Courses

Course

### **Learn SQL**

Learn to communicate with databases using SQL, the standard d