

Assignment – 4

Data Analytics, LIET College

1. Write an SQL query to display the names and salaries of employees whose salary is greater than the average salary in the company. Explain how the subquery works.

Ans.

```
bank_db=# select fname, lname , salary from employees where salary > (select avg(salary) from employees);
fname | lname | salary
-----+-----+-----
Arjun  | Verma | 55000.00
Suman  | Patel | 60000.00
Amit   | Gupta | 52000.00
Rahul  | Kumar | 53000.00
Anjali | Mehta | 61000.00
Vijay  | Nair  | 50000.00
(6 rows)
```

A subquery is a query written inside another SQL query and is executed first. The result obtained from the subquery is then used by the outer query to perform further operations.

2. Write a query to retrieve the top 5 highest-paid employees from an employees table. Explain how sorting affects the output.

Ans.

```
bank_db=# select * from employees order by salary desc limit(5);
emp_id | fname | lname | email | dept | salary | hire_date
-----+-----+-----+-----+-----+-----+-----
9 | Anjali | Mehta | anjali.mehta@example.com | Finance | 61000.00 | 2018-12-03
4 | Suman | Patel | suman.patel@example.com | Finance | 60000.00 | 2018-07-30
3 | Arjun | Verma | arjun.verma@example.com | IT | 55000.00 | 2021-06-01
8 | Rahul | Kumar | rahul.kumar@example.com | IT | 53000.00 | 2021-02-14
6 | Amit | Gupta | amit.gupta@example.com | Marketing | 52000.00 | 2020-09-25
(5 rows)
```

Sorting in SQL is performed using the ORDER BY clause, which arranges the data in a specific order (ascending or descending).

3. Write a query to calculate:
 - Total number of employees
 - Average salary
 - Minimum and maximum salary

Explain the difference between aggregate and scalar functions.

Ans.

```
bank_db=# select count(emp_id), Avg(salary), Min(salary), Max(salary) from employees;
count | avg | min | max
-----+-----+-----+-----
10 | 48600.000000000000 | 30000.00 | 61000.00
(1 row)
```

Aggregate functions summarize multiple rows into one result, whereas scalar functions perform operations on individual values without combining rows.

4. Given a sales table with columns (region, amount), write a query to find total sales per region. Filter only those regions where total sales exceed 50,000

Ans.

```
as_4=# select sum(amount) as total_sales, region from sales group by region having sum(amount)>50000;
total_sales | region
-----+-----
      60000 | South
      60000 | West
      60000 | North
(3 rows)
```

5. Write a query to find the number of unique job roles in an employees table. Explain why DISTINCT is necessary here.

Ans.

```
as_4=# select count(distinct job_role) from employees;
count
-----
      4
(1 row)
```

The DISTINCT keyword is used to eliminate duplicate values from a column and return only unique entries.

6. Write a query to retrieve students who scored between 60 and 80 marks. Rewrite the same query using BETWEEN.

Ans.

```
as_4=# select * from students where marks between 60 and 80;
student_id | name  | marks
-----+-----+-----
          1 | Aman  |    75
          3 | Neha  |    65
          7 | Rahul |    60
(3 rows)
```

7. Write a query to display employees whose commission is NULL. Explain the correct way to check NULL values in SQL.

Ans.

```
as_4=# select name from employees where commission is NULL;
name
-----
Aman
Neha
Karan
Rahul
(4 rows)
```

In SQL, NULL represents the absence of a value, and it cannot be compared using standard comparison operators such as = . To check for NULL values, the IS NULL or IS NOT NULL operators must be used.

8. Write a query to increase the salary of employees in the “IT” department by 10%. Explain how arithmetic operations are handled in SQL.

Ans.

```
as_4=# update employees set salary = salary + (salary*.10) where department = 'IT';
UPDATE 3
```

Arithmetic operations in SQL are performed using standard mathematical operators such as + (addition), - (subtraction), * (multiplication), and / (division). These operations can be applied directly within SQL queries, especially in SELECT and UPDATE statements, and are evaluated for each row individually.

9. Write a query to delete records of students who scored less than 40 marks. What precaution should be taken before executing DELETE?

Ans.

```
as_4=# delete from students where marks < 40;
DELETE 1
```

Before executing a DELETE statement, it is important to ensure that the correct records are being targeted, as the operation permanently removes data from the table.

A common precaution is to first run a SELECT query with the same condition to verify which rows will be deleted.

10. Write a query to find employees who earn more than the average salary of their department (without using joins). Explain the logic of the subquery

Ans.

```
as_4=# select * from employees e where salary > (select avg(salary) from employees where department = e.department);
```

emp_id	name	salary	department	job_role	commission
3	Neha	45000	HR	Manager	
6	Priya	80000	Finance	Manager	15000
4	Simran	77000	IT	Team Lead	10000

(3 rows)

The outer query then compares each employee's salary with the average salary of their respective department and selects only those employees whose salary is higher than that average.

Thus, the subquery dynamically provides department-wise average values, enabling row-by-row comparison in the main query.

Submitted By: Inderjeet Singh