

Fork process graphs

You are asked to answer questions about 10 sample programs which make use of `fork()`. Assume the programs run normally. For each program, first construct a process graph by hand.

This assignment is an extension of the previous assignment providing more hands-on experience with `fork()` calls and process graphs. You could even try building a tool to construct a process graph or identify a tool that automatically constructs a process graph given a C program.

program: p0.c

How many processes are created upon the execution of this program in the shell (including the first process created by the shell)?

```
#include <sys/types.h>
#include <unistd.h>
int main() {
    pid_t pid;

    pid = fork();
    if (pid != 0) {
        fork();
    }
    fork();
    return 0;
}
```

program: p1.c

How many processes are created upon the execution of this program in the shell (including the first process created by the shell)?

```
#include <sys/types.h>
#include <unistd.h>

int main() {
    pid_t pid;

    fork();
    pid = fork();
    if (pid == 0) {
        fork();
    }
    return 0;
}
```

program: p2.c

What is the total number of processes that will be created by running this program? How many of each character 'A' to 'C' will be printed out?

```
#include <sys/types.h>
#include <unistd.h>
#include <stdio.h>
int main() {
    pid_t pid1, pid2, pid3;

    pid1 = fork();
    pid2 = fork();

    if (pid1 == 0) {
        printf("A");
    } else {
        pid3 = fork();
        printf("B");
    }

    if (pid2 != 0 && pid3 != 0) {
        printf("C");
    }
}
```

program: p3.c

What is the total number of processes that will be created by running this program?

```
#include <sys/types.h>
#include <unistd.h>
#include <stdio.h>
int main() {
    pid_t pid1, pid2;

    pid1 = fork();
    pid2 = fork();

    if (pid1 != 0 && pid2 != 0) {
        printf("A");
    }

    if (pid1 != 0 || pid2 != 0) {
        printf("B");
    } else {
        printf("C");
    }
}
```

program: p4.c

How many times will the message “Hello!” be displayed?

```
#include <sys/types.h>
#include <unistd.h>
#include <stdio.h>

int main() {
    fork();
    fork();
    if (fork() == 0) {
        printf("Hello!");
    } else {
        printf("Goodbye!");
    }
}
```

program: p5.c

List all of the possible outputs that can occur when this program is run.

```
#include <sys/types.h>
#include <unistd.h>
#include <stdio.h>

int main() {
    puts("0\n");
    if (fork() != 0) {
        puts("1");
        fork();
        puts("2");
    } else {
        puts("3");
    }
}
```

program: p6.c

List all the possible outputs that can occur when this program is run.

```
#include <sys/types.h>
#include <unistd.h>
#include <stdio.h>

int main() {
    fork();
    if (fork())
        puts("Hello");
    if (fork())
        puts("Hello");
}
```

program: p8.c

Suppose I want to print exactly 37 exclamation marks (!). How many successive calls would I need to write in place of `--X--` to produce this output?

```
#include <sys/types.h>
#include <unistd.h>
#include <stdio.h>

int main() {
    puts("!");
    if (fork()) {
        puts("!");
    }
    else {
        // -- X --
        puts("!");
    }
    puts("!");
    puts("!!!");
}
```