## Exercise TP 1:

1. Launch the Terminal Emulator (Ctrl + Alt + T)
2. In this sequence of commands, you'll be moving around in the file system hierarchy.

   **a)** Print the name of the current/working directory:

   **pwd**

   This displays your current file system location, in this case, /home/[your username]. Every non-root user has a home directory in /home, named after the username.

   **b)** Make a directory:
   **mkdir [your directory]**
   This creates a directory named [your directory] in /home/[your username].

   **c)** List directory contents:
   **ls**
   By listing the contents of the current directory, you can verify that the [your directory] directory was created.

   **d)** Change the current directory with a relative reference:
   **cd [your directory]**
   This changes your location to the [your directory] directory. The prompt will change to ~/[your directory]to reflect your new location.

   **e)** Move up one directory level from the current location with a relative reference using the .. characters:
   **cd ..**
   The pair of dots represents the parent directory of where you currently are.

   **f)** Go to a specific directory, regardless of the current location, with an absolute reference (the full path to the directory from the root of the file system is specified):

   **cd /home/[your username]/ [your directory]**

   In this case, it would have been easier to use a relative reference as before, but sometimes an absolute reference makes more sense.

For example, if you wanted to go to the /etc directory, from /home/[your username], a relative reference would be **cd ../../etc**. The first pair of dots gets you to /home, and the second pair of dots gets you to / (the root of the file system). From there, you instruct the system to go down to the etc directory. An absolute reference would have been simply **cd /etc**.

**g)** Create multiple directories in [your directory] at the same time with a single command:

**mkdir [subdirectory1] [subdirectory2]**

This creates two directories inside [your directory]. Some commands allow multiple arguments that represent multiple items.

**h)** Change the current directory with a relative reference:

**cd [subdirectory1]**

This changes the current location to the first subdirectory.

**i)** Change the current directory with a relative reference using the .. characters:

**cd ../[subdirectory2]**

This changes the current location to the second subdirectory.

**3.** In the seed directory:

**a)** Create a test directory [Test]

**b)** Move to this directory

**c)** Create a text file and edit it

**d)** Show file contents

**e)** Delete the file and folder

**f)** Shutdown Ubuntu Cleanly