

NAVIA_PATH

Autonomous multi-provider intelligent Web automation agent for RPA robots and Windows workstations.

Overview

NAVIA_PATH is an autonomous, compiled runtime designed to allow automation platforms (UiPath, background scripts, enterprise schedulers) to interact intelligently with complex Web applications through large language models.

It pairs deterministic browser control with multimodal context reasoning to:

- Execute multi-step business journeys across pages and tabs.
- Extract structured data from complex tables, dashboards, and dynamic views.
- Interact seamlessly with enterprise browsers (**Microsoft Edge** and **Google Chrome**).
- Maintain persistent, authenticated browser sessions to eliminate repetitive logins.

Key Highlights

- **Standalone & Autonomous:** Packaged as a single Windows x64 executable (`NAVIA_PATH.exe`). No external Python runtime, pip dependencies, or virtual environment required on user machines.
- **Ready-to-Use UiPath Integration:** Ships with the `NAVIA_PATH.Activities` library (`NAVIA_PATH - Edge` , `NAVIA_PATH - Chrome`) for native UiPath Studio workflows.
- **Multi-Provider Architecture:** Native support for **Google Vertex AI**, **Google Gemini Direct API**, **OpenAI**, **Anthropic Claude**, and **Azure OpenAI Service**.
- **External Configuration:** Credentials, endpoints, models, and timeouts are fully configured outside the binary via isolated `.env.<provider>` files.
- **Persistent Sessions:** User session cookies and profiles are maintained automatically in `%LOCALAPPDATA%\NAVIA_PATH` .
- **Integrated Health Diagnostics:** Instant environment and credentials validation via `NAVIA_PATH.exe --check` .

Quick Start

1. **Extract** the release archive (`NAVIA_PATH-v1.1.2-windows-x64.zip`) into your target folder (e.g., `C:\NAVIA_PATH`).
2. **Choose your LLM provider** and create your configuration file in `config\providers\` (e.g., copy `.env.vertex.example` to `.env.vertex`).
3. **Run the pre-flight check:**

```
.\NAVIA_PATH.exe --check
```

4. **Execute your first prompt:**

```
.\NAVIA_PATH.exe --prompt "Navigate to the internal portal and extract order status"
```

For a detailed step-by-step walkthrough, see **QUICKSTART.md**.

For provider-specific configuration guides, see **PREPARE_LLM_ENVIRONMENTS.txt**.

Supported Providers

Provider	Default Model	Authentication Mechanism
Google Vertex AI (<i>Default</i>)	Gemini 3.8 Flash	Application Default Credentials (<code>gcloud auth application-default login</code>)
Google Gemini Direct	Gemini 2.5 Flash	API Key (<code>GEMINI_API_KEY</code>)
OpenAI	GPT-4o	API Key (<code>OPENAI_API_KEY</code>)
Anthropic Claude	Claude 3.5 Sonnet	API Key (<code>ANTHROPIC_API_KEY</code>)
Azure OpenAI	GPT-4o (<i>deployment</i>)	Endpoint & API Key (<code>AZURE_OPENAI_API_KEY</code>)

UiPath Integration

The distribution includes the ready-to-import activity project in `uipath\NAVIA_PATH.Activities` :

- **NAVIA_PATH - Edge** : Automates a persistent Microsoft Edge session.
- **NAVIA_PATH - Chrome** : Automates a persistent Google Chrome session.

The activities dynamically discover `NAVIA_PATH.exe` , ensure debugging prerequisites, run synchronously without background console windows, and populate `out_ExecutionResult` with structured JSON data.

CLI Reference

```
NAVIA_PATH.exe [--check] [--version] [run] [OPTIONS]
```

Commands:

check	Verify configuration and runtime environment
run	Execute the agent on a user prompt

Options:

--prompt TEXT	Task objective in plain text
--prompt-base64 B64	Task objective encoded in base64
--max-iterations INT	Maximum iteration limit (default: 20)
--result-file PATH	Path to JSON result output file
--close-browser BOOL	Close browser upon completion (true/false)
--require-attached-browser BOOL	Require strict attachment to existing debug browser
--browser CHANNEL	Target browser channel: msedge or chrome
--check	Quick health and configuration check
--version, -v	Display version information

License

This project is licensed under the MIT License - see the **LICENSE** file for details.