

Homework 3

Lecturer: Cho-Jui Hsieh

Date Due: June 1, 13:30pm (in class), 2017

Keywords: *Classification, Regression.*

For this homework, we will try classification and regression using datasets listed in <https://www.csie.ntu.edu.tw/~cjlin/libsvmtools/datasets/>. The format of data is called “SVMLight” format:

```
<label> <index>:<value1> <index>:<value2> . . .
```

Each line contains an instance. For classification, <label> is an integer indicating the class label. For regression, <label> is the target value which can be any real number. Indices are in ascending order.

Problem 1. Regression [50 pt]

1. Download the “cpusmall” data from <https://www.csie.ntu.edu.tw/~cjlin/libsvmtools/datasets/regression.html#cpusmall>. Randomly split the file into training set and testing set. Training set contains 80% instances and testing set contains 20% instances. Solve the ridge regression problem on the training set:

$$\mathbf{w}^* = \arg \min_{\mathbf{w}} \left\{ \frac{1}{2} \sum_{i=1}^n (\mathbf{x}_i^T \mathbf{w}_i) + \frac{\lambda}{2} \|\mathbf{w}\|^2 \right\} := f(\mathbf{w}), \quad (1)$$

where $\mathbf{x}_i \in \mathbb{R}^d$ is the i -th training sample, and $y_i \in \mathbb{R}$ is the i -th target value. Set $\lambda = 1$, solve (1) to get the model \mathbf{w}^* , and compute the Mean Square Error (MSE) on the testing set. The MSE is defined by

$$\frac{1}{n_{test}} \sum_{i=1}^{n_{test}} (\mathbf{x}_i^T \mathbf{w}^* - y_i)^2,$$

where n_{test} is the number of testing instances. Report the MSE.

2. Run the ridge regression for $\lambda = 0.01, 0.1, 1, 10, 100$, and report the test MSE for each λ value.
3. Write the gradient descent algorithm with fixed step size for solving (1). The gradient descent algorithm is in Algorithm 1. Set $\lambda = 1, \epsilon = 0.001$ and test the algorithm for $\eta = 1, 0.1, 0.01, 0.001$. Report the testing accuracy for each step size. What’s your finding?
4. Run gradient descent (with fixed step size) on “E2006-tfidf” data (download from <https://www.csie.ntu.edu.tw/~cjlin/libsvmtools/datasets/regression.html#E2006-tfidf>). Download both training and testing data from the website. Run your gradient descent implementation. Set $\epsilon = 0.001$ and $\lambda = 1$, try to select a good step size, and report your step size and the prediction accuracy you get.

Algorithm 1 Gradient Descent with Fixed Step Size

- Input: η : step size, ϵ : Stopping condition, \mathbf{w}_0 : initial solution
 - $\mathbf{w} \leftarrow \mathbf{w}_0$
 - $r_0 \leftarrow \|\nabla f(\mathbf{w}_0)\|$
 - For iter = 1, 2, ..., 50 (Maximum 50 iterations)
 - $\mathbf{g} = \nabla f(\mathbf{w})$
 - If $\|\mathbf{g}\| \leq \epsilon r_0$: Break (End program)
 - $\mathbf{w} \leftarrow \mathbf{w} - \eta \mathbf{g}$
-

Algorithm 2 Gradient Descent with Line Search

- Input: ϵ : Stopping condition, \mathbf{w}_0 : initial solution
 - $\mathbf{w} \leftarrow \mathbf{w}_0$
 - $r_0 \leftarrow \|\nabla f(\mathbf{w}_0)\|$
 - For iter = 1, 2, ..., 50 (Maximum 50 iterations)
 - $\mathbf{g} = \nabla f(\mathbf{w})$
 - If $\|\mathbf{g}\| \leq \epsilon r_0$: Break (End program)
 - $\eta \leftarrow 1$
 - While ($f(\mathbf{w} - \eta \mathbf{g}) \geq f(\mathbf{w})$)
 - $\eta \leftarrow \eta/2$
 - $\mathbf{w} \leftarrow \mathbf{w} - \eta \mathbf{g}$
-

Problem 2. Classification (Logistic Regression) [50pt]

In this problem, you will write your own code for logistic regression. Given training data $\{\mathbf{x}_i, y_i\}$ for $i = 1, 2, \dots, n$. Each \mathbf{x}_i is a feature vector and each y_i is the +1/-1 label. logistic regression model can be learned by solving

$$\mathbf{w}^* = \arg \min_{\mathbf{w}} \left\{ \sum_{i=1}^n \log(1 + e^{-y_i \mathbf{w}^T \mathbf{x}_i}) + \frac{\lambda}{2} \|\mathbf{w}\|^2 \right\} := f(\mathbf{w}). \quad (2)$$

The model \mathbf{w}^* can then be used for prediction.

1. Derive the gradient of (2).
2. Implement gradient descent with fixed step size to solve (2). Test it on news20 dataset (<https://www.csie.ntu.edu.tw/~cjlin/libsvmtools/datasets/multiclass.html#news20>). (Use the file “news20.scale” as training data and “news20.scale.t” as testing data). Report the accuracy when $\lambda = 1$.
3. Implement gradient descent with line search (see Algorithm 2). Report the testing accuracy for $\lambda = 0.01, 0.1, 1, 10, 100$.

Problem 3. Bonus [30pt]

Try some of the scikit-learn classification/regression packages for these two problems, and compare the result with your implementation. Report your findings.