

JSW ENERGY BARMER LIMITED
PRICE BID FORMAT

Material	Mat.Description	UOM	Total Qty	M/s	
				Unit Rate	Amount
2200145644	LUMINAIRE,LED,TYPE:WELL GLASS;TOTAL POWER CONSUMED INCLUDING DRIVER:45 W,VOLTAGE RANGE:230 VAC,EFFICACY:80 W/LUM,TOTAL HARMONIC DISTORTION:<10 %,SYSTEM LUMEN OUTPUT:4200 LM,CRI:>70,CCT (LED COLOUR):>54000 K,WORKING TEMPERATURE RANGE:-10 to 45 DEG.C,LUMINAIRE LIFE EXPECTANCE:50000,INGRESS PROTECTION:IP66,MOUNTING:SUSPENDED,DRIVER SURGE PROTECTION:2 KV,POWER FACTOR:0.8,ADDITIONAL INFORMATION:EXPLOSION PROOF ExD IIC T2	Nos.	180		0
2200174325	LUMINAIRE,LED,TYPE:POST TOP;TOTAL POWER CONSUMED INCLUDING DRIVER:35-45 W;VOLTAGE RANGE:110-300;EFFICACY:90 LUM/W;TOTAL HARMONIC DISTORTION:<10 %;SYSTEM LUMEN OUTPUT:3800 LUMEN;CRI:>70;CCT (LED COLOUR):3000 K;WORKING TEMPERATURE RANGE:-10 TO 60 DEG.C;LUMINAIRE LIFE EXPECTANCE:50000 HRS;INGRESS PROTECTION:IP66;MOUNTING:POLE;DRIVER SURGE PROTECTION:K KV;POWER FACTOR:>0.9	Nos.	260		0
2200174327	LUMINAIRE,LED,TYPE:WELL GLASS;TOTAL POWER CONSUMED INCLUDING DRIVER:35-45;VOLTAGE RANGE:110-300 V;EFFICACY:100 LUM/W;TOTAL HARMONIC DISTORTION:<10%;SYSTEM LUMEN OUTPUT:4000 LUMENS;CRI:>70;CCT (LED COLOUR):3000 K;WORKING TEMPERATURE RANGE:-10 TO 60 DEG C;LUMINAIRE LIFE EXPECTANCE:50000 HRS;INGRESS PROTECTION:IP66;MOUNTING:SUSPENDED;DRIVER SURGE PROTECTION:5 KV;POWER FACTOR:>0.95	Nos.	950		0
2200117240	LUMINAIRE,LED,TYPE:DOWNLIGHTER;TOTAL POWER CONSUMED INCLUDING DRIVER:15-25 W,VOLTAGE RANGE:120-270 VAC,EFFICACY:160 LUM/W,TOTAL HARMONIC DISTORTION:<10 %,SYSTEM LUMEN OUTPUT:1100 lumens,CRI:>70,CCT (LED COLOUR):6500K,WORKING TEMPERATURE RANGE:10 TO 50 deg C,LUMINAIRE LIFE EXPECTANCE:50000 HRS,INGRESS PROTECTION:IP45,MOUNTING:RECESS,DRIVER SURGE PROTECTION:2 KV,POWER FACTOR:>.95,CUT OUT:185 MM ,DIMENSION:DIA 200xH120 MM.	Nos.	270		0
2200132910	LUMINAIRE,LED,TYPE:SPOT LIGHT;TOTAL POWER CONSUMED INCLUDING DRIVER:7-10 W;VOLTAGE RANGE:140-270 VAC,EFFICACY:130 LUM/W;TOTAL HARMONIC DISTORTION:<10 %;SYSTEM LUMEN OUTPUT:1170 LUMENS;CRI:65;CCT (LED COLOUR):2000 K;WORKING TEMPERATURE RANGE:50 DEG.C;LUMINAIRE LIFE EXPECTANCE:50000 HRS;INGRESS PROTECTION:IP65;MOUNTING:SPIKE;DRIVER SURGE PROTECTION:4 KV;POWER FACTOR:0.9	Nos.	110		0
SUB TOTAL					-
GST				12%	-
GRAND TOTAL					-
JSWBL TERMS AND CONDITIONS				VENDOR'S REPLY	
PAYMENT TERMS - 90% of basic purchase price along with applicable taxes shall be paid on pro rata basis within 30 days from date of receipt of material at site. 10% of the basic purchase price along with applicable taxes shall be paid against submission of PBG of equiv. amount valid till warranty period plus 2 months.					
PRICE BASIS - FOR JSWBL Site (I.E. Freight in Vendor scope)					
DELIVERY PERIOD - Within 4-8 weeks					
WARRANTY - 60 months from date of commissioning / installation or 72 months from the date of delivery as per Article 4, whichever is earlier					