

LED 25W Strip Light

HLFSL-01-25-CW

As per IS 10322 (Part-5/Sec-3) & IEC 60598-1




Product Description: Energy efficient 25W LED Strip Light

Technical Specifications:

Body Material:	Flexible PCB
Cover:	NA
LED:	LM80 certified LED
Lumen Maintenance:	50000 hours @ L70
Control Gear:	Isolated, Electronic CV Driver
Internal Wiring:	Insulated Cu wire
Ingress Protection:	IP20
Operating Voltage Range:	140V~ 270V
Operating Temperature:	-10°C~ 50°C

GA Drawing:



All dimensions in mm (Tolerance: ± 5 mm)

Electrical & Photometry Parameters:

Rated Voltage & Frequency	System Wattage	System Current	Power Factor	CCT	CRI	THD	Driver Efficiency
240V, 50Hz	25W $\pm 10\%$	<125mA	≥ 0.95	6500K	≥ 80	$\leq 30\%$	$\geq 80\%$

System Protections:

Open & Short circuit protection, reverse polarity protection, surge protection of 2.5KV internal.

Application:

Living room, Hospital, hotel, shopping complex, display area, etc.

Mounting:

Adhesive tape.

Note: Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt Ltd reserves the right to make changes in the design and data and withdraw the luminaries without any prior notice.

Prepared by :

MK/NK

Industrial Luminaire :

Checked by :

AS

Cat. Ref. : HLFSL-01-25-CW

Approved by :

RL

Document No : 052019

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.