



70W LED ORNAMENTAL STREET LIGHT

Photometric & Electrical Measurement (As per IES LM 79-08 / IS 16106-12)

70W Energy Efficient LED Ornamental Street Light

Issued by: Halonix Technologies Private Limited (NABL Certification No: TC-7634)

07/24/2019

HALONIX TECHNOLOGIES PRIVATE LIMITED
HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Fax:

Web: <http://www.halonix.co.in>

Test Report

Report Number: 24-07-2019 -001	Date: 24-07-2019
Product Description: 70W Energy Efficient LED Ornamental Street Light	
Product Catalogue Reference: HLOSL-04-70-CWL	Brand: HALONIX
Construction: Pressure die casted aluminum heat sink, Aluminum spun sheet housing, Acrylic front visor, SMD LED, Electronic driver etc.	
Test Details:	Document References/Standard:
<ul style="list-style-type: none">• Light intensity distribution Measurement• Total Lumen output Measurement• Electrical Parameters Measurement	<ul style="list-style-type: none">• IES-LM-79-08 "Electrical and Photometric Measurements of Solid-State Lighting Products"• IS : 16106-2012 "Method of Electrical and Photometric solid state lighting (LED) Products"• IS : 16105-2012 "Method of measurement of Lumen maintenance of solid state light sources"
Enclosures:	
Prepared By:	Approved By:
Sanjay Sharma	Rajeev Chhabra

HALONIX TECHNOLOGIES PRIVATE LIMITED
HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Fax:

Web: <http://www.halonix.co.in>

Electrical & Photometric Test Report

Photometric Test Report: (As Per IES LM 79-08)			
Sample ID: 24-07-2019 -001			
Catalogue Reference:	HLOSL-04-70-CWL	Testing Date:	24-07-2019
Testing Agency:	HTPL Laboratory	Brand:	HALONIX
Equipment Used:	EVERFINE Brand Gonio Photometer (Type: GO - 2000B V1) and Globe Photometer (Type: PMS – 50/80) with Power Meter		

Ambient Temperature:	25±2°C	Relative Humidity:	65%
Test Voltage:	240V	Frequency:	50Hz
Stabilization Time:	30Min	Total Operating Time:	1.30Hours


Rated Performance Parameters:			
Rated Wattage :	70W	Rated Input Current :	0.338A
Nomical CCT :	5700K	Nominal CRI :	>70

Measured Electrical Parameters:			
Supply Voltage :	240V	Input Current :	0.295A
Frequency :	50Hz		
Total Power :	69.56W	Power Factor :	0.982

Photometric Measurement Data:			
Total Measured Lumen :	7103.47lm	Luminaries Efficacy :	102.12lm/W
CCT :	5795K	CRI :	72.4
Light Intensity Distribution:	Attached (Refer to Page No. 4)		
Approved By: Rajeev Chhabra	Tested By: Sanjay Sharma		

HALONIX TECHNOLOGIES PRIVATE LIMITED
HTPL LABORATORY (NABL Certificate No: TC-7634)
 Plot-5, Sector-12, IIE, SIDCUL
 Haridwar (Uttarakhand), PIN-249403, India
 Contact:
 Email: customercare@halonix.co.in
 Fax:
 Web: <http://www.halonix.co.in>

Light intensity Distribution Diagram



Catalogue Reference		HLOSL-04-70-CWL	Sample ID	24-07-2019 -001
---------------------	--	-----------------	-----------	-----------------