

LED 15W Tube Light

HLTLD-05-15-CW

As per IS 10322 & IEC 60598-1




Product Description: Energy efficient 15W LED Tube Light

Technical Specifications:

Main Housing:	Extruded aluminum
Front Cover:	PC
LED:	LM80 certified LED
Lumen Maintenance:	50000 hours @ L70
Internal Wiring:	Insulated Cu wire
Hardwares:	SS & MS Zinc plated and passivated
Ingress Protection:	IP20
Operating Voltage Range:	140V~ 270V
Operating Temperature:	-10°C~ 50°C
Control Gear:	Electronic, External CC driver, push fit connector at o/p end

GA Drawing:



All dimensions are in mm (Tolerance: ±5mm)

Electrical & Photometry Parameters:

Rated Voltage & Frequency	System Wattage	System Current	Power Factor	System Lumen Efficacy	CCT (As per ANSI)	CRI	THD	Driver Efficiency
240V, 50Hz	15W±10%	<72mA	≥0.95	≥100lm/W	6500K	≥80	≤15%	≥85%

System Protections:

Open & Short circuit protection, reverse polarity protection, surge protection of 3KV internal.

Application:

Offices, hospitals, retail outlets, banks, etc.

Mounting:

Retrofit-G5

Note: Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt Ltd reserves the right to make changes in the design and data and withdraw the luminaries without any prior notice.

Prepared by :

MK./NK

Industrial Luminaire :

Checked by :

AS

Cat. Ref. : HLTLD-05-15-CW

Approved by :

RL

Document No : PLL-2019

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.