

## LED 40W Linear Light

### HLLL-P04-40-CW-AL

As per IS 10322 & IEC 60598-1




**Product Description:** Energy efficient 40W LED Linear Light

### Technical Specifications:

Main Housing:	Epoxy powder coated Aluminum extruded
Front Cover:	Extruded Acrylic
LED:	LM80 certified LED
Lumen Maintenance:	50000 hours @ L70
Control Gear:	Isolated, Electronic, CC Driver
Internal Wiring:	Insulated Cu wire
Hardware:	SS & MS Zinc plated and passivated
Ingress Protection:	IP20
Operating Voltage Range:	140V~270V
Operating Temperature:	-10°C~ 50°C

### GA Drawing:



All dimensions in mm (Tolerance: ±5mm)

### Electrical & Photometry Parameters:

Rated Voltage & Frequency	System Wattage	System Current	Power Factor	System Lumen Efficacy	CCT (As per ANSI)	CRI	THD	Driver Efficiency
240V, 50Hz	40W±10%	<204mA	≥0.90	≥85lm/W	6500K	≥80	≤10%	≥85%

### System Protections:

Open & Short circuit protection, reverse polarity protection, surge protection of 3KV internal.

### Application:

Office space, conference room, general area, etc.

### Mounting:

Recessed or Suspended mounting.

Note: Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt. Ltd. reserves the right to make changes in the design and data and withdraw the luminaries without any prior notice.

Prepared by :

MK/NK

Industrial Luminaire :

Checked by :

AS

Cat. Ref. : HLLL-P04-40-CW-AL

Approved by :

RL

Document No :

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.