

HALONIX TECHNOLOGIES PRIVATE LIMITED

Regd Office:-

B-31, Noida Phase - II, Dist.-Gautam Budh Nagar, U.P, Pin-201305

TECHNICAL DATA **SHEET**

LED 72W HW Street Light

HLSLD-ML04-72-CWL-HL2-4M

As per IS 10322 (Part-5/Sec-3) & IEC 60598-1

Product Description: Energy efficient 72W LED Street Light

Technical Specifications:

Housing Material: Aluminum PDC, Top maintainable

Front Cover: Clear toughened glass

Suitable high efficient secondary lens

LM80 certified LED 50,000 hours @ L70

Isolated, Electronic, CC driver

Insulated Cu wire

SS & MS Zinc plated and passivated

IP66 IK05

120V~280V

-10°C~ 50°C

Size: 0.75sq.mm. tinned copper PVC insulated 3 core cable & least 4meters lengh cable connected from LED fixture with Earth

wire-green, Neutral wire-Black & Phase wire-Red color.

Lens: LED:


LED Lumen Maintenance:


Control Gear: **Internal Wiring:** Hardware:

Ingress Protection: Impact Resistance: Operating Voltage:

Operating Temperature: Input /Incoming Cable:

GA Drawing:





All dimensions are in mm (Tolerance: ±5mm)

Electrical & Photometry Parameters:

Rated Voltage & Frequency	System Wattage	System Current	Power Factor	System Lumen Efficacy	CCT (As per ANSI)	CRI	THD	Driver Efficiency
240V, 50Hz	72W±10%	<347mA	≥0.95	≥120lm/W	5700K	≥70	≤10%	≥85%

System Protections:

Open & Short circuit protection, reverse polarity protection, high voltage cut off at 300V±10V and 5KV Internal Surge protection.

Application:

Street and road lighting, city squares, periphery lighting, complex boundary lighting, outdoor lighting, etc.

Mounting:

Pole mounting, suitable up to 50mm OD pipe bracket.

Note: Due to continuous efforts in developing products,		MK/NK	Industrial Luminaire :
improvement M/s Halonix Technologies Pvt. Ltd. reserves the right to make changes in the design and data and withdraw the	Checked by :	AS	Cat. Ref. : HLSLD-ML04-72-CWL-HL2-4M
luminaries without any prior notice.	Approved by :	RL	Document No : HWR-2019-KML