

LED 20W Batten Light

HLLL-P02-20-CW

As per IS: 10322 & 60598-1




Product Description: Energy efficient 20W LED Batten Light.

Technical Specifications:

Main Housing:	Powder coated MS housing
Front Cover:	Opal glare free PC diffuser
LED:	LM80 certified LED
Control Gear:	Electronic, CC driver
Internal Wiring:	Insulated Cu wire
Hardware:	SS & MS zinc plated and passivated
Ingress Protection:	IP20
Operating Voltage:	110V~ 270V
Operating Temperature:	-10°C~ 50°C

GA Drawing:



All dimensions in mm (Tolerance: ± 5 mm)

Electrical & Photometry Parameters:

Rated Voltage & Frequency	System Wattage	System Current	Power Factor	System Lumen Efficacy	CCT (AS per ANSI)	CRI	THD	Driver Efficiency
240V, 50Hz	20W $\pm 10\%$	<100mA	≥ 0.90	$\geq 100\text{lm/W}$	6500K	≥ 80	$\leq 15\%$	$\geq 85\%$

System Protections:

Open & Short circuit protection, reverse polarity protection and surge protection of up to 3KV.

Application:

Offices, commercial complexes, showrooms, retail outlets, malls, reception lobbies, hotel lobbies, indoor lighting applications.

Mounting:

Surface / Pendent.

Note : Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt Ltd reserves the right to make changes in the design and data and withdraw the luminaries without any prior notice.	Prepared by :	MK/NK	Industrial Luminaire :
	Checked by :	AS	Cat. Ref. : HLLL-P02-20-CW
	Approved by :	RL	Document No :

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.