

HALONIX TECHNOLOGIES PRIVATE LIMITED

Regd Office:-

B-31, Noida Phase - II, Dist.-Gautam Budh Nagar, U.P, Pin-201305

TECHNICAL DATA SHEET

LED 48W 2X2 Panel Light

HLFPR22-11-48-CW

As per IS 10322 & IEC 60598-1

Product Description: Energy efficient 48W LED 2X2 Panel Light

Technical Specifications:

Main Housing: Duly powder coated CRCA sheet steel

Front Cover: PMMA

LED: LM80 certified LED Lumen Maintenance: 50000 hours @ L70

Control Gear: Isolated, Electronic, CC Driver


Internal Wiring: Insulated Cu wire

Hardwares: SS & MS Zinc plated and passivated

Ingress Protection: IP20

Operating Voltage Range: $140V^{\sim} 270V$ Operating Temperature: $-10^{\circ}C^{\sim} 50^{\circ}C$

GA Drawing:



All dimensions in mm (Tolerance: ±5mm)

Electrical & Photometry Parameters:

| Rated Voltage | System | System | Power | System Lumen | CCT (AS per ANSI) | CRI | THD | Driver |
|---------------|---------|---------|--------|--------------|-------------------|-----|------|------------|
| & Frequency | Wattage | Current | Factor | Efficacy | | | | Efficiency |
| 240V, 50Hz | 48W±10% | <232mA | ≥0.95 | ≥90lm/W | 6500K | ≥80 | ≤10% | ≥85% |

System Protections:

Open & Short circuit protection, reverse polarity protection, surge protection of 3KV internal.

Application:

Offices, hospitals, retail outlets, banks, etc.

Mounting:

Recessed mounting.

| Note: Due to continuous efforts in developing products, | | MK/NK | Industrial Luminaire : |
|---|---------------|-------|------------------------------|
| improvement M/s Halonix Technologies Pvt Ltd reserves the right to make changes in the design and data and withdraw the | | AS | Cat. Ref. : HLFPR22-11-48-CW |
| luminaries without any prior notice. | Approved by : | RL | Document No : HWR-R-2019 |