

LED 18W Down Light

HLDLR-31-18-CW

As per IS 10322 & IEC 60598-1



Product Description: Energy efficient 18W LED Down Light

Technical Specifications:

Main Housing / Heat Sink Material:

Duly powder coated Aluminium PDC

Front Cover:

PMMA

LED:

LM80 certified LED

Control Gear:

External CC driver

Internal Wiring:

Insulated Cu wire

Hardware:

SS & MS Zinc plated and passivated

Ingress Protection:

IP20


Operating Voltage:

140V~270V

Operating Temperature:

-10°C~ 50°C

GA Drawing:



All dimensions in mm (Tolerance: ± 5 mm)

Electrical & Photometry Parameters:

Rated Voltage & Frequency	System Wattage	System Current	Power Factor	System Lumen Efficacy	CCT (As per ANSI)	CRI	THD	Driver Efficiency
240V, 50Hz	18W \pm 10%	<87mA	>0.95	≥ 100 lm/W	5700K	≥ 80	$\leq 10\%$	$\geq 85\%$

System Protections:

Open & Short circuit protection, reverse polarity protection, surge protection of 2.5KV internal.

Application:

Offices, commercial complexes, showrooms, retail outlets, malls, reception lobbies, hotel lobbies, high roof Indoor lighting applications, etc.

Mounting:

Recessed mounting.

Note: Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt Ltd reserves the right to make changes in the design and data and withdraw the luminaries without any prior notice.	Prepared by :	MK/NK	Industrial Luminaire :
	Checked by :	AS	Cat. Ref. : HLDLR-31-18-CW
	Approved by :	RL	Document No :

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.