

LED 15W Down Light**HLDLS- S06 -15-CW**As per IS 10322 & IEC 60598-1**Product Description:** Energy efficient 15W LED Down Light**Technical Specifications:**

Main Housing / Heat Sink Material:

Front Cover:

LED:

Control Gear:

Internal Wiring:

Hardware:

Ingress Protection:

Operating Voltage:

Operating Temperature:

Duly powder coated Aluminium PDC

PMMA

LM80 certified LED

External CC driver


Insulated Cu wire

SS & MS Zinc plated and passivated

IP20

140V~270V

-10°C~ 50°C

**GA Drawing:**All dimensions in mm (Tolerance: ± 5 mm)**Electrical & Photometry Parameters:**

Rated Voltage & Frequency	System Wattage	System Current	Power Factor	System Lumen Efficacy	CCT (As per ANSI)	CRI	THD	Driver Efficiency
240V, 50Hz	15W $\pm 10\%$	<72mA	>0.95	≥ 80 lm/W	6500K	≥ 80	$\leq 15\%$	$\geq 85\%$

System Protections:

Open & Short circuit protection, reverse polarity protection, surge protection of 2.5KV internal.

Application:

Offices, commercial complexes, showrooms, retail outlets, malls, reception lobbies, hotel lobbies, high roof Indoor lighting applications, etc.

Mounting:

Surface mounting.

Note: Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt Ltd reserves the right to make changes in the design and data and withdraw the luminaries without any prior notice.

Prepared by :

MK/NK

Industrial Luminaire :

Checked by :

AS

Cat. Ref. : HLDLS- S06 -15-CW

Approved by :

RL

Document No :

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.