

40W LED HW STREET LIGHT

Photometric & Electrical Measurement (As per IES LM 79-08 / IS 16106-12)

40W Energy Efficient LED Street Light

Issued by: Halonix Technologies Private Limited (NABL Certification No: TC-7634) 01/28/2019

HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Fax:

Web: http://www.halonix.co.in

Test Report

Report Number: 28-01-2019 -001	Date	28-01-2019
Product Description: 40W Energy Efficient LED Street Light		
Product Catalogue Reference: HLSLD-15-40-CWL-R	Brand	: HALONIX
Construction:	•	•
Pressure die casted aluminum housing, Glass front visor, SMD Li	ED, Electronic driver etc.	
Test Details: Document		ces/Standard:
 Light intensity distribution Measurement Total Lumen output Measurement Electrical Parameters Measurement 	 IES-LM-79-08 "Electrical and Photometric Measurements of Solid-State Lighting Products" IS: 16106-2012 "Method of Electrical and Photometric solid state lighting (LED) Products" IS: 16105-2012 "Method of measurement of Lumen maintenance of solid state light sources" 	
Enclosures:		
Prepared By:	Approved By:	
Sanjay Sharma	Rajeev Chhabra	

HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Total Power:

Email: customercare@halonix.co.in

Fax:

Web: http://www.halonix.co.in

Electrical & Photometric Test Report

Photometric Test Report: (As Pe	r IES LM 79-08)			
Sample ID: 28-01-2019 -001				
Catalogue Reference:	HLSLD-15-4	HLSLD-15-40-CWL-R		28-01-2019
Testing Agency:	HTPL Labor	HTPL Laboratory		HALONIX
Equipment Used:	EVERFINE B	EVERFINE Brand Gonio Photometer (Type: GO - 2000B V1) and Globe		
	Photomete	Photometer (Type: PMS – 50/80) with Power Meter		
Ambient Temperature:	25±2°C	Relative Humidity:	65%	
Test Voltage:	240V	Frequency:	50Hz	
Stabilization Time:	30Min	Total Operating Time:	1.30Hours	
Rated Performance Parameters:				
Rated Wattage :	40W	Rated Input Current:	0.193A	
Nomical CCT :	5700K	Nominal CRI:	>70	
Measured Electrical Parameters:				
Supply Voltage:	240V	Input Current :	0.169A	
Frequency:	50Hz			

Photometric Measurement Data:					
Total Measured Lumen :	4035.86lm	Luminaries Efficacy:	101.89lm/W		
CCT:	5866K	CRI:	73.2		
Light Intensity Distribution:		Attached (Refer to Page No. 4)			
Approved By: Rajeev Chhabra		Tested By: Sanjay Sharma			

Power Factor:

0.977

39.61W

HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Fax:

Web: http://www.halonix.co.in

Light intensity Distribution Diagram



Catalogue Reference	HLSLD-15-40-CWL-R	Sample ID	28-01-2019 -001